

Noise Calculation Worksheets

Sunset Gower Project

Noise Calculations Worksheets

Provided by Acoustical Engineering Services

Ambient Noise Measurements



Location: R1 -

Date: 4/24/2018

Time Overload	d Leq	Lmax	L10	L90
10:04:07 AM No	59.3	69.2	62.9	50.9
10:05:07 AM No	62.2	71.3	66.6	53.6
10:06:07 AM No	56.9	64.4	61	50.8
10:07:07 AM No	59.5	70.2	63.5	50.1
10:08:07 AM No	61.1	66.9	65	53.4
10:09:07 AM No	60.9	68.4	65.2	52.9
10:10:07 AM No	59.7	68.3	63.7	52.9
10:11:07 AM No	60.1	69.5	63.1	53
10:12:07 AM No	60.8	68.6	64.9	50.8
10:13:07 AM No	63.2	73.4	67.8	52.5
10:14:07 AM No	60.7	67.8	65	57.7
10:15:07 AM No	65.6	73.9	70.3	57.6
10:16:07 AM No	59	65	62.7	51.8
10:17:07 AM No	57.5	65.3	61.1	53.1
10:18:07 AM No	61.5	69.1	65.7	50.9
	61.1			

Time Overload	Leq	Lmax	L10	L90
10:00:29 PM No	45.9	50.5	47	44.9
10:01:29 PM No	49.6	57.1	52.7	47.1
10:02:29 PM No	56.1	68.3	58.7	47.3
10:03:29 PM No	46.9	48.4	47.6	46.3
10:04:29 PM No	46.9	52.9	47.5	45.9
10:05:29 PM No	47.9	51	49.6	46.5
10:06:29 PM No	49.3	60	49.6	46.4
10:07:29 PM No	50.6	60.1	55.3	45.3
10:08:29 PM No	55.2	65.7	59.4	47.3
10:09:29 PM No	66.2	73.8	70.8	47.5
10:10:29 PM No	57.1	66.5	61	49
10:11:29 PM No	57.7	69.6	61.7	47.7
10:12:29 PM No	53.1	65.4	55.4	45.8
10:13:29 PM No	56.2	67.5	61	45.9
10:14:29 PM No	54.1	64.7	58.7	46.8



Location: R2 -

Date: 4/24/2018

Time Overload	Leq	Lmax	L10	L90
10:23:13 AM No	62.2	69.5	66.8	49.3
10:24:13 AM No	63.3	73.9	65.6	55.4
10:25:13 AM No	67.8	77.9	72.1	54.6
10:26:13 AM No	63.5	69.2	66	59.1
10:27:13 AM No	61.3	69.5	65.8	55.4
10:28:13 AM No	59.1	68.2	63.4	51.3
10:29:13 AM No	65.6	73.5	69.4	57.9
10:30:13 AM No	61.8	68.2	66.4	52.5
10:31:13 AM No	62.2	71.7	65.7	52.7
10:32:13 AM No	62.4	67.8	66.4	53.2
10:33:13 AM No	63.3	69	67.2	55
10:34:13 AM No	64.1	73	67.6	53.6
10:35:13 AM No	58.9	68.6	62.7	51.7
10:36:13 AM No	62.1	68.7	64.6	58.8
10:37:13 AM No	75.1	83.2	80.2	64.8
	66.2			
Time Overload	Leq	Lmax	L10	L90
10:19:17 PM No	60.8	69.8	66.1	48.6
10:20:17 PM No	50.5	60.1	54.3	45.4
10:21:17 PM No	62.6	71.8	66.5	51.5
10:22:17 PM No	60.6	67.7	66	45
10:23:17 PM No	59.4	67.1	64.7	46.7
10:24:17 PM No	59.5	67.8	64.8	47.7
10:25:17 PM No	56.2	69	59.1	45.3
10:26:17 PM No	61.7	70.2	66.1	48.3
10:27:17 PM No	56.3	68	61	44.8
10:28:17 PM No	55.8	61.5	59.3	46.5
10:29:17 PM No	61.3	70.3	66.5	48.6
10:30:17 PM No	60.7	69.9	65.4	49.4
10:31:17 PM No	59.3	68	63.7	48
10:32:17 PM No	60.5	68.6	66	48.2
10:33:17 PM No	60.8	70.3	66.9	47.9



Location: R3

Date: 4/24/2018

Time Overload	Leq	Lmax	L10	L90
10:46:13 AM No	64.2	70.7	68.7	52.9
10:47:13 AM No	64.5	68.2	67	56.4
10:48:13 AM No	62.9	67.5	65.5	55.9
10:49:13 AM No	65.7	73	68.5	59.5
10:50:13 AM No	66.3	73.9	69.4	54.4
10:51:13 AM No	64.9	71.2	68.1	52.3
10:52:13 AM No	63.4	69.6	66.8	57.5
10:53:13 AM No	69.8	79.9	73.2	59.6
10:54:13 AM No	67.3	76.1	69.4	61.7
10:55:13 AM No	66.7	73.5	69.8	61.1
10:56:13 AM No	64.4	70.1	67.9	58.5
10:57:13 AM No	67.5	72.6	70.6	63.2
10:58:13 AM No	66.9	74.5	69.7	60.8
10:59:13 AM No	68.6	77.6	72.6	57.8
11:00:13 AM No	61.1	68.7	65	53.2
	66.2	_		

Time Overload	Leq	Lmax	L10	L90
10:40:02 PM No	60.7	68.7	64	48.2
10:41:02 PM No	63.6	72.7	68.2	46.9
10:42:02 PM No	53.4	62.8	58.7	44.8
10:43:02 PM No	61.5	69.4	66.9	47.6
10:44:02 PM No	60.4	67.4	65.5	46.9
10:45:02 PM No	62.3	71.9	66	47.3
10:46:02 PM No	62.9	69.8	67	54.1
10:47:02 PM No	61.9	69	66.3	49.3
10:48:02 PM No	57.3	66.1	63.1	45.9
10:49:02 PM No	58	66	63.5	48.2
10:50:02 PM No	65	75.2	67.5	49.1
10:51:02 PM No	58.8	66.6	62.8	51.3
10:52:02 PM No	64.4	71.3	68.2	53.5
10:53:02 PM No	59.3	68.9	65.4	46.8
10:54:02 PM No	64.4	71	67.6	47.7



Location: R4

Date: 4/24/2018

11:16:46 PM No

11:17:46 PM No

11:18:46 PM No

11:19:46 PM No

11:20:46 PM No

11:21:46 PM No

Leq	Lmax	L10	L90
69.9	75.1	73	65.6
72.4	79.7	75.6	67.8
71.4	76.9	74.7	65.4
72.0	79.7	75.9	59.8
71.3	75.8	74.4	61
66.3	71	69.1	58
72.9	75.1	74.4	70.7
68.7	75.1	72.8	55.7
71.3	75.9	74.2	56.7
70.6	76.6	74.3	57.7
80.5	93.4	84.7	65
75.8	84.6	78.9	71.9
70.7	82.5	74.9	59.7
72.5	76.7	73.8	71
71.6	78.4	74.9	60.1
73.3			
			L90
			56.6
			66
			62.4
73.9	81.8	78.2	66.9
72.5	79.6	74.8	65.8
67.3	73.3	72	59.1
72.4	80.2	74.9	64.8
72.3	78.3	75.8	63.2
75.6	88.1	79.3	55.9
	69.9 72.4 71.4 72.0 71.3 66.3 72.9 68.7 71.3 70.6 80.5 75.8 70.7 72.5 71.6 73.3 Leq 71.1 69.9 71.2 73.9 72.5 67.3 72.4 72.3	69.9 75.1 72.4 79.7 71.4 76.9 72.0 79.7 71.3 75.8 66.3 71 72.9 75.1 68.7 75.1 71.3 75.9 70.6 76.6 80.5 93.4 75.8 84.6 70.7 82.5 72.5 76.7 71.6 78.4 73.3 Leq Lmax 71.1 76.9 69.9 75.9 71.2 75.7 73.9 81.8 72.5 79.6 67.3 73.3 72.4 80.2 72.3 78.3	69.9 75.1 73 72.4 79.7 75.6 71.4 76.9 74.7 72.0 79.7 75.9 71.3 75.8 74.4 66.3 71 69.1 72.9 75.1 74.4 68.7 75.1 72.8 71.3 75.9 74.2 70.6 76.6 74.3 80.5 93.4 84.7 75.8 84.6 78.9 70.7 82.5 74.9 72.5 76.7 73.8 71.6 78.4 74.9 73.3 Leq Lmax L10 71.1 76.9 75.6 69.9 75.9 72.5 71.2 75.7 73.6 73.9 81.8 78.2 72.5 79.6 74.8 67.3 73.3 72 72.4 80.2 74.9 72.3 78.3 75.8

72.3 **72.0**

70.3

69.7

80.9

69.9

72.8

78.1

74.7

93.5

76.4

78.9

78.2

74.3

72.6

83.3

73.8

76.1

75.3

57.6

64.1

61.2

62.8

64.5

69



Location: R5

Date: 4/24/2018

11:33:19 PM No

11:34:19 PM No

11:35:19 PM No

11:36:19 PM No

11:37:19 PM No

11:38:19 PM No

11:39:19 PM No

11:40:19 PM No

Time Overload	Leq	Lmax	L10	L90
11:28:35 AM No	61.5	67.2	64.5	58.6
11:29:35 AM No	62	70.5	63.8	59.3
11:30:35 AM No	65.5	72.9	68.6	61.7
11:31:35 AM No	76.8	86.7	83.4	61.6
11:32:35 AM No	66	74.2	70.7	60.5
11:33:35 AM No	61.5	66.6	63.5	58.2
11:34:35 AM No	62.8	69.6	65.5	59.9
11:35:35 AM No	67.7	76.8	72.2	62.5
11:36:35 AM No	62.8	68.9	65.4	59.4
11:37:35 AM No	62.1	67.5	63.9	56.3
11:38:35 AM No	59	62.8	61.2	54.4
11:39:35 AM No	62.6	67.8	65.8	56.8
11:40:35 AM No	68.6	78.6	72.7	59.1
11:41:35 AM No	64.4	71.6	65.8	62.5
11:42:35 AM No	63.6	71.4	66.1	60.2
	67.6			
Time Overload	Leq	Lmax	L10	L90
11:26:19 PM No	59.8	66.5	65	52.8
11:27:19 PM No	62.6	70.6	65.8	52.8
11:28:19 PM No	66	73.8	69.2	60.6
11:29:19 PM No	63.1	67.5	65.5	58.1
11:30:19 PM No	65.5	76.9	66.1	57.5
11:31:19 PM No	61.2	66.3	64.3	52.8
11:32:19 PM No	65.5	76.4	67.5	53.4

61.2 **63.5**

65.9

64.4

63.5

62.1

60.8

62.7

61

73

71.3

70.4

67

66

66

70.3

67.7

69.2

68

67

65.3

64.1

65.4

65.2

65

60.1

57.5

58.3

55.1

52.8

49.1

59.6

Construction Noise & Vibration Calculations Project



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	60	0
1	79	40%	60	0
1	79	40%	85	0
1	79	40%	85	0
1	81	40%	110	0
1	78	40%	110	0
1	75	20%	135	0
1	79	40%	135	0
1	78	40%	135	0
1	75	20%	160	0
1	90	20%	160	0
1	82	10%	160	0
		No. of Equip. Noise Level at 50ft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 79 1 78 1 75 1 90	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 78 40% 1 75 20% 1 78 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 60 1 79 40% 85 1 79 40% 85 1 81 40% 110 1 78 40% 110 1 75 20% 135 1 79 40% 135 1 79 40% 135 1 78 40% 135 1 75 20% 160 1 90 20% 160

12

Receptor: R1

Results:

1-hour Leq: 83.6



Construction Phase: Grading/Excavation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	60	0
Excavator	1	81	40%	60	0
Crane	1	81	16%	85	0
Tractor/Loader/Backhoe	1	79	40%	85	0
Air Compressor	1	78	40%	110	0
Bore/Drill Rig	1	84	20%	110	0
Excavator	1	81	40%	135	0
Crane	1	81	16%	135	0
Tractor/Loader/Backhoe	1	79	40%	160	0
Water truck	1	82	10%	160	0

10

Receptor: R1

Results:

1-hour Leq: 80.7



Construction Phase: Mat Foundation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	60	0
Concrete Pump	1	81	20%	60	0
Tractor/Loader/Backhoe	1	79	40%	85	0
Welders	1	74	40%	85	0
Crane	1	81	16%	110	0
Cement and Mortar Mixer	3	80	50%	110	0
Concrete Pump	3	81	20%	135	0
Welders	1	74	40%	135	0
Crane	1	81	16%	160	0

13

Receptor: R1

Results:

1-hour Leq: 80.6



Construction Phase: Building Construction Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	60	0
Air Compressor	1	78	40%	60	0
Aerial Lift	1	75	20%	85	0
Fork Lift	1	75	20%	85	0
Concrete Pump	1	81	20%	110	0
Crane	1	81	16%	110	0
Tractor/Loader/Backhoe	2	79	40%	135	0
Welders	2	74	40%	135	0
Air Compressor	1	78	40%	160	0
Aerial Lift	1	75	20%	160	0
Fork Lift	1	75	20%	185	0
Crane	1	81	16%	185	0

14

Receptor: R1

Results:

1-hour Leq: 79.2



Construction Phase: Grading/Excavation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	200	0
Excavator	1	81	40%	200	0
Crane	1	81	16%	225	0
Tractor/Loader/Backhoe	1	79	40%	225	0
Air Compressor	1	78	40%	250	0
Bore/Drill Rig	1	84	20%	250	0
Excavator	1	81	40%	275	0
Crane	1	81	16%	275	0
Tractor/Loader/Backhoe	1	79	40%	300	0
Water truck	1	82	10%	300	0

10

Receptor: R1

Results:

1-hour Leq: 71.9



Construction Phase: Mat Foundation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	200	0
Concrete Pump	1	81	20%	200	0
Tractor/Loader/Backhoe	1	79	40%	225	0
Welders	1	74	40%	225	0
Crane	1	81	16%	250	0
Cement and Mortar Mixer	3	80	50%	250	0
Concrete Pump	3	81	20%	275	0
Welders	1	74	40%	275	0
Crane	1	81	16%	300	0

13

Receptor: R1

Results:

1-hour Leq: 72.3



Construction Phase: Building Construction

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	200	0
Air Compressor	1	78	40%	200	0
Aerial Lift	1	75	20%	225	0
Fork Lift	1	75	20%	225	0
Tractor/Loader/Backhoe	1	79	40%	250	0
Welders	1	74	40%	250	0
Crane	1	81	16%	275	0
Concrete Pump	1	81	20%	275	0
Air Compressor	1	78	40%	300	0
Aerial Lift	1	75	20%	300	0
Fork Lift	1	75	20%	325	0
Crane	1	81	16%	325	0
Tractor/Loader/Backhoe	1	79	40%	325	0
Welders	1	74	40%	325	0

14

Receptor: R1

Results:

1-hour Leq: 70.4



Construction Phase: Grading/Excavation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	395	15
Excavator	1	81	40%	395	15
Crane	1	81	16%	420	15
Tractor/Loader/Backhoe	1	79	40%	420	15
Bore/Drill Rig	1	84	20%	445	15
Excavator	1	81	40%	445	15
Crane	1	81	16%	470	15
Tractor/Loader/Backhoe	1	79	40%	470	15
Water truck	1	82	10%	495	15

9

Receptor: R1

Results:

1-hour Leq: 51.4



Construction Phase: Mat Foundation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	395	15
Concrete Pump	1	81	20%	395	15
Tractor/Loader/Backhoe	1	79	40%	420	15
Welders	1	74	40%	420	15
Crane	1	81	16%	445	15
Cement and Mortar Mixer	3	80	50%	445	15
Concrete Pump	3	81	20%	470	15
Welders	1	74	40%	470	15
Crane	1	81	16%	495	15

13

Receptor: R1

Results:

1-hour Leq: 52.1



Construction Phase: Building Construction Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	395	15
Air Compressor	1	78	40%	395	15
Aerial Lift	1	75	20%	420	15
Fork Lift	1	75	20%	420	15
Concrete Pump	1	81	20%	445	15
Tractor/Loader/Backhoe	1	79	40%	445	15
Welders	1	74	40%	470	15
Crane	1	81	16%	470	15
Air Compressor	1	78	40%	495	15
Aerial Lift	1	75	20%	495	15
Fork Lift	1	75	20%	520	15
Crane	1	81	16%	520	15
Tractor/Loader/Backhoe	1	79	40%	520	15
Welders	1	74	40%	520	15

14

Receptor: R1

Results:

1-hour Leq: 50.3



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	65	0
1	79	40%	65	0
1	79	40%	90	0
1	79	40%	90	0
1	81	40%	115	0
1	78	40%	115	0
1	75	20%	140	0
1	79	40%	140	0
1	78	40%	140	0
1	75	20%	165	0
1	90	20%	165	0
1	82	10%	165	0
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 75 20% 1 79 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20% 1 82 10%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 65 1 79 40% 90 1 79 40% 90 1 79 40% 90 1 81 40% 115 1 78 40% 115 1 75 20% 140 1 78 40% 140 1 78 40% 140 1 75 20% 165 1 90 20% 165 1 82 10% 165

12

Receptor: R2

Results:

1-hour Leq: 83.0



Construction Phase: Grading/Excavation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	65	0
Excavator	1	81	40%	65	0
Crane	1	81	16%	90	0
Tractor/Loader/Backhoe	1	79	40%	90	0
Air Compressor	1	78	40%	115	0
Bore/Drill Rig	1	84	20%	115	0
Excavator	1	81	40%	140	0
Crane	1	81	16%	140	0
Tractor/Loader/Backhoe	1	79	40%	165	0
Water truck	1	82	10%	165	0

10

Receptor: R2

Results:

1-hour Leq: 80.1



Construction Phase: Mat Foundation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	65	0
Concrete Pump	1	81	20%	65	0
Tractor/Loader/Backhoe	1	79	40%	90	0
Welders	1	74	40%	90	0
Crane	1	81	16%	115	0
Cement and Mortar Mixer	3	80	50%	115	0
Concrete Pump	3	81	20%	140	0
Welders	1	74	40%	140	0
Crane	1	81	16%	165	0

13

Receptor: R2

Results:

1-hour Leq: 80.1



Construction Phase: Building Construction Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	65	0
Air Compressor	1	78	40%	65	0
Aerial Lift	1	75	20%	90	0
Fork Lift	1	75	20%	90	0
Concrete Pump	1	81	20%	115	0
Crane	1	81	16%	115	0
Tractor/Loader/Backhoe	2	79	40%	140	0
Welders	2	74	40%	140	0
Air Compressor	1	78	40%	165	0
Aerial Lift	1	75	20%	165	0
Fork Lift	1	75	20%	190	0
Crane	1	81	16%	190	0

14

Receptor: R2

Results:

1-hour Leq: 78.6



Construction Phase: Grading/Excavation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	280	10
Excavator	1	81	40%	280	10
Crane	1	81	16%	305	10
Tractor/Loader/Backhoe	1	79	40%	305	10
Air Compressor	1	78	40%	330	10
Bore/Drill Rig	1	84	20%	330	10
Excavator	1	81	40%	355	10
Crane	1	81	16%	355	10
Tractor/Loader/Backhoe	1	79	40%	380	10
Water truck	1	82	10%	380	10

10

Receptor: R2

Results:

1-hour Leq: 59.3



Construction Phase: Mat Foundation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	280	10
Concrete Pump	1	81	20%	280	10
Tractor/Loader/Backhoe	1	79	40%	305	10
Welders	1	74	40%	305	10
Crane	1	81	16%	330	10
Cement and Mortar Mixer	3	80	50%	330	10
Concrete Pump	3	81	20%	355	10
Welders	1	74	40%	355	10
Crane	1	81	16%	380	10

13

Receptor: R2

Results:

1-hour Leq: 59.8



Construction Phase: Building Construction

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	280	10
Air Compressor	1	78	40%	280	10
Aerial Lift	1	75	20%	305	10
Fork Lift	1	75	20%	305	10
Tractor/Loader/Backhoe	1	79	40%	330	10
Welders	1	74	40%	330	10
Crane	1	81	16%	355	10
Concrete Pump	1	81	20%	355	10
Air Compressor	1	78	40%	380	10
Aerial Lift	1	75	20%	380	10
Fork Lift	1	75	20%	405	10
Crane	1	81	16%	405	10
Tractor/Loader/Backhoe	1	79	40%	405	10
Welders	1	74	40%	405	10

14

Receptor: R2

Results:

1-hour Leq: 57.9



Construction Phase: Grading/Excavation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	330	5
Excavator	1	81	40%	330	5
Crane	1	81	16%	355	5
Tractor/Loader/Backhoe	1	79	40%	355	5
Bore/Drill Rig	1	84	20%	380	5
Excavator	1	81	40%	380	5
Crane	1	81	16%	405	5
Tractor/Loader/Backhoe	1	79	40%	405	5
Water truck	1	82	10%	430	5

9

Receptor: R2

Results:

1-hour Leq: 62.8



Construction Phase: Mat Foundation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	330	5
Concrete Pump	1	81	20%	330	5
Tractor/Loader/Backhoe	1	79	40%	355	5
Welders	1	74	40%	355	5
Crane	1	81	16%	380	5
Cement and Mortar Mixer	3	80	50%	380	5
Concrete Pump	3	81	20%	405	5
Welders	1	74	40%	405	5
Crane	1	81	16%	430	5

13

Receptor: R2

Results:

1-hour Leq: 63.5



Construction Phase: Building Construction Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	330	5
Air Compressor	1	78	40%	330	5
Aerial Lift	1	75	20%	355	5
Fork Lift	1	75	20%	355	5
Concrete Pump	1	81	20%	380	5
Tractor/Loader/Backhoe	1	79	40%	380	5
Welders	1	74	40%	405	5
Crane	1	81	16%	405	5
Air Compressor	1	78	40%	430	5
Aerial Lift	1	75	20%	430	5
Fork Lift	1	75	20%	455	5
Crane	1	81	16%	455	5
Tractor/Loader/Backhoe	1	79	40%	455	5
Welders	1	74	40%	455	5

14

Receptor: R2

Results:

1-hour Leq: 61.7



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	275	15
1	79	40%	275	15
1	79	40%	300	15
1	79	40%	300	15
1	81	40%	325	15
1	78	40%	325	15
1	75	20%	350	15
1	79	40%	350	15
1	78	40%	375	15
1	75	20%	375	15
1	90	20%	380	15
1	82	10%	380	15
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 78 40% 1 75 20% 1 78 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 275 1 79 40% 275 1 79 40% 300 1 79 40% 300 1 81 40% 325 1 78 40% 325 1 75 20% 350 1 78 40% 375 1 75 20% 375 1 75 20% 375 1 90 20% 380 1 82 10% 380

12

Receptor: R3

Results:

1-hour Leq: 57.1



Construction Phase: Grading/Excavation Phase 2

Building A, Parking Structure F

Equipment

	No. of	Reference Noise Level at	Acoustical	Distance to	Estimated Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	500	15
Excavator	1	81	40%	500	15
Crane	1	81	16%	525	15
Tractor/Loader/Backhoe	1	79	40%	525	15
Air Compressor	1	78	40%	550	15
Bore/Drill Rig	1	84	20%	550	15
Excavator	1	81	40%	575	15
Crane	1	81	16%	575	15
Tractor/Loader/Backhoe	1	79	40%	575	15
Water truck	1	82	10%	575	15

10

Receptor: R3

Results:

1-hour Leq: 49.8



Construction Phase: Mat Foundation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	500	15
Concrete Pump	1	81	20%	500	15
Tractor/Loader/Backhoe	1	79	40%	525	15
Welders	1	74	40%	525	15
Crane	1	81	16%	550	15
Cement and Mortar Mixer	3	80	50%	550	15
Concrete Pump	3	81	20%	575	15
Welders	1	74	40%	575	15
Crane	1	81	16%	575	15

13

Receptor: R3

Results:

1-hour Leq: 50.2



Construction Phase: Building Construction Phase 2
Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	500	15
Air Compressor	1	78	40%	500	15
Aerial Lift	1	75	20%	525	15
Fork Lift	1	75	20%	525	15
Concrete Pump	1	81	20%	550	15
Crane	1	81	16%	550	15
Tractor/Loader/Backhoe	2	79	40%	575	15
Welders	2	74	40%	575	15
Air Compressor	1	78	40%	575	15
Aerial Lift	1	75	20%	575	15
Fork Lift	1	75	20%	575	15
Crane	1	81	16%	575	15
	4.4				

14

Receptor: R3

Results:

1-hour Leq: 48.6



Construction Phase: Grading/Excavation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	385	15
Excavator	1	81	40%	385	15
Crane	1	81	16%	410	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Air Compressor	1	78	40%	435	15
Bore/Drill Rig	1	84	20%	435	15
Excavator	1	81	40%	460	15
Crane	1	81	16%	460	15
Tractor/Loader/Backhoe	1	79	40%	460	15
Water truck	1	82	10%	460	15

10

Receptor: R3

Results:

1-hour Leq: 51.9



Construction Phase: Mat Foundation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Concrete Pump	1	81	20%	385	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Welders	1	74	40%	410	15
Crane	1	81	16%	435	15
Cement and Mortar Mixer	3	80	50%	435	15
Concrete Pump	3	81	20%	460	15
Welders	1	74	40%	460	15
Crane	1	81	16%	460	15

13

Receptor: R3

Results:

1-hour Leq: 52.3



Construction Phase: Building Construction

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Air Compressor	1	78	40%	385	15
Aerial Lift	1	75	20%	410	15
Fork Lift	1	75	20%	410	15
Tractor/Loader/Backhoe	1	79	40%	435	15
Welders	1	74	40%	435	15
Crane	1	81	16%	460	15
Concrete Pump	1	81	20%	460	15
Air Compressor	1	78	40%	460	15
Aerial Lift	1	75	20%	460	15
Fork Lift	1	75	20%	460	15
Crane	1	81	16%	460	15
Tractor/Loader/Backhoe	1	79	40%	460	15
Welders	1	74	40%	460	15

14

Receptor: R3

Results:

1-hour Leq: 50.7



Construction Phase: Grading/Excavation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	275	15
Excavator	1	81	40%	275	15
Crane	1	81	16%	300	15
Tractor/Loader/Backhoe	1	79	40%	300	15
Bore/Drill Rig	1	84	20%	325	15
Excavator	1	81	40%	325	15
Crane	1	81	16%	350	15
Tractor/Loader/Backhoe	1	79	40%	350	15
Water truck	1	82	10%	350	15

9

Receptor: R3

Results:

1-hour Leq: 54.3



Construction Phase: Mat Foundation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	275	15
Concrete Pump	1	81	20%	275	15
Tractor/Loader/Backhoe	1	79	40%	300	15
Welders	1	74	40%	300	15
Crane	1	81	16%	325	15
Cement and Mortar Mixer	3	80	50%	325	15
Concrete Pump	3	81	20%	350	15
Welders	1	74	40%	350	15
Crane	1	81	16%	350	15

13

Receptor: R3

Results:

1-hour Leq: 54.9



Construction Phase: Building Construction Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	275	15
Air Compressor	1	78	40%	275	15
Aerial Lift	1	75	20%	300	15
Fork Lift	1	75	20%	300	15
Concrete Pump	1	81	20%	325	15
Tractor/Loader/Backhoe	1	79	40%	325	15
Welders	1	74	40%	350	15
Crane	1	81	16%	350	15
Air Compressor	1	78	40%	350	15
Aerial Lift	1	75	20%	350	15
Fork Lift	1	75	20%	350	15
Crane	1	81	16%	350	15
Tractor/Loader/Backhoe	1	79	40%	350	15
Welders	1	74	40%	350	15

14

Receptor: R3

Results:

1-hour Leq: 53.4



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	185	0
1	79	40%	185	0
1	79	40%	210	0
1	79	40%	210	0
1	81	40%	235	0
1	78	40%	235	0
1	75	20%	260	0
1	79	40%	260	0
1	78	40%	285	0
1	75	20%	285	0
1	90	20%	285	0
1	82	10%	285	0
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 75 20% 1 79 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20% 1 82 10%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 185 1 79 40% 185 1 79 40% 210 1 79 40% 210 1 81 40% 235 1 78 40% 235 1 75 20% 260 1 79 40% 285 1 75 20% 285 1 75 20% 285 1 90 20% 285 1 82 10% 285

12

Receptor: R4

Results:

1-hour Leq: 75.2



Construction Phase: Grading/Excavation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	185	0
Excavator	1	81	40%	185	0
Crane	1	81	16%	210	0
Tractor/Loader/Backhoe	1	79	40%	210	0
Air Compressor	1	78	40%	235	0
Bore/Drill Rig	1	84	20%	235	0
Excavator	1	81	40%	260	0
Crane	1	81	16%	260	0
Tractor/Loader/Backhoe	1	79	40%	285	0
Water truck	1	82	10%	285	0

10

Receptor: R4

Results:

1-hour Leq: 72.5



Construction Phase: Mat Foundation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	185	0
Concrete Pump	1	81	20%	185	0
Tractor/Loader/Backhoe	1	79	40%	210	0
Welders	1	74	40%	210	0
Crane	1	81	16%	235	0
Cement and Mortar Mixer	3	80	50%	235	0
Concrete Pump	3	81	20%	260	0
Welders	1	74	40%	260	0
Crane	1	81	16%	285	0

13

Receptor: R4

Results:

1-hour Leq: 72.9



Construction Phase: Building Construction Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	185	0
Air Compressor	1	78	40%	185	0
Aerial Lift	1	75	20%	210	0
Fork Lift	1	75	20%	210	0
Concrete Pump	1	81	20%	235	0
Crane	1	81	16%	235	0
Tractor/Loader/Backhoe	2	79	40%	260	0
Welders	2	74	40%	260	0
Air Compressor	1	78	40%	285	0
Aerial Lift	1	75	20%	285	0
Fork Lift	1	75	20%	310	0
Crane	1	81	16%	310	0

14

Receptor: R4

Results:

1-hour Leq: 71.1



Construction Phase: Grading/Excavation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	770	15
Excavator	1	81	40%	770	15
Crane	1	81	16%	795	15
Tractor/Loader/Backhoe	1	79	40%	795	15
Air Compressor	1	78	40%	820	15
Bore/Drill Rig	1	84	20%	820	15
Excavator	1	81	40%	845	15
Crane	1	81	16%	845	15
Tractor/Loader/Backhoe	1	79	40%	870	15
Water truck	1	82	10%	870	15

10

Receptor: R4

Results:

1-hour Leq: 46.2



Construction Phase: Mat Foundation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	770	15
Concrete Pump	1	81	20%	770	15
Tractor/Loader/Backhoe	1	79	40%	795	15
Welders	1	74	40%	795	15
Crane	1	81	16%	820	15
Cement and Mortar Mixer	3	80	50%	820	15
Concrete Pump	3	81	20%	845	15
Welders	1	74	40%	845	15
Crane	1	81	16%	870	15

13

Receptor: R4

Results:

1-hour Leq: 46.7



Construction Phase: Building Construction

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	770	15
Air Compressor	1	78	40%	770	15
Aerial Lift	1	75	20%	795	15
Fork Lift	1	75	20%	795	15
Tractor/Loader/Backhoe	1	79	40%	820	15
Welders	1	74	40%	820	15
Crane	1	81	16%	845	15
Concrete Pump	1	81	20%	845	15
Air Compressor	1	78	40%	870	15
Aerial Lift	1	75	20%	870	15
Fork Lift	1	75	20%	895	15
Crane	1	81	16%	895	15
Tractor/Loader/Backhoe	1	79	40%	920	15
Welders	1	74	40%	920	15

14

Receptor: R4

Results:

1-hour Leq: 45.0



Construction Phase: Grading/Excavation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	615	15
Excavator	1	81	40%	615	15
Crane	1	81	16%	640	15
Tractor/Loader/Backhoe	1	79	40%	640	15
Bore/Drill Rig	1	84	20%	665	15
Excavator	1	81	40%	665	15
Crane	1	81	16%	690	15
Tractor/Loader/Backhoe	1	79	40%	690	15
Water truck	1	82	10%	715	15

9

Receptor: R4

Results:

1-hour Leq: 47.8



Construction Phase: Mat Foundation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	615	15
Concrete Pump	1	81	20%	615	15
Tractor/Loader/Backhoe	1	79	40%	640	15
Welders	1	74	40%	640	15
Crane	1	81	16%	665	15
Cement and Mortar Mixer	3	80	50%	665	15
Concrete Pump	3	81	20%	690	15
Welders	1	74	40%	690	15
Crane	1	81	16%	715	15

13

Receptor: R4

Results:

1-hour Leq: 48.5



Construction Phase: Building Construction Phase 3

Buildings C and D

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	80	50%	615	15
1	78	40%	615	15
1	75	20%	640	15
1	75	20%	640	15
1	81	20%	665	15
1	79	40%	665	15
1	74	40%	690	15
1	81	16%	690	15
1	78	40%	715	15
1	75	20%	715	15
1	75	20%	740	15
1	81	16%	740	15
1	79	40%	765	15
1	74	40%	765	15
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Noise Level at 50ft, Lmax 1 80 1 78 1 75 1 75 1 81 1 79 1 74 1 81 1 78 1 75 1 81 1 75 1 81 1 79	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 80 50% 1 78 40% 1 75 20% 1 75 20% 1 81 20% 1 79 40% 1 81 16% 1 78 40% 1 75 20% 1 75 20% 1 81 16% 1 75 20% 1 81 16% 1 75 20% 1 81 16% 1 79 40%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 80 50% 615 1 78 40% 615 1 75 20% 640 1 75 20% 640 1 81 20% 665 1 79 40% 665 1 74 40% 690 1 81 16% 690 1 78 40% 715 1 75 20% 740 1 81 16% 740 1 81 16% 740 1 81 16% 740 1 79 40% 765

14

Receptor: R4

Results:

1-hour Leq: 46.8



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	385	15
1	79	40%	385	15
1	79	40%	410	15
1	79	40%	410	15
1	81	40%	435	15
1	78	40%	435	15
1	75	20%	460	15
1	79	40%	460	15
1	78	40%	485	15
1	75	20%	485	15
1	90	20%	485	15
1	82	10%	485	15
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 75 20% 1 79 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20% 1 82 10%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 385 1 79 40% 385 1 79 40% 410 1 79 40% 410 1 81 40% 435 1 78 40% 435 1 75 20% 460 1 78 40% 485 1 75 20% 485 1 75 20% 485 1 90 20% 485 1 82 10% 485

12

Receptor: R5

Results:

1-hour Leq: 54.5



Construction Phase: Grading/Excavation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	385	15
Excavator	1	81	40%	385	15
Crane	1	81	16%	410	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Air Compressor	1	78	40%	435	15
Bore/Drill Rig	1	84	20%	435	15
Excavator	1	81	40%	455	15
Crane	1	81	16%	455	15
Tractor/Loader/Backhoe	1	79	40%	455	15
Water truck	1	82	10%	455	15
	4.0				

10

Receptor: R5

Results:

1-hour Leq: 51.9



Construction Phase: Mat Foundation Phase 2

Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Concrete Pump	1	81	20%	385	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Welders	1	74	40%	410	15
Crane	1	81	16%	435	15
Cement and Mortar Mixer	3	80	50%	435	15
Concrete Pump	3	81	20%	455	15
Welders	1	74	40%	455	15
Crane	1	81	16%	455	15

13

Receptor: R5

Results:

1-hour Leq: 52.3



Construction Phase: Building Construction Phase 2
Building A, Parking Structure F

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Air Compressor	1	78	40%	385	15
Aerial Lift	1	75	20%	410	15
Fork Lift	1	75	20%	410	15
Concrete Pump	1	81	20%	435	15
Crane	1	81	16%	435	15
Tractor/Loader/Backhoe	2	79	40%	455	15
Welders	2	74	40%	455	15
Air Compressor	1	78	40%	455	15
Aerial Lift	1	75	20%	455	15
Fork Lift	1	75	20%	455	15
Crane	1	81	16%	455	15
	4.4				

14

Receptor: R5

Results:

1-hour Leq: 50.8



Construction Phase: Grading/Excavation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	610	15
Excavator	1	81	40%	610	15
Crane	1	81	16%	635	15
Tractor/Loader/Backhoe	1	79	40%	635	15
Air Compressor	1	78	40%	660	15
Bore/Drill Rig	1	84	20%	660	15
Excavator	1	81	40%	680	15
Crane	1	81	16%	680	15
Tractor/Loader/Backhoe	1	79	40%	680	15
Water truck	1	82	10%	680	15

10

Receptor: R5

Results:

1-hour Leq: 48.2



Construction Phase: Mat Foundation Phase 2

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	610	15
Concrete Pump	1	81	20%	610	15
Tractor/Loader/Backhoe	1	79	40%	635	15
Welders	1	74	40%	635	15
Crane	1	81	16%	660	15
Cement and Mortar Mixer	3	80	50%	660	15
Concrete Pump	3	81	20%	680	15
Welders	1	74	40%	680	15
Crane	1	81	16%	680	15

13

Receptor: R5

Results:

1-hour Leq: 48.6



Construction Phase: Building Construction

Below Grade Parking

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	610	15
Air Compressor	1	78	40%	610	15
Aerial Lift	1	75	20%	635	15
Fork Lift	1	75	20%	635	15
Tractor/Loader/Backhoe	1	79	40%	660	15
Welders	1	74	40%	660	15
Crane	1	81	16%	680	15
Concrete Pump	1	81	20%	680	15
Air Compressor	1	78	40%	680	15
Aerial Lift	1	75	20%	680	15
Fork Lift	1	75	20%	680	15
Crane	1	81	16%	680	15
Tractor/Loader/Backhoe	1	79	40%	680	15
Welders	1	74	40%	680	15

14

Receptor: R5

Results:

1-hour Leq: 47.1



Construction Phase: Grading/Excavation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	550	15
Excavator	1	81	40%	550	15
Crane	1	81	16%	575	15
Tractor/Loader/Backhoe	1	79	40%	575	15
Bore/Drill Rig	1	84	20%	600	15
Excavator	1	81	40%	600	15
Crane	1	81	16%	620	15
Tractor/Loader/Backhoe	1	79	40%	620	15
Water truck	1	82	10%	620	15

9

Receptor: R5

Results:

1-hour Leq: 48.7



Construction Phase: Mat Foundation Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	550	15
Concrete Pump	1	81	20%	550	15
Tractor/Loader/Backhoe	1	79	40%	575	15
Welders	1	74	40%	575	15
Crane	1	81	16%	600	15
Cement and Mortar Mixer	3	80	50%	600	15
Concrete Pump	3	81	20%	620	15
Welders	1	74	40%	620	15
Crane	1	81	16%	620	15

13

Receptor: R5

Results:

1-hour Leq: 49.5



Construction Phase: Building Construction Phase 3

Buildings C and D

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	550	15
Air Compressor	1	78	40%	550	15
Aerial Lift	1	75	20%	575	15
Fork Lift	1	75	20%	575	15
Concrete Pump	1	81	20%	600	15
Tractor/Loader/Backhoe	1	79	40%	600	15
Welders	1	74	40%	620	15
Crane	1	81	16%	620	15
Air Compressor	1	78	40%	620	15
Aerial Lift	1	75	20%	620	15
Fork Lift	1	75	20%	620	15
Crane	1	81	16%	620	15
Tractor/Loader/Backhoe	1	79	40%	620	15
Welders	1	74	40%	620	15

14

Receptor: R5

Results:

1-hour Leq: 47.9



Concurrent Construction and Operation - Off-Site Analysis

Off-Site	Gordon St.	Fountain Ave.	Gower St.
Project construction traffic	72.2	67.9	67.2
Project operation interim	67.7	71.1	70.5
Composite	73.5	72.8	72.2
Ambient	61.1	66.2	66.2
Composite + Ambient	73.8	73.7	73.1
Significance threshold	66.1	71.2	71.2
•	7.7	2.5	1.9

On-Site		Estimate	d Construction	& Operation N	loise Levels, dl	BA Leq			
	Construction -	Operation -	Operation -	Operation -	Operation -	Operation -	Operation -		Project +
Rec.	P3 Foundation	Mechanical	Loading	People	Speakers	Parking	All Sources	Ambient	Ambient
R1	52.1	27.0	33.4	34.5	46.5	49.9	51.7	61.1	62.0
R2	63.5	20.5	31.3	28.7	38.9	45.8	46.8	66.2	68.1
R3	54.9	26.2	36.1	41.5	50.7	24.2	51.3	66.2	66.6
R4	48.5	33.7	28.8	49.8	62.5	20.4	62.7	73.3	73.7
R5	49.5	35.4	30.3	39.8	60.6	33.3	60.7	67.6	68.5

Off-Site	Gordon St.	Fountain Ave.	Gower St.
Operation - Existing	64.6	70.4	70.3
Existing + Project	66.4	70.8	70.4
Adjustment for Interm	3.0	3.0	3.0
Existing + Project, Interim	69.4	73.8	73.4
Project Only, Interim	67.7	71.1	70.5
Project ADT Interim ADT	4110 8244		



Off-Site Haul Trucks

	Maximum Nu	mber of Truck			Estimated N	Noise Levels,		
	One W	ay Trips			L	.eq		
	(delive	ry/haul)	Worke	r Trips	(from TN	IM Model)		
		Per Hour (8-		Trips during				
Phase	Per Day	hr day)	Daily Trips	Pk Hr.	Sunset Blvd.	Gordon St.	Fountain Ave.	Gower St.
1. Demolition	80	10	60	24	62.3	63.7	59.7	59.1
Grading - All Phases	314	40	60	24	68.0	69.4	65.1	64.5
Mat Foundation P1	832	70	60	24	70.4	71.8	67.4	66.8
4. Building P1	60	8	400	160	63.6	65.0	62.3	61.7
5. Grading P2	314	40	60	24	68.0	69.4	65.1	64.5
6. Mat Foundation P2	1148	96	60	24	71.7	73.1	68.8	68.1
7. Building P2	60	8	400	160	63.6	65.0	62.3	61.7
8. Grading P3	314	40	60	24	68.0	69.4	65.1	64.5
9. Mat Foundation P3	918	77	60	24	70.8	72.2	67.9	67.2
10. Building P3	60	8	400	160	63.6	65.0	62.3	61.7

	Number of trips per day Trucks/Work		stimated Nois	e Levels, dBA L	eq	Existing Ambient, dBA Leq						
	ers	Sunset Blvd.	Gordon St.	Fountain Ave.	Gower St.	Sunset Blvd.	Gordon St.	Fountain Ave.	Gower St.			
Demolition	80/60	62.3	63.7	59.7	59.1	73.3	61.1	66.2	66.2			
Grading - All Phases	314/60	68.0	69.4	65.1	64.5	73.3	61.1	66.2	66.2			
Foundation - Phase 1	832/60	70.4	71.8	67.4	66.8	73.3	61.1	66.2	66.2			
Foundation - Phase 2	1148/60	71.7	73.1	68.8	68.1	73.3	61.1	66.2	66.2			
Foundation - Phase 3	918/60	70.8	72.2	67.9	67.2	73.3	61.1	66.2	66.2			
Building Construction - All Ph	60/400	63.6	65.0	62.3	61.7	73.3	61.1	66.2	66.2			

	Proje	ct + Ambient I	Noise Levels, dE	BA Leq	Noise E	Exceedance o	ver Threshold,	dBA Leq
	Sunset Blvd.	Gordon St.	Fountain Ave.	Gower St.	Sunset Blvd.	Gordon St.	Fountain Ave	Gower St.
Demolition	73.6	65.6	67.1	67	-4.7	-0.5	-4.1	-4.2
Grading - All Phases	74.4	70.0	68.7	68.4	-3.9	3.9	-2.5	-2.8
Foundation - Phase 1	75.1	72.2	69.9	69.5	-3.2	6.1	-1.3	-1.7
Foundation - Phase 2	75.6	73.4	70.7	70.3	-2.7	7.3	-0.5	-0.9
Foundation - Phase 3	75.2	72.5	70.1	69.7	-3.1	6.4	-1.1	-1.5
Building Construction - All Phases	73.7	66.5	67.7	67.5	-4.6	0.4	-3.5	-3.7
			Maximur	n Exceedance	-2.7	7.3	-0.5	-0.9

	Maximum Nu	ımber of Truck	Worke	r Trips
		Per Hour (8-		Trips during
Overlapping Construction	Per Day	hr day)	Daily Trips	Pk Hr.
P1 Building and P2 Grading	374	48	460	184
P1 Building and P2	1208	104	460	184
Foundation				
P1 and P2 Building	120	16	800	320

	E	stimated Nois	e Levels, dBA L	.eq	Project + Ambient, dBA Leq					
Overlapping Construction	Sunset Blvd.	Gordon St.	Fountain Ave.	Gower St.	Sunset Blvd.	Gordon St.	Fountain Ave. Gower St.			
P1 Building and P2 Grading	69.4	70.8	66.9	66.3	74.8	71.2	69.6	69.3		
P1 Building and P2	72.4	73.8	69.7	69.0	75.9	74.0	71.3	70.8		
Foundation										
P1 and P2 Building	66.7	68.0	65.3	64.7	74.2	68.8	68.8	68.5		

	Noise Exceedance over Threshold, dBA Leq									
Overlapping Construction	Sunset Blvd.	Gordon St.	Fountain Ave. Gower St.							
P1 Building and P2 Grading	-3.5	5.1	-1.6	-1.9						
P1 Building and P2	-2.4	7.9	0.1	-0.4						
Foundation										
P1 and P2 Building	-4.1	2.7	-2.4	-2.7						
Maximum Exceedance	-2 4	7.9	0.1	-0 4						

INPUT: ROADWAYS							Sunse	et Gower Pro	ject		
Eyestone Environmental					25 March 201	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	JECT/CONTRACT: Sunset Gower Project						a State hi	ighway agend	y substant	iates the u	se
RUN:	Construction Trucks - Demo Phase								the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Con	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	unset Go	wer Pr	oject			
Eyestone Environmental				25 Ma	rch 2019							
Sean Bui				TNM 2	2.5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Constructi	on Trucks	s - Demo	Phase								
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTrucks HTrucks			3	Buses		Motorcycles	
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 2	4 35	5 C	0	10	35	5 (0 0	0 0) (
	point2		2									

INPUT: RECEIVERS								Sunset G	ower P	roject			
Eyestone Environmental						25 March	2019						
Sean Bui						TNM 2.5							
INPUT: RECEIVERS													
PROJECT/CONTRACT:	Suns	et Gow	er Project										
RUN:	Cons	Construction Trucks - Demo Phase											
Receiver													
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Cr	iteria	/	Active	
			X	Υ	Z	above	Existing	Impact C	riteria	NR	i	in	
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	(Calc.	
			ft	ft	ft	ft	dBA	dBA	dB	dB			
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	2 0.00	7	1	5.0	0.0	Υ	
Along Sunset Blvd.		8 1	250.0	40.0	0.00	4.92	2 0.00	6	6	10.0	8.0	Υ	

RESULTS: SOUND LEVELS			T.				Sunset Go	wer Proje	ct				
Eyestone Environmental							25 March	 2019					
Sean Bui							TNM 2.5						
							Calculated	with TNN	/I 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Constru	uction Truc	ks - Demo F	hase								
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	ss	
								a State hi	ighway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a diffe	rent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	63.	7 71	63.7	5		63.7	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	62.	3 66	62.3	10		62.3	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0.0)							
All Impacted		0	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS							Sunse	et Gower Pro	ject		
Eyestone Environmental					25 March 201	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:				a State hi	ighway agend	y substant	iates the u	se			
RUN:		of a different type with the approval of FHWA									
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Con	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes		Sunset Gower Project										
Eyestone Environmental				25 Ma	│ rch 2019							
Sean Bui			TNM 2.5									
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gower Project											
RUN:	Constructi	on Trucks	s - Gradin	g Phas	e							
Roadway	Points											
Name	Name	No.	Segmen	nt								
			Autos	utos		MTrucks		HTrucks			Motorcycles	
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	5 0) () 40	35		0 0) /	0
	point2		2									

INPUT: RECEIVERS									Sunset Go	ower Proje	ect	
Eyestone Environmental						25	March 2	2019				
Sean Bui						TNI	M 2.5					
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Suns	set Gow	er Project		'							
RUN:	Cons	structio	n Trucks - Gr	ading Phase								
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height		Input Sound Levels		and Criter	ia	Active
			X	Υ	Z	abo	ove	Existing	Impact Cr	iteria	NR	in
						Gro	ound	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft		dBA	dBA	dB	dB	
Along Gordon St.		1 1	1 250.0	30.0)	0.00	4.92			5.	0.0) Y
Along Sunset Blvd.		8 1	1 250.0	40.0		0.00	4.92	0.00	66	10.	0 8.0) Y

RESULTS: SOUND LEVELS			T			<u> </u>	Sunset Go	wer Projec	et .				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							Calculated	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Constru	uction Truc	ks - Gradino	g Phase								
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	ss	
								a State hi	ghway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	69.	4 71	69.4	5		69.4	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	68.	0 66	68.0	10	Snd Lvl	68.0	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
-			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0.0)							
All Impacted		1	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS	<u> </u>						Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be i	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Pro	ject				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	on Phase	2A			of a different type with the approval of FHWA					
Roadway		Points									
Name	Width	Name No.		Coordinates	(pavement)		Flow Cor	ntrol	Segment		
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes		Sunset Gower Project										
Eyestone Environmental				25 Ma	│ rch 2019							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Foundation Phase 2A											
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTrucks		HTruck	S	Buses		Motorcycles	
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	5 0) (70	35	5	0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ect	
Eyestone Environmental						25 March	2019				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Found	dation F	Phase 2A								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'I	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0	0 Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	6 10.	0 8.	0 Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	t				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5	2013					
Sean Bui							_	d with TNN	125				
RESULTS: SOUND LEVELS							Calculate		1 2.3				
PROJECT/CONTRACT:		Sunset	Gower Pro	iect									
RUN:			tion Phase	-									
BARRIER DESIGN:		INPUT	HEIGHTS					Average r	oavement type	shall be use	d unles	SS	
									ghway agenc				
ATMOSPHERICS:		68 deg	F, 50% RH						ent type with				
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1 1	0.0	71.	8 71	71.8	5	Snd Lvl	71.8	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	70.	4 66	70.4	10	Snd Lvl	70.4	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0.0)							
All Impacted		2	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Pro	ject					ighway agend			
RUN:	Foundati	on Phase	2B				of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)	-	Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes							Sunset G	ower Pr	oject			
Eyestone Environmental				25 Ma	∣ rch 2019							
Sean Bui				TNM 2	2.5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Foundation	n Phase 2	В									
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	4 35	5 () (96	35	5	0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ect	
Eyestone Environmental						25 March	2019				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Found	dation F	Phase 2B								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	above	Existing	Impact Cı	iteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'I	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.	0 Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	6 10.	0 8.	0 Y

RESULTS: SOUND LEVELS						Sunset Go	wer Projec	:t				
Eyestone Environmental						25 March	2019					
Sean Bui						TNM 2.5						
						Calculated	with TNN	1 2.5				
RESULTS: SOUND LEVELS												
PROJECT/CONTRACT:	Sunset	Gower Pro	ject									
RUN:	Founda	ation Phase	2B									
BARRIER DESIGN:	INPUT	HEIGHTS					Average p	pavement type	shall be use	d unless	;	
							a State hi	ghway agenc	y substantiate	s the us	e	
ATMOSPHERICS:	68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver												
Name No.	#DUs	Existing	No Barrier					With Barrier				
		LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
			Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calculat	ted
						Sub'l Inc					minus	
											Goal	
		dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1 1	0.0	73.1	71	73.1	5	Snd Lvl	73.1	0.0		0	0.0
Along Sunset Blvd.	8 1	0.0	71.7	66	71.7	10	Snd Lvl	71.7	0.0		8	-8.0
Dwelling Units	# DUs	Noise Red	duction									
		Min	Avg	Max								
		dB	dB	dB								
All Selected	2	0.0	0.0	0.0)							
All Impacted	2	0.0	0.0	0.0								
All that meet NR Goal	1	0.0	0.0	0.0	1							

25

1

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Pro	ject				_	ighway agend			
RUN:	Foundati	on Phase	3				of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes	П				1		Sunset G	ower Pi	roject			
Eyestone Environmental				25 Ma	∣ rch 2019							
Sean Bui				TNM 2	2.5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Foundation	n Phase 3	3									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	1 35	5 () (77	7 35	5	0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						25 March	2019				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunse	et Gowe	er Project								
RUN:	Found	dation F	Phase 3								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Y	Z	above	Existing	Impact Cr	iteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS						Sunset Gov	wer Projec	t	,			
Eyestone Environmental						25 March 2	2019					
Sean Bui						TNM 2.5						
RESULTS: SOUND LEVELS						Calculated	I WITH I NM	2.5				
PROJECT/CONTRACT:	Sunset	Gower Pro	oject									
RUN:		tion Phase	-									
BARRIER DESIGN:	INPUT	HEIGHTS					Average p	avement type	shall be us	ed unless	i	'
							a State hig	jhway agenc	y substantia	tes the us	.e	
ATMOSPHERICS:	68 deg	F, 50% RH	I				of a different	ent type with	approval of	FHWA.		
Receiver												
Name No.	#DUs	Existing	No Barrier					With Barrier				
		LAeq1h	LAeq1h	1	Increase over		Туре	Calculated	Noise Redu	ction		
			Calculated	Crit'n	Calculated	ļ l	Impact	LAeq1h	Calculated	Goal	Calcula	ated
						Sub'l Inc					minus	
											Goal	
		dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1 1	0.0						72.2			0	0.0
Along Sunset Blvd.	8 1	0.0	70.8	66	70.8	10	Snd Lvl	70.8	0.	0	8	-8.0
Dwelling Units	# DUs	Noise Re	duction									
		Min	Avg	Max								
		dB	dB	dB								
All Selected	2	0.0	0.0	0.0)							
All Impacted	2	0.0	0.0	0.0								
All that meet NR Goal	1	0.0	0.0	0.0								

INPUT: ROADWAYS		П					Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Construc	tion Buildi	ing Phas	е			of a diffe	rent type with	the approv	al of FHW	Δ.
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	unset Go	wer Pı	oject			
				05.11	1 0040							
Eyestone Environmental				25 Ma	rch 2019							
Sean Bui				TNM 2	2.5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Constructi	on Buildiı	ng Phase									
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	S	HTrucks	S	Buses		Motorcy	cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 160	35	5 0	0	8	35	5 (0 0	0) (
	point2		2									

INPUT: RECEIVERS								Sunset G	ower P	roject		
Eyestone Environmental						25 March	2019					
Sean Bui						TNM 2.5						
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Suns	et Gow	er Project		•							
RUN:	Cons	truction	n Building Pha	ase								
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Cr	iteria	1	Active
			X	Y	Z	above	Existing	Impact C	riteria	NR	i	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	(Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB		
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	7	1	5.0	0.0	Υ
Along Sunset Blvd.		8 1	250.0	40.0	0.00	4.92	0.00	6	6	10.0	8.0	Υ

RESULTS: SOUND LEVELS							Sunset Go	wer Proje	ect				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							Calculate	d with TN	M 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunse	Gower Pro	ject									
RUN:		Constr	uction Buil	ding Phase									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement typ	e shall be us	ed unles	s	
								a State h	nighway agend	y substantia	tes the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ				of a diffe	erent type with	approval of	FHWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrie	r			
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Redu	ction		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calculate	d
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.		1 .	1 0.0	65.0)	71 65.0) 5	5	65.0	0.	0	0	0.0
Along Sunset Blvd.	3	8	1 0.0	63.6	6	63.6	6 10)	63.0	6 0.	0	8 -	8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected			2 0.0	0.0) (.0							
All Impacted		(0.0	0.0) (.0							
All that meet NR Goal			1 0.0	0.0) (.0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 1					of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)	-	Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

|

INPUT: TRAFFIC FOR LAeq1h Volumes	П				1		Sunset G	ower Pi	oject			
Eyestone Environmental				25 Ma	∣ rch 2019							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	ver Proje	ect									
RUN:	Overlapping	g 1										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	5 0) () 48	35		0 0)	0
	point2		2									

INPUT: RECEIVERS										Sunset Go	ower Proje	ct	
Eyestone Environmental								25 March	2019				
Sean Bui								TNM 2.5					
INPUT: RECEIVERS													
PROJECT/CONTRACT:	Suns	et Gow	er Proje	ect									
RUN:	Over	lapping	1										
Receiver													
Name	No.	#DUs	Coord	inates (gro	und)			Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Y		Z		above	Existing	Impact Cr	iteria	NR	in
								Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft		ft		ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1		250.0	30.0	0.	00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.		8 1		250.0	40.0	0.	00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	et .		7		
Eyestone Environmental							25 March	 2019					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:	Sur	nset G	ower Pro	ject									
RUN:	Ove	erlapp	ing 1										
BARRIER DESIGN:	INF	PUT H	IEIGHTS					Average p	pavement type	shall be use	ed unless	3	
								a State hi	ghway agenc	y substantiat	es the us	ie .	
ATMOSPHERICS:	68	deg F	, 50% RH					of a differ	ent type with	approval of I	FHWA.		
Receiver													
Name N	o. #Dl	Js E	Existing	No Barrier					With Barrier	-			
		L	_Aeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Redu	ction		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ted
							Sub'l Inc					minus	
												Goal	
		d	BA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	70.8	3 7	70.8	5		70.8	0.0)	0	0.0
Along Sunset Blvd.	8	1	0.0	69.4	1 6	69.4	10	Snd Lvl	69.4	0.0)	8	-8.0
Dwelling Units	# 0)Us I	Noise Red	duction									
		I	Min	Avg	Max								
		(dB	dB	dB								
All Selected		2	0.0	0.0	0.0	0							
All Impacted		1	0.0	0.0	0.0	0							
All that meet NR Goal		1	0.0	0.0	0.0	0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 2					of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)	-	Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

|

INPUT: TRAFFIC FOR LAeq1h Volumes					1		Sunset G	ower Pi	oject			
Eyestone Environmental				25 Ma	∣ rch 2019							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	wer Proje	ect									
RUN:	Overlappin	g 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	5 0) (0 104	35		0 0)	0
	point2		2									

INPUT: RECEIVERS										Sunset Go	ower Proje	ct	
Eyestone Environmental								25 March	2019				
Sean Bui								TNM 2.5					
INPUT: RECEIVERS													
PROJECT/CONTRACT:	Suns	et Gowe	er Proj	ect									
RUN:	Over	apping	2										
Receiver													
Name	No.	#DUs	Coord	dinates (gro	ound)			Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Y		Z		above	Existing	Impact Cr	iteria	NR	in
								Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft		ft		ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1		250.0	30.0	0	.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	:	3 1		250.0	40.0	0	.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS			Y			<u> </u>	Sunset Go	wer Projec	ot				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							-	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overlap	ping 2										
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	SS	
									ghway agency				
ATMOSPHERICS:		68 deg	F, 50% RH						ent type with				
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ited
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	73.8	3 71	73.8	5	Snd Lvl	73.8	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	72.4	66	72.4	10	Snd Lvl	72.4	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.0	0.0)							
All Impacted		2	0.0	0.0	0.0)							
All that meet NR Goal		1	0.0	0.0	0.0)							

INPUT: ROADWAYS							Suns	et Gower Pro	ject	<u> </u>	
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 3					of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)	-	Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				25 Ma	∣ rch 2019							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	wer Proje	ct		1							
RUN:	Overlappin	g 3										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 320	35) (16	35		0 0)	0
	point2		2									

INPUT: RECEIVERS										Sunset Go	ower Proje	ct	
Eyestone Environmental								25 March	2019				
Sean Bui								TNM 2.5					
INPUT: RECEIVERS													
PROJECT/CONTRACT:	Suns	et Gow	er Proj	ect									
RUN:	Over	apping	3										
Receiver													
Name	No.	#DUs	Coord	dinates (gro	ound)			Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Υ		Z		above	Existing	Impact Cr	iteria	NR	in
								Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft		ft		ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1		250.0	30.0	C	.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	:	3 1		250.0	40.0	C	.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS			Y	·		<u> </u>	Sunset Go	wer Projec	ot				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							-	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overlap	ping 3	-									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	SS	
									ghway agency				
ATMOSPHERICS:		68 deg	F, 50% RH						ent type with				
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ited
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1 1	0.0	68.0	71	68.0	5		68.0	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	66.7	66	66.7	10	Snd Lvl	66.7	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
_			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.0	0.0)							
All Impacted		1	0.0	0.0	0.0)							
All that meet NR Goal		1	0.0	0.0	0.0)							

INPUT: ROADWAYS							Suns	et Gower Proj	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Construc	tion Truck	s - Demo	Phase			of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes					1	S	Sunset G	ower Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Constructi	on Truck	s - Demo	Phase								
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	5 () () !	5 35		0 0)	0
	point2		2									

INPUT: RECEIVERS										Sunset Go	ower Proje	ct		
Eyestone Environmental								11 May 20	20					
Sean Bui								TNM 2.5						
INPUT: RECEIVERS														
PROJECT/CONTRACT:	Sun	set Gow	er Project											
RUN:	Con	structio	n Trucks -	Den	no Phase									
Receiver														
Name	No.	#DUs	Coordina	tes	(ground)			Height	Input Sou	nd Levels	and Criteria	a	A	Active
			X		Υ	Z		above	Existing	Impact Cr	iteria	NR	i	n
								Ground	LAeq1h	LAeq1h	Sub'l	Goal	(Calc.
			ft		ft	ft		ft	dBA	dBA	dB	dB		
Along Fountain Ave.		1 1	1 25	50.0	40.0	0	0.00	4.92	0.00	71	5.0		0.0	Υ
Along Gower St.		8 1	1 25	50.0	45.0	כ	0.00	4.92	0.00	66	10.0		8.0	Υ

RESULTS: SOUND LEVELS							Sunset Go	wer Proje	ct				
Eyestone Environmental							11 May 20	20					
								20					
Sean Bui							TNM 2.5						
							Calculate	d with TNI	M 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Constru	uction Truc	ks - Demo	Phase								
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unless	3	
								a State h	ighway agenc	y substantiate	s the us	3 e	
ATMOSPHERICS:		68 deg	F, 50% RH						rent type with	=			
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	rexisting	Type	Calculated	Noise Reduc	tion	-	
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ted
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	59	.7	71 59.7	7 5		59.7	0.0		0	0.0
Along Gower St.	8	3 1	0.0	59).1	59.	1 10		59.1	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0	0.0	.0							
All Impacted		0	0.0	0	0.0	.0							
All that meet NR Goal		1	0.0	0	0.0	.0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					11 May 2020	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Construc	tion Truck	ks - Gradi	ing Phase			of a diffe	rent type with	the approv	al of FHW	۵/
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Co	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.	0.00	Signal	0.00	100	Average	
		point2	2	1.000.0	0.	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect		1							
RUN:	Constructi	on Trucks	s - Gradin	g Phas	е							
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	0) () 20	35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunse	t Gowe	er Project								
RUN:	Const	ruction	Trucks - Gra	ding Phase							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.	1	1	250.0	40.0	0.00	4.92	0.00	71	5.0	0.0	Y
Along Gower St.	8	1	250.0	45.0	0.00	4.92	0.00	66	3 10.0	8.0) Y

RESULTS: SOUND LEVELS								Sunset Go	wer Proje	ct				
Eyestone Environmental								11 May 20	20					
Sean Bui								TNM 2.5						
								Calculated	d with TNI	M 2.5				
RESULTS: SOUND LEVELS														
PROJECT/CONTRACT:		Sunset	Gower Pro	ject										
RUN:		Constr	uction Truc	ks - Gradi	ing Phase									
BARRIER DESIGN:		INPUT	HEIGHTS						Average	pavement type	shall be use	d unles	s	
									a State h	ighway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ					of a diffe	rent type with	approval of F	HWA.		
Receiver														
Name	No.	#DUs	Existing	No Barrie	r					With Barrier				
			LAeq1h	LAeq1h			Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculate	d Crit'n		Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcul	ated
								Sub'l Inc					minus	
													Goal	
			dBA	dBA	dBA		dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1 1	0.0	6	55.1	71	65.1	5		65.1	0.0		0	0.0
Along Gower St.	8	3 1	0.0	6	64.5	66	64.5	10		64.5	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction										
			Min	Avg	Max									
			dB	dB	dB									
All Selected		2	0.0		0.0	0.0)							
All Impacted		0	0.0		0.0	0.0)							
All that meet NR Goal		1	0.0		0.0	0.0)							

INPUT: ROADWAYS							Suns	et Gower Proj	ject		
Eyestone Environmental					11 May 2020)					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	on Phase 2	2 A				of a diffe	rent type with	the approv	al of FHW	Δ.
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes	П						Sunset Go	wer Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Foundation	n Phase 2	Α									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTrucks	3	Buses		Motorcy	cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	, c) (35	35	0	0	C)
	point2	2	2									

INPUT: RECEIVERS								Sunset G	ower Pro	ject		
Eyestone Environmental						11 May 20	20					
Sean Bui						TNM 2.5						
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Sunse	et Gow	er Project		1							
RUN:	Found	dation l	Phase 2A									
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Crite	ria		Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR		in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal		Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB		
Along Fountain Ave.	1	1	250.0	40.0	0.00	4.92	0.00	7′	1 5	5.0	0.0	Υ
Along Gower St.	8	3 1	250.0	45.0	0.00	4.92	0.00	66	3 10	0.0	8.0	Υ

RESULTS: SOUND LEVELS				,				Sunset Go	wer Projec	et .		1		
Eyestone Environmental								11 May 20	20					
									20					
Sean Bui								TNM 2.5						
								Calculated	d with TNN	1 2.5				
RESULTS: SOUND LEVELS														
PROJECT/CONTRACT:		Sunset	Gower Pro	ject										
RUN:		Founda	tion Phase	2A										
BARRIER DESIGN:		INPUT	HEIGHTS						Average p	pavement type	shall be use	d unless		
									a State hi	ghway agency	y substantiate	s the us	е	
ATMOSPHERICS:		68 deg	F, 50% RH							ent type with				
Receiver														
Name	No.	#DUs	Existing	No Barrier						With Barrier				
			LAeq1h	LAeq1h		ı	Increase over	existing	Type	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	(Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
								Sub'l Inc					minus	
													Goal	
			dBA	dBA	dBA	c	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	67	'.4	71	67.4	5		67.4	0.0		0	0.0
Along Gower St.	8	3 1	0.0	66	5.8	66	66.8	10	Snd Lvl	66.8	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction										
			Min	Avg	Max									
			dB	dB	dB									
All Selected		2	0.0	0	0.0	0.0								
All Impacted		1	0.0	0	0.0	0.0								
All that meet NR Goal		1	0.0	0	0.0	0.0								

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	Si
PROJECT/CONTRACT:	Sunset G	ower Proj	ject				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	ion Phase	2B				of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)	-	Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.	.00 Signal	0.00	100	Average	
		point2	2	1.000.0	0.0	0.	00				

INPUT: TRAFFIC FOR LAeq1h Volumes						8	Sunset G	ower Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Foundation	n Phase 2	B									
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motoro	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	4 35	() () 48	35		0 ()	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Foun	dation I	Phase 2B								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.		1 1	250.0	40.0	0.00	4.92	0.00	7′	5.0	0.0) Y
Along Gower St.	8	3 1	250.0	45.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	t				
Eyestone Environmental							11 May 20	20					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Founda	ition Phase	2B									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	s	
								a State hi	ghway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ				of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	68	3.8 7	1 68.8	5		68.8	0.0		0	0.0
Along Gower St.	8	3 1	0.0	68	3.1 6	6 68.1	10	Snd Lvl	68.1	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	C	0.0								
All Impacted		1	0.0	C	0.0	0							
All that meet NR Goal		1	0.0	C	0.0	0							

INPUT: ROADWAYS							Suns	et Gower Proj	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State hi	ighway agend	y substant	iates the u	se
RUN:	Foundati		of a differ	rent type with	the approv	al of FHW	A				
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Con	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes	П						Sunset Go	wer Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	2.5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Foundation	n Phase 3										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTrucks	3	Buses		Motorcy	cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	, c) (39	35	0	0	C)
	point2	2	2									

INPUT: RECEIVERS								Sunset G	ower Proje	ect	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunse	et Gowe	er Project								
RUN:	Found	dation F	Phase 3	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.	1	1	250.0	40.0	0.00	4.92	0.00	7′	5.	0 0.	0 Y
Along Gower St.	8	3 1	250.0	45.0	0.00	4.92	0.00	66	6 10.	0 8.	0 Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	:t				
Functions Fundamental							44 May 00						
Eyestone Environmental							11 May 20	120					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Founda	tion Phase	3									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	oavement type	shall be use	d unles	ss	
								a State hi	ghway agency	y substantiate	es the u	ise	
ATMOSPHERICS:		68 deg	F, 50% RH						ent type with	-			
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcul	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	67.	9 71	67.9	5		67.9	0.0		0	0.0
Along Gower St.	8	3 1	0.0	67.	2 66	67.2	10	Snd Lvl	67.2	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.									
All Impacted		1	0.0	0.	0.0								
All that meet NR Goal		1	0.0	0.	0.0								

INPUT: ROADWAYS		П					Suns	et Gower Pro	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	 e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Construc	tion Build	ing Phas	е			of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						8	Sunset G	ower Pi	roject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Constructi	on Buildi	ng Phase									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 160	35	5 () () 4	4 35	5	0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Cons	ruction	Building Pha	ase							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.		1	250.0	40.0	0.00	4.92	0.00	7′	5.0	0.0) Y
Along Gower St.	3	3 1	250.0	45.0	0.00	4.92	0.00	66	3 10.0	8.0) Y

RESULTS: SOUND LEVELS							;	Sunset Go	wer Proje	ct				
Eyestone Environmental								11 May 20	20					
									20					
Sean Bui								TNM 2.5						
DEGUI TO GOUND EVEL O								Calculated	a with INI	WI 2.5				
RESULTS: SOUND LEVELS														
PROJECT/CONTRACT:		Sunset	Gower Pro	oject										
RUN:		Constr	uction Buil	ding Phase										
BARRIER DESIGN:		INPUT	HEIGHTS						Average	pavement type	shall be use	d unless	i	
									a State h	ighway agenc	y substantiate	s the us	е	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ					of a diffe	rent type with	approval of F	HWA.		
Receiver														
Name	No.	#DUs	Existing	No Barrier						With Barrier		-		
			LAeq1h	LAeq1h		lr	ncrease over	existing	Type	Calculated	Noise Reduc	tion	-	
				Calculated	Crit'n	C	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ited
								Sub'l Inc					minus	
													Goal	
			dBA	dBA	dBA	d	lB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	62	.3	71	62.3	5		62.3	0.0		0	0.0
Along Gower St.	8	3 1	0.0	61	.7	66	61.7	10		61.7	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction										
			Min	Avg	Max									
			dB	dB	dB									
All Selected		2	0.0	0	.0 0	0.0								
All Impacted		0	0.0	0	.0 0	0.0								
All that meet NR Goal		1	0.0	0	.0 0	0.0								

INPUT: ROADWAYS							Suns	et Gower Proj	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 1			of a diffe	rent type with	the approv	al of FHW	A		
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes					1		Sunset G	ower Pr	oject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	ver Proje	ect									
RUN:	Overlappin	g 1										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	5 () () 24	35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	∍ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project		'						
RUN:	Overl	apping	1	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	above	Existing	Impact C	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.	,	1 1	250.0	40.0	0.00	4.92	0.00	7	1 5.	0 0.	0 Y
Along Gower St.	8	3 1	250.0	45.0	0.00	4.92	0.00	66	3 10.	0 8.	0 Y

RESULTS: SOUND LEVELS			·				,	Sunset Go	wer Projec	et .	·			
Franksis Franksis								44 М 00	00					
Eyestone Environmental								11 May 20	20					
Sean Bui								TNM 2.5						
								Calculated	d with TNN	1 2.5				
RESULTS: SOUND LEVELS														
PROJECT/CONTRACT:		Sunset	Gower Pro	oject										
RUN:		Overla	oping 1											
BARRIER DESIGN:		INPUT	HEIGHTS						Average p	pavement type	shall be use	d unles	s	
									a State hi	ghway agency	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ					of a differ	ent type with	approval of F	HWA.		
Receiver														
Name	No.	#DUs	Existing	No Barrier	,					With Barrier	÷			
			LAeq1h	LAeq1h			Increase over	existing	Type	Calculated	Noise Reduc	tion		
				Calculated	Crit'n		Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcu	ılated
								Sub'l Inc					minu	s
													Goal	
			dBA	dBA	dBA		dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	,	1 1	0.0	66	3.9	71	66.9	5		66.9	0.0		0	0.0
Along Gower St.	3	3 1	0.0	66	3.3	66	66.3	10	Snd Lvl	66.3	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction										
			Min	Avg	Max									
			dB	dB	dB									
All Selected		2	0.0	(0.0	0.0								
All Impacted		1	0.0	(0.0	0.0								
All that meet NR Goal		1	0.0	(0.0	0.0								

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	Si
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 2					of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0) (0.00 Signal	0.00	100	Average	
		point2	2	1,000.0	0.0) (0.00				

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject				_
Eyestone Environmental				11 Ma	y 2020								
Sean Bui				TNM 2	.5		ı						
INPUT: TRAFFIC FOR LAeq1h Volumes													
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct										
RUN:	Overlappin	ıg 2											
Roadway	Points												
Name	Name	No.	Segmer	nt									
			Autos		MTruck	s	HTruck	S	Buses		Motorc	ycles	
			V	S	V	S	V	S	V	S	V	S	
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	
Haul Route	point1		1 184	35	() (52	2 35		0 (ס	0	(
	point2		2										

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Overl	apping	2	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Υ	Z	above	Existing	Impact Cr	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.	,	1 1	250.0	40.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Gower St.	8	3 1	250.0	45.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS			,				Sunset Go	wer Projec	:t				
Eyestone Environmental							11 May 20	20					
Sean Bui							TNM 2.5						
							Calculated	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overla	pping 2										
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	s	
								a State hi	ghway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ				of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	69.	7 71	69.7	5		69.7	0.0		0	0.0
Along Gower St.	8	3 1	0.0	69.	0 66	69.0	10	Snd Lvl	69.0	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0 0.0)							
All Impacted		1	0.0										
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS							Suns	et Gower Proj	ject		
Eyestone Environmental					11 May 2020						
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the us	se
RUN:	Overlapp	ing 3					of a diffe	rent type with	the approv	al of FHW	4
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						8	Sunset G	ower Pi	roject			
Eyestone Environmental				11 Ma	y 2020							
Sean Bui				TNM 2	.5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect		1							
RUN:	Overlappin	ıg 3										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 320	35	() () (8 35	5	0 (0	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Projec	ct	
Eyestone Environmental						11 May 20	20				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunse	t Gowe	er Project								
RUN:	Overla	apping	3								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Υ	Z	above	Existing	Impact Cr	iteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Fountain Ave.	1	1	250.0	40.0	0.00	4.92	0.00	71	5.0	0.0	Υ
Along Gower St.	8	1	250.0	45.0	0.00	4.92	0.00	66	10.0	8.0	Y

RESULTS: SOUND LEVELS		·r	1			·	Sunset Gower Project						
Eyestone Environmental							11 May 20	120					
Sean Bui							TNM 2.5	720					
Sean Bui								al::41a TNI	M 0 5				
RESULTS: SOUND LEVELS							Calculate	u with IN	IVI 2.5				
PROJECT/CONTRACT:		Sunset	Gower Pro	niect									
RUN:		Overlap),cci									
BARRIER DESIGN:			HEIGHTS					Avorago	navement type	chall be us	od uploce		
BARRIER DESIGN.		INFUI	пеівніз						pavement type				
ATMOSPHERICS:		CO dos	E 500/ DI	•					ighway agenc	=		e	
		bo deg	F, 50% RH	<u> </u>	-	+		or a diffe	erent type with	approval of	гпииА.	_	
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Type	Calculated	Noise Redu	ction		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calculat	ed
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Fountain Ave.	1	1	0.0	65.3	3 7	1 65.3	5 5		65.3	0.	0	0	0.0
Along Gower St.	8	3 1	0.0	64.7	6	64.7	10		64.7	0.	0	8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.0	0.0)							
All Impacted		0	0.0	0.0	0.0	ס							
All that meet NR Goal		1	0.0	0.0	0.0	0							



Project: Sunset Gower Project

Construction Vibration Impacts

Reference Levels at 25 feet are based on FTA, 2006 (Transit Noise and Vibration Impact Assessment)

Calculations using FTA procedure with n= 1.5 (for receptors 25 feet or greater)

n= **1.1** (for receptors less than 25 feet, per Caltrans procedure)

ON-SITE CONSTRUCTION ACTIVITIES

Table 1: Estimated Construction Equipment Vibration Levels (PPV) - Building Damages

		Estimate	ed Vibration Le	vels at neares	t off-site build	ing structures	(distance in fe	et), PPV
	Reference Vibration Levels at 25	Single-Story Commercial Building to the North	Two-Story Commercial Building the South	Residential buildings to the West	Residential buildings to the East	On-Site Structure	Bldg. 25	
Equipment	ft., PPV	100	65	275	60	10	25	
Large Bulldozer	0.089	0.011	0.021	0.002	0.024	0.244	0.089	
Caisson Drilling	0.089	0.011	0.021	0.002	0.024	0.244	0.089	
Loaded Trucks	0.076	0.010	0.018	0.002	0.020	0.208	0.076	
Jackhammer	0.035	0.004	0.008	0.001	0.009	0.096	0.035	
Small bulldozer	0.003	0.000	0.001	0.000	0.001	0.008	0.003	
Significance	Threshold, PPV	0.3	0.3	0.2	0.2	0.12	0.2	

Table 2: Estimated Construction Equipment Vibration Levels (VdB) - Human Annoyance

	Reference Vibration	Estir	Estimated Vibration Levels at Off-Site Receptors (at note distance in feet), VdB						
	Levels at 25	R1	R2	R3	R4	R5			
Equipment	ft., VdB	60	65	275	185	385			
Large Bulldozer	87	76	75	56	61	51			
Caisson Drilling	87	76	75	56	61	51			
Loaded Trucks	86	75	74	55	60	50			
Jackhammer	79	68	67	48	53	43			
Small bulldozer	58	47	46	27	32	22			
Sig	nificance Threshold, VdB	72	72	72	72	75			

OFF-SITE CONSTRUCTION HAUL TRUCKS

Table 3: Off-Site Haul Trucks - Building Damage

Reference Vibration		Estimated Vibration Levels at noted distance in feet, PPV							
Equipment	Levels at 50 ft., PPV	20							
Typical road surface	0.00565	0.022							
Significance T	hreshold, PPV	0.12							

Ref. Levels based on FTA Figure 7-3 (converted from VdB to PPV)

Table 4: Off-Site Haul Trucks - Human Annoyance

	Reference Vibration	Estimated Vibration Levels at noted distance in feet, VdB								
Equipment	Levels at 50 ft., VdB	30								
Typical road surface	63	70								
Significance Threshold, VdB		72								

Ref. Levels based on FTA Figure 7-3

Operation Noise Calculations Project



Project Composite Noise Calculations (CNEL)Project: Sunset Gower

							Project	Ambient +	
Receptor	Ambient	Traffic ^a	Mechanical	Parking	Loading	Outdoor	Composite	Project	Increase
R1	62.8	50.7	39.0	56.6	30.6	50.0	58.3	64.1	1.3
R2	66.6	60.2	42.9	52.5	28.5	45.1	61.1	67.7	1.1
R3	67.7	54.0	37.1	30.9	33.3	61.1	61.9	68.7	1.0
R4	77.0	60.7	41.8	27.1	26.0	65.1	66.4	77.4	0.4
R5	69.3	61.7	45.8	40.0	27.5	63.1	65.5	70.8	1.5

^a - traffic noise levels at each receptor is based on the traffic noise analysis for the roadway segment in front of the receptor.

		Traffic N	Noise Levels,	CNEL					distance to	
			Existing +	Project	distance to		Existing +		Center	adj. for
Receptor	Roadway Segment	Existing	Project	Only	roadway, ft	Existing	Project	barrier	Line	distance
R1	Gordon St.	60.9	61.3	50.7	10	60.9	61.3	0	30	0.0
R2	Fountain Ave.	70.4	70.8	60.2	10	70.4	70.8	0	30	0.0
R3	Gower St.	70.3	70.4	54.0	10	70.3	70.4	0	35	0.0
R4	Sunset Blvd.	74.0	74.2	60.7	10	74.0	74.2	0	40	0.0
R5	Gordon St.	64.6	66.4	61.7	10	64.6	66.4	0	30	0.0



Outdoor Mechanical Equipment Noise Calculations Project: Sunset Gower

Project:

Hours of Operations

	riouro er operatione				
	Estimated No	oise Levels,	Ld (7am to	Le (7pm to	Ln (10pm to
	Leq from SC	UNDPLAN	7pm)	10pm)	7am)
Receptor	Leq	CNEL	12	3	9
R1	32.3	39.0	32.3	32.3	32.3
R2	36.2	42.9	36.2	36.2	36.2
R3	30.4	37.1	30.4	30.4	30.4
R4	35.1	41.8	35.1	35.1	35.1
R5	39.1	45.8	39.1	39.1	39.1

		Ambient +			
	Ambient	Project	Increase		Ambient +
Receptor	CNEL	(CNEL)	(CNEL)	ambient (Leq)	Project (Leq)
R1	62.8	62.8	0.0	56.9	56.9
R2	66.6	66.6	0.0	59.8	59.8
R3	67.7	67.7	0.0	61.8	61.8
R4	77.0	77.0	0.0	72.0	72.0
R5	69.3	69.3	0.0	63.5	63.5



Parking Structure Noise Calculations Project: Sunset Gower

Project:

Hours of Operations

	Estimated N	Noise Levels,	Ld (7am to	Le (7pm to	Ln (10pm to			
	Leq from S	OUNDPLAN	7pm)	10pm)	7am)			
Receptor	Leq	CNEL	12	3	9			
R1	49.9	56.6	49.9	49.9	49.9			
R2	45.8	52.5	45.8	45.8	45.8			
R3	24.2	30.9	24.2	24.2	24.2			
R4	20.4	27.1	20.4	20.4	20.4			
R5	33.3	40.0	33.3	33.3	33.3			
				_				

		Ambient +		nighttime	Ambient +	
	Ambient	Project	Increase	ambient	Project	Increase
Receptor	CNEL	(CNEL)	(CNEL)	(Leq)	(Leq)	(Leq)
R1	62.8	63.7	0.9	56.9	57.7	8.0
R2	66.6	66.8	0.2	59.8	60.0	0.2
R3	67.7	67.7	0.0	61.8	61.8	0.0
R4	77.0	77.0	0.0	72.0	72.0	0.0
R5	69.3	69.3	0.0	63.5	63.5	0.0



Outdoor Noise Calculations

Project: Sunset Gower

ALL LEVEL Hours of Operations

					Ld (7am to	Le (7pm to	Ln (10pm to
	Estimated nois	se levels, Leq	(FROM SOUN	DPLAN)	7pm)	10pm)	7am)
Receptor	Sound System	Occupants	Total, Leq	CNEL	11	3	2
R1	47.4	35.4	47.7	50.0	47.3	47.7	41.2
R2	42.5	31.4	42.8	45.1	42.4	42.8	36.3
R3	58.5	46.6	58.8	61.1	58.4	58.8	52.3
R4	62.6	49.8	62.8	65.1	62.4	62.8	56.3
R5	60.8	40.3	60.8	63.1	60.4	60.8	54.3

TOTAL COMBINED

			Ambient +		Project		
		Ambient	Project	Increase	Noise,	Ambient	Ambient +
Receptor	Project (CNEL)	(CNEL)	(CNEL)	(CNEL)	(Leq)	(Leq)	Project (Leq)
R1	50.0	62.8	63.0	0.2	47.7	56.9	57.4
R2	45.1	66.6	66.6	0.0	42.8	59.8	59.9
R3	61.1	67.7	68.6	0.9	58.8	61.8	63.6
R4	65.1	77.0	77.3	0.3	62.8	72.0	72.5
R5	63.1	69.3	70.2	0.9	60.8	63.5	65.4



Loading and Trash Compactor Noise Calculations Project: Sunset Gower

	Estimated Levels, Louis	eq from	Ld (7am to 7pm)	Le (7pm to 10pm)	Ln (10pm to 7am)
Receptor	Lea	CNEL	3	3	0
R1	33.4	30.6	27.4	33.4	0.0
R2	31.3	28.5	25.3	31.3	0.0
R3	36.1	33.3	30.1	36.1	0.0
R4	28.8	26.0	22.8	28.8	0.0
R5	30.3	27.5	24.3	30.3	0.0

			Ambient +				Ambient +
	Project	Ambient	Project	Increase	Project	daytime	Project
Receptor	CNEL	CNEL	(CNEL)	(CNEL)	Noise, (Leq)	ambient (Leq)	(Leq)
R1	30.6	62.8	62.8	0.0	33.4	61.1	61.1
R2	28.5	66.6	66.6	0.0	31.3	66.2	66.2
R3	33.3	67.7	67.7	0.0	36.1	66.2	66.2
R4	26.0	77.0	77.0	0.0	28.8	73.3	73.3
R5	27.5	69.3	69.3	0.0	30.3	67.6	67.6

Sunset Gower Source Levels in dB(A) - Mechanical

Name	Source type	Lw	
		dB(A)	
Building B - Mechanical L1	Point	90.0	
Building B - Mechanical L2	Point	90.0	
Building B - Mechanical L3	Point	90.0	
Building B - Mechanical L4	Point	90.0	
Building B - Mechanical L5	Point	90.0	
Building B - Mechanical L6	Point	90.0	
Building C - Mechanical L1	Point	90.0	
Building C - Mechanical L2	Point	90.0	
Building C - Mechanical L3	Point	90.0	
Building C - Mechanical L4	Point	90.0	
Building C - Mechanical L5	Point	90.0	
Building C - Mechanical L6	Point	90.0	
Cooling Tower 1	Point	100.0	
Cooling Tower 2	Point	100.0	
Cooling Tower 3	Point	100.0	

Source	Ld				
Source					
	dB(A)				
Receiver R1 Ld 32.3 dB(A)					
Cooling Tower 1	23.9				
Cooling Tower 2	21.4				
Cooling Tower 3	20.6				
Building B - Mechanical L1	22.3				
Building C - Mechanical L1	22.2				
Building B - Mechanical L2	19.9				
Building C - Mechanical L2	20.6				
Building B - Mechanical L3	19.6				
Building C - Mechanical L3	20.1				
Building B - Mechanical L4	19.2				
Building C - Mechanical L4	19.5				
Building B - Mechanical L5	18.8				
Building C - Mechanical L5	18.8				
Building B - Mechanical L6	18.8				
Building C - Mechanical L6	18.3				
Receiver R2 Ld 36.2 dB(A)					
Cooling Tower 1	15.3				
Cooling Tower 2	15.5				
Cooling Tower 3	16.3				
Building B - Mechanical L1	23.3				
Building C - Mechanical L1	24.0				
Building B - Mechanical L2	21.8				
Building C - Mechanical L2	23.2				
Building B - Mechanical L3	24.4				
Building C - Mechanical L3	26.2				
Building B - Mechanical L4	24.7				
Building C - Mechanical L4	26.7				
Building B - Mechanical L5	25.1				
Building C - Mechanical L5	27.2				
Building B - Mechanical L6	25.3				
Building C - Mechanical L6	27.7				
Receiver R3 Ld 30.4 dB(A)	Receiver R3 Ld 30.4 dB(A)				
Cooling Tower 1	21.8				
Cooling Tower 2	22.0				
Cooling Tower 3	20.2				
Building B - Mechanical L1	16.3				
Building C - Mechanical L1	19.3				
Building B - Mechanical L2	15.8				
Building C - Mechanical L2	18.4				

Source	Ld	
	dB(A)	
Building B - Mechanical L3	15.8	
Building C - Mechanical L3	17.1	
Building B - Mechanical L4	15.9	
Building C - Mechanical L4	17.2	
Building B - Mechanical L5	16.3	
Building C - Mechanical L5	17.5	
Building B - Mechanical L6	18.7	
Building C - Mechanical L6	19.2	
Receiver R4 Ld 35.1 dB(A)	-	
Cooling Tower 1	28.2	
Cooling Tower 2	28.2	
Cooling Tower 3	30.2	
Building B - Mechanical L1	19.2	
Building C - Mechanical L1	17.8	
Building B - Mechanical L2	19.8	
Building C - Mechanical L2	16.1	
Building B - Mechanical L3	20.6	
Building C - Mechanical L3	15.2	
Building B - Mechanical L4	22.6	
Building C - Mechanical L4	15.2	
Building B - Mechanical L5	16.2	
Building C - Mechanical L5	14.9	
Building B - Mechanical L6	18.8	
Building C - Mechanical L6	17.4	
Receiver R5 Ld 39.1 dB(A)		
Cooling Tower 1	30.6	
Cooling Tower 2	30.6	
Cooling Tower 3	30.6	
Building B - Mechanical L1	22.4	
Building C - Mechanical L1	22.1	
Building B - Mechanical L2	22.4	
Building C - Mechanical L2	21.7	
Building B - Mechanical L3	26.4	
Building C - Mechanical L3	25.3	
Building B - Mechanical L4	27.2	
Building C - Mechanical L4	25.9	
Building B - Mechanical L5	28.0	
Building C - Mechanical L5	26.6	
Building B - Mechanical L6	28.8	
Building C - Mechanical L6	27.3	

Sunset Gower Source Levels in dB(A) - People

Source	Ld	
	dB(A)	
Receiver R1 Ld 35.4 dB(A)	uB(//)	
	40.0	
People - Level 1 Plaza	10.9	
People - Level 1 Paseo	19.7	
People - Level 1 Plaza (Bldg B&C)	16.5	
People - Level 1 Central Plaza	27.4	
People - Building A Level 2	16.1	
People - Building B&C Level 2	12.1	
People - Building B Level 3 W	12.9	
People - Building B Level 3 S	13.1	
People - Building B Level 3 E	19.2	
People - Building B Level 3 N	6.3	
People - Building A Level 3	5.5	
People - Building B&C Level 4	15.9	
People - Building B&C Level 4	12.6	
People - Building A Level 4	20.1	
People - Building B&C Level 5	16.7	
People - Building A Level 5	6.8	
People - Building C Level 6	13.8	
People - Building B Level 6	24.5	
People - Building A Level 6	22.3	
People - Building A Level 7 SW	17.9	
People - Building A Level 7	7.5	
People - Building A Level 8	24.1	
People - Building A Level 9	8.3	
People - Building A Level 10 NW	14.0	
People - Building A Level 10 SE	29.3	
People - Building A Level 11	8.5	
People - Building A Level 12	20.0	
People - Building A Level 13	7.9	
People - Building A Level 12	19.8	
People - Building A Level 15	7.7	
People - Building A Level 16 NW	11.2	
People - Building A Level 16 E	20.8	
People - Building A Level 17	8.4	
People - Building A Level 18	24.7	
1		

9

Source	Ld		
	dB(A)		
Receiver R2 Ld 31.4 dB(A)			
People - Level 1 Plaza	8.3		
People - Level 1 Paseo	18.4		
People - Level 1 Plaza (Bldg B&C)	18.1		
People - Level 1 Central Plaza	24.6		
People - Building A Level 2	12.9		
People - Building B&C Level 2	12.2		
People - Building B Level 3 W	12.6		
People - Building B Level 3 S	21.6		
People - Building B Level 3 E	14.5		
People - Building B Level 3 N	3.2		
People - Building A Level 3	1.3		
People - Building B&C Level 4	15.7		
People - Building B&C Level 4	22.7		
People - Building A Level 4	13.2		
People - Building B&C Level 5	17.7		
People - Building A Level 5	1.3		
People - Building C Level 6	16.0		
People - Building B Level 6	21.3		
People - Building A Level 6	14.4		
People - Building A Level 7 SW	11.3		
People - Building A Level 7	1.3		
People - Building A Level 8	16.1		
People - Building A Level 9	1.3		
People - Building A Level 10 NW	13.3		
People - Building A Level 10 SE	18.6		
People - Building A Level 11	1.2		
People - Building A Level 12	8.0		
People - Building A Level 13	1.4		
People - Building A Level 12	8.9		
People - Building A Level 15	1.2		
People - Building A Level 16 NW	10.4		
People - Building A Level 16 E	10.8		
People - Building A Level 17 People - Building A Level 18	0.7		
	15.2	I	

9

Receiver R3 Ld 46.6 dB(A)	dB(A)	
Receiver R3 Ld 46.6 dB(A)	- ()	
People - Level 1 Plaza	14.3	
People - Level 1 Paseo	31.7	
People - Level 1 Plaza (Bldg B&C)	35.6	
People - Level 1 Central Plaza	33.3	
People - Building A Level 2	20.0	
People - Building B&C Level 2	31.8	
People - Building B Level 3 W	32.8	
People - Building B Level 3 S	10.3	
People - Building B Level 3 E	10.2	
People - Building B Level 3 N	11.3	
People - Building A Level 3	5.2	
People - Building B&C Level 4	37.8	
People - Building B&C Level 4	10.2	
People - Building A Level 4	26.0	
People - Building B&C Level 5	38.7	
People - Building A Level 5	5.1	
People - Building C Level 6	36.4	
People - Building B Level 6	38.4	
People - Building A Level 6	28.9	
People - Building A Level 7 SW	32.1	
People - Building A Level 7	5.1	
People - Building A Level 8	32.7	
People - Building A Level 9	5.1	
People - Building A Level 10 NW	35.1	
People - Building A Level 10 SE	31.0	
People - Building A Level 11	5.5	
People - Building A Level 12	2.6	
People - Building A Level 13	5.2	
People - Building A Level 12	3.0	
People - Building A Level 15	5.2	
People - Building A Level 16 NW	29.5	
People - Building A Level 16 E	3.2	
People - Building A Level 17	5.2	
People - Building A Level 18	20.5	

9

	dB(A)	
	IUDIAI	
Receiver R4 Ld 49.8 dB(A)	- ()	
People - Level 1 Plaza	47.5	
People - Level 1 Paseo	40.1	
People - Level 1 Plaza (Bldg B&C)	14.4	
People - Level 1 Central Plaza	30.7	
People - Building A Level 2	12.9	
People - Building B&C Level 2	6.2	
People - Building B Level 3 W	8.6	
People - Building B Level 3 S	0.3	
People - Building B Level 3 E	9.3	
People - Building B Level 3 N	9.4	
People - Building A Level 3	41.0	
People - Building B&C Level 4	12.5	
People - Building B&C Level 4	0.6	
People - Building A Level 4	12.9	
People - Building B&C Level 5	13.5	
People - Building A Level 5	36.0	
People - Building C Level 6	9.1	
People - Building B Level 6	21.6	
People - Building A Level 6	12.8	
People - Building A Level 7 SW	10.9	
People - Building A Level 7	33.8	
People - Building A Level 8	13.1	
People - Building A Level 9	31.4	
People - Building A Level 10 NW	31.7	
People - Building A Level 10 SE	29.2	
People - Building A Level 11	27.6	
People - Building A Level 12	22.4	
People - Building A Level 13	27.2	
People - Building A Level 12	21.1	
People - Building A Level 15	26.0	
People - Building A Level 16 NW	28.2	
People - Building A Level 16 E	20.1	
People - Building A Level 17	24.0	
People - Building A Level 18	31.3	

9

Source	Ld	
	dB(A)	
Receiver R5 Ld 40.3 dB(A)	- ()	
People - Level 1 Plaza	21.1	
People - Level 1 Paseo	19.4	
People - Level 1 Plaza (Bldg B&C)	14.9	
People - Level 1 Central Plaza	32.9	
People - Building A Level 2	15.7	
People - Building B&C Level 2	10.2	
People - Building B Level 3 W	11.0	
People - Building B Level 3 S	2.6	
People - Building B Level 3 E	19.9	
People - Building B Level 3 N	16.6	
People - Building A Level 3	12.4	
People - Building B&C Level 4	16.7	
People - Building B&C Level 4	2.8	
People - Building A Level 4	16.9	
People - Building B&C Level 5	16.3	
People - Building A Level 5	20.0	
People - Building C Level 6	13.9	
People - Building B Level 6	29.3	
People - Building A Level 6	19.6	
People - Building A Level 7 SW	9.3	
People - Building A Level 7	21.4	
People - Building A Level 8	19.1	
People - Building A Level 9	24.1	
People - Building A Level 10 NW	28.4	
People - Building A Level 10 SE	35.1	
People - Building A Level 11	22.2	
People - Building A Level 12	25.3	
People - Building A Level 13	20.6	
People - Building A Level 12	24.0	
People - Building A Level 15	19.2	
People - Building A Level 16 NW	25.3	
People - Building A Level 16 E	23.4	
People - Building A Level 17	19.1	
People - Building A Level 18	30.3	

Sunset Gower Source Levels in dB(A) - Speakers

Name	Source type	Lw	
		dB(A)	
Speakers - Building A Level 16	Point	118.6	
Speakers - Building A Level 16	Point	118.6	
Speakers - Building A Level 16	Point	118.6	
Speakers - Building A Level 16	Point	118.6	
Speakers - Building A Level 16	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers - Building A Level 18	Point	118.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building A Level 10	Point	113.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Building B Level 6	Point	118.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	

Sunset Gower Source Levels in dB(A) - Speakers

3

Name	Source type	Lw
		dB(A)
Speakers Level 1 Central Plaza	Point	118.6
Speakers Level 1 Central Plaza	Point	118.6
<u> </u>	1 2	

Source	Ld	
	dB(A)	
Receiver R1 Ld 47.4 dB(A)		
Speakers Level 1	7.8	
Speakers Level 1	7.8	
Speakers Level 1	7.8	
Speakers Level 1 Central Plaza	34.6	
Speakers Level 1 Central Plaza	22.8	
Speakers Level 1 Central Plaza	38.4	
Speakers Level 1 Central Plaza	22.5	
Speakers Level 1 Central Plaza	20.1	
Speakers Level 1 Central Plaza	32.0	
Speakers Level 1	27.9	
Speakers Level 1	18.6	
Speakers Building B Level 6	29.8	
Speakers Building B Level 6	29.5	
Speakers Building B Level 6	29.5	
Speakers Building B Level 6	20.9	
Speakers Building B Level 6	29.7	
Speakers Building B Level 6	18.1	
Speakers Building B Level 6	30.4	
Speakers Building B Level 6	35.8	
Speakers Building B Level 6	32.0	
Speakers Building A Level 10	8.6	
Speakers Building A Level 10	8.9	
Speakers Building A Level 10	7.4	
Speakers Building A Level 10	5.9	
Speakers Building A Level 10	6.3	
Speakers Building A Level 10	36.4	
Speakers Building A Level 10	38.2	
Speakers Building A Level 10	7.7	
Speakers Building A Level 10	7.5	
Speakers - Building A Level 16	10.9	
Speakers - Building A Level 16	12.2	
Speakers - Building A Level 16	12.3	
Speakers - Building A Level 16	12.4	
Speakers - Building A Level 16	13.5	
Speakers - Building A Level 18	40.3	
Speakers - Building A Level 18	40.3	
Speakers - Building A Level 18	13.0	
Speakers - Building A Level 18	15.8	
Speakers - Building A Level 18	12.2	
Speakers - Building A Level 18	12.8	

4	۶	٠
۹	L	1
3	9	7
۹	١	4
	7	_

Source	Ld	
	dB(A)	
Speakers - Building A Level 18	13.6	
Receiver R2 Ld 42.5 dB(A)	10.0	
Speakers Level 1	7.4	
Speakers Level 1	6.5	
Speakers Level 1	6.4	
Speakers Level 1 Central Plaza	35.8	
Speakers Level 1 Central Plaza	18.1	
Speakers Level 1 Central Plaza	30.1	
Speakers Level 1 Central Plaza	19.8	
Speakers Level 1 Central Plaza	20.2	
• ·	28.4	
Speakers Level 1 Central Plaza Speakers Level 1	36.6	
Speakers Level 1	29.9	
Speakers Level 1 Speakers Building B Level 6	29.9	
Speakers Building B Level 6	25.9	
Speakers Building B Level 6	26.1	
Speakers Building B Level 6	28.9	
Speakers Building B Level 6	26.8	
Speakers Building B Level 6	20.6	
Speakers Building B Level 6	28.1	
Speakers Building B Level 6	28.0	
Speakers Building B Level 6	28.5	
Speakers Building A Level 10	7.9	
Speakers Building A Level 10	8.3	
Speakers Building A Level 10	5.7	
Speakers Building A Level 10	4.0	
Speakers Building A Level 10	4.0	
Speakers Building A Level 10	10.0	
Speakers Building A Level 10	21.9	
Speakers Building A Level 10	7.4	
Speakers Building A Level 10	7.4	
Speakers - Building A Level 16	8.7	
Speakers - Building A Level 16	12.1	
Speakers - Building A Level 16	12.1	
Speakers - Building A Level 16	12.4	
Speakers - Building A Level 16	12.9	
Speakers - Building A Level 18	30.9	
Speakers - Building A Level 18	26.4	
Speakers - Building A Level 18	9.1	
Speakers - Building A Level 18	9.7	
Speakers - Building A Level 18	8.9	
Speakers Building A Level 10	1 0.9	

9

Source	Ld	
Occasiona D. Tallian A.L. and 40	dB(A)	
Speakers - Building A Level 18	12.8	
Speakers - Building A Level 18	13.4	
Receiver R3 Ld 58.5 dB(A)		
Speakers Level 1	11.4	
Speakers Level 1	12.6	
Speakers Level 1	15.6	
Speakers Level 1 Central Plaza	35.3	
Speakers Level 1 Central Plaza	40.8	
Speakers Level 1 Central Plaza	32.1	
Speakers Level 1 Central Plaza	35.6	
Speakers Level 1 Central Plaza	40.2	
Speakers Level 1 Central Plaza	28.7	
Speakers Level 1	35.7	
Speakers Level 1	47.9	
Speakers Building B Level 6	47.2	
Speakers Building B Level 6	39.1	
Speakers Building B Level 6	39.6	
Speakers Building B Level 6	47.8	
Speakers Building B Level 6	38.7	
Speakers Building B Level 6	51.3	
Speakers Building B Level 6	52.3	
Speakers Building B Level 6	45.0	
Speakers Building B Level 6	47.0	
Speakers Building A Level 10	19.7	
Speakers Building A Level 10	39.2	
Speakers Building A Level 10	45.7	
Speakers Building A Level 10	14.4	
Speakers Building A Level 10	11.0	
Speakers Building A Level 10	6.6	
Speakers Building A Level 10	11.6	
Speakers Building A Level 10	39.2	
Speakers Building A Level 10	40.3	
Speakers - Building A Level 16	15.2	
Speakers - Building A Level 16	32.5	
Speakers - Building A Level 16	32.7	
Speakers - Building A Level 16	34.0	
Speakers - Building A Level 16	39.2	
Speakers - Building A Level 18	17.7	
Speakers - Building A Level 18	17.7	
Speakers - Building A Level 18	14.7	
Speakers - Building A Level 18	16.3	

9

Source	Ld	
Occasions D. H.Fr. Adv. 140	dB(A)	
Speakers - Building A Level 18	15.5	
Speakers - Building A Level 18	37.5	
Speakers - Building A Level 18	29.6	
Receiver R4 Ld 62.6 dB(A)		
Speakers Level 1	58.9	
Speakers Level 1	57.2	
Speakers Level 1	55.9	
Speakers Level 1 Central Plaza	30.2	
Speakers Level 1 Central Plaza	38.9	
Speakers Level 1 Central Plaza	30.4	
Speakers Level 1 Central Plaza	42.4	
Speakers Level 1 Central Plaza	36.2	
Speakers Level 1 Central Plaza	32.5	
Speakers Level 1	33.8	
Speakers Level 1	31.4	
Speakers Building B Level 6	24.5	
Speakers Building B Level 6	29.8	
Speakers Building B Level 6	29.0	
Speakers Building B Level 6	23.3	
Speakers Building B Level 6	28.2	
Speakers Building B Level 6	19.0	
Speakers Building B Level 6	28.0	
Speakers Building B Level 6	24.0	
Speakers Building B Level 6	28.2	
Speakers Building A Level 10	42.6	
Speakers Building A Level 10	15.3	
Speakers Building A Level 10	30.1	
Speakers Building A Level 10	37.0	
Speakers Building A Level 10	40.0	
Speakers Building A Level 10	17.7	
Speakers Building A Level 10	36.4	
Speakers Building A Level 10	15.3	
Speakers Building A Level 10	15.1	
Speakers - Building A Level 16	36.4	
Speakers - Building A Level 16	23.3	
Speakers - Building A Level 16	19.3	
Speakers - Building A Level 16	23.1	
Speakers - Building A Level 16	20.3	
Speakers - Building A Level 18	37.7	
Speakers - Building A Level 18	38.1	
Speakers - Building A Level 18	35.3	

9

Source	Ld	
Occasions D. H.Fr. Adv. 140	dB(A)	
Speakers - Building A Level 18	36.5	
Speakers - Building A Level 18	34.2	
Speakers - Building A Level 18	19.5	
Speakers - Building A Level 18	18.9	
Receiver R5 Ld 60.8 dB(A)		
Speakers Level 1	28.7	
Speakers Level 1	18.7	
Speakers Level 1	18.2	
Speakers Level 1 Central Plaza	34.3	
Speakers Level 1 Central Plaza	36.4	
Speakers Level 1 Central Plaza	38.6	
Speakers Level 1 Central Plaza	30.2	
Speakers Level 1 Central Plaza	36.0	
Speakers Level 1 Central Plaza	39.9	
Speakers Level 1	29.2	
Speakers Level 1	26.3	
Speakers Building B Level 6	30.9	
Speakers Building B Level 6	41.7	
Speakers Building B Level 6	40.6	
Speakers Building B Level 6	33.5	
Speakers Building B Level 6	40.0	
Speakers Building B Level 6	22.1	
Speakers Building B Level 6	38.5	
Speakers Building B Level 6	34.7	
Speakers Building B Level 6	36.1	
Speakers Building A Level 10	40.9	
Speakers Building A Level 10	12.7	
Speakers Building A Level 10	20.9	
Speakers Building A Level 10	16.7	
Speakers Building A Level 10	17.8	
Speakers Building A Level 10	54.2	
Speakers Building A Level 10	57.4	
Speakers Building A Level 10	11.9	
Speakers Building A Level 10	12.0	
Speakers - Building A Level 16	21.3	
Speakers - Building A Level 16	17.4	
Speakers - Building A Level 16	17.8	
Speakers - Building A Level 16	17.5	
Speakers - Building A Level 16	16.3	
Speakers - Building A Level 18	51.6	
Speakers - Building A Level 18	51.8	
<u> </u>	1	

9

Source	Ld	
	dB(A)	
Speakers - Building A Level 18	29.0	
Speakers - Building A Level 18	33.3	
Speakers - Building A Level 18	24.2	
Speakers - Building A Level 18	18.0	
Speakers - Building A Level 18	17.9	

Name	Source type	Lw
		dB(A)
Parking Level 1	PLot	87.0
Parking Level 2	PLot	89.7
Parking Level 3	PLot	89.7
Parking Level 4	PLot	89.7
Parking Level 5	PLot	89.7
Parking Level 6	PLot	89.7

Source	Ld	
Course	dB(A)	
D 1 D1 1 1 10 0 1D(1)	UD(A)	
Receiver R1 Ld 49.9 dB(A)		
Parking Level 1	47.2	
Parking Level 2	43.7	
Parking Level 3	39.9	
Parking Level 4	37.7	
Parking Level 5	35.9	
Parking Level 6	34.3	
Receiver R2 Ld 45.8 dB(A)		
Parking Level 1	42.5	
Parking Level 2	39.2	
Parking Level 3	36.9	
Parking Level 4	35.3	
Parking Level 5	33.4	
Parking Level 6	32.1	
Receiver R3 Ld 24.2 dB(A)		
Parking Level 1	13.5	
Parking Level 2	15.4	
Parking Level 3	15.0	
Parking Level 4	16.6	
Parking Level 5	17.5	
Parking Level 6	18.6	
Receiver R4 Ld 20.4 dB(A)		
Parking Level 1	7.7	
Parking Level 2	9.8	
Parking Level 3	10.3	
Parking Level 4	11.0	
Parking Level 5	14.7	
Parking Level 6	16.2	
Receiver R5 Ld 33.3 dB(A)		
Parking Level 1	18.5	
Parking Level 2	22.9	
Parking Level 3	26.5	
Parking Level 4	26.7	
Parking Level 5	26.8	
Parking Level 6	26.9	

Name	Source type	Lw
		J
		dB(A)
Loading (two trucks)	Point	104.9
Trash Compactor	Point	91.5

Sunset Gower Assessed contribution level - Loading & Trash Compactor

9

Source	Ld	
	dB(A)	
Receiver R1 Ld 33.4 dB(A)		
Trash Compactor	22.9	
Loading (two trucks)	33.0	
Receiver R2 Ld 31.3 dB(A)		
Trash Compactor	19.0	
Loading (two trucks)	31.1	
Receiver R3 Ld 36.1 dB(A)		
Trash Compactor	24.0	
Loading (two trucks)	35.8	
Receiver R4 Ld 28.8 dB(A)		
Trash Compactor	16.7	
Loading (two trucks)	28.6	
Receiver R5 Ld 30.3 dB(A)		
Trash Compactor	17.3	
Loading (two trucks)	30.0	



Project: Sunset Gower Project

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

EXISTING CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,312	23,120	10%	0	0	72.0
 Between Sunset Blvd. and Fountain Ave. 	70	10	45	35	2,569	25,690	10%	0	0	72.5
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,449	24,490	10%	0	0	72.2
Gower Street										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	1,319	13,190	10%	0	0	70.7
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	1,221	12,210	10%	0	0	70.3
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,207	12,070	10%	0	0	70.3
Bronson Avenue										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	843	8,430	10%	0	0	68.7
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	778	7,780	10%	0	0	68.4
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	728	7,280	10%	0	0	68.1
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		838	10%	0	0	59.5
Gordon Street										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	35	269	2,690	10%	0	0	64.6
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,167	10%	0	0	60.9
Tamarind Avenue										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	25		2,046	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,280	10%	0	0	61.3
Hollywood Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	1,839	18,390	10%	0	0	71.5
- Between Gower St. and Bronson Ave.	60	10	40	35	1,797	17,970	10%	0	0	71.4
Sunset Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,058	30,580	10%	0	0	73.7
- Between Gower St. and Gordon St.	60	10	40	35	3,237	32,370	10%	0	0	74.0
- Between Gordon St. and Bronson Ave.	60	10	40	35	3,247	32,470	10%	0	0	74.0

Date Printed: 3/25/2019



EXISTING CONDITIONS	Roadwav	Distance to Edge of	Distance to Centerline.	Speed	Traffic	Volume	PHV to	Barrier	Site Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
De Longpre Avenue										
- Between Vine St, and Gower St.	40	10	30	25		2,206	10%	0	0	63.7
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		777	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,030	10,300	10%	0	0	70.4
- Between Gower St. and Gordon St.	40	10	30	35	1,028	10,280	10%	0	0	70.4
- Between Gordon St. and Bronson Ave.	40	10	30	35	884	8,840	10%	0	0	69.7
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	2,481	24,810	10%	0	0	72.8
- Between Gower St. and Bronson Ave.	60	10	40	35	2,602	26,020	10%	0	0	73.0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.



Project: Sunset Gower Project

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

EXISTING + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,342	23,420	10%	0	0	72.1
- Between Sunset Blvd. and Fountain Ave.	70	10	45	35	2,582	25,820	10%	0	0	72.5
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,473	24,730	10%	0	0	72.3
Gower Street										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	1,340	13,400	10%	0	0	70.7
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	1,221	12,210	10%	0	0	70.3
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,243	12,430	10%	0	0	70.4
Bronson Avenue										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	876	8,760	10%	0	0	68.9
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	778	7,780	10%	0	0	68.4
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	783	7,830	10%	0	0	68.4
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		838	10%	0	0	59.5
Gordon Street										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	35	416	4,160	10%	0	0	66.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,270	10%	0	0	61.3
Tamarind Avenue										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	25		2,046	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,280	10%	0	0	61.3
Hollywood Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	1,839	18,390	10%	0	0	71.5
- Between Gower St. and Bronson Ave.	60	10	40	35	1,797	17,970	10%	0	0	71.4
Sunset Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,168	31,680	10%	0	0	73.9
- Between Gower St. and Gordon St.	60	10	40	35	3,401	34,010	10%	0	0	74.2
- Between Gordon St. and Bronson Ave.	60	10	40	35	3,418	34,180	10%	0	0	74.2

Date Printed: 3/25/2019



EXISTING + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
De Longpre Avenue										
 Between Vine St, and Gower St. 	40	10	30	25		2,206	10%	0	0	63.7
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		777	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,112	11,120	10%	0	0	70.7
- Between Gower St. and Gordon St.	40	10	30	35	1,145	11,450	10%	0	0	70.8
- Between Gordon St. and Bronson Ave.	40	10	30	35	939	9,390	10%	0	0	70.0
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	2,500	25,000	10%	0	0	72.8
- Between Gower St. and Bronson Ave.	60	10	40	35	2,607	26,070	10%	0	0	73.0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.



Project: Sunset Gower Project

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

FUTURE NO PROJECT CONDITIONS	Roadway	Distance to Edge of	Distance to Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Site Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,715	27,150	10%	0	0	72.7
 Between Sunset Blvd. and Fountain Ave. 	70	10	45	35	3,045	30,450	10%	0	0	73.2
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,872	28,720	10%	0	0	72.9
Gower Street										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,647	16,470	10%	0	0	71.6
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	1,437	14,370	10%	0	0	71.0
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,431	14,310	10%	0	0	71.0
Bronson Avenue										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,042	10,420	10%	0	0	69.6
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	851	8,510	10%	0	0	68.8
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	779	7,790	10%	0	0	68.4
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		853	10%	0	0	59.6
Gordon Street										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	35	274	2,740	10%	0	0	64.6
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,188	10%	0	0	61.0
Tamarind Avenue										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	25		2,083	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,303	10%	0	0	61.4
Hollywood Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	2,666	26,660	10%	0	0	73.1
- Between Gower St. and Bronson Ave.	60	10	40	35	2,671	26,710	10%	0	0	73.1
Sunset Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	4,351	43,510	10%	0	0	75.2
- Between Gower St. and Gordon St.	60	10	40	35	4,477	44,770	10%	0	0	75.4
- Between Gordon St. and Bronson Ave.	60	10	40	35	4,505	45,050	10%	0	0	75.4



FUTURE NO PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed		Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
De Longpre Avenue										
 Between Vine St, and Gower St. 	40	10	30	25		2,246	10%	0	0	63.8
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		791	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,070	10,700	10%	0	0	70.5
- Between Gower St. and Gordon St.	40	10	30	35	1,077	10,770	10%	0	0	70.6
- Between Gordon St. and Bronson Ave.	40	10	30	35	927	9,270	10%	0	0	69.9
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,247	32,470	10%	0	0	74.0
- Between Gower St. and Bronson Ave.	60	10	40	35	3,299	32,990	10%	0	0	74.0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.



Project: Sunset Gower Project

Traffic Distribution as % of ADT										
Vehicle Type	Day	Eve	Night	Sub total						
Auto	77.6%	9.7%	9.7%	97.0%						
Medium Truck	1.6%	0.2%	0.2%	2.0%						
Heavy Truck	0.8%	0.1%	0.1%	1.0%						
	80.0%	10.0%	10.0%	100.0%						

PHV to ADT factor 10%

FUTURE + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,745	27,450	10%	0	0	72.7
- Between Sunset Blvd. and Fountain Ave.	70	10	45	35	3,058	30,580	10%	0	0	73.2
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,896	28,960	10%	0	0	73.0
Gower Street										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,668	16,680	10%	0	0	71.7
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	1,437	14,370	10%	0	0	71.0
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,466	14,660	10%	0	0	71.1
Bronson Avenue										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,074	10,740	10%	0	0	69.8
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	851	8,510	10%	0	0	68.8
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	834	8,340	10%	0	0	68.7
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		853	10%	0	0	59.6
Gordon Street										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	35	421	4,210	10%	0	0	66.5
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,291	10%	0	0	61.4
Tamarind Avenue										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	25		2,083	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,303	10%	0	0	61.4
Hollywood Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	2,666	26,660	10%	0	0	73.1
 Between Gower St. and Bronson Ave. 	60	10	40	35	2,671	26,710	10%	0	0	73.1
Sunset Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	4,461	44,610	10%	0	0	75.3
- Between Gower St. and Gordon St.	60	10	40	35	4,641	46,410	10%	0	0	75.5
- Between Gordon St. and Bronson Ave.	60	10	40	35	4,676	46,760	10%	0	0	75.6



FUTURE + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
De Longpre Avenue										
- Between Vine St, and Gower St.	40	10	30	25		2,246	10%	0	0	63.8
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		791	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,151	11,510	10%	0	0	70.9
- Between Gower St. and Gordon St.	40	10	30	35	1,194	11,940	10%	0	0	71.0
- Between Gordon St. and Bronson Ave.	40	10	30	35	982	9,820	10%	0	0	70.2
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,266	32,660	10%	0	0	74.0
- Between Gower St. and Bronson Ave.	60	10	40	35	3,304	33,040	10%	0	0	74.0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.

Sunset Gower Project Alternative 2

Noise Calculations Worksheets

Provided by Acoustical Engineering Services

Construction Noise & Vibration Calculations



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	60	0
1	79	40%	60	0
1	79	40%	85	0
1	79	40%	85	0
1	81	40%	110	0
1	78	40%	110	0
1	75	20%	135	0
1	79	40%	135	0
1	78	40%	135	0
1	75	20%	160	0
1	90	20%	160	0
1	82	10%	160	0
		No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 75 20% 1 79 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20% 1 82 10%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 60 1 79 40% 60 1 79 40% 85 1 79 40% 85 1 81 40% 110 1 78 40% 110 1 75 20% 135 1 79 40% 135 1 78 40% 135 1 75 20% 160 1 90 20% 160 1 82 10% 160

12

Receptor: R1

Results:

1-hour Leq: 83.6



Construction Phase: Grading/Excavation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	60	0
Excavator	1	81	40%	60	0
Crane	1	81	16%	85	0
Tractor/Loader/Backhoe	1	79	40%	85	0
Air Compressor	1	78	40%	110	0
Bore/Drill Rig	1	84	20%	110	0
Excavator	1	81	40%	135	0
Crane	1	81	16%	135	0
Tractor/Loader/Backhoe	1	79	40%	160	0
Water truck	1	82	10%	160	0

10

Receptor: R1

Results:

1-hour Leq: 80.7



Construction Phase: Mat Foundation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	60	0
Concrete Pump	1	81	20%	60	0
Tractor/Loader/Backhoe	1	79	40%	85	0
Welders	1	74	40%	85	0
Crane	1	81	16%	110	0
Cement and Mortar Mixer	3	80	50%	110	0
Concrete Pump	3	81	20%	135	0
Welders	1	74	40%	135	0
Crane	1	81	16%	160	0

13

Receptor: R1

Results:

1-hour Leq: 80.6



Construction Phase: Building Construction Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	60	0
Air Compressor	1	78	40%	60	0
Aerial Lift	1	75	20%	85	0
Fork Lift	1	75	20%	85	0
Concrete Pump	1	81	20%	110	0
Crane	1	81	16%	110	0
Tractor/Loader/Backhoe	2	79	40%	135	0
Welders	2	74	40%	135	0
Air Compressor	1	78	40%	160	0
Aerial Lift	1	75	20%	160	0
Fork Lift	1	75	20%	185	0
Crane	1	81	16%	185	0

14

Receptor: R1

Results:

1-hour Leq: 79.2



Construction Phase: Grading/Excavation Phase 2

Building A

Equipment

	No. of	Reference Noise Level at	Acoustical	Distance to	Estimated Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	860	15
Excavator	1	81	40%	860	15
Crane	1	81	16%	885	15
Tractor/Loader/Backhoe	1	79	40%	885	15
Air Compressor	1	78	40%	910	15
Bore/Drill Rig	1	84	20%	910	15
Excavator	1	81	40%	935	15
Crane	1	81	16%	935	15
Tractor/Loader/Backhoe	1	79	40%	960	15
Water truck	1	82	10%	960	15

10

Receptor: R1

Results:

1-hour Leq: 45.3



Construction Phase: *Mat Foundation Phase 2 Building A*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	860	15
Concrete Pump	1	81	20%	860	15
Tractor/Loader/Backhoe	1	79	40%	885	15
Welders	1	74	40%	885	15
Crane	1	81	16%	910	15
Cement and Mortar Mixer	3	80	50%	910	15
Concrete Pump	3	81	20%	935	15
Welders	1	74	40%	935	15
Crane	1	81	16%	960	15

13

Receptor: R1

Results:

1-hour Leq: 45.8



Construction Phase: Building Construction

Building A

Equipment

			Reference			Estimated
		No. of	Noise Level at	Acoustical	Distance to	Noise
Description		Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
C	ement and Mortar Mixer	1	80	50%	860	15
Ai	ir Compressor	1	78	40%	860	15
A	erial Lift	1	75	20%	885	15
F	ork Lift	1	75	20%	885	15
Tr	ractor/Loader/Backhoe	1	79	40%	910	15
W	/elders	1	74	40%	910	15
C	rane	1	81	16%	935	15
C	oncrete Pump	1	81	20%	935	15
Ai	ir Compressor	1	78	40%	960	15
A	erial Lift	1	75	20%	960	15
F	ork Lift	1	75	20%	985	15
C	rane	1	81	16%	985	15
Tr	ractor/Loader/Backhoe	1	79	40%	985	15
W	/elders	1	74	40%	985	15

14

Receptor: R1

Results:

1-hour Leq: 44.1



Construction Phase: Grading/Excavation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	410	10
Excavator	1	81	40%	410	10
Crane	1	81	16%	435	10
Tractor/Loader/Backhoe	1	79	40%	435	10
Bore/Drill Rig	1	84	20%	460	10
Excavator	1	81	40%	460	10
Crane	1	81	16%	485	10
Tractor/Loader/Backhoe	1	79	40%	485	10
Water truck	1	82	10%	510	10
Air Compressor	1	78	40%	510	10

10

Receptor: R1

Results:

1-hour Leq: 56.4



Construction Phase: *Mat Foundation Phase 3 Buildings B and E*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	410	10
Concrete Pump	1	81	20%	410	10
Tractor/Loader/Backhoe	1	79	40%	435	10
Welders	1	74	40%	435	10
Crane	1	81	16%	460	10
Cement and Mortar Mixer	3	80	50%	460	10
Concrete Pump	3	81	20%	485	10
Welders	1	74	40%	485	10
Crane	1	81	16%	510	10

13

Receptor: R1

Results:

1-hour Leq: 56.8



Construction Phase: Building Construction Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	410	10
Air Compressor	1	78	40%	410	10
Aerial Lift	1	75	20%	435	10
Fork Lift	1	75	20%	435	10
Concrete Pump	1	81	20%	460	10
Tractor/Loader/Backhoe	1	79	40%	460	10
Welders	1	74	40%	485	10
Crane	1	81	16%	485	10
Air Compressor	1	78	40%	510	10
Aerial Lift	1	75	20%	510	10
Fork Lift	1	75	20%	535	10
Crane	1	81	16%	535	10
Tractor/Loader/Backhoe	1	79	40%	535	10
Welders	1	74	40%	535	10

14

Receptor: R1

Results:

1-hour Leq: 55.0



Construction Phase: Demolition

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Concrete Saw	1	90	20%	65	0
Skid Steer Loader	1	79	40%	65	0
Rubber Tired Dozer	1	79	40%	90	0
Tractor/Loader/Backhoe	1	79	40%	90	0
Excavator	1	81	40%	115	0
Air Compressor	1	78	40%	115	0
Aerial Lift	1	75	20%	140	0
Tractor/Loader/Backhoe	1	79	40%	140	0
Air Compressor	1	78	40%	140	0
Aerial Lift	1	75	20%	165	0
Concrete Saw	1	90	20%	165	0
Water truck	1	82	10%	165	0

12

Receptor: R2

Results:

1-hour Leq: 83.0



Construction Phase: Grading/Excavation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	65	0
Excavator	1	81	40%	65	0
Crane	1	81	16%	90	0
Tractor/Loader/Backhoe	1	79	40%	90	0
Air Compressor	1	78	40%	115	0
Bore/Drill Rig	1	84	20%	115	0
Excavator	1	81	40%	140	0
Crane	1	81	16%	140	0
Tractor/Loader/Backhoe	1	79	40%	165	0
Water truck	1	82	10%	165	0

10

Receptor: R2

Results:

1-hour Leq: 80.1



Construction Phase: Mat Foundation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	65	0
Concrete Pump	1	81	20%	65	0
Tractor/Loader/Backhoe	1	79	40%	90	0
Welders	1	74	40%	90	0
Crane	1	81	16%	115	0
Cement and Mortar Mixer	3	80	50%	115	0
Concrete Pump	3	81	20%	140	0
Welders	1	74	40%	140	0
Crane	1	81	16%	165	0

13

Receptor: R2

Results:

1-hour Leq: 80.1



Construction Phase: Building Construction Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	80	50%	65	0
1	78	40%	65	0
1	75	20%	90	0
1	75	20%	90	0
1	81	20%	115	0
1	81	16%	115	0
2	79	40%	140	0
2	74	40%	140	0
1	78	40%	165	0
1	75	20%	165	0
1	75	20%	190	0
1	81	16%	190	0
	Equip. 1 1 1 1 1 2 2 1 1 1	No. of Equip. Noise Level at 50ft, Lmax 1 80 1 78 1 75 1 81 1 81 2 79 2 74 1 75 1 75 1 75 1 75 1 75 1 75	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 80 50% 1 78 40% 1 75 20% 1 81 20% 1 81 16% 2 79 40% 2 74 40% 1 78 40% 1 75 20% 1 75 20% 1 75 20%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 80 50% 65 1 78 40% 65 1 75 20% 90 1 75 20% 90 1 81 20% 115 1 81 16% 115 2 79 40% 140 2 74 40% 140 1 78 40% 165 1 75 20% 165 1 75 20% 190

14

Receptor: R2

Results:

1-hour Leq: 78.6



Construction Phase: Grading/Excavation Phase 2

Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	1020	15
Excavator	1	81	40%	1020	15
Crane	1	81	16%	1045	15
Tractor/Loader/Backhoe	1	79	40%	1045	15
Air Compressor	1	78	40%	1070	15
Bore/Drill Rig	1	84	20%	1070	15
Excavator	1	81	40%	1095	15
Crane	1	81	16%	1095	15
Tractor/Loader/Backhoe	1	79	40%	1120	15
Water truck	1	82	10%	1120	15
	- 40				

10

Receptor: R2

Results:

1-hour Leq: 43.9



Construction Phase: *Mat Foundation Phase 2 Building A*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	1020	15
Concrete Pump	1	81	20%	1020	15
Tractor/Loader/Backhoe	1	79	40%	1045	15
Welders	1	74	40%	1045	15
Crane	1	81	16%	1070	15
Cement and Mortar Mixer	3	80	50%	1070	15
Concrete Pump	3	81	20%	1095	15
Welders	1	74	40%	1095	15
Crane	1	81	16%	1120	15

13

Receptor: R2

Results:

1-hour Leq: 44.4



Construction Phase: Building Construction

Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	1020	15
Air Compressor	1	78	40%	1020	15
Aerial Lift	1	75	20%	1045	15
Fork Lift	1	75	20%	1045	15
Tractor/Loader/Backhoe	1	79	40%	1070	15
Welders	1	74	40%	1070	15
Crane	1	81	16%	1095	15
Concrete Pump	1	81	20%	1095	15
Air Compressor	1	78	40%	1120	15
Aerial Lift	1	75	20%	1120	15
Fork Lift	1	75	20%	1145	15
Crane	1	81	16%	1145	15
Tractor/Loader/Backhoe	1	79	40%	1145	15
Welders	1	74	40%	1145	15

14

Receptor: R2

Results:

1-hour Leq: 42.7



Construction Phase: Grading/Excavation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	405	10
Excavator	1	81	40%	405	10
Crane	1	81	16%	430	10
Tractor/Loader/Backhoe	1	79	40%	430	10
Bore/Drill Rig	1	84	20%	455	10
Excavator	1	81	40%	455	10
Crane	1	81	16%	480	10
Tractor/Loader/Backhoe	1	79	40%	480	10
Water truck	1	82	10%	505	10
Air Compressor	1	78	40%	505	10

10

Receptor: R2

Results:

1-hour Leq: 56.5



Construction Phase: Mat Foundation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	405	10
Concrete Pump	1	81	20%	405	10
Tractor/Loader/Backhoe	1	79	40%	430	10
Welders	1	74	40%	430	10
Crane	1	81	16%	455	10
Cement and Mortar Mixer	3	80	50%	455	10
Concrete Pump	3	81	20%	480	10
Welders	1	74	40%	480	10
Crane	1	81	16%	505	10

13

Receptor: R2

Results:

1-hour Leq: 56.9



Construction Phase: Building Construction Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	405	10
Air Compressor	1	78	40%	405	10
Aerial Lift	1	75	20%	430	10
Fork Lift	1	75	20%	430	10
Concrete Pump	1	81	20%	455	10
Tractor/Loader/Backhoe	1	79	40%	455	10
Welders	1	74	40%	480	10
Crane	1	81	16%	480	10
Air Compressor	1	78	40%	505	10
Aerial Lift	1	75	20%	505	10
Fork Lift	1	75	20%	530	10
Crane	1	81	16%	530	10
Tractor/Loader/Backhoe	1	79	40%	530	10
Welders	1	74	40%	530	10

14

Receptor: R2

Results:

1-hour Leq: 55.1



Construction Phase: Demolition

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Concrete Saw	1	90	20%	275	15
Skid Steer Loader	1	79	40%	275	15
Rubber Tired Dozer	1	79	40%	300	15
Tractor/Loader/Backhoe	1	79	40%	300	15
Excavator	1	81	40%	325	15
Air Compressor	1	78	40%	325	15
Aerial Lift	1	75	20%	350	15
Tractor/Loader/Backhoe	1	79	40%	350	15
Air Compressor	1	78	40%	375	15
Aerial Lift	1	75	20%	375	15
Concrete Saw	1	90	20%	380	15
Water truck	1	82	10%	380	15

12

Receptor: R3

Results:

1-hour Leq: 57.1



Construction Phase: Grading/Excavation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	385	15
Excavator	1	81	40%	385	15
Crane	1	81	16%	410	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Air Compressor	1	78	40%	435	15
Bore/Drill Rig	1	84	20%	435	15
Excavator	1	81	40%	460	15
Crane	1	81	16%	460	15
Tractor/Loader/Backhoe	1	79	40%	460	15
Water truck	1	82	10%	460	15

10

Receptor: R3

Results:

1-hour Leq: 51.9



Construction Phase: Mat Foundation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Concrete Pump	1	81	20%	385	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Welders	1	74	40%	410	15
Crane	1	81	16%	435	15
Cement and Mortar Mixer	3	80	50%	435	15
Concrete Pump	3	81	20%	460	15
Welders	1	74	40%	460	15
Crane	1	81	16%	460	15

13

Receptor: R3

Results:

1-hour Leq: 52.3



Construction Phase: Building Construction Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Air Compressor	1	78	40%	385	15
Aerial Lift	1	75	20%	410	15
Fork Lift	1	75	20%	410	15
Concrete Pump	1	81	20%	435	15
Crane	1	81	16%	435	15
Tractor/Loader/Backhoe	2	79	40%	460	15
Welders	2	74	40%	460	15
Air Compressor	1	78	40%	460	15
Aerial Lift	1	75	20%	460	15
Fork Lift	1	75	20%	460	15
Crane	1	81	16%	460	15

14

Receptor: R3

Results:

1-hour Leq: 50.7



Construction Phase: Grading/Excavation Phase 2
Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	500	15
Excavator	1	81	40%	500	15
Crane	1	81	16%	525	15
Tractor/Loader/Backhoe	1	79	40%	525	15
Air Compressor	1	78	40%	550	15
Bore/Drill Rig	1	84	20%	550	15
Excavator	1	81	40%	575	15
Crane	1	81	16%	575	15
Tractor/Loader/Backhoe	1	79	40%	575	15
Water truck	1	82	10%	575	15
	40				

10

Receptor: R3

Results:

1-hour Leq: 49.8



Construction Phase: Mat Foundation Phase 2

Building A

Equipment

	No. of	Reference Noise Level at	Acoustical	Distance to	Estimated Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	500	15
Concrete Pump	1	81	20%	500	15
Tractor/Loader/Backhoe	1	79	40%	525	15
Welders	1	74	40%	525	15
Crane	1	81	16%	550	15
Cement and Mortar Mixer	3	80	50%	550	15
Concrete Pump	3	81	20%	575	15
Welders	1	74	40%	575	15
Crane	1	81	16%	575	15

13

Receptor: R3

Results:

1-hour Leq: 50.2



Construction Phase: Building Construction

Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	500	15
Air Compressor	1	78	40%	500	15
Aerial Lift	1	75	20%	525	15
Fork Lift	1	75	20%	525	15
Tractor/Loader/Backhoe	1	79	40%	550	15
Welders	1	74	40%	550	15
Crane	1	81	16%	575	15
Concrete Pump	1	81	20%	575	15
Air Compressor	1	78	40%	575	15
Aerial Lift	1	75	20%	575	15
Fork Lift	1	75	20%	575	15
Crane	1	81	16%	575	15
Tractor/Loader/Backhoe	1	79	40%	575	15
Welders	1	74	40%	575	15

14

Receptor: R3

Results:

1-hour Leq: 48.6



Construction Phase: Grading/Excavation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	275	15
Excavator	1	81	40%	275	15
Crane	1	81	16%	300	15
Tractor/Loader/Backhoe	1	79	40%	300	15
Bore/Drill Rig	1	84	20%	325	15
Excavator	1	81	40%	325	15
Crane	1	81	16%	350	15
Tractor/Loader/Backhoe	1	79	40%	350	15
Water truck	1	82	10%	350	15
Air Compressor	1	78	40%	350	15

10

Receptor: R3

Results:

1-hour Leq: 54.6



Construction Phase: Mat Foundation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	275	15
Concrete Pump	1	81	20%	275	15
Tractor/Loader/Backhoe	1	79	40%	300	15
Welders	1	74	40%	300	15
Crane	1	81	16%	325	15
Cement and Mortar Mixer	3	80	50%	325	15
Concrete Pump	3	81	20%	350	15
Welders	1	74	40%	350	15
Crane	1	81	16%	350	15

13

Receptor: R3

Results:

1-hour Leq: 54.9



Construction Phase: Building Construction Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	275	15
Air Compressor	1	78	40%	275	15
Aerial Lift	1	75	20%	300	15
Fork Lift	1	75	20%	300	15
Concrete Pump	1	81	20%	325	15
Tractor/Loader/Backhoe	1	79	40%	325	15
Welders	1	74	40%	350	15
Crane	1	81	16%	350	15
Air Compressor	1	78	40%	350	15
Aerial Lift	1	75	20%	350	15
Fork Lift	1	75	20%	350	15
Crane	1	81	16%	350	15
Tractor/Loader/Backhoe	1	79	40%	350	15
Welders	1	74	40%	350	15

14

Receptor: R3

Results:

1-hour Leq: 53.4



Construction Phase: Demolition

Equipment

	No. of	Reference Noise Level at	Acoustical	Distance to	Estimated Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Concrete Saw	1	90	20%	185	0
Skid Steer Loader	1	79	40%	185	0
Rubber Tired Dozer	1	79	40%	210	0
Tractor/Loader/Backhoe	1	79	40%	210	0
Excavator	1	81	40%	235	0
Air Compressor	1	78	40%	235	0
Aerial Lift	1	75	20%	260	0
Tractor/Loader/Backhoe	1	79	40%	260	0
Air Compressor	1	78	40%	285	0
Aerial Lift	1	75	20%	285	0
Concrete Saw	1	90	20%	285	0
Water truck	1	82	10%	285	0

12

Receptor: R4

Results:

1-hour Leq: 75.2



Construction Phase: Grading/Excavation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	735	15
Excavator	1	81	40%	735	15
Crane	1	81	16%	760	15
Tractor/Loader/Backhoe	1	79	40%	760	15
Air Compressor	1	78	40%	785	15
Bore/Drill Rig	1	84	20%	785	15
Excavator	1	81	40%	810	15
Crane	1	81	16%	810	15
Tractor/Loader/Backhoe	1	79	40%	835	15
Water truck	1	82	10%	835	15

10

Receptor: R4

Results:

1-hour Leq: 46.6



Construction Phase: Mat Foundation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	735	15
Concrete Pump	1	81	20%	735	15
Tractor/Loader/Backhoe	1	79	40%	760	15
Welders	1	74	40%	760	15
Crane	1	81	16%	785	15
Cement and Mortar Mixer	3	80	50%	785	15
Concrete Pump	3	81	20%	810	15
Welders	1	74	40%	810	15
Crane	1	81	16%	835	15

13

Receptor: R4

Results:

1-hour Leq: 47.1



Construction Phase: Building Construction Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	80	50%	735	15
1	78	40%	735	15
1	75	20%	760	15
1	75	20%	760	15
1	81	20%	785	15
1	81	16%	785	15
2	79	40%	810	15
2	74	40%	810	15
1	78	40%	835	15
1	75	20%	835	15
1	75	20%	860	15
1	81	16%	860	15
	Equip. 1 1 1 1 1 2 2 1 1 1	No. of Equip. Noise Level at 50ft, Lmax 1 80 1 78 1 75 1 75 1 81 1 81 2 79 2 74 1 78 1 75 1 78 1 75 1 75	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 80 50% 1 78 40% 1 75 20% 1 81 20% 1 81 16% 2 79 40% 2 74 40% 1 78 40% 1 75 20% 1 75 20% 1 75 20%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 80 50% 735 1 78 40% 735 1 75 20% 760 1 81 20% 785 1 81 16% 785 2 79 40% 810 2 74 40% 810 1 78 40% 835 1 75 20% 835 1 75 20% 860

14

Receptor: R4

Results:

1-hour Leq: 45.4



Construction Phase: Grading/Excavation Phase 2
Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	185	0
Excavator	1	81	40%	185	0
Crane	1	81	16%	210	0
Tractor/Loader/Backhoe	1	79	40%	210	0
Air Compressor	1	78	40%	235	0
Bore/Drill Rig	1	84	20%	235	0
Excavator	1	81	40%	260	0
Crane	1	81	16%	260	0
Tractor/Loader/Backhoe	1	79	40%	285	0
Water truck	1	82	10%	285	0

10

Receptor: R4

Results:

1-hour Leq: 72.5



Construction Phase: *Mat Foundation Phase 2 Building A*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	185	0
Concrete Pump	1	81	20%	185	0
Tractor/Loader/Backhoe	1	79	40%	210	0
Welders	1	74	40%	210	0
Crane	1	81	16%	235	0
Cement and Mortar Mixer	3	80	50%	235	0
Concrete Pump	3	81	20%	260	0
Welders	1	74	40%	260	0
Crane	1	81	16%	285	0

13

Receptor: R4

Results:

1-hour Leq: 72.9



Construction Phase: Building Construction

Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	185	0
Air Compressor	1	78	40%	185	0
Aerial Lift	1	75	20%	210	0
Fork Lift	1	75	20%	210	0
Tractor/Loader/Backhoe	1	79	40%	235	0
Welders	1	74	40%	235	0
Crane	1	81	16%	260	0
Concrete Pump	1	81	20%	260	0
Air Compressor	1	78	40%	285	0
Aerial Lift	1	75	20%	285	0
Fork Lift	1	75	20%	310	0
Crane	1	81	16%	310	0
Tractor/Loader/Backhoe	1	79	40%	335	0
Welders	1	74	40%	335	0

14

Receptor: R4

Results:

1-hour Leq: 70.9



Construction Phase: Grading/Excavation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	700	15
Excavator	1	81	40%	700	15
Crane	1	81	16%	725	15
Tractor/Loader/Backhoe	1	79	40%	725	15
Bore/Drill Rig	1	84	20%	750	15
Excavator	1	81	40%	750	15
Crane	1	81	16%	775	15
Tractor/Loader/Backhoe	1	79	40%	775	15
Water truck	1	82	10%	800	15
Air Compressor	1	78	40%	800	15
	4.0				

10

Receptor: R4

Results:

1-hour Leq: 47.0



Construction Phase: *Mat Foundation Phase 3 Buildings B and E*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	700	15
Concrete Pump	1	81	20%	700	15
Tractor/Loader/Backhoe	1	79	40%	725	15
Welders	1	74	40%	725	15
Crane	1	81	16%	750	15
Cement and Mortar Mixer	3	80	50%	750	15
Concrete Pump	3	81	20%	775	15
Welders	1	74	40%	775	15
Crane	1	81	16%	800	15

13

Receptor: R4

Results:

1-hour Leq: 47.5



Construction Phase: Building Construction Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	700	15
Air Compressor	1	78	40%	700	15
Aerial Lift	1	75	20%	725	15
Fork Lift	1	75	20%	725	15
Concrete Pump	1	81	20%	750	15
Tractor/Loader/Backhoe	1	79	40%	750	15
Welders	1	74	40%	775	15
Crane	1	81	16%	775	15
Air Compressor	1	78	40%	800	15
Aerial Lift	1	75	20%	800	15
Fork Lift	1	75	20%	825	15
Crane	1	81	16%	825	15
Tractor/Loader/Backhoe	1	79	40%	850	15
Welders	1	74	40%	850	15

14

Receptor: R4

Results:

1-hour Leq: 45.7



Construction Phase: Demolition

Equipment

	Reference			Estimated
No. of	Noise Level at	Acoustical	Distance to	Noise
Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
1	90	20%	385	15
1	79	40%	385	15
1	79	40%	410	15
1	79	40%	410	15
1	81	40%	435	15
1	78	40%	435	15
1	75	20%	460	15
1	79	40%	460	15
1	78	40%	485	15
1	75	20%	485	15
1	90	20%	485	15
1	82	10%	485	15
	Equip. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	No. of Equip. Soft, Lmax 1 90 1 79 1 79 1 79 1 81 1 78 1 75 1 79 1 78 1 75 1 90 1 82	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor 1 90 20% 1 79 40% 1 79 40% 1 79 40% 1 81 40% 1 75 20% 1 79 40% 1 78 40% 1 78 40% 1 75 20% 1 90 20% 1 82 10%	No. of Equip. Noise Level at 50ft, Lmax Acoustical Usage Factor Distance to Receptor, ft 1 90 20% 385 1 79 40% 385 1 79 40% 410 1 79 40% 410 1 81 40% 435 1 78 40% 435 1 75 20% 460 1 78 40% 485 1 75 20% 485 1 75 20% 485 1 90 20% 485 1 82 10% 485

12

Receptor: R5

Results:

1-hour Leq: 54.5



Construction Phase: Grading/Excavation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	565	15
Excavator	1	81	40%	565	15
Crane	1	81	16%	590	15
Tractor/Loader/Backhoe	1	79	40%	590	15
Air Compressor	1	78	40%	615	15
Bore/Drill Rig	1	84	20%	615	15
Excavator	1	81	40%	635	15
Crane	1	81	16%	635	15
Tractor/Loader/Backhoe	1	79	40%	635	15
Water truck	1	82	10%	635	15

10

Receptor: R5

Results:

1-hour Leq: 48.8



Construction Phase: Mat Foundation Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	565	15
Concrete Pump	1	81	20%	565	15
Tractor/Loader/Backhoe	1	79	40%	590	15
Welders	1	74	40%	590	15
Crane	1	81	16%	615	15
Cement and Mortar Mixer	3	80	50%	615	15
Concrete Pump	3	81	20%	635	15
Welders	1	74	40%	635	15
Crane	1	81	16%	635	15

13

Receptor: R5

Results:

1-hour Leq: 49.3



Construction Phase: Building Construction Phase 1

Base Camp, Bldg. D, Parking Structure

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	565	15
Air Compressor	1	78	40%	565	15
Aerial Lift	1	75	20%	590	15
Fork Lift	1	75	20%	590	15
Concrete Pump	1	81	20%	615	15
Crane	1	81	16%	615	15
Tractor/Loader/Backhoe	2	79	40%	635	15
Welders	2	74	40%	635	15
Air Compressor	1	78	40%	635	15
Aerial Lift	1	75	20%	635	15
Fork Lift	1	75	20%	635	15
Crane	1	81	16%	635	15

14

Receptor: R5

Results:

1-hour Leq: 47.7



Construction Phase: Grading/Excavation Phase 2

Building A

Equipment

	No. of	Reference Noise Level at	Acoustical	Distance to	Estimated Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	385	15
Excavator	1	81	40%	385	15
Crane	1	81	16%	410	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Air Compressor	1	78	40%	435	15
Bore/Drill Rig	1	84	20%	435	15
Excavator	1	81	40%	455	15
Crane	1	81	16%	455	15
Tractor/Loader/Backhoe	1	79	40%	455	15
Water truck	1	82	10%	455	15

10

Receptor: R5

Results:

1-hour Leq: 51.9



Construction Phase: *Mat Foundation Phase 2 Building A*

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Concrete Pump	1	81	20%	385	15
Tractor/Loader/Backhoe	1	79	40%	410	15
Welders	1	74	40%	410	15
Crane	1	81	16%	435	15
Cement and Mortar Mixer	3	80	50%	435	15
Concrete Pump	3	81	20%	455	15
Welders	1	74	40%	455	15
Crane	1	81	16%	455	15

13

Receptor: R5

Results:

1-hour Leq: 52.3



Construction Phase: Building Construction

Building A

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	385	15
Air Compressor	1	78	40%	385	15
Aerial Lift	1	75	20%	410	15
Fork Lift	1	75	20%	410	15
Tractor/Loader/Backhoe	1	79	40%	435	15
Welders	1	74	40%	435	15
Crane	1	81	16%	455	15
Concrete Pump	1	81	20%	455	15
Air Compressor	1	78	40%	455	15
Aerial Lift	1	75	20%	455	15
Fork Lift	1	75	20%	455	15
Crane	1	81	16%	455	15
Tractor/Loader/Backhoe	1	79	40%	455	15
Welders	1	74	40%	455	15

14

Receptor: R5

Results:

1-hour Leq: 50.8



Construction Phase: Grading/Excavation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Bore/Drill Rig	1	84	20%	565	15
Excavator	1	81	40%	565	15
Crane	1	81	16%	590	15
Tractor/Loader/Backhoe	1	79	40%	590	15
Bore/Drill Rig	1	84	20%	615	15
Excavator	1	81	40%	615	15
Crane	1	81	16%	635	15
Tractor/Loader/Backhoe	1	79	40%	635	15
Water truck	1	82	10%	635	15
Air Compressor	1	78	40%	635	15

10

Receptor: R5

Results:

1-hour Leq: 48.8



Construction Phase: Mat Foundation Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	565	15
Concrete Pump	1	81	20%	565	15
Tractor/Loader/Backhoe	1	79	40%	590	15
Welders	1	74	40%	590	15
Crane	1	81	16%	615	15
Cement and Mortar Mixer	3	80	50%	615	15
Concrete Pump	3	81	20%	635	15
Welders	1	74	40%	635	15
Crane	1	81	16%	635	15

13

Receptor: R5

Results:

1-hour Leq: 49.3



Construction Phase: Building Construction Phase 3

Buildings B and E

Equipment

		Reference			Estimated
	No. of	Noise Level at	Acoustical	Distance to	Noise
Description	Equip.	50ft, Lmax	Usage Factor	Receptor, ft	Shielding, dBA
Cement and Mortar Mixer	1	80	50%	565	15
Air Compressor	1	78	40%	565	15
Aerial Lift	1	75	20%	590	15
Fork Lift	1	75	20%	590	15
Concrete Pump	1	81	20%	615	15
Tractor/Loader/Backhoe	1	79	40%	615	15
Welders	1	74	40%	635	15
Crane	1	81	16%	635	15
Air Compressor	1	78	40%	635	15
Aerial Lift	1	75	20%	635	15
Fork Lift	1	75	20%	635	15
Crane	1	81	16%	635	15
Tractor/Loader/Backhoe	1	79	40%	635	15
Welders	1	74	40%	635	15

14

Receptor: R5

Results:

1-hour Leq: 47.7





Off-Site Haul Trucks

	Maximum Nu	mber of Truck		Estimated Noise Levels,							
	One Wa	ay Trips			Le	q					
	(delive	ry/haul)	Worke	er Trips	(from TNI	/ Model)	Am	bient			
		Per Hour (8-		Trips during	at 30 feet	at 40 feet					
Phase	Per Day	hr day)	Daily Trips	Pk Hr.	(Gordon St.)	(Sunset)	Gordon St.	Sunset Blvd.			
1. Demolition	80	10	60	24	63.7	62.3	61.1	73.3			
2. Grading - All Phases	314	40	60	24	69.4	68.0	61.1	73.3			
3. Mat Foundation P1	828	69	60	24	71.7	70.3	61.1	73.3			
4. Building P1	60	8	400	160	65.0	63.6	61.1	73.3			
5. Grading P2	314	40	60	24	69.4	68.0	61.1	73.3			
6. Mat Foundation P2	1028	86	60	24	72.7	71.3	61.1	73.3			
7. Building P2	60	8	400	160	65.0	63.6	61.1	73.3			
8. Grading P3	314	40	60	24	69.4	68.0	61.1	73.3			
9. Mat Foundation P3	880	74	60	24	72.0	70.6	61.1	73.3			
10. Building P3	60	8	400	160	65.0	63.6	61.1	73.3			

	Number of trips per day Trucks/Work	dB <i>A</i>	Noise Levels, A Leq	Existing Amb	oient, dBA Leq	Project + Am	bient, dBA Leq
	ers	Sunset Blvd.	Gordon St.	Sunset Blvd.	Gordon St.	Sunset Blvd.	Gordon St.
Demolition	80/60	62.3	63.7	73.3	61.1	73.6	65.6
Grading - All Phases	314/60	68.0	69.4	73.3	61.1	74.4	70.0
Foundation - Phase 1	828/60	70.3	71.7	73.3	61.1	75.1	72.1
Foundation - Phase 2	1028/60	71.3	72.7	73.3	61.1	75.4	73.0
Foundation - Phase 3	880/60	70.6	72.0	73.3	61.1	75.2	72.3
Building Construction - All Phases	60/400	63.6	65.0	73.3	61.1	73.7	66.5
Maximum Exceedance						-2.9	6.9

	Maximum Nur	mber of Truck	Worke	er Trips
		Per Hour (8-		Trips during
Overlapping Construction	Per Day hr day) Daily Trips I 374 48 460 ion 1088 94 460 120 16 800 374 48 460 ion 940 82 460			
P1 Building and P2 Grading	374	48	460	184
P1 Building and P2 Foundation	1088	94	460	184
P1 and P2 Building	120	16	800	320
P2 Building and P3 Grading	374	48	460	184
P2 Building and P3 Foundation	940	82	460	184
P2 and P3 Building	120	16	800	320

	Estimated I	Noise Levels,					Significance	e Threshold,
	dBA	\ Leq	Existing Amb	pient, dBA Leq	Project + Am	bient, dBA Leq	dBA	\ Leq
Overlapping Construction	Sunset Blvd.	Gordon St.	Sunset Blvd.	Gordon St.	Sunset Blvd.	Gordon St.	Sunset Blvd.	Gordon St.
P1 Building and P2 Grading	69.4	70.8	73.3	61.1	74.8	71.2	78.3	66.1
P1 Building and P2 Foundation	72.0	73.4	73.3	61.1	75.7	73.6	78.3	66.1
P1 and P2 Building	66.7	68.0	73.3	61.1	74.2	68.8	78.3	66.1
P2 Building and P3 Grading	69.4	70.8	73.3	61.1	74.8	71.2	78.3	66.1
P2 Building and P3 Foundation	71.4	72.8	73.3	61.1	75.5	73.1	78.3	66.1
P2 and P3 Building	66.7	68.0	73.3	61.1	74.2	68.8	78.3	66.1

INPUT: ROADWAYS							Sunse	et Gower Pro	ject		
Eyestone Environmental					25 March 201	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State hi	ighway agend	y substant	iates the u	se
RUN: Construction Trucks - Demo Phase							of a differ	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Con	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	unset Go	wer Pr	oject			
Eyestone Environmental				25 Ma	rch 2019							
Sean Bui				TNM 2	2.5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Constructi	on Trucks	s - Demo	Phase								
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	s	HTrucks	3	Buses		Motorcy	/cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 2	4 35	5 C	0	10	35	5 (0 0	0 0) (
	point2		2									

INPUT: RECEIVERS								Sunset G	ower P	roject		
Eyestone Environmental						25 March	2019					
Sean Bui						TNM 2.5						
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Suns	et Gow	er Project									
RUN:	Cons	truction	Trucks - Der	no Phase								
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Cr	iteria	/	Active
			X	Υ	Z	above	Existing	Impact C	riteria	NR	i	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	(Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB		
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	2 0.00	7	1	5.0	0.0	Υ
Along Sunset Blvd.		8 1	250.0	40.0	0.00	4.92	2 0.00	6	6	10.0	8.0	Υ

RESULTS: SOUND LEVELS			T.				Sunset Go	wer Proje	ct				
Eyestone Environmental							25 March	 2019					
Sean Bui							TNM 2.5						
							Calculated	with TNN	/I 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Constru	uction Truc	ks - Demo F	hase								
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	ss	
								a State hi	ighway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a diffe	rent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	63.	7 71	63.7	5		63.7	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	62.	3 66	62.3	10		62.3	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0.0)							
All Impacted		0	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS							Sunse	et Gower Pro	ject		
Eyestone Environmental					25 March 201	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State hi	ighway agend	y substant	iates the u	se
RUN:	Construc		of a differ	rent type with	the approv	al of FHW	A				
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Con	itrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes	П					S	Sunset G	ower Pr	oject			
Eyestone Environmental				25 Ma	│ rch 2019							
Sean Bui				TNM 2	2.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Construction	on Trucks	s - Gradin	g Phas	e							
Roadway	Points											
Name	Name	No.	Segmen	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	5 () () 40	35		0 0) /	0
	point2	2	2									

INPUT: RECEIVERS									Sunset Go	ower Proje	ect	
Eyestone Environmental						25	March 2	2019				
Sean Bui						TNI	M 2.5					
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Suns	set Gow	er Project		'							
RUN:	Cons	structio	n Trucks - Gr	ading Phase								
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Hei	ght	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	abo	ove	Existing	Impact Cr	iteria	NR	in
						Gro	ound	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft		dBA	dBA	dB	dB	
Along Gordon St.		1 1	1 250.0	30.0)	0.00	4.92			5.	0.0) Y
Along Sunset Blvd.		8 1	1 250.0	40.0		0.00	4.92	0.00	66	10.	0 8.0) Y

RESULTS: SOUND LEVELS			T				Sunset Go	wer Projec	et .				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							Calculated	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Constru	uction Truc	ks - Gradino	g Phase								
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	ss	
								a State hi	ghway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	69.	4 71	69.4	5		69.4	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	68.	0 66	68.0	10	Snd Lvl	68.0	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
-			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	0.0)							
All Impacted		1	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0)							

INPUT: ROADWAYS			Suns	et Gower Pro	ject						
Eyestone Environmental					28 April 202	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	on Phase	1 Alt 2				of a diffe	rent type with	the approv	al of FHW	A \
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				28 Ap	ril 2020							
Sean Bui				TNM 2	5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect		1							
RUN:	Foundation	n Phase 1	Alt 2									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	0) (69	35		0 0)	0
	point2		2									

INPUT: RECEIVERS	γ			T	1	1		Sunset G	ower Proje	ct	
Eyestone Environmental						28 April 20	20				
•							020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gow	er Project		'						
RUN:	Found	dation I	Phase 1 Alt 2	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Y	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1 1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	:t				
Eventone Environmental							20 April 2	020					
Eyestone Environmental							28 April 2	020					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Founda	ation Phase	1 Alt 2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	ss	
								a State hi	ghway agency	y substantiate	s the u	ise	
ATMOSPHERICS:		68 deg	F, 50% RH						ent type with				
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcul	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	71.	7 71	71.7	5	Snd Lvl	71.7	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	70.	3 66	70.3	10	Snd Lvl	70.3	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.									
All Impacted		2	0.0	0.	0.0								
All that meet NR Goal		1	0.0	0.	0.0								

INPUT: ROADWAYS				Suns	et Gower Pro	ject					
Eyestone Environmental					28 April 202	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	on Phase	2 Alt2				of a diffe	rent type with	the approv	al of FHW	A \
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				28 Apı	ril 2020							
Sean Bui				TNM 2	5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect		1							
RUN:	Foundation	n Phase 2	Alt2									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35	0) (86	35		0 0)	0
	point2		2									

INPUT: RECEIVERS				T			·	Sunset G	ower Proje	ct	
Eyestone Environmental						28 April 2	020				
•						-	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunso	et Gowe	er Project		'						
RUN:	Found	dation F	Phase 2 Alt2	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Y	Z	above	Existing	Impact Cr	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1 1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	:t				
Evectore Environmental							20 April 2	020					
Eyestone Environmental							28 April 2	020					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Founda	ation Phase	2 Alt2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	ss	
								a State hi	ghway agency	y substantiate	s the u	ise	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcul	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	72.	7 71	72.7	5	Snd Lvl	72.7	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	71.	3 66	71.3	10	Snd Lvl	71.3	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.									
All Impacted		2	0.0	0.	0.0)							
All that meet NR Goal		1	0.0	0.	0.0								

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					28 April 202	20					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Foundati	ion Phase	3 Alt 2				of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Co	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.	0.00	Signal	0.00	100	Average	
		point2	2	1.000.0	0.	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				28 Ap	ril 2020							
Sean Bui				TNM 2	5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ect									
RUN:	Foundation	n Phase 3	Alt 2									
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 24	35) (74	35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ect	
Eyestone Environmental						28 April 2	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project		'						
RUN:	Found	dation I	Phase 3 Alt 2								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criter	ia	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	7′	1 5.	0 0.	0 Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	3 10.	0 8.	0 Y

RESULTS: SOUND LEVELS		÷	·		·	Sunset Go	wer Projec	et .			
Frankona Frankonanantal						20 Amril 20	000				
Eyestone Environmental						28 April 20	020				
Sean Bui						TNM 2.5					
						Calculated	d with TNN	1 2.5			
RESULTS: SOUND LEVELS											
PROJECT/CONTRACT:		Gower Pro	=								
RUN:	Founda	ation Phase	3 Alt 2								
BARRIER DESIGN:	INPUT	HEIGHTS					Average p	pavement type	shall be use	d unless	
							a State hi	ghway agenc	y substantiate	s the us	е
ATMOSPHERICS:	68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.	
Receiver											
Name No.	#DUs	Existing	No Barrier					With Barrier			
		LAeq1h	LAeq1h		Increase over	existing	Type	Calculated	Noise Reduc	tion	
			Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calculated
						Sub'l Inc					minus
											Goal
		dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB
Along Gordon St.	1 1	0.0	72.0	71	72.0	5	Snd Lvl	72.0	0.0		0 0.
Along Sunset Blvd.	8 1	0.0	70.6	66	70.6	10	Snd Lvl	70.6	0.0		8 -8.
Dwelling Units	# DUs	Noise Red	duction								
		Min	Avg	Max							
		dB	dB	dB							
All Selected	2	0.0	0.0	0.0							
All Impacted	2	0.0	0.0	0.0							
All that meet NR Goal	1	0.0	0.0	0.0							

INPUT: ROADWAYS		П					Suns	et Gower Pro	ject		
Eyestone Environmental					25 March 20	19					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Construc	tion Buildi	ing Phas	е			of a diffe	rent type with	the approv	al of FHW	Δ.
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	unset Go	wer Pı	oject			
				05.11	1 0040							
Eyestone Environmental				25 Ma	rch 2019							
Sean Bui				TNM 2	2.5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Constructi	on Buildiı	ng Phase									
Roadway	Points											
Name	Name	No.	Segme	nt								
			Autos		MTruck	S	HTrucks	5	Buses		Motorcy	cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 160	35	5 0	0	8	35	5 (0 0	0) (
	point2		2									

INPUT: RECEIVERS								Sunset G	ower P	roject		
Eyestone Environmental						25 March	2019					
Sean Bui						TNM 2.5						
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Suns	et Gow	er Project		•							
RUN:	Cons	truction	n Building Pha	ase								
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Cr	iteria	1	Active
			X	Υ	Z	above	Existing	Impact C	riteria	NR	i	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	(Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB		
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	7	1	5.0	0.0	Υ
Along Sunset Blvd.		8 1	250.0	40.0	0.00	4.92	0.00	6	6	10.0	8.0	Υ

RESULTS: SOUND LEVELS							Sunset Go	wer Proje	ect				
Eyestone Environmental							25 March	2019					
Sean Bui							TNM 2.5						
							Calculate	d with TN	M 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunse	Gower Pro	ject									
RUN:		Constr	uction Buil	ding Phase									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement typ	e shall be us	ed unles	s	
								a State h	nighway agend	y substantia	tes the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a diffe	erent type with	approval of	FHWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrie	r			
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Redu	ction		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calculate	d
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.		1 .	1 0.0	65.0)	71 65.0) 5	5	65.0	0.	0	0	0.0
Along Sunset Blvd.	3	8	1 0.0	63.6	6	63.6	6 10)	63.0	6 0.	0	8 -	8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected			2 0.0	0.0) (.0							
All Impacted		(0.0	0.0) (.0							
All that meet NR Goal			1 0.0	0.0) (.0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					28 April 202	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 1 Alt 2					of a diffe	rent type with	the approv	al of FHW	A \
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	·	100	Average								
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject			
Eyestone Environmental				28 Ap	ril 2020							
Sean Bui				TNM 2			I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	ver Proje	ect									
RUN:	Overlappin	g 1 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	s	HTruck	s	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35) () 48	35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Pro	oject	
Eyestone Environmental						28 April 20	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project		ı						
RUN:	Overl	apping	1 Alt 2								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Crit	eria	Active
			X	Υ	Z	above	Existing	Impact C	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	7	1	5.0	0.0 Y
Along Sunset Blvd.	3	3 1	250.0	40.0	0.00	4.92	0.00	66	3 1	0.0	8.0 Y

RESULTS: SOUND LEVELS								Sunset Gower Project							
Eyestone Environmental							28 April 2	020							
Sean Bui							TNM 2.5								
							Calculate	d with TNN	1 2.5						
RESULTS: SOUND LEVELS															
PROJECT/CONTRACT:		Sunset	Gower Pro	ject											
RUN:		Overla	ping 1 Alt	2											
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	s			
								a State hi	ghway agenc	y substantiate	s the us	se			
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.				
Receiver															
Name	No.	#DUs	Existing	No Barrier					With Barrier						
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion				
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ited		
							Sub'l Inc					minus			
												Goal			
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB			
Along Gordon St.	1	1	0.0	70).8 7	1 70.8	3 5		70.8	0.0		0	0.0		
Along Sunset Blvd.	8	3 1	0.0	69	0.4 6	6 69.4	1 10	Snd Lvl	69.4	0.0		8	-8.0		
Dwelling Units		# DUs	Noise Red	duction											
			Min	Avg	Max										
			dB	dB	dB										
All Selected		2	0.0	C	0.0	0									
All Impacted		1	0.0	C	0.0	0									
All that meet NR Goal		1	0.0	C	0.0	0									

INPUT: ROADWAYS							Suns	et Gower Proj	ject						
Eyestone Environmental					28 April 202	0									
Sean Bui					TNM 2.5										
INPUT: ROADWAYS							Average	pavement typ	e shall be ι	ısed unles	S				
PROJECT/CONTRACT: Sunset Gower Project								a State highway agency substantiates the use							
RUN:	Overlapping 2 Alt 2								of a different type with the approval of FHWA						
Roadway		Points													
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment					
				X	Υ	Z	Control	Speed	Percent	Pvmt	On				
							Device	Constraint	Vehicles	Type	Struct?				
									Affected						
	ft			ft	ft	ft		mph	%						
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average					
		point2	2	1,000.0	0.0	0.00									

INPUT: TRAFFIC FOR LAeq1h Volumes			S	Sunset G	ower Pr	oject						
Eyestone Environmental		28 Apı	ril 2020									
Sean Bui				TNM 2	5							
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct		1							
RUN:	Overlappin	g 2 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTrucks		HTrucks		Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	0) (94	35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						28 April 2	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Overl	apping	2 Alt 2								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.		1	250.0	30.0	0.00	4.92	0.00	7′	5.0	0.0) Y
Along Sunset Blvd.	3	3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS				,			Sunset Go	wer Projec	et .				
Eyestone Environmental							28 April 2	020					
								020					
Sean Bui							TNM 2.5						
DEG!!! TO GO!!!!D! 51/5! 0							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:			Gower Pro	-									
RUN:		Overlap	pping 2 Alt	2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unless	;	
								a State hi	ghway agenc	y substantiate	s the us	ie .	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion	-	
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ted
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	73	3.4 7	73.4	1 5	Snd Lvl	73.4	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	72	.0 6	6 72.0	10	Snd Lvl	72.0	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0	0.0	0							
All Impacted		2	0.0	0	0.0	0							
All that meet NR Goal		1	0.0	0	0.0	.0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					28 April 2020	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Pro	ject				a State h	ighway agend	cy substant	iates the u	se
RUN:	Overlapp	ing 3 Alt	2				of a diffe	rent type with	the approv	al of FHW	A
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Co	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes						8	Sunset G	ower Pr	oject		1	
Eyestone Environmental				28 Ap	ril 2020							
Sean Bui				TNM 2	5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Overlappin	g 3 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 320	35	C) (16	35		0 0) (0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						28 April 2	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project								
RUN:	Overl	apping	3 Alt 2	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteria	a	Active
			X	Y	Z	above	Existing	Impact Ci	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	3	3 1	250.0	40.0	0.00	4.92	0.00	66	3 10.0	8.0) Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	t				
Eyestone Environmental							28 April 2	020					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overlap	ping 3 Alt	2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average p	pavement type	shall be use	d unles	3	
								a State hi	ghway agenc	y substantiate	s the us	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Type	Calculated	Noise Reduc	tion	-	
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ted
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	68	.0 7	1 68.0) 5		68.0	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	66	.7 6	6 66.7	7 10	Snd Lvl	66.7	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0	.0 0.	0							
All Impacted		1	0.0	0	.0 0.	0							
All that meet NR Goal		1	0.0	0	.0 0.	0							

INPUT: ROADWAYS					Suns	et Gower Pro	ject				
Eyestone Environmental					28 April 2020)					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	 e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp		of a diffe	rent type with	the approv	al of FHW	A				
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Υ	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes	П						Sunset Go	wer Pr	oject			
Eyestone Environmental				28 Ap	ril 2020							
Sean Bui				TNM 2	2.5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Go	wer Proje	ct									
RUN:	Overlappin	g 4 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTrucks	3	Buses		Motorcy	cles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	, c) (0 48	35	0	0	C)
	point2		2									

INPUT: RECEIVERS				T				Sunset G	ower Proje	ct	
Evectore Environmental						20 April 20	020				
Eyestone Environmental						28 April 20	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Sunse	et Gowe	er Project		'						
RUN:	Overl	apping	4 Alt 2	,							
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Y	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
									ļ. <u>.</u>		
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.	1	1 1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0	Y

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	et				
Eyestone Environmental							28 April 2	020					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overla	ping 4 Alt	2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	s	
								a State hi	ghway agenc	y substantiate	s the u	se	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion	-	
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	70).8 7	1 70.8	3 5		70.8	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	69	0.4 6	6 69.4	1 10	Snd Lvl	69.4	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	C	0.0	0							
All Impacted		1	0.0	C	0.0	0							
All that meet NR Goal		1	0.0	C	0.0	0							

INPUT: ROADWAYS					Suns	et Gower Pro	ject				
Eyestone Environmental					28 April 2020	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	e shall be u	used unles	S
PROJECT/CONTRACT:	Sunset G	ower Proje	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp		of a diffe	rent type with	the approv	al of FHW	A				
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Cor	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Type	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1,000.0	0.0	0.00					

INPUT: TRAFFIC FOR LAeq1h Volumes						S	Sunset G	ower Pr	oject		1	
Eyestone Environmental				28 Apı	ril 2020							
Sean Bui				TNM 2	.5		ı					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	wer Proje	ct									
RUN:	Overlappin	g 5 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTruck	S	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 184	35	C) C	82	2 35		0 0)	0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Pro	ject		
Eyestone Environmental						28 April 2	020					
Sean Bui						TNM 2.5						
INPUT: RECEIVERS												
PROJECT/CONTRACT:	Sunse	et Gow	er Project		1							
RUN:	Overl	apping	5 Alt 2									
Receiver												
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Crite	eria		Active
			X	Υ	Z	above	Existing	Impact C	riteria	NR		in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal		Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB		
Along Gordon St.	1	1	250.0	30.0	0.00	4.92	0.00	7	1 .	5.0	0.0	Υ
Along Sunset Blvd.	8	3 1	250.0	40.0	0.00	4.92	0.00	66	3 10	0.0	8.0	Υ

RESULTS: SOUND LEVELS							Sunset Go	wer Projec	ct				
Eyestone Environmental							28 April 2	020					
								020					
Sean Bui							TNM 2.5		• • •				
DEG!!! TO GO!!!!D! E!!T! O							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:			Gower Pro	-									
RUN:		Overlap	ping 5 Alt	2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unless	3	
								a State hi	ghway agenc	y substantiate	s the us	3 e	
ATMOSPHERICS:		68 deg	F, 50% RH	ĺ				of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Type	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcula	ted
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	72	2.8 7	72.8	3 5	Snd Lvl	72.8	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	71	.4 6	66 71.4	1 10	Snd Lvl	71.4	0.0		8	-8.0
Dwelling Units		# DUs	Noise Re	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	(0.0	.0							
All Impacted		2	0.0	(0.0	.0							
All that meet NR Goal		1	0.0	(0.0	.0							

INPUT: ROADWAYS							Suns	et Gower Pro	ject		
Eyestone Environmental					28 April 202	0					
Sean Bui					TNM 2.5						
INPUT: ROADWAYS							Average	pavement typ	 e shall be ι	used unles	Si
PROJECT/CONTRACT:	Sunset G	ower Proj	ect				a State h	ighway agend	y substant	iates the u	se
RUN:	Overlapp	ing 6 Alt 2	2				of a diffe	rent type with	the approv	al of FHW	Δ.
Roadway		Points									
Name	Width	Name	No.	Coordinates	(pavement)		Flow Co	ntrol		Segment	
				X	Y	Z	Control	Speed	Percent	Pvmt	On
							Device	Constraint	Vehicles	Туре	Struct?
									Affected		
	ft			ft	ft	ft		mph	%		
Haul Route	12.0	point1	1	0.0	0.0	0.00	Signal	0.00	100	Average	
		point2	2	1.000.0	0.0	0.00)				

INPUT: TRAFFIC FOR LAeq1h Volumes						S	unset Go	wer Pr	oject			
Eyestone Environmental				28 Apı	il 2020							
Sean Bui				TNM 2	.5		I					
INPUT: TRAFFIC FOR LAeq1h Volumes												
PROJECT/CONTRACT:	Sunset Gov	wer Proje	ct		'							
RUN:	Overlappin	g 6 Alt 2										
Roadway	Points											
Name	Name	No.	Segmer	nt								
			Autos		MTruck	S	HTrucks	3	Buses		Motorc	ycles
			V	S	V	S	V	S	V	S	V	S
			veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph	veh/hr	mph
Haul Route	point1		1 320	35	C	0	16	35		0 0		0
	point2		2									

INPUT: RECEIVERS								Sunset G	ower Proje	ct	
Eyestone Environmental						28 April 20	020				
Sean Bui						TNM 2.5					
INPUT: RECEIVERS											
PROJECT/CONTRACT:	Suns	et Gowe	er Project		'						
RUN:	Overl	apping	6 Alt 2								
Receiver											
Name	No.	#DUs	Coordinates	(ground)		Height	Input Sou	nd Levels	and Criteri	a	Active
			X	Υ	Z	above	Existing	Impact Cı	riteria	NR	in
						Ground	LAeq1h	LAeq1h	Sub'l	Goal	Calc.
			ft	ft	ft	ft	dBA	dBA	dB	dB	
Along Gordon St.		1 1	250.0	30.0	0.00	4.92	0.00	71	5.0	0.0) Y
Along Sunset Blvd.		3 1	250.0	40.0	0.00	4.92	0.00	66	10.0	8.0) Y

RESULTS: SOUND LEVELS	,		·				Sunset Go	wer Projec	t	,			
Eyestone Environmental							28 April 2	020					
Sean Bui							TNM 2.5						
							Calculate	d with TNN	1 2.5				
RESULTS: SOUND LEVELS													
PROJECT/CONTRACT:		Sunset	Gower Pro	ject									
RUN:		Overla	pping 6 Alt	2									
BARRIER DESIGN:		INPUT	HEIGHTS					Average	pavement type	shall be use	d unles	ss	
								a State hi	ghway agenc	y substantiate	es the ເ	ıse	
ATMOSPHERICS:		68 deg	F, 50% RH					of a differ	ent type with	approval of F	HWA.		
Receiver													
Name	No.	#DUs	Existing	No Barrier					With Barrier				
			LAeq1h	LAeq1h		Increase over	existing	Туре	Calculated	Noise Reduc	tion		
				Calculated	Crit'n	Calculated	Crit'n	Impact	LAeq1h	Calculated	Goal	Calcul	ated
							Sub'l Inc					minus	
												Goal	
			dBA	dBA	dBA	dB	dB		dBA	dB	dB	dB	
Along Gordon St.	1	1	0.0	68.	.0 7	1 68.0) 5	5	68.0	0.0		0	0.0
Along Sunset Blvd.	8	3 1	0.0	66.	.7 6	66.7	7 10	Snd Lvl	66.7	0.0		8	-8.0
Dwelling Units		# DUs	Noise Red	duction									
			Min	Avg	Max								
			dB	dB	dB								
All Selected		2	0.0	0.	.0 0.	D							
All Impacted		1	0.0	0.	.0 0.0	D							
All that meet NR Goal		1	0.0	0.	.0 0.0)							

Operation Noise Calculations

Project Composite Noise Calculations (CNEL)Project: Sunset Gower - ALTERNATIVE 2

							Project	Ambient +	
Receptor	Ambient	Traffic ^a	Mechanical	Parking	Loading	Outdoor	Composite	Project	Increase
R1	62.8	50.7	53.6		30.3	50.8	56.7	63.8	1.0
R2	66.6	60.2	49.1		30.6	51.0	61.0	67.7	1.1
R3	67.7	54.0	39.2		34.1	58.4	59.8	68.3	0.6
R4	77.0	60.7	41.3		26.4	65.2	66.5	77.4	0.4
R5	69.3	62.5	50.7		31.5	66.0	67.7	71.6	2.3

^a - traffic noise levels at each receptor is based on the traffic noise analysis for the roadway segment in front of the receptor.

		Traffic I	Traffic Noise Levels, CNEL						distance to	
			Existing +	Project	distance to		Existing +		Center	adj. for
Receptor	Roadway Segment	Existing	Project	Only	roadway, ft	Existing	Project	barrier	Line	distance
R1	Gordon St.	60.9	61.3	50.7	10	60.9	61.3	0	30	0.0
R2	Fountain Ave.	70.4	70.8	60.2	10	70.4	70.8	0	30	0.0
R3	Gower St.	70.3	70.4	54.0	10	70.3	70.4	0	35	0.0
R4	Sunset Blvd.	74.0	74.2	60.7	10	74.0	74.2	0	40	0.0
R5	Gordon St.	64.6	66.7	62.5	10	64.6	66.7	0	30	0.0



Outdoor Mechanical Equipment Noise Calculations Project: Sunset Gower - ALTERNATIVE 2

Project:

Hours of Operations

		_			
	Estimated No	oise Levels,	Ld (7am to	Le (7pm to	Ln (10pm to
	Leq from SC	UNDPLAN	7pm)	10pm)	7am)
Receptor	Leq	CNEL	12	3	9
R1	46.9	53.6	46.9	46.9	46.9
R2	42.4	49.1	42.4	42.4	42.4
R3	32.5	39.2	32.5	32.5	32.5
R4	34.6	41.3	34.6	34.6	34.6
R5	44.0	50.7	44.0	44.0	44.0
		_		_	

		Ambient +			
	Ambient	Project	Increase		Ambient +
Receptor	CNEL	(CNEL)	(CNEL)	ambient (Leq)	Project (Leq)
R1	62.8	63.3	0.5	56.9	57.3
R2	66.6	66.7	0.1	59.8	59.9
R3	67.7	67.7	0.0	61.8	61.8
R4	77.0	77.0	0.0	72.0	72.0
R5	69.3	69.4	0.1	63.5	63.5



Loading and Trash Compactor Noise Calculations Project: Sunset Gower - ALTERNATIVE 2

	Estimated Levels, Le SOUND	eq from	Ld (7am to 7pm)	Le (7pm to 10pm)	Ln (10pm to 7am)
Receptor	Leq	CNEL	3	3	0
R1	33.1	30.3	27.1	33.1	0.0
R2	33.4	30.6	27.4	33.4	0.0
R3	36.9	34.1	30.9	36.9	0.0
R4	29.2	26.4	23.2	29.2	0.0
R5	34.3	31.5	28.3	34.3	0.0

			Ambient +				Ambient +
	Project	Ambient	Project	Increase	Project	daytime	Project
Receptor	CNEL	CNEL	(CNEL)	(CNEL)	Noise, (Leq)	ambient (Leq)	(Leq)
R1	30.3	62.8	62.8	0.0	33.1	61.1	61.1
R2	30.6	66.6	66.6	0.0	33.4	66.2	66.2
R3	34.1	67.7	67.7	0.0	36.9	66.2	66.2
R4	26.4	77.0	77.0	0.0	29.2	73.3	73.3
R5	31.5	69.3	69.3	0.0	34.3	67.6	67.6

Outdoor Noise Calculations

Project: Sunset Gower - ALTERNATIVE 2

ALL LEVEL Hours of Operations

					Ld (7am to	Le (7pm to	Ln (10pm to
	Estimated nois	7pm)	10pm)	7am)			
Receptor	Sound System	Occupants	Total, Leq	CNEL	11	3	2
R1	48.2	37.3	48.5	50.8	48.1	48.5	42.0
R2	48.4	36.7	48.7	51.0	48.3	48.7	42.2
R3	55.3	48.4	56.1	58.4	55.7	56.1	49.6
R4	62.7	49.9	62.9	65.2	62.5	62.9	56.4
R5	63.7	41.8	63.7	66.0	63.3	63.7	57.2

TOTAL COMBINED

			Ambient +		Project		
		Ambient	Project	Increase	Noise,	Ambient	Ambient +
Receptor	Project (CNEL)	(CNEL)	(CNEL)	(CNEL)	(Leq)	(Leq)	Project (Leq)
R1	50.8	62.8	63.1	0.3	48.5	56.9	57.5
R2	51.0	66.6	66.7	0.1	48.7	59.8	60.1
R3	58.4	67.7	68.2	0.5	56.1	61.8	62.8
R4	65.2	77.0	77.3	0.3	62.9	72.0	_
R5	66.0	69.3	71.0	1.7	63.7	63.5	66.6

Sunset Gower Alternative 2 Source Levels in dB(A) - Alt 2 - Mechanical (2020)

Name	Source type	Lw	
		dB(A)	
Building B - Mechanical L1	Point	90.0	
Building B - Mechanical L2	Point	90.0	
Building B - Mechanical L3	Point	90.0	
Building B - Mechanical L4	Point	90.0	
Building B - Mechanical L5	Point	90.0	
Building B - Mechanical L6	Point	90.0	
Building C - Mechanical L1	Point	90.0	
Building C - Mechanical L2	Point	90.0	
Building C - Mechanical L3	Point	90.0	
Building C - Mechanical L4	Point	90.0	
Building C - Mechanical L5	Point	90.0	
Building C - Mechanical L6	Point	90.0	
Building D - Mechanical 1	Point	90.0	
Building D - Mechanical 2	Point	90.0	
Building E - Mechanical 1	Point	90.0	
Building E - Mechanical 2	Point	90.0	
Cooling Tower 1	Point	100.0	
Cooling Tower 2	Point	100.0	
Cooling Tower 3	Point	100.0	
-			

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - Mechanical (2020)

Source	Source type	Leq	
		dB(A)	
Receive R1 Lo	d 46.9	dB(A)	
Cooling Tower 1	Point	32.7	
Cooling Tower 2	Point	32.7	
Cooling Tower 3	Point	31.7	
Building B - Mechanical L1	Point	22.3	
_	Point	37.6	
Building C - Mechanical L1	Point	20.7	
Building B - Mechanical L2 Building C - Mechanical L2	Point	36.4	
Building B - Mechanical L3	Point	20.9	
Building C - Mechanical L3	Point	37.2	
_	Point	22.3	
Building B - Mechanical L4	1	37.7	
Building C - Mechanical L4 Building B - Mechanical L5	Point Point	25.8	
Building C - Mechanical L5	Point	38.4	
Building B - Mechanical L6	Point	31.8	
Building C - Mechanical L6	Point	38.8	
Building D - Mechanical 1	Point	33.7	
Building E - Mechanical 1	Point	26.5	
Building E - Mechanical 2	Point	29.7	
Building D - Mechanical 2	Point	32.5	
•	d 42.4	dB(A)	
Cooling Tower 1	Point	27.1	
Cooling Tower 2	Point	27.1	
Cooling Tower 3	Point	27.1	
Building B - Mechanical L1	Point	24.6	
Building C - Mechanical L1	Point	27.1	
Building B - Mechanical L2	Point	23.1	
Building C - Mechanical L2	Point	26.7	
Building B - Mechanical L3	Point	25.5	
Building C - Mechanical L3	Point	30.4	
Building B - Mechanical L4	Point	26.3	
Building C - Mechanical L4	Point	31.4	
Building B - Mechanical L5	Point	28.2	
Building C - Mechanical L5	Point	32.5	
Building B - Mechanical L6	Point	32.6	
Building C - Mechanical L6	Point	33.6	
Building D - Mechanical 1	Point	27.2	
Building E - Mechanical 1	Point	28.2	
Building E - Mechanical 2	Point	32.3	
Building D - Mechanical 2	Point	31.8	
	32.5	dB(A)	
Cooling Tower 1	Point	22.6	
Cooling Tower 2	Point	22.6	
Cooling Tower 3	Point	22.8	
	1		

Source	Source type	Leq	
l		dB(A)	
	<u></u>	` ' '	
Building B - Mechanical L1	Point	21.8	
Building C - Mechanical L1	Point	17.6	
Building B - Mechanical L2	Point	20.3	
Building C - Mechanical L2	Point	17.1	
Building B - Mechanical L3	Point	19.9	
Building C - Mechanical L3	Point	17.1	
Building B - Mechanical L4	Point	15.9	
Building C - Mechanical L4	Point	17.2	
Building B - Mechanical L5	Point	16.3	
Building C - Mechanical L5	Point	17.5	
Building B - Mechanical L6	Point	18.7	
Building C - Mechanical L6	Point	19.2	
Building D - Mechanical 1	Point	14.8	
Building E - Mechanical 1	Point	18.5	
Building E - Mechanical 2	Point	23.4	
Building D - Mechanical 2	Point	16.8	
	34.6	dB(A)	
Cooling Tower 1	Point	28.5	
Cooling Tower 2	Point	27.9	
Cooling Tower 3	Point	27.6	
Building B - Mechanical L1	Point	19.2	
Building C - Mechanical L1	Point	17.8	
Building B - Mechanical L2	Point	19.8	
Building C - Mechanical L2	Point	16.1	
Building B - Mechanical L3	Point	20.6	
Building C - Mechanical L3	Point	15.2	
Building B - Mechanical L4	Point	22.6	
Building C - Mechanical L4	Point	15.2	
Building B - Mechanical L5	Point	16.2	
Building C - Mechanical L5	Point	14.9	
Building B - Mechanical L6	Point	18.8	
Building C - Mechanical L6	Point	17.4	
Building D - Mechanical 1	Point	12.5	
Building E - Mechanical 1	Point	17.3	
Building E - Mechanical 2	Point	15.1	
Building D - Mechanical 2	Point	11.4	
	44.0	dB(A)	
Cooling Tower 1	Point	38.1	
Cooling Tower 2	Point	38.2	
Cooling Tower 3	Point	38.1	
Building B - Mechanical L1	Point	22.6	
Building C - Mechanical L1	Point	19.3	
Building B - Mechanical L2	Point	22.5	
Building C - Mechanical L2	Point	17.7	

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - Mechanical (2020)

	•	-
4	r	٦
٦	L	4
	7	7
4	•	-

Source	Source type	Leq	
		dB(A)	
Building B - Mechanical L3	Point	26.4	
Building C - Mechanical L3	Point	18.1	
Building B - Mechanical L4	Point	27.2	
Building C - Mechanical L4	Point	19.4	
Building B - Mechanical L5	Point	28.1	
Building C - Mechanical L5	Point	21.6	
Building B - Mechanical L6	Point	28.8	
Building C - Mechanical L6	Point	23.4	
Building D - Mechanical 1	Point	28.6	
Building E - Mechanical 1	Point	27.9	
Building E - Mechanical 2	Point	23.5	
Building D - Mechanical 2	Point	25.0	

Name	Source type	Lw		
	, , , , , , , , , , , , , , , , , , , ,			
		dB(A)		
Loading (two trucks)	Point	104.9		
Trash Compactor	Point	91.5		

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - Loading & Trash

-	•
4	
۹	2
_	
٦	×

Source	Source type	Leq	
		dB(A)	
Receive R1	Leq 33.1	dB(A)	
Loading (two trucks)	Point	32.7	
Trash Compactor	Point	22.1	
Receive R2	Leq 33.4	dB(A)	
Loading (two trucks)	Point	33.1	
Trash Compactor	Point	22.6	
Receive R3	Leq 36.9	dB(A)	
Loading (two trucks)	Point	36.6	
Trash Compactor	Point	24.9	
Receive R4	Leq 29.2	dB(A)	
Loading (two trucks)	Point	28.7	
Trash Compactor	Point	19.3	
Receive R5	Leq 34.3	dB(A)	
Loading (two trucks)	Point	34.0	
Trash Compactor	Point	22.9	

Sunset Gower Alternative 2 Source Levels in dB(A) - Alt 2 - People (2020)

Name	Source type	Lw	
		dB(A)	
Building A Level 2 People	Area	85.8	
Building A Level 3 People S	Area	87.1	
Building A Level 4 People NE	Area	85.8	
Building A Level 4 People NW	Area	85.0	
Building A Level 5 People S	Area	87.1	
Building A Level 8 People N	Area	95.0	
Building A Level 8 People S	Area	95.0	
Building A Level 9 People E	Area	83.6	
Building A Level 9 People NW	Area	85.0	
Building A Level 10 People E	Area	85.8	
Building A Level 11 People E	Area	83.6	
Building A Level 11 People NW	Area	85.0	
Building A Level 12 People NE	Area	85.8	
Building A Level 13 People deck	Area	96.2	
Building A Level 13 People E	Area	83.6	
Building A Level 14 People NE	Area	85.8	
Building A Level 15 People	Area	94.7	
Building Level 6 People NE	Area	85.8	
Building Level 6 People NW	Area	85.0	
Builidng A Level 7 People S	Area	87.1	
People - Building B Level 3 E	Area	84.8	
People - Building B Level 3 N	Area	84.1	
People - Building B Level 3 S	Area	84.1	
People - Building B Level 3 W	Area	89.0	
People - Building B Level 6	Area	98.2	
People - Building B&C Level 2	Area	87.8	
People - Building B&C Level 4	Area	93.4	
People - Building B&C Level 4	Area	84.4	
People - Building B&C Level 5	Area	94.2	
People - Building B&C Level 5	Area	94.2	
People - Building C Level 6	Area	90.8	
People - Level 1 Central Plaza	Area	100.4	
People - Level 1 Paseo	Area	95.8	
People - Level 1 Plaza	Area	91.3	
People - Level 1 Plaza (Bldg B&C)	Area	91.1	

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - People (2020)

Source	Source type	Leq	
		dB(A)	
Danis D4	-ID/A		
Receive R1 Leq 37.3	dB(A)		
People - Level 1 Plaza	Area	11.0 19.8	
People - Level 1 Place (Pldg P&C)	Area Area	20.2	
People - Level 1 Plaza (Bldg B&C) People - Level 1 Central Plaza	Area	25.6	
	1	27.2	
People - Building B&C Level 5	Area	27.2	
People - Building B&C Level 5	Area	16.3	
Building A Level 5 People S	Area	24.3	
People - Building C Level 6 People - Building B Level 6	Area	30.8	
Building Level 6 People NE	Area Area	7.0	
•		-0.3	
Building Level 6 People NW	Area Area	-0.3 23.2	
Builidng A Level 7 People S Building A Level 8 People S	1	28.0	
Building A Level 8 People N	Area	25.0 25.0	
Building A Level 9 People NW	Area Area	-0.3	
	1	19.3	
Building A Level 9 People E Building A Level 10 People E	Area Area	7.5	
Building A Level 11 People E	Area	-0.3	
Building A Level 11 People RW	Area	-0.3 19.4	
Building A Level 12 People NE	Area	7.2	
Building A Level 13 People deck	1	11.2	
Building A Level 13 People Geck	Area Area	21.1	
Building A Level 13 People E Building A Level 14 People NE	Area	7.1	
Building A Level 15 People	Area	25.2	
People - Building B&C Level 2	Area	14.0	
Building A Level 2 People	Area	3.2	
People - Building B Level 3 W	Area	20.5	
People - Building B Level 3 V	Area	16.8	
•			
People - Building B Level 3 E People - Building B Level 3 N	Area Area	10.9 3.8	
Building A Level 3 People S	Area	3.6 14.9	
People - Building B&C Level 4	Area	19.3	
People - Building B&C Level 4	Area	16.8	
Building A Level 4 People NE	Area	5.6	
Building A Level 4 People NW	Area	-0.4	
Receive R2 Leq 36.7	dB(A)		
People - Level 1 Plaza	Area	10.4	
People - Level 1 Paseo	Area	21.1	
People - Level 1 Plaza (Bldg B&C)	Area	19.9	
People - Level 1 Central Plaza	Area	25.8	
People - Building B&C Level 5	Area	21.9	
People - Building B&C Level 5	Area	21.9	
Building A Level 5 People S	Area	20.2	
244g / (2010) 0 1 00pio 0	, oa	20.2	

	I.a		
Source	Source type	Leq	
		dB(A)	
People - Building C Level 6	Area	17.0	
People - Building B Level 6	Area	31.0	
Building Level 6 People NE	Area	2.9	
Building Level 6 People NW	Area	0.7	
Builidng A Level 7 People S	Area	25.3	
Building A Level 8 People S	Area	29.4	
Building A Level 8 People N	Area	23.0	
Building A Level 9 People NW	Area	0.6	
Building A Level 9 People E	Area	17.8	
Building A Level 10 People E	Area	3.3	
Building A Level 11 People NW	Area	0.6	
Building A Level 11 People E	Area	18.0	
Building A Level 12 People NE Building A Level 13 People deck	Area Area	3.2 12.7	
Building A Level 13 People deck	Area	19.3	
Building A Level 13 People L	Area	3.0	
Building A Level 14 People Building A Level 15 People	Area	22.7	
People - Building B&C Level 2	Area	13.1	
Building A Level 2 People	Area	3.3	
People - Building B Level 3 W	Area	16.1	
People - Building B Level 3 S	Area	22.0	
People - Building B Level 3 E	Area	13.8	
People - Building B Level 3 N	Area	5.5	
Building A Level 3 People S	Area	16.1	
People - Building B&C Level 4	Area	17.0	
People - Building B&C Level 4	Area	23.3	
Building A Level 4 People NE	Area	2.5	
Building A Level 4 People NW	Area	0.7	
Receive R3 Leq 48.4	dB(A)	
People - Level 1 Plaza	Area	13.5	
People - Level 1 Paseo	Area	30.7	
People - Level 1 Plaza (Bldg B&C)	Area	35.6	
People - Level 1 Central Plaza	Area	33.2	
People - Building B&C Level 5	Area	39.9	
People - Building B&C Level 5	Area	39.9	
Building A Level 5 People S People - Building C Level 6	Area	28.1 38.2	
People - Building C Level 6 People - Building B Level 6	Area	38.2 41.5	
Building Level 6 People NE	Area Area	41.5	
Building Level 6 People NW	Area	18.5	
Builiding A Level 7 People S	Area	31.3	
Building A Level 8 People S	Area	36.4	
Building A Level 8 People N	Area	30.4	
Building A Level 9 People NW	Area	18.9	
gg	1		

Source	Source type	Leq	
		dB(A)	
Building A Level 9 People E	Area	0.0	
Building A Level 10 People E	Area	4.2	
Building A Level 11 People NW	Area	18.0	
Building A Level 11 People E	Area	1.4	
Building A Level 12 People NE	Area	4.5	
Building A Level 13 People deck	Area	31.0	
Building A Level 13 People E	Area	0.7	
Building A Level 14 People NE	Area	4.8	
Building A Level 15 People	Area	22.7	
People - Building B&C Level 2	Area	34.5	
Building A Level 2 People	Area	4.5	
People - Building B Level 3 W	Area	34.9	
People - Building B Level 3 S	Area	9.5	
People - Building B Level 3 E	Area	12.1	
People - Building B Level 3 N	Area	11.8	
Building A Level 3 People S	Area	26.4	
People - Building B&C Level 4	Area	37.9	
People - Building B&C Level 4	Area	10.0	
Building A Level 4 People NE	Area	4.3	
Building A Level 4 People NW	Area	18.4	
Receive R4 Leq 49.9	dB(A		
People - Level 1 Plaza	Area	47.7	
People - Level 1 Paseo	Area	40.3	
People - Level 1 Plaza (Bldg B&C)	Area	14.4	
People - Level 1 Central Plaza	Area	30.8	
People - Building B&C Level 5	Area	13.5	
People - Building B&C Level 5	Area	13.5	
Building A Level 5 People S	Area	11.4	
People - Building C Level 6	Area	10.7	
People - Building B Level 6	Area	23.3	
Building Level 6 People NE	Area	34.8	
Building Level 6 People NW	Area	20.2	
Builidng A Level 7 People S	Area	11.3	
Building A Level 8 People S	Area	25.6	
Building A Level 8 People N Building A Level 9 People NW	Area	38.0	
Building A Level 9 People RVV	Area Area	19.3 21.6	
Building A Level 10 People E	Area	29.5	
Building A Level 11 People E	Area	18.5	
Building A Level 11 People R	Area	23.2	
Building A Level 12 People NE	Area	23.2 27.4	
Building A Level 13 People deck	Area	29.5	
Building A Level 13 People Geck	Area	21.8	
Building A Level 13 People L	Area	25.9	
Danding / Lover 14 1 Gopie NL	, "Ou	20.9	I

Source	Source type	Leq	
	Course type	dB(A)	
		, ,	
Building A Level 15 People	Area	31.3	
People - Building B&C Level 2	Area	6.4	
Building A Level 2 People	Area	38.5	
People - Building B Level 3 W	Area	8.8	
People - Building B Level 3 S	Area	-0.1	
People - Building B Level 3 E	Area	9.3	
People - Building B Level 3 N	Area	9.4	
Building A Level 3 People S	Area	11.5	
People - Building B&C Level 4	Area	12.7	
People - Building B&C Level 4	Area	0.4	
Building A Level 4 People NE	Area	37.1	
Building A Level 4 People NW	Area	20.5	
Receive R5 Leq 41.8	dB(A)	
People - Level 1 Plaza	Area	17.4	
People - Level 1 Paseo	Area	21.4	
People - Level 1 Plaza (Bldg B&C)	Area	14.6	
People - Level 1 Central Plaza	Area	33.4	
People - Building B&C Level 5	Area	15.4	
People - Building B&C Level 5	Area	15.4	
Building A Level 5 People S	Area	21.6	
People - Building C Level 6	Area	13.9	
People - Building B Level 6	Area	32.8	
Building Level 6 People NE	Area	18.2	
Building Level 6 People NW	Area	7.9	
Builidng A Level 7 People S	Area	20.6	
Building A Level 8 People S	Area	33.2	
Building A Level 8 People N	Area	35.9	
Building A Level 9 People NW	Area	7.4	
Building A Level 9 People E	Area	27.6	
Building A Level 10 People E	Area	23.1	
Building A Level 11 People NW	Area	8.0	
Building A Level 11 People E	Area	26.3	
Building A Level 12 People NE	Area	21.3	
Building A Level 13 People deck	Area	28.6	
Building A Level 13 People E	Area	25.7	
Building A Level 14 People NE	Area	20.2	
Building A Level 15 People	Area	31.7	
People - Building B&C Level 2	Area	10.0	
Building A Level 2 People	Area	12.1	
People - Building B Level 3 W	Area	10.5	
People - Building B Level 3 S	Area	0.8	
People - Building B Level 3 E	Area	19.9	
People - Building B Level 3 N	Area	16.8	
Building A Level 3 People S	Area	20.7	
People - Building B Level 3 N	Area	16.8	

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - People (2020)

9

Source	Source type	Leq	
		dB(A)	
	_		
People - Building B&C Level 4	Area	14.1	
People - Building B&C Level 4	Area	1.2	
Building A Level 4 People NE	Area	13.5	
Building A Level 4 People NW	Area	7.7	

Sunset Gower Alternative 2 Source Levels in dB(A) - Alt 2 - Speakers (2020)

Name	Source type	Lw	
		dB(A)	
Level 8 Speaker 1	Point	113.6	
Level 8 Speaker 2	Point	113.6	
Level 8 Speaker 3	Point	113.6	
Level 8 Speaker 4	Point	113.6	
Level 8 Speaker 5	Point	113.6	
Level 8 Speaker 6	Point	113.6	
Level 8 Speaker 7	Point	113.6	
Level 8 Speaker 8	Point	113.6	
Level 8 Speaker 9	Point	113.6	
Level 8 Speaker 10	Point	113.6	
Level 13 Speaker 1	Point	113.6	
Level 13 Speaker 3	Point	113.6	
Level 13 Speaker 4	Point	113.6	
Level 13 Speaker 2	Point	113.6	
Level 15 Speaker 1	Point	118.6	
Level 15 Speaker 2	Point	118.6	
Level 15 Speaker 3	Point	118.6	
Level 15 Speaker 4	Point	118.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1	Point	113.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	
Speakers Level 1 Central Plaza	Point	118.6	

Source	Source type	Ld	
Course	Course type	dB(A)	
		ub(A)	
Receive R1 Leq 48.2	dB(A)		
Speakers Level 1	Point	8.2	
Speakers Level 1	Point	7.8	
Speakers Level 1	Point	7.7	
Speakers Level 1 Central Plaza	Point	31.9	
Speakers Level 1 Central Plaza	Point	17.8	
Speakers Level 1 Central Plaza	Point	37.3	
Speakers Level 1 Central Plaza	Point	24.1	
Speakers Level 1 Central Plaza	Point	18.7	
Speakers Level 1 Central Plaza	Point	28.2	
Speakers Level 1	Point	34.8	
Speakers Level 1	Point	16.8	
Level 8 Speaker 1	Point	15.6	
Level 8 Speaker 2	Point	7.0	
Level 8 Speaker 3	Point	35.8	
Level 8 Speaker 4	Point	36.6	
Level 8 Speaker 5	Point	7.5	
Level 8 Speaker 6	Point	9.6	
Level 8 Speaker 7	Point	10.2	
Level 8 Speaker 8	Point	43.1	
Level 8 Speaker 9	Point	37.7	
Level 8 Speaker 10	Point	38.5	
Level 13 Speaker 4	Point	6.1	
Level 13 Speaker 3	Point	7.5	
Level 13 Speaker 2	Point	7.4	
Level 13 Speaker 1	Point	8.1	
Level 15 Speaker 1	Point	41.0	
Level 15 Speaker 2	Point	13.5	
Level 15 Speaker 3	Point	12.0	
Level 15 Speaker 4	Point	13.4	
Receive R2 Leq 48.4	dB(A)		
Speakers Level 1	Point	8.9	
Speakers Level 1	Point	8.7	
Speakers Level 1	Point	8.7	
Speakers Level 1 Central Plaza	Point	35.6	
Speakers Level 1 Central Plaza	Point	18.7	
Speakers Level 1 Central Plaza	Point	34.4	
Speakers Level 1 Central Plaza	Point	20.8	
Speakers Level 1 Central Plaza	Point	24.9	
Speakers Level 1 Central Plaza	Point	31.2	
Speakers Level 1	Point	37.2	
Speakers Level 1	Point	34.2	
Level 8 Speaker 1	Point	16.6	
Level 8 Speaker 2	Point	6.8	

AES 22801 Crespi St Woodland Hills, CA 91364 USA

Source	Source type	Ld	
		dB(A)	
Level 8 Speaker 3	Point	31.3	
Level 8 Speaker 4	Point	31.0	
Level 8 Speaker 5	Point	9.3	
Level 8 Speaker 6	Point	13.2	
Level 8 Speaker 7	Point	13.8	
Level 8 Speaker 8	Point	46.1	
Level 8 Speaker 9	Point	33.6	
Level 8 Speaker 10	Point	34.5	
Level 13 Speaker 4	Point	6.2	
Level 13 Speaker 3	Point	9.6	
Level 13 Speaker 2	Point	9.4	
Level 13 Speaker 1	Point	9.9	
Level 15 Speaker 1	Point	36.6	
Level 15 Speaker 2	Point	16.1	
Level 15 Speaker 3	Point	12.0	
Level 15 Speaker 4	Point	12.5	
Receive R3 Leq 55.3	dB(A)		
Speakers Level 1	Point	11.4	
Speakers Level 1	Point	11.8	
Speakers Level 1	Point	15.6	
Speakers Level 1 Central Plaza	Point	35.9	
Speakers Level 1 Central Plaza	Point	41.0	
Speakers Level 1 Central Plaza	Point	31.6	
Speakers Level 1 Central Plaza	Point	35.6	
Speakers Level 1 Central Plaza	Point	39.7	
Speakers Level 1 Central Plaza	Point	28.5	
Speakers Level 1	Point	35.8	
Speakers Level 1	Point	47.9	
Level 8 Speaker 1	Point	14.6	
Level 8 Speaker 2	Point	9.9	
Level 8 Speaker 3	Point	11.1	
Level 8 Speaker 4	Point	12.6	
Level 8 Speaker 5	Point	39.1	
Level 8 Speaker 6	Point	40.1	
Level 8 Speaker 7	Point	41.0	
Level 8 Speaker 8	Point	52.5	
Level 8 Speaker 9	Point	11.9	
Level 8 Speaker 10	Point	15.9	
Level 13 Speaker 4	Point	10.7	
Level 13 Speaker 3	Point	30.1	
Level 13 Speaker 2	Point	29.7	
Level 13 Speaker 1	Point	34.9	
Level 15 Speaker 1	Point	16.8	
Level 15 Speaker 2	Point	44.0	
	·		

AES 22801 Crespi St Woodland Hills, CA 91364 USA

Source	Source type	Ld	
Cource	Journe type		
		dB(A)	
Level 15 Speaker 3	Point	16.1	
Level 15 Speaker 4	Point	15.4	
Receive R4 Leq 62.7	dB(A)		
Speakers Level 1	Point	58.6	
Speakers Level 1	Point	57.2	
Speakers Level 1	Point	55.9	
Speakers Level 1 Central Plaza	Point	30.0	
Speakers Level 1 Central Plaza	Point	38.9	
Speakers Level 1 Central Plaza	Point	30.4	
Speakers Level 1 Central Plaza	Point	40.8	
Speakers Level 1 Central Plaza	Point	34.8	
Speakers Level 1 Central Plaza	Point	32.5	
Speakers Level 1	Point	33.8	
Speakers Level 1	Point	31.4	
Level 8 Speaker 1	Point	44.6	
Level 8 Speaker 2	Point	47.4	
Level 8 Speaker 3	Point	46.1	
Level 8 Speaker 4	Point	41.3	
Level 8 Speaker 5	Point	17.6	
Level 8 Speaker 6	Point	15.8	
Level 8 Speaker 7	Point	15.7	
Level 8 Speaker 8	Point	14.6	
Level 8 Speaker 9	Point	38.1	
Level 8 Speaker 10	Point	35.0	
Level 13 Speaker 4	Point	33.8	
Level 13 Speaker 3	Point	15.5	
Level 13 Speaker 2	Point	16.2	
Level 13 Speaker 1	Point	16.4	
Level 15 Speaker 1	Point	41.2	
Level 15 Speaker 2	Point	19.5	
Level 15 Speaker 3	Point	36.2	
Level 15 Speaker 4	Point	37.4	
Receive R5 Leq 63.7	dB(A)		
Speakers Level 1	Point	29.0	
Speakers Level 1	Point	20.9	
Speakers Level 1	Point	18.2	
Speakers Level 1 Central Plaza	Point	36.7	
Speakers Level 1 Central Plaza	Point	36.5	
Speakers Level 1 Central Plaza	Point	39.5	
Speakers Level 1 Central Plaza	Point	30.7	
Speakers Level 1 Central Plaza	Point	36.1	
Speakers Level 1 Central Plaza	Point	40.0	
Speakers Level 1	Point	29.2	
Speakers Level 1	Point	26.3	

AES 22801 Crespi St Woodland Hills, CA 91364 USA

Sunset Gower Alternative 2 Assessed contribution level - Alt 2 - Speakers (2020)

4	•	
4	r	٦
٦	L	4
ì	•	7
	٠	ø
		_

Source	Source type	Ld	
		dB(A)	
Level 8 Speaker 1	Point	43.4	
Level 8 Speaker 2	Point	34.5	
Level 8 Speaker 3	Point	56.8	
Level 8 Speaker 4	Point	56.8	
Level 8 Speaker 5	Point	12.8	
Level 8 Speaker 6	Point	12.6	
Level 8 Speaker 7	Point	11.7	
Level 8 Speaker 8	Point	19.4	
Level 8 Speaker 9	Point	57.1	
Level 8 Speaker 10	Point	55.6	
Level 13 Speaker 4	Point	16.8	
Level 13 Speaker 3	Point	11.5	
Level 13 Speaker 2	Point	11.6	
Level 13 Speaker 1	Point	11.8	
Level 15 Speaker 1	Point	56.6	
Level 15 Speaker 2	Point	17.2	
Level 15 Speaker 3	Point	25.3	
Level 15 Speaker 4	Point	33.5	

Off-Site Traffic Noise Calculations

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

EXISTING CONDITIONS Roadway Segment	Roadway Width*, ft	Distance to Edge of Roadway, ft	Distance to Centerline, feet	Speed mph	Traffic PHV	Volume ADT	PHV to ADT factor	Barrier Atten.	Site Adjust., dBA	24-Hour CNEL
Vine Street				·						
- Between Hollywood Blvd. and Sunset Blvd.	70	10	45	35	2,312	23,120	10%	0	0	72.0
- Between Sunset Blvd. and Fountain Ave.	70	10	45	35	2,569	25,690	10%	0	0	72.5
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,449	24,490	10%	0	0	72.2
Gower Street										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	1,319	13,190	10%	0	0	70.7
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	1,221	12,210	10%	0	0	70.3
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,207	12,070	10%	0	0	70.3
Bronson Avenue										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	843	8,430	10%	0	0	68.7
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	778	7,780	10%	0	0	68.4
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	743	7,430	10%	0	0	68.2
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		838	10%	0	0	59.5
Gordon Street										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	35	269	2,690	10%	0	0	64.6
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,167	10%	0	0	60.9
Tamarind Avenue										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	25		2,046	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,280	10%	0	0	61.3
Hollywood Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	1,839	18,390	10%	0	0	71.5
- Between Gower St. and Bronson Ave.	60	10	40	35	1,797	17,970	10%	0	0	71.4
Sunset Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,058	30,580	10%	0	0	73.7
- Between Gower St. and Gordon St.	60	10	40	35	3,237	32,370	10%	0	0	74.0
- Between Gordon St. and Bronson Ave.	60	10	40	35	3,247	32,470	10%	0	0	74.0
De Longpre Avenue										

ay Edge of , ft Roadway, 10	Centerline, ft feet 30	Speed mph 25	Traffic PHV	Volume ADT	PHV to ADT factor	Barrier Atten.	Adjust., dBA	24-Hour CNEL
, ,,			PHV	ADT	ADT factor	Atten.	dΒΛ	CNEL
10	30	25				,	ubA	CINEL
		23		2,206	10%	0	0	63.7
10	30	25		777	10%	0	0	59.2
10	30	35	1,030	10,300	10%	0	0	70.4
10	30	35	1,028	10,280	10%	0	0	70.4
10	30	35	884	8,840	10%	0	0	69.7
10	40	35	2,481	24,810	10%	0	0	72.8
10	40	35	2,618	26,180	10%	0	0	73.0
	10 10 10	10 30 10 30 10 30	10 30 35 10 30 35 10 30 35 10 40 35	10 30 35 1,030 10 30 35 1,028 10 30 35 884 10 40 35 2,481	10 30 35 1,030 10,300 10 30 35 1,028 10,280 10 30 35 884 8,840 10 40 35 2,481 24,810	10 30 35 1,030 10,300 10% 10 30 35 1,028 10,280 10% 10 30 35 884 8,840 10% 10 40 35 2,481 24,810 10%	10 30 35 1,030 10,300 10% 0 10 30 35 1,028 10,280 10% 0 10 30 35 884 8,840 10% 0 10 40 35 2,481 24,810 10% 0	10 30 35 1,030 10,300 10% 0 0 10 30 35 1,028 10,280 10% 0 0 10 30 35 884 8,840 10% 0 0 10 40 35 2,481 24,810 10% 0 0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.

Off-Site Traffic Noise Calculations

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

EXISTING + PROJECT CONDITIONS	Roadway	Distance to Edge of	Distance to Centerline,	Speed		Volume	PHV to	Barrier	Site Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,342	23,420	10%	0	0	72.1
 Between Sunset Blvd. and Fountain Ave. 	70	10	45	35	2,582	25,820	10%	0	0	72.5
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,474	24,740	10%	0	0	72.3
Gower Street										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,342	13,420	10%	0	0	70.7
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	1,221	12,210	10%	0	0	70.3
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,243	12,430	10%	0	0	70.4
Bronson Avenue										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	876	8,760	10%	0	0	68.9
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	778	7,780	10%	0	0	68.4
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	774	7,740	10%	0	0	68.3
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		838	10%	0	0	59.5
Gordon Street										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	35	442	4,420	10%	0	0	66.7
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,270	10%	0	0	61.3
Tamarind Avenue										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	25		2,046	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,280	10%	0	0	61.3
Hollywood Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	1,839	18,390	10%	0	0	71.5
 Between Gower St. and Bronson Ave. 	60	10	40	35	1,797	17,970	10%	0	0	71.4
Sunset Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	3,169	31,690	10%	0	0	73.9
 Between Gower St. and Gordon St. 	60	10	40	35	3,404	34,040	10%	0	0	74.2
- Between Gordon St. and Bronson Ave.	60	10	40	35	3,445	34,450	10%	0	0	74.2
De Longpre Avenue										

EXISTING + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
- Between Vine St, and Gower St.	40	10	30	25		2,206	10%	0	0	63.7
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		777	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,112	11,120	10%	0	0	70.7
- Between Gower St. and Gordon St.	40	10	30	35	1,146	11,460	10%	0	0	70.8
- Between Gordon St. and Bronson Ave.	40	10	30	35	915	9,150	10%	0	0	69.9
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	2,501	25,010	10%	0	0	72.8
- Between Gower St. and Bronson Ave.	60	10	40	35	2,623	26,230	10%	0	0	73.0

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.

Off-Site Traffic Noise Calculations

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

FUTURE NO PROJECT CONDITIONS	Roadway	Distance to Edge of	Distance to Centerline,	Speed		Volume	PHV to	Barrier	Site Adjust.,	24-Hour
Roadway Segment Vine Street	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
	70	40	45	25	0.745	07.450	400/	0	0	70.7
- Between Hollywood Blvd. and Sunset Blvd.	70 70	10	45	35	2,715	27,150	10%	0	0	72.7
- Between Sunset Blvd. and Fountain Ave.	70	10	45	35	3,045	30,450	10%	0	0	73.2
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,872	28,720	10%	0	0	72.9
Gower Street										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,647	16,470	10%	0	0	71.6
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	1,437	14,370	10%	0	0	71.0
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,431	14,310	10%	0	0	71.0
Bronson Avenue										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,042	10,420	10%	0	0	69.6
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	851	8,510	10%	0	0	68.8
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	794	7,940	10%	0	0	68.5
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		853	10%	0	0	59.6
Gordon Street										
- Between Sunset Blvd. and Fountain Ave.	40	10	30	35	274	2,740	10%	0	0	64.6
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,188	10%	0	0	61.0
Tamarind Avenue						,				
- Between Sunset Blvd, and Fountain Ave.	40	10	30	25		2,083	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,303	10%	0	0	61.4
Hollywood Boulevard						1,000		•	-	
- Between Vine St, and Gower St.	60	10	40	35	2,666	26,660	10%	0	0	73.1
- Between Gower St. and Bronson Ave.	60	10	40	35	2,671	26,710	10%	Ö	0	73.1
Sunset Boulevard	00	.0		00	2,01 .	20,1.10	1070	·	ŭ	70.1
- Between Vine St. and Gower St.	60	10	40	35	4,351	43,510	10%	0	0	75.2
- Between Gower St. and Gordon St.	60	10	40	35	4,477	44,770	10%	0	0	75.4
- Between Gordon St. and Bronson Ave.	60	10	40	35	4,505	45,050	10%	0	0	75.4 75.4
	00	10	40	33	4,505	45,050	10 /0	U	U	13.4
De Longpre Avenue										

	Distance to	Distance to					Site			
Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour	
Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL	
40	10	30	25		2,246	10%	0	0	63.8	
40	10	30	25		791	10%	0	0	59.2	
40	10	30	35	1,070	10,700	10%	0	0	70.5	
40	10	30	35	1,077	10,770	10%	0	0	70.6	
40	10	30	35	927	9,270	10%	0	0	69.9	
60	10	40	35	3,247	32,470	10%	0	0	74.0	
60	10	40	35	3,315	33,150	10%	0	0	74.1	
	Width*, ft 40 40 40 40 40 40 60	Roadway Width*, ft Edge of Roadway, ft 40 10 40 10 40 10 40 10 40 10 40 10 40 10 60 10	Roadway Width*, ft Edge of Roadway, ft Centerline, feet 40 10 30 40 10 30 40 10 30 40 10 30 40 10 30 40 10 30 40 10 30 60 10 40	Roadway Width*, ft Edge of Roadway, ft Centerline, feet Speed mph 40 10 30 25 40 10 30 25 40 10 30 35 40 10 30 35 40 10 30 35 40 10 30 35 60 10 40 35	Roadway Width*, ft Edge of Roadway, ft Centerline, feet Speed mph Traffic PHV 40 10 30 25 40 10 30 25 40 10 30 35 1,070 40 10 30 35 1,077 40 10 30 35 927 60 10 40 35 3,247	Roadway Width*, ft Edge of Roadway, ft Centerline, feet Speed mph Traffic Volume PHV ADT 40 10 30 25 2,246 40 10 30 25 791 40 10 30 35 1,070 10,700 40 10 30 35 1,077 10,770 40 10 30 35 1,077 10,770 40 10 30 35 927 9,270 60 10 40 35 3,247 32,470	Roadway Width*, ft Edge of Width*, ft Centerline, feet Speed mph Traffic Volume PHV PHV to ADT ADT factor 40 10 30 25 2,246 10% 40 10 30 25 791 10% 40 10 30 35 1,070 10,700 10% 40 10 30 35 1,077 10,770 10% 40 10 30 35 927 9,270 10% 60 10 40 35 3,247 32,470 10%	Roadway Width*, ft Edge of Width*, ft Centerline, feet Speed mph mph Traffic Volume PHV ADT ADT factor Atten. PHV to ADT factor Atten. Barrier Atten. 40 10 30 25 2,246 10% 0 40 10 30 25 791 10% 0 40 10 30 35 1,070 10,700 10% 0 40 10 30 35 1,077 10,770 10% 0 40 10 30 35 927 9,270 10% 0 60 10 40 35 3,247 32,470 10% 0	Roadway Width*, ft Edge of Width*, ft Centerline, feet Speed mph Traffic Volume PHV PHV to ADT ADT factor Barrier Atten. dBA Adjust., dBA 40 10 30 25 2,246 10% 0 0 40 10 30 25 791 10% 0 0 40 10 30 35 1,070 10,700 10% 0 0 40 10 30 35 1,077 10,770 10% 0 0 40 10 30 35 1,077 10,770 10% 0 0 40 10 30 35 927 9,270 10% 0 0 40 10 30 35 3,247 32,470 10% 0 0	

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.

Off-Site Traffic Noise Calculations

Traffic Distribution as % of ADT				
Vehicle Type	Day	Eve	Night	Sub total
Auto	77.6%	9.7%	9.7%	97.0%
Medium Truck	1.6%	0.2%	0.2%	2.0%
Heavy Truck	0.8%	0.1%	0.1%	1.0%
	80.0%	10.0%	10.0%	100.0%

PHV to ADT factor 10%

FUTURE + PROJECT CONDITIONS	Roadway	Distance to Edge of	Distance to Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Site Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
Vine Street										
 Between Hollywood Blvd. and Sunset Blvd. 	70	10	45	35	2,745	27,450	10%	0	0	72.7
 Between Sunset Blvd. and Fountain Ave. 	70	10	45	35	3,058	30,580	10%	0	0	73.2
- Between Fountain Ave. and Santa Monica Blvd.	70	10	45	35	2,897	28,970	10%	0	0	73.0
Gower Street										
 Between Hollywood Blvd. and Sunset Blvd. 	50	10	35	35	1,670	16,700	10%	0	0	71.7
 Between Sunset Blvd. and Fountain Ave. 	50	10	35	35	1,437	14,370	10%	0	0	71.0
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	1,467	14,670	10%	0	0	71.1
Bronson Avenue										
- Between Hollywood Blvd. and Sunset Blvd.	50	10	35	35	1,075	10,750	10%	0	0	69.8
- Between Sunset Blvd. and Fountain Ave.	50	10	35	35	851	8,510	10%	0	0	68.8
- Between Fountain Ave. and Santa Monica Blvd.	50	10	35	35	825	8,250	10%	0	0	68.6
Beachwood Drive										
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		853	10%	0	0	59.6
Gordon Street										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	35	447	4,470	10%	0	0	66.8
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,291	10%	0	0	61.4
Tamarind Avenue										
 Between Sunset Blvd. and Fountain Ave. 	40	10	30	25		2,083	10%	0	0	63.4
- Between Fountain Ave. and Santa Monica Blvd.	40	10	30	25		1,303	10%	0	0	61.4
Hollywood Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	2,666	26,660	10%	0	0	73.1
 Between Gower St. and Bronson Ave. 	60	10	40	35	2,671	26,710	10%	0	0	73.1
Sunset Boulevard										
 Between Vine St, and Gower St. 	60	10	40	35	4,462	44,620	10%	0	0	75.4
 Between Gower St. and Gordon St. 	60	10	40	35	4,644	46,440	10%	0	0	75.5
 Between Gordon St. and Bronson Ave. 	60	10	40	35	4,702	47,020	10%	0	0	75.6
De Longpre Avenue										

FUTURE + PROJECT CONDITIONS		Distance to	Distance to						Site	
	Roadway	Edge of	Centerline,	Speed	Traffic	Volume	PHV to	Barrier	Adjust.,	24-Hour
Roadway Segment	Width*, ft	Roadway, ft	feet	mph	PHV	ADT	ADT factor	Atten.	dBA	CNEL
- Between Vine St, and Gower St.	40	10	30	25		2,246	10%	0	0	63.8
Afton Place										
- Between Vine St, and Gower St.	40	10	30	25		791	10%	0	0	59.2
Fountain Avenue										
- Between Vine St, and Gower St.	40	10	30	35	1,152	11,520	10%	0	0	70.9
- Between Gower St. and Gordon St.	40	10	30	35	1,195	11,950	10%	0	0	71.0
- Between Gordon St. and Bronson Ave.	40	10	30	35	958	9,580	10%	0	0	70.1
Santa Monica Boulevard										
- Between Vine St, and Gower St.	60	10	40	35	3,266	32,660	10%	0	0	74.0
- Between Gower St. and Bronson Ave.	60	10	40	35	3,320	33,200	10%	0	0	74.1

^{*} Estimated based on Google Earth map.

^{**} Calculated using FHWA's TNM Version 2.5 Computer Noise Model.