

GROUP



DELTA

**REPORT OF GEOTECHNICAL INVESTIGATION
AZTEC STADIUM
SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA**

Prepared for

GATZKE DILLON & BALLANCE LLP
2762 Gateway Road
Carlsbad, California 92009

Prepared by

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

Project No. SD605
May 10, 2019



GROUP DELTA

May 10, 2019

Gatzke Dillon & Ballance LLP
2762 Gateway Road
Carlsbad, California 92009

Attention: Mr. Michael Masterson

SUBJECT: REPORT OF GEOTECHNICAL INVESTIGATION
Aztec Stadium
SDSU Mission Valley
San Diego, California

Mr. Masterson:

Group Delta Consultants (Group Delta) is submitting this geotechnical investigation report for the proposed Aztec Stadium (Stadium) that will be part of the redevelopment of the former SDCCU stadium site (overall site) into the San Diego State University Mission Valley (SDSU MV) campus. The ultimate development of the site (*Full Build Out*) will consist of a Stadium, Campus Expansion, Tailgate Park, Hotel and Conference Center, Residential, and Park Space.

Group Delta prepared this report per our Agreement for Consulting Services dated January 23rd, 2019. This issue of the report is the first draft of the Report of Geotechnical Investigation. The purpose of this report is to provide preliminary information to support the collaborative design-build procurement of the project. Revisions may be needed for design development and to obtain construction permits.

This report provides interpretations of the geologic and geotechnical conditions observed and recommendations for design and construction of the Stadium, the Phase 1A Grading and the portion of the Phase 1B Grading that is the responsibility of the Stadium Contractor. Group Delta submitted a separate geotechnical report for the grading and civil works (*Site Development*) and another report regarding subsurface environmental conditions of the overall site.

We appreciate this opportunity to be of continued professional service. Please contact us with questions or comments, or if you need anything else.

GROUP DELTA CONSULTANTS

Christopher K. Vonk, P.E. 86619
Project Engineer

James C. Sanders, C.E.G. 2258
Associate Engineering Geologist

Charles Robin (Rob) Stroop, G.E. 2298
Associate Geotechnical Engineer

Distribution: Addressee, Mr. Michael Masterson (MMasterson@gdandb.com)

TABLE OF CONTENTS

1.0	INTRODUCTION	1
1.1	Scope of Services.....	1
1.2	Site Description.....	2
1.3	Proposed Development.....	2
1.3.1	Stadium Structure.....	2
1.3.2	Site Formation and Civil Works.....	3
1.4	Previous Site Use and Development.....	4
1.5	Previous Geotechnical Studies.....	5
1.6	Previous Environmental Subsurface Explorations.....	5
2.0	FIELD AND LABORATORY INVESTIGATION	6
2.1	Current Subsurface Exploration.....	6
2.2	Laboratory Testing.....	6
3.0	GEOLOGY AND SUBSURFACE CONDITIONS	6
3.1	Friars Formation.....	7
3.2	Surficial Soils - Undifferentiated.....	8
3.2.1	Surface Gravel/Fill.....	8
3.2.2	Middle Sand/Fine-Grained Soils.....	8
3.2.3	Basal Gravel.....	9
3.3	Groundwater.....	9
4.0	GEOLOGIC HAZARDS	9
4.1	Strong Ground Motion.....	10
4.2	Earthquake Surface Fault-Rupture Hazard.....	10
4.3	Earthquake Induced Ground Failure.....	10
4.3.1	Results of Liquefaction Analyses.....	10
4.3.2	Methodology.....	12
4.4	Landslides and Slope Stability.....	12
4.5	Tsunami, Seiche, and Flooding.....	12
4.6	Subsidence.....	12

5.0	GEOTECHNICAL CONDITIONS.....	13
5.1	Expansive Soils.....	14
5.2	Compressible Soils.....	14
5.3	Reactive Soils.....	15
5.4	Reuse of Onsite Soils.....	16
6.0	CONCLUSIONS.....	17
7.0	RECOMMENDATIONS.....	18
7.1	General.....	18
7.1.1	Design Groundwater Level.....	18
7.1.2	Seismic Design.....	18
7.1.3	Surface Drainage.....	19
7.2	Ground Improvement.....	19
7.2.1	Purpose and Need.....	19
7.2.2	Summary Assessment of Effectiveness.....	20
7.2.3	Deep Dynamic Compaction.....	21
7.2.4	Vibro-Replacement.....	21
7.2.5	Deep Soil Mixing.....	21
7.3	Earthwork.....	22
7.3.1	Site Preparation.....	22
7.3.2	Remedial Earthwork.....	22
7.3.3	Fill Compaction.....	23
7.3.4	On-Site Soils and Materials Management.....	23
7.3.5	Import Soil.....	24
7.3.6	Cut and Fill Slope Construction.....	25
7.4	Shallow Foundations.....	26
7.5	Deep Foundations.....	26
7.5.1	Axial Capacity.....	27
7.5.2	Lateral Capacity.....	28
7.6	Reinforced Concrete Slabs-On-Grade.....	29
7.6.1	Subgrade Support and Preparation.....	29
7.6.2	Slab Thickness and Reinforcement.....	29

7.6.3	Moisture Protection for Interior Slabs.....	29
7.7	Earth Retaining Structures.....	30
7.8	Asphalt Concrete Pavements.....	31
7.9	Underground Utilities.....	32
7.9.1	Settlement.....	32
7.9.2	Soil Loads.....	32
7.9.3	Thrust Blocks.....	32
7.9.4	Modulus of Soil Reaction.....	32
7.9.5	Pipe Bedding.....	33
7.9.6	Existing Utilities.....	33
8.0	CONSTRUCTION CONSIDERATIONS.....	33
9.0	LIMITATIONS.....	34
10.0	REFERENCES.....	35

FIGURES

- Figure 1 – Site Location
- Figure 2 – Proposed Development
- Figure 3 – Geologic Map
- Figure 4 – Seismic Safety Map
- Figure 5 – Fault Map
- Figures 6A and 6B – Parameter Plots
- Figure 7 – Shallow Foundation Dimension Details (*to follow*)
- Figure 8A – Allowable Vertical Pile Capacity – Steel H-Piles (*to follow*)
- Figure 8B – Allowable Vertical Pile Capacity – Cast-In-Drilled-Hole Piles (*to follow*)
- Figure 9A – Lateral Earth Pressures for Yielding Retaining Wall (*to follow*)
- Figure 9B – Lateral Earth Pressures for Restrained Retaining Walls (*to follow*)
- Figure 9C – Lateral Earth Pressures for Anchored Retaining Walls (*to follow*)
- Figure 9D – Wall Drainage Details (*to follow*)
- Figure 10A – Settlement Monument Details – Surface Monument (*to follow*)
- Figure 10B – Settlement Monument Details – Riser Plate (*to follow*)

PLATES

- Plate 1 – Geotechnical Map
- Plates 2A through 2C – Geologic Cross Sections A-A' through C-C'
- Plate 3 – Groundwater Elevations

Plate 4 – Estimated Settlements Summary

APPENDICES

Appendix A – Previous Boring Records

Appendix B – Current Exploration Records

Appendix C – Laboratory Testing

D
R
A
F
T

1.0 INTRODUCTION

This report presents the results of a geotechnical investigation by Group Delta Consultants (Group Delta) for the Aztec Stadium (Stadium) that is part of the redevelopment of the SDCCU site (overall site) into the San Diego State University Mission Valley (SDSU MV) campus. The ultimate development of the site (Full Build Out) will consist of a Stadium, Campus Expansion, Tailgate Park, Hotel and Conference Center, Residential, and Park Space. Figure 1, Site Location, shows the location of the project. Figure 2, Proposed Development, shows the plan layout of the Stadium.

The purpose of this report is to provide geotechnical information to support the collaborative design-build procurement of the project. This report provides interpretations of the geologic and geotechnical conditions observed and recommendations for design and construction of the Stadium, the Phase 1A Grading and the portion of the Phase 1B Grading that is the responsibility of the Stadium Contractor.

Group Delta 2019 submitted a separate geotechnical investigation report (Group Delta, 2019b) for the grading and civil works (Site Development) and another report regarding the subsurface environmental conditions (Group Delta, 2019c) of the SDCCU stadium site (overall site).

Group Delta developed the recommendations from reviewing the previous studies referenced in this report, recent subsurface exploration and laboratory testing, geologic and geotechnical engineering interpretation and analyses, and our previous experience with similar geologic conditions.

1.1 Scope of Services

This report was prepared in general accordance with the provisions of the referenced proposal (GDC, 2019a). In summary, we provided the following scope of services.

- Review of the previous geologic and geotechnical studies referenced in this report. Plate 1, Geotechnical Map, shows the locations of relevant prior exploratory borings. Appendix A provides the records from these explorations.
- Subsurface exploration consisting of 17 exploratory borings and five Cone Penetration Tests (CPTs) at the approximate locations shown on Plate 1, Geotechnical Map. Appendix B provides records from these explorations.
- Laboratory testing of soil samples collected from the borings. Laboratory tests included sieve analysis, Plasticity Index, Expansion Index, corrosion (pH, resistivity, soluble sulfate and chloride), shear strength (direct shear) and compressibility (consolidation). Appendix C provides a summary of the laboratory test results.
- Engineering analysis of the field and laboratory data to develop geotechnical parameters and preliminary recommendations for design and construction.
- Preparation of this report with our findings, conclusions and recommendations.

1.2 Site Description

The Stadium site (including the Tailgate Parks to the west) occupies about 26 acres in the northwest portion of the approximately 170-acre former SDCCU stadium site, as shown on Figure 1, Site Location. The existing stadium is located directly southeast of the new Stadium. The site is currently used for surface parking and it is covered with asphalt paving.

Surface elevations vary from about 50 to 95 feet NAVD 88. The ground surface slopes to the southwest to a minimum elevation of about 50 feet and then ascends northeast to an elevation of about 80 feet due to the placement of fill for the existing stadium. The basis of elevations stated further in this report is NAVD 88, unless noted otherwise.

1.3 Proposed Development

We have based our understanding of the project on information in a San Diego State University Football Stadium Study (Populous, 2018) and the Phase 1A and B Grading Plans and Conceptual Phasing Plan (Rick Engineering, 2019a and 2019b). Figure 2, Proposed Development, shows the plan layout of the project. Plate 1, Geotechnical Map uses the "Opening Day" cut/fill exhibit as the base map.

The overall site will be developed in two main phases referred to as *Opening Day* and *Full Build Out*. The Opening Day configuration comprises the new Stadium, temporary surface parking surrounding the Stadium, and the Park Space along the southern and eastern perimeter of the overall site. Full Build Out replaces the temporary surface parking with a Campus Expansion, Tailgate Park, Hotel & Conference Center, and Residential areas.

1.3.1 Stadium Structure

The Stadium will have 35,000 seats. The Stadium will consist of the following components:

- Service Level
- Field Level
- Main Concourse
- Upper Seating Bowl
- Elevated Club Lounges and Suites

The Service Level is located within the western and southern portions of the Stadium below the Main Concourse. This level will be partially underground, and it will have locker and field club rooms, and a loading dock. It will be constructed using free-standing retaining walls with soil backfill to tie into newly formed fill platforms with temporary slopes. The retaining walls will be up to 30 feet high.

The Main Concourse and Field Levels will be cast-in-place concrete structures. The lower seating bowl from the Main Concourse Level to the Field Level will be on-grade or above occupied

structures associated with the Field Level. The upper seating will be elevated cast-in-place concrete. The Main Concourse will also have numerous one story “Garden Buildings” constructed with cold formed metal or Concrete Masonry Unit (CMU) walls.

The Upper Seating Bowl will primarily be structural steel. The Elevated Club lounges and Suites will be located within the western portion of the Stadium above the Service Level. These structures will also be structural steel.

Foundation loads and settlement tolerances are not known at this time.

1.3.2 Site Formation and Civil Works

The Stadium Contractor will complete the entire Phase 1A Grading and the part of the Phase 1B Grading that will demolish the existing SDCCU stadium within the southeast portion of the Stadium site.

Cut and fill grading will form the site to four levels by placing fill to establish the Main Concourse level with cuts to create the Field Level and associated slopes for the Stadium seating. The table below summarizes grading planned for the four levels.

GRADING DATA

Grading Level	Finished Subgrade Elevation, feet	Maximum Cut Thickness, feet	Maximum Fill Thickness, feet
Field	56.0	10	0
Loading	56.0	10	< 5
Locker Room	60.0	10	5
Concourse	87.0	< 5	30

Cut and fill volumes are estimated to be 180,000 cubic yards (CY) and 270,000 CY with a net import of 90,000 CY. A temporary borrow area is planned south of the Stadium.

Permanent and temporary cut and fill slopes will be formed at 2:1 (horizontal:vertical) to a maximum height of about 30 feet. The Phase 1A grading includes retaining walls with a maximum height of about 25 feet to reconfigure an existing loading ramp for the SDCCU stadium. The reconfigured loading dock will be removed when the SDCCU stadium is demolished.

New streets will be modified 2-lane collectors that border the north, west and south perimeters of the Stadium site. These streets will be constructed according to City of San Diego Standard Drawings, Schedule J, Pavement Design Standards.

Surface parking covered with asphalt concrete or gravel is planned for Opening Day in areas north, west and south of the Stadium. The Stadium Contractor is not responsible for construction of these improvements. Above and below ground parking for the Campus Expansion and the Hotel & Conference Center, and the Tailgate Park will ultimately replace the surface parking.

Existing sewer, storm drain, and dry utilities will be abandoned. New temporary sewer and storm drain will be installed to tie into existing utilities. A temporary desilting basin will be constructed south of the Stadium.

1.4 Previous Site Use and Development

AECOM (2015) prepared a Geotechnical and Geologic Evaluation Report for a proposed National Football League stadium to replace the SDCCU stadium that opened in 1967. This report summarized the prior use and development of the site. Salient information is provided below.

- There were two previous quarries. They were located near the northeast and western perimeters of SDCCU stadium. We noted an anomalously thick clay layer in Group Delta explorations S-2 and CPT-2 that may be related to prior mining.
- About 35 feet of fill, or more in localized areas, was placed around the perimeter of SDCCU stadium. The fill was placed to raise the stadium site above the floodplain and to establish a field level at +50 feet Mean Sea Level (MSL). The fill was sourced from hillsides located north and northwest of the overall site in areas mapped as underlain by the Stadium Conglomerate (Kennedy and Tan, 2008). The Stadium Conglomerate possesses a relatively high percent of gravel, cobbles and boulders.
- Steel H-Piles (HP 8X36, 12X53, 12X74 and 14X102) support the original stadium. AECOM indicated that based on as-built drawings, the piles were driven to refusal and they extend 10 to 20 feet into formational materials. Recorded pile tip elevations on the south side of the stadium ranged from +1 to +9 feet MSL (66 to 77 feet long) and recorded pile tip elevations on the north site of the stadium ranged from -12 to -24 feet MSL (70 to 100 feet long). Tip levels varied because the formational materials were shallower on the south side of the stadium. Batter piles support lateral loads.
- Cast-in-Drilled-Hole (CIDH) piles support the enclosure of the southeast side of the stadium that opened in 1997. AECOM indicated that based on the geotechnical report and structural drawings, the piles were designed considering end bearing and they extend 5 feet into formational materials, or the basal gravels that overlies this formation. Pile diameters ranged from 36 to 72 inches and specified pile tip levels ranged +12.6 to -9 feet MSL (70 to 95 feet long). As-built or construction records were not available.

1.5 Previous Geotechnical Studies

AECOM (2015) and Geocon (2016) completed prior geotechnical and geologic evaluations for the redevelopment of the SDCCU stadium site. These evaluations reviewed existing geotechnical and geologic information and did not include any additional subsurface exploration. Relevant information from these evaluations is included in this report.

It is important to note these evaluations provided different opinions regarding the potential for liquefaction. Geocon made a qualitative evaluation by assuming that most of the alluvial soils are geologically old, and therefore should not be susceptible to liquefaction. AECOM made a quantitative evaluation by using the few geotechnical test borings completed at the site with soil resistance data (Standard Penetration Test blow counts) to estimate about 2 to 6 inches of liquefaction-induced settlement. AECOM therefore concluded there was “moderate to high” potential for liquefaction. Note also that Geocon’s assessment was for the entire site, while AECOM’s assessment was limited to a stadium located in the northeast portion of the site, and an alternate stadium located in the northwest portion of the site. The assessment of liquefaction in this report using site specific subsurface data supersedes these desk study type evaluations.

Additional data is available from the geotechnical studies completed for the Mission Valley West Light Rail Transit (LRT) that runs east-west near the southern perimeter of the overall stadium site. The As-Built Log of Test Borings (dated 1999, as referenced in Gillingham Water and CH2M, 2018) for the portion of the alignment within the site includes 21 geotechnical explorations. The records from these explorations indicate subsurface conditions similar to those interpreted from Group Delta’s current explorations and described in the report.

Large diameter Cast-In-Drilled (CIDH) piles support this segment of the LRT that derive support in the underlying gravels and formational materials. We understand from anecdotal construction information (Curt Scheyhing, 2019 personal communication) that construction of some of these piles experienced unusual difficulties with soft soils that may have been the remnants of prior local mining operations. CIDH pile construction was able to remove gravels with some difficulty using conventional rock drilling and excavating equipment and tooling.

1.6 Previous Environmental Subsurface Explorations

Since 1992, numerous groundwater monitoring wells have been constructed within the overall site. These wells are part of on-going investigation and remediation activities for petroleum hydrocarbon impacts to soil and groundwater resulting from operations at an adjacent tank farm. The records from these well installations include descriptions of soil and rock types and layers observed from drilling cuttings. Most of the well installations did not collect samples of the soil and rock and they did not obtain geotechnical sampler resistance data, such as Standard Penetration Tests. Plate 1, Geotechnical Map, shows the locations of relevant prior exploratory borings. Appendix A provides the records from these explorations. We have used the data from some of these installations to help develop the Geologic Cross Sections, Plates 2A through 2C.

2.0 FIELD AND LABORATORY INVESTIGATION

2.1 Current Subsurface Exploration

The current subsurface exploration consisted of 13 exploratory borings within the Stadium site (designated S-) that were advanced using a combination of hollow stem auger, rotary wash, casing advancement, and rock coring drilling methods to depths ranging from 30 to 100 feet. Four explorations from the Site Development (designated a B-) that are located south of the site in a proposed borrow area are included in the interpretation and analyses for this report. The borings were completed during February and March 2019.

Five Cone Penetrometer Test (CPTs) were also completed. Downhole seismic data were recorded for three of the CPTs, which are further designated as Seismic CPTs (SCPTs). CPT-2 initially encountered refusal at a depth of about 25 feet due to gravel and cobbles causing resistance to further advancement and flexure of the CPT rods. CPT-2 was reattempted by locating a second CPT a few feet away, which was able to be advanced to a depth of about 45 feet where refusal on gravel and cobbles was encountered. SCPT-7 and CPT-11 both encountered relatively shallow refusal on gravel and cobbles at about 17 feet. The CPTs were advanced on March 18 and April 8, 2019.

Note the SDCCU stadium precluded exploration within a large area of the overall site. The stadium occupies about 20 acres of the overall 170-acre site. Plate 1, Geotechnical Map, shows the approximate locations of the explorations. Appendix B provides records from these explorations.

2.2 Laboratory Testing

Soil samples were collected from the borings for laboratory testing. The geotechnical testing program included sieve analyses and Plasticity Index testing to aid in soil classification using the ASTM Unified Soil Classification System (USCS). Index tests were also conducted to help evaluate the soil expansion potential and corrosivity. Direct shear and consolidation tests were conducted on relatively intact samples to evaluate soil strength and compressibility. *Maximum density, optimum moisture content and R-Value tests are in progress.* The laboratory test results are shown on the Current Exploration Records in Appendix B and in Appendix C.

3.0 GEOLOGY AND SUBSURFACE CONDITIONS

The site is located within the Peninsular Ranges geomorphic province of southern California. This province stretches from the Los Angeles basin to the tip of Baja California. It is characterized as a series of northwest trending mountain ranges separated by subparallel fault zones. The site is located within the coastal plain transected by the west-flowing San Diego River drainage known as Mission Valley and it is underlain at depth by Eocene-age sedimentary deposits mapped as the Friars Formation (Map Symbol Tf).

The Friars Formation consists of six intertonguing, depositionally time-equivalent facies ranging from deep-marine, fine-grained siltstone and claystone to the southwest and continental, coarse-

grained sandstone and conglomerate to the northeast. The Friars Formation are nonmarine and near-shore deposits of lagoonal sandstone, siltstone, and claystone. The Friars Formation is found in Mission Valley at elevations below approximately 160 feet Mean Sea Level. Regionally, the Friars Formation dips gently to the southwest between 3 and 5 degrees.

Thick deposits of poorly consolidated, mostly granular alluvium associated with the San Diego River and Murphy Creek drainages, local deposits of slopewash and colluvium, and relatively shallow fill soils associated with the original stadium construction overlies the Friars Formation. These materials are collectively referred to as Surficial Soils - Undifferentiated (Map Symbol su) in this report.

Figure 3, Geologic Map depicts the general geology in the site area. Plates 2A through 2C are geologic cross sections through the site. The sections below describe the geologic units encountered.

3.1 Friars Formation

As encountered in the explorations completed for this investigation and those conducted for the previous environmental monitoring well installations, the elevation of the top of Friars Formation ranges from 25 feet in the northwest portion of the overall site to less than 0 feet in the central portion of the overall site (including the SDCCU stadium footprint). The elevation of the top of the Friars Formation rises in the southeast portion of the overall site to about 25 feet. The elevation of the top of the Friars Formation under the Stadium site varies up to 40 feet, ranging from a high of about 35 feet in the northwest portion of the site to a low of about -5 feet in the eastern portion of the site.

The overall site is located at the confluence of two major drainages - the San Diego River and Murphy Creek. We interpret that the variability of the elevation of the top of Friars Formation occurs from erosion of the San Diego River and Murphy Canyon paleochannels into this formation below the SDCCU stadium. Significant and abrupt declines in elevation occur northwest to southeast from transitions at the margins of the paleochannels. Geologic Cross Sections B-B' (Plate 2B) and C-C' (Plate 2C) depicts this paleochannel as the significant drop in the elevation of the Friars Formation across a short horizontal distance. Note the eastern margin of the paleochannel is inferred because we were unable to conduct subsurface exploration in the stadium.

As observed in all our deep borings, the Friars Formation generally consists of gray to yellowish brown, interbedded, fine- to coarse-grained silty sandstone with some fine gravel and gray, sandy siltstone with minor amounts of gray claystone. Auger cuttings and drive samples obtained from these materials were observed to be sand with silt (SP-SM), silty and clayey sand (SM, SC), and lean to fat clay (CL, CH). The apparent density was dense to very dense considering SPT blow counts and the consistency was very stiff to hard considering the undrained shear strength obtained from hand-held Pocket Penetration and Torvane tests.

3.2 Surficial Soils - Undifferentiated

The thickness of the Surficial Soils - Undifferentiated (map symbol su) varies across the overall site based on the elevation of the top of Friars Formation. The thickness of these materials ranged from an average of 25 to 60 feet in the northwest portion of the overall site, to more than 50 to 75 feet in the central portion of the overall site. The thickness of these materials in the Stadium site ranged from 25 to 75 feet. They are thicker in the central to southcentral to southeastern areas of the Stadium Site. These materials are subdivided into *Surface Gravel/Fill*, *Middle Sand/Fine-Grained Soils*, and *Basal Gravel*. These units are described in the following sections.

3.2.1 Surface Gravel/Fill

Historical topographic maps indicate that at least three separate active river channels existed through the overall site with the broadest U-shaped meander near Murphy Canyon extending north almost to the current Friars Road alignment U.S Department of the Interior, 1903). The Murphy Canyon drainage empties into the site from the north. Deposition of coarse-grained alluvium within these river and stream channels has created locally discontinuous gravel layers across the site in the near surface elevations.

Various amounts of fill placed during previous quarrying activities and the original stadium and parking lot construction also cover the site. Historical records indicate that up to 35 feet of fill, or more in localized areas, was placed around the perimeter of the stadium to raise grades above the floodplain. The fill materials were apparently imported from nearby excavations.

These soils were observed in the borings to mostly consist of poorly to well graded sand (SP, SW), silty and clayey sand (SM, SC), silty to clayey gravel (GM, GC) and gravel and cobbles. The apparent density ranged from loose to dense considering SPT blow counts, some of which were erroneously impacted by the gravel and cobbles.

3.2.2 Middle Sand/Fine-Grained Soils

Sea level transgressions in the last 10,000 years backfilled the San Diego River channels with finer grained alluvial deposits including silt, clay, sand, and finer gravel. The Middle Sand/Fine-Grained Soils unit was encountered in all the explorations.

These soils were observed in the borings to mostly consist of poorly to well graded sand (SP, SW), silty and clayey sand (SM, SC), silty to clayey gravel (GM, GC) and gravel and cobbles. The clay soils observed in the borings were mostly medium plasticity lean clay (CL). The apparent density ranged from loose to dense and the consistency ranged medium stiff to stiff, considering SPT blow counts and hand-held Pocket Penetration and Torvane tests. Some of the SPT test were erroneously impacted by loose flowing sands or gravels and cobbles.

3.2.3 Basal Gravel

The Basal Gravel consists of San Diego River alluvium deposited unconformably on the erosional contact with the Friars Formation. The Basal Gravel appears to be located within the old San Diego River paleochannels that formed from sea level changes and regional uplift over the past several hundred thousand years.

These soils were observed in the borings to mostly consist sandy coarse gravel and boulders up to two feet in diameter. Since the subsurface exploration used small diameter drilling methods (augers and drill bits less than 8-inches in diameter) maximum clast sizes were not directly observed. However, historical documents, nearby riverbed exposures, and our experience with construction projects in Mission Valley provide us with these data. The apparent density ranged from dense to very dense considering SPT blow counts, most of which were erroneously impacted by the gravel.

3.3 Groundwater

Groundwater was measured during drilling in the subsurface explorations completed for this investigation (except S-9, S-13 and B-14 where the drilling method and/or conditions did not allow for measurement) at elevations of 42 to 49 feet along the northern portion of the overall site and at elevations of 36 to 40 feet in the southwest portion of the overall site. Groundwater was measured below the Stadium site at elevations ranging from 36 to 49 feet. The lower measurements are from explorations in the southern area of the Stadium site.

Local variations in groundwater elevation up to 7 feet were measured in adjacent explorations. This variation may be due to: 1) groundwater measurements were conducted when the drilling was finished, and the groundwater level may not have stabilized; 2) groundwater may be locally perched on less-permeable, fine grained soils; or 3) a combination of the two. The apparent gradient across the site from northwest to southwest is approximately 7 degrees as measured in the explorations.

Groundwater was also measured in select existing monitoring wells constructed by others at the site following our site investigation. Groundwater was measured below the Stadium site at elevations ranging from approximately 44 to 48 feet. Plate 3 shows an interpretation of the groundwater elevations under the Stadium site using groundwater measurements from: 1) select explorations by Group Delta and 2) select environmental monitoring wells constructed by others.

4.0 GEOLOGIC HAZARDS

We anticipate the primary geologic hazards to be strong ground shaking from earthquakes and the associated soil liquefaction. As shown in Figure 4, Seismic Safety Map, the site is within Geologic Hazard Category 31, which is characterized as having high potential for liquefaction due to shallow groundwater, major drainages, or hydraulic fills (City of San Diego, 2008). Geologic hazards for the site are described below.

4.1 Strong Ground Motion

The site could be subject to moderate to strong ground shaking from nearby or more distant, large magnitude earthquakes occurring during the expected life span of the project. This hazard is managed by structural design of the structures per the latest edition of the California Building Code (CBC, 2016) and California State University requirements. Seismic design parameters are provided in the Recommendations section.

4.2 Earthquake Surface Fault-Rupture Hazard

The potential for surface fault rupture is low. Surface rupture is the result of movement on an active fault reaching the ground surface. Structures intended for human occupancy as defined by the California Geological Survey, (CGS, 2008) are located outside of Earthquake Fault Zones.

As shown on Figure 5, Fault Map, the closest known active fault is the Rose Canyon section of the Newport-Inglewood-Rose Canyon fault zone, which is approximately 4 miles to the west of the overall site.

4.3 Earthquake Induced Ground Failure

Potentially liquefiable soils underlie the site. Liquefaction is the sudden loss of soil shear strength within saturated, loose to medium dense, sands and non-plastic silts. Liquefaction is caused by the build-up of pore water pressure during strong ground shaking from an earthquake. We interpret liquefaction-induced settlement to be the most likely secondary effect to occur given the site surface and subsurface conditions. The secondary effects of liquefaction are sand boils, settlement, and instabilities within sloping ground (lateral spreading, seismic deformation and flow sliding). Associated with earthquake-induced ground failure is seismic compaction, which is the densification of loose to medium dense granular soils that are above groundwater.

4.3.1 Results of Liquefaction Analyses

Based on the results of analyses to evaluate the triggering of liquefaction, the potential for liquefaction is widespread throughout the Surficial Soils - Undifferentiated that are below groundwater. Significant variations in the estimated liquefaction-induced settlement occur from differences in the thickness of these soils and the depth to groundwater, which varies with changes in surface elevations. In addition, there are local zones of relatively thick non-liquefiable clayey soils. Provided below is a summary of the main findings of the analyses.

- Total settlement is estimated to range from 1 to 5 inches.
- The estimates of total settlement could increase by about one-third, ranging from 1.5 to 6.5 inches, depending on the assumptions used in the analyses.
- The estimates of total settlement increase by 0.5 inches using seismic design inputs from expected Building Code revisions (ASCE 7-16: PGAM = 0.58g, Mw = 6.89).
- The largest settlements are estimated to occur within eastern portion of the Stadium site.

The table below provides estimated total dynamic (liquefaction and seismic compaction) settlement within each development area. A summary of these estimated settlements is also included on Plate 4.

ESTIMATED DYNAMIC SETTLEMENT

Exploration	Thickness of Potentially Liquefiable Soils, Feet	Total Settlement, Inches
S-1	10	1
S-2	10	2
S-3	5	2
S-4	< 5	1
S-5	25	4
S-6	0	1
S-7	10	1
S-8	25	5
S-9	10	2
S-10	20	4
S-11	15	2
S-12	15	2
S-13	20	4

1. Settlement is the combination of liquefaction-induced and seismic compaction. Estimated magnitude of seismic compaction insignificant.
2. Settlement is a “free-field” estimate that does not consider: a) the shear strain due to foundation loading, b) contribution of ejecta-related settlement and c) the ability of thick non-liquefiable soils above groundwater to attenuate the estimated settlement.

Differential settlement over a horizontal distance of 30 to 40 feet may be estimated to be two-thirds of the total settlement. Consequently, differential settlement in some areas exceed thresholds that allow for conventional shallow foundations, such as 1 to 2 inches over 30 feet for multistory structures and 2 to 4 inches over 30 feet for single story structures (ASCE 7-16, Risk Category III). The thickness of non-liquefiable soils at the surface, removal and recompaction of this material, and the placement of fill could attenuate differential settlement to the extent that conventional shallow foundations could be suitable in some areas for certain structures.

Silt and clay soils should not be susceptible to liquefaction or have the potential to lose shear strength from strong ground shaking considering the plasticity characteristics obtained from Plasticity Index testing (Boulanger and Idriss, 2006; Bray and Sancio, 2006).

4.3.2 Methodology

The liquefaction triggering calculations used Standard Penetration Test data (blow counts per foot) and laboratory test data on the percentage of fines (silt and clay) to obtain the resistance of the soil to liquefaction, as recommended by the NCEER Workshops (Youd and Idriss, 2001) and Boulanger and Idriss (2014). Free-field volumetric settlement was estimated using Tokimatsu and Seed (1987) and Pradel (1998). The analyses adopted the following ASCE 7-10 input parameters:

Peak Ground Acceleration (PGA_M):0.46g
Earthquake Magnitude (M_w): 6.7
Groundwater Level: + 50 feet NAVD 88

The PGA_M was developed using the maximum considered earthquake geometric mean (MCE_G) peak ground acceleration adjusted for Site Class effects obtained from the SEAOC/OSHPD Seismic Design Maps Tool in accordance with the 2016 CBC (as referenced in SEAOC/OSHPD, 2019). The controlling magnitude used in the liquefaction evaluation was selected by reviewing deaggregation results obtained from the USGS Unified Hazard Tool (2018b).

4.4 Landslides and Slope Stability

Based on the relatively flat topography of the site and proximity to nearby hillsides, landslides are not design considerations. Cut and fill slopes planned to form the site should possess adequate surface and overall stability if designed and constructed as recommended in this report.

4.5 Tsunami, Seiche, and Flooding

The site is above the mapped tsunami inundation line and it is outside of the mapped tsunami inundation area (CalEMA et al, 2009). The site is not located below any lakes or confined bodies of water so there is no potential for seiches or earthquake induced flooding. The site is outside of mapped high-risk dam inundation areas on the County of San Diego draft dam failure hazard map (County of San Diego, 2018).

We understand that a Conditional Letter of Map Revision (CLOMR) prepared by others is revising the Federal Emergency Management Agency (FEMA) 100-year floodplain in consideration of site grading and elevations changes.

4.6 Subsidence

Subsidence is customarily associated with long term groundwater extraction. The City of San Diego (City) is assessing the feasibility of developing the Mission Valley groundwater basin as a sustainable source of water (Gillingham Water and CH2M, 2018). The City is considering installing three groundwater extraction wells south and southwest of the Stadium site. The City's consultants should address the potential for subsidence considering the proposed SDSU MV redevelopment. Group Delta should review the assessment made by the City's consultant.

5.0 GEOTECHNICAL CONDITIONS

Fill and thick alluvium underlies the Stadium site. We have not differentiated the fill soils from alluvial soils as discussed in Section 3.0 (Geology and Subsurface Conditions). A northeast to southwest trending paleochannel (ancient buried stream or river channel) causes the thickness of these undifferentiated soils to increase from 45 to 55 feet in the northwest portion of the overall site to more than 65 to 75 feet in the southeast portion of the overall site. The thickness of these soils under the Stadium site varies from 25 to 75 feet. Formational materials (geologically mapped as Friars Formation) underlie these soils.

The Surficial Soils - Undifferentiated are predominately coarse-grained soils with apparent densities that vary from loose to dense with a corresponding variable shear strength and stiffness. However, there are also significant zones of gravel and clay. Relatively thick (ranging from 5 to 15 feet) layers of gravel were encountered near the ground surface, at an intermediate depth, or above the formational material in 10 of the 13 explorations. In addition, a relatively thick (ranging mostly from 10 to 15 feet) layer of clay was observed at an intermediate depth in six of the 13 explorations. Therefore, for geotechnical engineering purposes we subdivided the Surficial Soils - Undifferentiated into *Surface Gravel/Fill*, *Middle Sand/Fine-Grained Soils*, and *Basal Gravel* to emphasize the distribution of the gravel and clay soils, as summarized below.

- The gravel in the Surface Gravel/Fill is not widespread (encountered in four of 13 explorations) and it was observed to range from 10 to 15 feet thick.
- The gravel in the Middle Sand/Fine-Grained Soil is not widespread (encountered in 4 of 13 explorations) and it was observed to range from 5 to 10 feet thick. There are also zones of clay (encountered in 6 of 13 explorations) that were observed to be to 15 feet thick.
- The Basal Gravel is found along the bottom of the channels eroded into the underlying formational materials. This gravel was encountered in 6 of 13 explorations and it was observed to be 10 to 15 feet thick.

Note that gravel can possess relatively high shear strength and stiffness relative to the other soils, even with the low apparent densities that may exist within the Surface Gravel/Fill. Overburden stresses and confinement should substantially increase the shear strength and stiffness of the Basal Gravel. However, the amount of gravel, cobbles and boulders; the distribution of these sizes; their roundness or angularity influences their geotechnical engineering characteristics. Apart from the thickness, the current subsurface data only allows for qualitative, rather than quantitative assessment of engineering properties.

The formational materials are intermediate geomaterials (informally referred to as soft rock) consisting mostly of weakly cemented sandstone with localized, strongly cemented concretions (sediment that hardened into rock) and some thin layers of claystone. We interpret the formational materials to have geotechnical engineering characteristics like a very dense sand or

where there is claystone, a clay with a hard consistency, all with a corresponding high shear strength and stiffness.

Plates 2A through 2C, Geologic Cross Sections A-A' through C-C' depicts the interpreted subsurface conditions. Figures 6A and 6B, Parameter Plots, provides Standard Penetration Test blow counts (N, corrected for sampler type only with depth) and the Undrained Shear Strength measures from hand-held Pocket Penetration and Torvane tests.

5.1 Expansive Soils

Laboratory tests indicate the soils in proposed cut and borrow areas should have a "Very Low" to "Medium" Potential Expansion. The results of nine Expansion Index (EI) tests conducted on bulk soils samples obtained from the surface to a depth of 5 feet below existing surface levels ranged from 6 to 75, averaging 43 (Low Potential Expansion) with a median of 50 (borderline Low-Medium Potential Expansion). Appendix C provides this data.

5.2 Compressible Soils

Compressible soils underlie the site. Most of these soils are sands and gravels that should settle elastically with the initial fill and structure loading. However, there are local zones of thick clay that should experience some time dependent consolidation settlement. The clay has a medium plasticity and we interpret it to be relatively stiff and slightly overconsolidated from Plasticity Index data. The insitu moisture contents are near the Plastic Limit and the Liquidity Indices are less than 0.7, which indicate relatively stiff and low compressibility soils. Most of the long-term settlement should occur in a relatively short time following initial loading. The zones of clay are usually surrounded by sand, which allows horizontal drainage to more quickly dissipate the excess porewater pressures that develop from loading. However, there are local variations in the estimated duration where this condition does not exist.

Provided below is a summary of the main findings of the analyses.

- Total long-term settlement is estimated to range from less than 0.5 to 5.5 inches.
- The estimated duration for settlement to be substantially complete varies from 1 to 12 months.
- The largest settlements and durations are estimated to occur mostly within the eastern portion of the Stadium site. An anomalously high settlement and duration was estimated using data from boring S-2 within the Hotel area.

The table below provides the estimated settlement and durations where new fill will be placed. A summary of these estimated settlements is also included on Plate 4.

ESTIMATED STATIC SETTLEMENT

Exploration	New Fill Thickness, Feet	Depth to Formation, Feet	Saturated Clay Thickness, Feet	Short-Term Elastic Settlement, Inches	Long-Term Consolidation Settlement, Inches	Duration for Substantial Completion, Months
S-1	5	57	N/A	1.0	N/A	N/A
S-2	20	43	15	2.0	4.5	8 - 24
S-3	10	44	2	1.0	< 0.5	< 0.5
S-4	20	34	9	1.5	4.0	3 - 9
S-5	25	59	10	4.0	5.5	1 - 3
S-8	20	73	4	4.0	2.0	< 0.5 - 1
S-9	5	29	N/A	0.5	N/A	N/A
S-10	15	70	15	3.0	1.5	2 - 6
S-11	5	30	10	0.5	1.5	4 - 12
S-13	10	75	N/A	2.5	N/A	N/A

The assessment of settlement and duration is based on engineering analyses using data obtained from widely spaced explorations, where subsurface conditions could vary significantly across the site. Due to these uncertainties, the estimated settlement and duration could vary across relatively short distances.

Settlement analyses were conducted using the soil profiles and groundwater conditions encountered in the recent explorations and laboratory test data. The settlement magnitude and areal distribution was estimated with conventional elastic and consolidation soil mechanics methods that used SPT correlations to elastic modulus and index property correlations to consolidation parameters.

Settlement monitoring is recommended to confirm these estimates and to plan the timing for construction of settlement sensitive improvements.

5.3 Reactive Soils

Seven suites of corrosion tests were completed on bulk soil samples obtained from proposed cut and borrow areas. Appendix C provides the test results.

To assess the sulfate exposure of concrete in contact with the site soils, samples were tested for water-soluble sulfate content. The test results suggest the on-site soils have a negligible potential for sulfate attack based on commonly accepted criteria. The sulfate content of the finish grade soils should be established at the completion of earthwork.

The pH, resistivity and chloride contents were estimated to assess the reactivity of the site soils with buried metals. The test results suggest the on-site soils are corrosive to very corrosive to buried metals. A Corrosion Consultant should be contacted for specific recommendations.

5.4 Reuse of Onsite Soils

Most of the soils from proposed cut and borrow areas at the site should be sand, sand and gravel, and gravel that should require minimal processing and generally possess good geotechnical engineering characteristics when used for fill. The On-Site Soils and Materials Management section of this report provide recommendations for processing.

6.0 CONCLUSIONS

In our opinion the site is geotechnically suitable for the proposed Stadium. However, design and construction will need to manage the substantial variability observed in the subsurface materials. The site is within a broad east-west trending valley that is part of the San Diego River floodplain and it is located at the confluence of the large Murphy Canyon drainage basin. Consequently, geologically young alluvial soils with very variable physical characteristics have filled the valley and there is shallow groundwater. The thickness of these soils can fluctuate substantially across the site. Prior episodes of fill placement and quarrying operations in local areas adds to this variability. Competent geotechnical materials occur at depths ranging from 25 to 75 feet. Specific conclusions regarding geotechnical conditions are provided below.

- The Surficial Soils - Undifferentiated consist mostly of sand with significant zones of gravel and clay. A north to south trending paleochannel causes large variations of the thickness of this unit at the margins of the channel. The gravel is pervasive while the clay occurs locally. Sandstone with local concretions and thin layers of claystone is below these soils.
- The Surficial Soils - Undifferentiated are mostly coarse-grained with apparent densities that vary from loose to dense with a corresponding variable soil shear strength and stiffness. When excavated, these materials should generally be a good source of fill. There may be some processing of wet soils.
- Gravels within the Surficial Soils - Undifferentiated have a higher shear strength and stiffness compared to the other soils. The gravels are resistant to the installation of ground improvement columns and piles, but they provide a high geotechnical resistance. When excavated, they are a good source of fill with some processing of oversize material.
- There are local zones of thick clay that will experience time dependent settlement that exceeds thresholds that would allow for shallow foundations. Most of the settlement should occur in a relatively short time following initial loading. However, there are local variations where the estimated duration could impact the construction schedule.
- The potential for liquefaction is widespread and there are significant variations in the estimated liquefaction-induced settlement. Consequently, differential settlement is likely to exceed thresholds that would allow for shallow foundations.
- Groundwater will influence deep construction activities, such as CIDH piling and the installation of deeper underground utilities. It should not adversely impact most other construction activities since it was measured to be about 15 feet below the deepest cut.
- New and existing underground utilities below new fill will experience time dependent settlement locally depending on the timing of their installation following grading.

7.0 RECOMMENDATIONS

The remainder of this report presents recommendations for earthwork and the design and construction of the proposed improvements. These recommendations are based on empirical and analytical methods typical of the standards of practice in southern California and typical San Diego area construction methods and practice. They are provided for preliminary design and may need to be updated for design development, the results of field testing (e.g., pile load testing) or actual subsurface conditions encountered during construction. If these recommendations do not address a specific feature of the project, please contact Group Delta for additions or revisions.

7.1 General

7.1.1 Design Groundwater Level

We recommend a design groundwater level of +50 feet.

Note that changes in rainfall, irrigation, or site drainage may produce seepage or perched groundwater at any location within the Surficial Soils - Undifferentiated underlying the site. Such conditions are difficult to predict and are typically mitigated if and where they occur.

7.1.2 Seismic Design

Seismic design parameters should be evaluated by the Structural Engineer per the California State University Seismic Design Requirements (CSU, 2016). For reference, seismic design parameters were also developed in accordance with the 2016 CBC and ASCE 7-10 using the online SEAOC/OSHPD Seismic Design Maps tool (SEAOC/OSHPD, 2019). They are based on: 1) an estimated average shear wave velocity (V_{s30}) of about 900 feet per second, 2) an assumed structure fundamental period of less than 0.5 seconds and 3) Risk Category = III (Populous, 2018). The estimated shear wave velocity will be subject to revision based on upcoming field testing.

Our office should be contacted if the structure fundamental period is 0.5 seconds or greater, as the applicable classification would be Site Class F per Section 20.3.1 of ASCE 7-10 due to the liquefiable soils at the site, which requires site-specific ground motion analysis. The table below provides the parameters.

2016 CBC SEISMIC DESIGN PARAMETERS

Latitude: 32.7843°N Longitude: 117.1224°W	
Site Class	D*
MCE _R Spectral Response Acceleration for Short Periods, S_s	1.017 g
MCE _R Spectral Response Acceleration at 1-second Period, S_1	0.390 g
Site Coefficient F_a	1.093

2016 CBC SEISMIC DESIGN PARAMETERS

Latitude: 32.7843°N Longitude: 117.1224°W	
Site Coefficient F_v	1.621
Adjusted MCE_R Spectral Response Acceleration at Short Periods, S_{MS}	1.112 g
Adjusted MCE_R Spectral Response Acceleration at 1-second Period, S_{M1}	0.632 g
Design Spectral Response Acceleration at Short Periods, S_{DS}	0.741 g
Design Spectral Response Acceleration at 1-second Period, S_{D1}	0.421 g
MCE Geometric Mean Peak Ground Acceleration, PGA_M	0.456 g

*Assumes structure fundamental period is 0.5 seconds or less. Subject to change for longer structure periods.

7.1.3 Surface Drainage

Foundation and slab performance depend on how well surface runoff drains from the site. The ground surface should be graded so that water flows rapidly away from the structures and tops of slopes without ponding. The surface gradient needed to achieve this may depend on the planned landscaping. Planters should be built so that water will not seep into the foundation, slab, or pavement areas. If roof drains are used, the drainage should be channeled by pipe to storm drains or discharge 10 feet or more from buildings. Irrigation should be limited to that needed to sustain landscaping. Excessive irrigation, surface water, water line breaks, or rainfall may cause perched groundwater to develop within the underlying soil.

7.2 Ground Improvement

7.2.1 Purpose and Need

Ground improvement could reduce static and dynamic settlement to economically facilitate construction of the structures for the Full Build Out and mitigate potentially adverse settlement of utilities. Group improvement is typically completed within the footprint of the more lightly loaded buildings to reduce settlement or within the footprint of the heavier loaded to reduce liquefaction-induced loads on the piling used to support these structures. Ground improvement can also be completed to protect Lifelines, which are structures that are critical for communities and must remain operational following an earthquake. They are typically selected major roadways, inflexible essential pipelines, powerlines and communications facilities.

The purposes of ground improvement are to increase the allowable bearing pressure and to reduce the static and dynamic (liquefaction-induced) settlement. The improved ground will often support allowable bearing pressures up to 4,000 pounds per square foot (psf) and provide settlement tolerances ranging from ½ to 1 inch over a horizontal distance of 30 to 40 feet.

The following types of ground improvement may be suitable considering the subsurface conditions at the site.

- Deep Dynamic Compaction
- Vibro-Replacement
- Deep Soil Mixing
- Vertical Drains

Note the variability of the soil physical characteristics, the pervasive gravel, and the observation of the mineral mica and its corresponding structure in the soil can complicate the use of these methods at the site. Therefore, an evaluation of their applicability should consider the following factors:

- Schedule and cost implications associated with a pilot study program with a large upfront equipment mobilization fee.
- Additional evaluation and design period following the pilot study program.
- Difficulty conducting pre-and post-improvement subsurface exploration for quality control where there are pervasive gravels.
- Additional construction costs associated with penetrating through pervasive gravels.

The following sections provide additional discussions of the above ground improvement methods. There is a summary evaluation of their effectiveness at this site, followed by details regarding the specifics of each of the methods. Note Vertical Drains are included mainly to decrease the duration of the time-dependent settlement, or as a secondary measure to increase the effectiveness of the other methods.

7.2.2 Summary Assessment of Effectiveness

To assess the effectiveness of these methods, Group Delta undertook a matrix evaluation of the geotechnical conditions at the locations of the 13 subsurface explorations. The evaluation focused on conditions observed in the explorations, such as: a) the depth and thickness of potentially liquefiable soils; b) the depth and thickness of gravel, and c) the depth, thickness and saturation of the clay, that could hinder the various methods of ground improvement in mitigating liquefaction-induced settlement.

The findings of this evaluation indicate that Deep Dynamic Compaction should only be marginally effective at the Stadium site (improvement mainly needed in eastern portion of this site). This conclusion indicates the need for a carefully thought out and planned pilot study program to further assess the effectiveness of DDC, along with its ability to manage and consistently improve the soil (i.e., meet performance objectives) given the variability of subsurface conditions interpreted at the site. An additional method of ground improvement may need to be planned for and used where DDC does not entirely meet the performance objectives. FHWA (2017) reports

that DDC has been combined with Aggregate Columns (stone columns and rammed aggregate piers).

Vibro-Replacement and Deep Soil Mixing should be feasible to mitigate liquefaction. However, the gravels could substantially impede installation of these methods. Since this is a constructability concern, further feasibility evaluation should include preliminary consultation with reputable geotechnical contractors that specialize in the methods of these methods of ground improvement.

If feasible, the Geotechnical and Structural Engineer will develop a performance specification for design by a specialist geotechnical contractor. The design is often further evaluated by pilot studies along with pre-and post-improvement subsurface exploration (typically Cone Penetration Testing), which is also used for production ground improvement quality control.

7.2.3 Deep Dynamic Compaction

Deep Dynamic Compaction (DDC) uses a crane to drop a static weight from a defined height in a grid pattern over the treatment area to improve soils to a depth ranging from 10 to 35 feet. There is typically more than one pass of compaction over the treatment area to improve the deeper zones first. The design develops the static weight and drop height to determine the applied energy needed to increase the apparent density of the soils to meet the performance objectives.

This method is mostly suitable for coarse grained soils (fines content less 15%) that are not saturated (depth to groundwater is 6 feet or more) and possess a relatively high permeability (SHRP2, 2012). DDC can produce unacceptable levels of noise and vibration and therefore it has not been used in urban areas of San Diego.

7.2.4 Vibro-Replacement

Vibro-Replacement systems install “stone columns” that are typically 24 to 36 inches in diameter and filled with compacted gravel, spaced at 6 to 10 feet (center to center) and installed uniformly over the entire treatment area to depths ranging from 30 to 50 feet. The design uses an area replacement ratio over a treatment area and depth to meet the required performance objectives.

This method is suitable for coarse grained soils that are saturated that do not have thick gravel, cobble or boulder obstructions. It has commonly been used to mitigate liquefaction in San Diego. However, the extensive gravels at the site would require predrilling that could substantially increase the cost. Micaceous soils encountered in our some of our explorations may also reduce the effectiveness of this method.

7.2.5 Deep Soil Mixing

Deep Soil Mixing (DSM) mixes a binder (typically cement) with the soils to create a column or panel (an element) with increased shear strength and stiffness and reduced compressibility. Typically, the elements overlap to create a block or cellular structure in the ground that uniformly improves

a large volume of soil supporting a foundation or creates cellular structures that confine the soil to mitigate the potential for liquefaction. The design uses an area replacement ratio over a treatment area and depth to meet the required performance objectives.

The method is suitable for most soil types that are saturated and do not have thick gravel, cobble or boulder obstructions. The cross-sectional area and depth of the element is a function of the equipment used and the area replacement ratio. This method has recently been used to mitigate liquefaction in San Diego. The extensive gravels at the site could preclude this method entirely or substantially increase installation costs, which could also limit using this method.

7.3 Earthwork

Earthwork should be conducted per applicable requirements of The California State University, the current California Building Code and the project specifications. This report provides the following recommendations for specific aspects of earthwork, which may need to be revised based on the conditions observed during construction.

7.3.1 Site Preparation

General site preparation should begin with the removal of deleterious materials and demolition debris from the site, such as asphalt pavements, concrete slabs and pavements, existing structures, remnant foundations, landscaping and topsoil and any expansive ($EI > 50$) located within 36 inches of the planned finished subgrade elevations. Areas disturbed by demolition should be restored with a subgrade that is stabilized to the satisfaction of the Geotechnical Engineer.

Existing subsurface utilities that will be abandoned should be removed and the excavations backfilled and compacted as described in the Fill Compaction section. Alternatively, abandoned pipes may be grouted using a two-sack sand-cement slurry under the observation of the Geotechnical Engineer.

Areas to receive fill should be scarified 12 inches and recompacted to 90 percent of the maximum dry density based on ASTM D1557. In areas of saturated or “pumping” subgrade, a geogrid such as Tensar BX-1200, Terragrid RX1200 or Mirafi BXG120 may be placed directly on the excavation bottom, and then covered with at least 12 inches of $\frac{3}{4}$ -inch Aggregate Base (AB). Once the subgrade is firm enough to attain compaction within the AB, the remainder of the excavation may be backfilled. It may be necessary to place additional AB to stabilize the subgrade sufficiently to place fill.

7.3.2 Remedial Earthwork

For planning purposes, we recommend removing the existing soils to a depth of 2 feet below existing surface levels (following removal of asphalt paving) across the site to provide a uniform surface for additional fill placement, a uniform fill surface in cut areas and to allow for observation of unsuitable soils (clayey, wet, loose) in the exposed subgrade. Plate 5, Remedial Grading Exhibit,

illustrates this recommendation. The recommendation does not consider the following factors that could increase the depth of the remedial grading:

- Some areas may require additional remedial grading based on demolition activities.
- The period of placement for the existing fill (1960s) and the lack of documentation regarding placement may increase its physical variability and consequently increase the need for remedial grading.
- The variability inherent in native subgrades where there may be loose and/or soft areas.
- The findings from additional subsurface exploration and/or observations by the Geotechnical Engineer during earthwork.
- The residential development building areas may require additional remedial grading depending on final product and foundation designs.
- Planned hardscape, graded paths, pavements, concrete slabs, and structural improvements in the park sites could require some remedial grading for subgrade preparation.

The fill may be recompacted provided it is processed as recommended in the On-Site Soils and Materials Management section.

7.3.3 Fill Compaction

All fill and backfill should be placed at slightly above optimum moisture content using equipment that can produce a uniformly compacted product. The loose lift thickness should be 8 inches, unless performance observed and testing during earthwork indicates a thinner loose lift is needed, or a thicker loose lift is possible, up to a loose lift thickness of 12 inches. The recommended relative compaction is 90 percent or more, or 95 percent or more where specified, of the maximum dry density based on ASTM D1557.

A two-sack sand and cement slurry may also be used for structural fill as an alternative to compacted soil. It has been our experience that slurry is often useful in confined areas which may be difficult to access with typical compaction equipment. Samples of the slurry should be fabricated and tested for compressive strength during construction. A 28-day compressive strength of 100 pounds per square inch (psi) or more is recommended for the sand and cement slurry. Gravel ($\frac{3}{4}$ -inch) completely wrapped in filter fabric (Mirafi 140N, or approved equivalent) may also be used as backfill in confined areas.

7.3.4 On-Site Soils and Materials Management

The following existing soils and materials are available for processing and reuse.

- Soil
- Asphalt Concrete (AC)
- Portland Cement Concrete (PCC)

The following sections provide recommendations for processing and reuse as fill.

7.3.4.1 Soil

Most of the existing soils above groundwater should be suitable for reuse. They should be processed to produce fill soil with a well graded particle distribution with a suitable moisture content for compaction. Some processing of wet soils should be anticipated. Soil with an $EI > 50$ should be removed and disposed of offsite. Rocks or concrete fragments greater than 3 inches in maximum dimension should not be reused. They could be stockpiled on site for processing as part of the stadium demolition.

7.3.4.2 Asphalt Concrete

Existing AC should be crushed to less than 1 inch in maximum dimension and blended with approved fill soils. Existing AC can be recycled, reprocessed, and reused as a base course for new AC paving. City of San Diego personnel have anecdotally observed paving fabric in portions of the AC. We did not observe this fabric in the explorations.

7.3.4.3 Portland Cement Concrete

Concrete may be crushed to less than 1 inch in maximum dimension for use as fill. It should be added to other soils to create a well graded fill material. Reinforcing steel should be removed prior to crushing the concrete. Properly crushed concrete will often meet the gradation and quality criteria from Section 200-2.4 of the Standard Specifications for Public Works Construction for use as Crushed Miscellaneous Base (CMB).

7.3.5 Import Soil

The project proposes to import approximately 90,000 CY of soil for use as fill. Imported fill sources should be observed and tested by the Geotechnical Engineer prior to hauling onto the site to determine the suitability for use. Imported soil for common fill should consist of granular soil that is free of organic materials, with an Expansion Index less than 50 based on ASTM D4829, and a gradation that meets the criteria shown in the table below.

RECOMMENDED GRADATION FOR IMPORT SOIL

Sieve Size	(% Passing)
3 inches	100
3/4 inch	100 - 80
No. 4	100 - 65
No. 200	0 - 35

Soils should also have a minimum resistivity value greater than 1,000 ohm-centimeters, chloride content of less than 500 ppm and sulfate content of less than 1,000 ppm and pH greater than 5.5.

Additional testing per the guidelines provided the Department of Toxic Substances Control (DTSC, 2001) is required by the Owner prior to accepting soil for import. Test results should meet most

stringent State and Federal residential screening levels including the most up-to-date DTSC-Modified Screening Levels (DTSC-SLs) and United States Environmental Protection Agency Regional Screening Level (RSL).

During earthwork, soil types may be encountered by the Contractor that do not appear to conform to those discussed within this report. The Geotechnical Engineer should evaluate the suitability of these soils for their proposed use.

For each proposed fill source, the Contractor should provide a submittal to the Geotechnical Engineer demonstrating that the proposed site and materials meet the geotechnical and environmental guidelines for import. Prior to import of the proposed materials, samples of all proposed import should be tested by the Geotechnical Engineer to evaluate the suitability of these soils for their proposed use. The following screening tests should be performed for every 1,000 cubic yards of import, with a minimum of two sets of screening tests for each import site:

- Particle Size Distribution (ASTM D6913)
- Maximum Density (ASTM D1557)
- Expansion Index (ASTM D4829)
- Sulfate Content (ASTM D516)
- Chloride Content (ASTM D512)
- pH & Resistivity (CT 643)

If a long-term, steady source of import material is utilized that consistently meets the import soil recommendations described above, import material testing frequency may be reduced at the discretion of the Geotechnical Engineer and SDSU.

7.3.6 Cut and Fill Slope Construction

Cut and fill slopes should be formed at inclinations no steeper than 2:1 (horizontal to vertical). Fill slopes above cut slopes or natural slopes with gradient steeper than 5:1 should be formed with a keyway at the base and benches into competent materials as fill is placed according to the following dimensions, or as recommended by the Geotechnical Engineer.

- Minimum width of keyway should be 15 feet.
- Base of the keyway should tilt back 2 percent, or a minimum of 1 vertical foot.
- Minimum depth and height for benches should be 4 feet.
- Minimum horizontal thickness of the fill from the face to the forward edge of the bench should be 10 feet.

The face of fill slopes should be thoroughly compacted and tested for in-place density after each 4-foot increase in slope height. When finished pad grade is achieved, the face of the fill slope should be further compacted along a vertical grid that overlap with appropriate equipment, such as a cable-lowered "sheepsfoot" pad roller, or similar.

7.4 Shallow Foundations

Continuous strip and isolated pad footings may be used for the one story “Garden Buildings” constructed with cold formed metal or Concrete Masonry Unit (CMU) walls, where they can be designed to satisfactorily tolerate the estimated long-term static and dynamic (liquefaction-induced) settlement. ASCE 7-16 provides guidance to combine strip and pad footings with foundation ties for single story buildings to accommodate liquefaction-induced differential settlement. Foundation ties may be used where the estimated differential settlement does not exceed 2 and 4 inches over a horizontal distance of 30 feet for single story building with concrete or masonry wall systems and other single-story structures respectively (Table 12.13-3 of ASCE 7-16).

For preliminary evaluation purposes, strip and pad footings may be designed using the following parameters and recommendations:

- Allowable bearing pressure of 2,000 pounds per square foot (psf). The bearing pressure assumes infinite level ground surrounds the footing.
- Allowable lateral bearing using a soil passive pressure of 200 pounds per cubic foot (pcf) combined with a sliding resistance estimated using a coefficient of friction of 0.3. The passive pressure assumes infinite level ground in front of the footing.
- Bearing pressure and soil passive pressure may be increased by one-third for short term seismic and wind loads.
- Embedment to the bottom of footing in properly compacted fill of 18 inches or more below lowest adjacent grade.
- Footing width of 18 inches (continuous) or more and pad width of 24 inches (square/rectangular) or more. Figure 7, Shallow Foundation Dimension Details, depicts these recommendations graphically.
- Footings do not span between cut and fill without specific recommendations from a Geotechnical Engineer.
- Foundation subgrades should be prepared as recommended in the *Site Preparation* section of this report.

7.5 Deep Foundations

The purpose of deep foundations is to transmit structure loads to more competent geotechnical materials at depth. Typically, the Geotechnical and Structural Engineer will choose one or more types of piles for preliminary evaluation that can support the structural vertical and lateral loads and settlement tolerances (not known at this time) and that are suitable for the site and geotechnical conditions. Piling contractors may promote alternatives based on their experience and specialist equipment.

In our opinion, low displacement or replacement types of piles should be suitable considering the pervasive gravels. The gravels are resistant to pile installation, but they provide very high

geotechnical resistance in end bearing. Therefore, the displacement pile cross section needs to be slender enough to drive through the surface gravel with the least resistance and be robust enough to sustain high driving stresses. The diameter and type of drilling tool for replacement piles needs to be able to remove gravel, cobbles and boulders without difficulty.

For low displacement piles, we preliminary recommend driven steel H-Piles with a square cross section of at least from 14 inches. Larger pile cross sections ranging from 16 to 18 inches and/or greater sections weights (pounds per lineal foot) may be needed to accommodate structural lateral loads and to sustain driving stresses.

For replacement piles, we preliminary recommend Cast-In-Drilled (CIDH) piles with a minimum diameter of 36 inches, although larger diameters up to 72 inches have been previously used locally.

We have considered these types of piles and cross-sectional areas to help evaluate the difference between a large number of smaller cross-sectional area piles arranged in group with a pile cap (H-piles) or a small number or a single, large cross-sectional area pile (CIDH piles) at each support.

7.5.1 Axial Capacity

The piles will gain vertical support from skin friction and end bearing within the basal gravel and/or underlying sandstone. Piles lengths are estimated to range from 50 to 90 feet, assuming an average pile cap elevation of 65 feet and embedment into the basal gravel and/or underlying sandstone that are typical to the previous installation of similar piles at the site. Many of the steel H-Piles may encounter refusal on gravel. CIDH piles may need to be designed for shaft resistance only considering the difficulties in cleaning the bottom of the shafts that are below groundwater.

No support is derived from the alluvial soils due to the potential for liquefaction. The Structural Engineer should include liquefaction settlement-induced downdrag loads at the pile head. The loads should be considered permanent. Where there is new fill, the piles should be installed after settlement of the underlying soils is substantially complete to avoid static settlement-induced downdrag loads. Otherwise the piles should be designed for these loads. The structural capacity of the pile section should be evaluated relative to the downdrag loads and allowable driving stresses.

The table below provides preliminary allowable downward resistance, including skin friction and end bearing. Downdrag loads have not been calculated at this time as further input from the Structural Engineer is needed. However, downdrag loads will be significant due to the thickness of the liquefiable soils at the site and they will likely approach or exceed the anticipated structure service loads. Figures 8A and 8B – Allowable Vertical Pile Capacity – Steel H-Piles and – Cast-In-Drilled-Hole Piles will replace this table and provide estimates of allowable compression and tension for the pile types and sizes selected for further evaluation and design development.

ESTIMATED ALLOWABLE PILE RESISTANCES

Pile Type	Allowable Downward Resistance ^{a, b} , Kips
HP14 / 16 ^c	165 / 185
36 / 72 Inch Diameter CIDH ^d	400 / 940

- a. Allowable assuming a Factor of Safety of 2 on skin friction and 3 on end bearing.
- b. May be increased by one-third for wind or seismic forces.
- c. Skin friction and end bearing estimated over the gross cross-sectional area and half of the gross cross-sectional area, respectively.
- d. Group Delta (2000) reported an ultimate skin friction of 3.5 kips per square foot (ksf) and an ultimate end bearing of 60 ksf from pile loads in similar formational materials nearby using the Osterberg Cell method.

7.5.2 Lateral Capacity

Resistance to lateral loads can be estimated using a passive soil pressure against the pile caps and grade beams and the bending resistance of the piles. Due to the potential for liquefaction-induced settlement, we do not recommend using friction between these elements and the underlying soil.

7.5.2.1 Passive Soil Pressure

Passive soil pressure may be preliminary estimated using an equivalent fluid weight of 200 pounds per cubic foot (pcf) for grade beams and pile caps poured neat against properly compacted fill. The passive soil pressure can be increased by one-third for loads that include wind or seismic forces. The passive pressure assumes infinite level ground in front of the pile cap. A curve with the relationship between passive pressure and horizontal deformation can be provided.

7.5.2.2 Lateral Pile Resistance

The bending resistance of a pile depends on its length, stiffness in the direction of loading, proximity to other piles and the degree of fixity at the head, and the engineering properties of the soil surrounding the pile. For preliminary evaluation purposes, we recommend the following permissible lateral loads. This table will be replaced with recommended LPILE (Ensoft, 2016) soil parameters for the design of piles once the type of pile and cap elevations are known.

PERMISSIBLE LATERAL LOAD

Pile Type	Lateral Load ^a , Kips
HP14 / 16	35 / 40 ^b
36 / 72 Inch Diameter CIDH	50 / 150 ^c

- a. Free head conditions with horizontal displacement of ½ inch
- b. Caltrans Bridge Design Aid 12-2 (2016)
- c. Estimated using LPILE (Ensoft, 2016)

7.6 Reinforced Concrete Slabs-On-Grade

Reinforced concrete slabs-on-grade will support the Main Concourse, the Lower Seating Bowl and the interior portions of the Service Level and Garden Buildings. The soil subgrade will support the reinforced concrete slab-on-grades. A slab-on-grade could experience some damage from liquefaction-induced settlement. This damage could be proportionate to the estimated liquefaction-induced settlement provided in this report. The damage can usually be repaired with jacking the settled portions of slab with compaction grout and fixing the damaged portions as needed to restore functionality. Otherwise a structurally supported slab should be used in areas where this type of distress and repair is not desired.

7.6.1 Subgrade Support and Preparation

The upper 24 inches of soils below finished subgrade elevation for reinforced concrete slabs-on-grade should consist of coarse-grained soils with a low expansive potential ($EI < 20$) that is prepared and compacted as recommended in the Earthwork section. Where expansive soils are encountered in the upper 24 inches of subgrade, which are soils with an EI greater than 50, we recommend removing and replacing them with properly compacted non-expansive soils ($EI < 20$).

7.6.2 Slab Thickness and Reinforcement

There are several chart solutions (ACI, 2006) to complete analyses to develop the slab-on-grade thickness and reinforcement for preliminary evaluation. These charts use modulus of subgrade reaction (k). We recommend using 200 pounds per cubic inch (pci).

The San Diego State University Football Stadium Study (Populous, 2018) recommended a typical slab-on-grade thickness of 6 inches and a thickness of 12 inches for a “structured reinforced” slab-on-grade. The slab thickness, control joints, and reinforcement should be designed by the Structural Engineer considering the type of support (structural or subgrade) and should conform to the requirements of the current California Building Code. For design development, the Geotechnical Engineer should provide a range of moduli that considers potential soil variability and the specific input parameter needed and how it is applied in the software used by the Structural Engineer.

7.6.3 Moisture Protection for Interior Slabs

Moisture protection should comply with requirements of the current CBC, American Concrete Institute (ACI 302.1R-15) and the desired functionality of the interior ground level spaces. The Architect typically specifies an appropriate level of moisture protection considering allowable moisture transmission rates for the flooring or other functionality considerations.

Moisture protection may be a “Vapor Retarder” or “Vapor Barrier” that use membranes with a thickness of 10 and 15 mil or more, respectively. The membrane may be placed between the concrete slab and the AB or finished subgrade immediately below the slab, provided it is protected from puncture and repaired per the manufacturer’s recommendations if damaged. Note the CBC specifies a Capillary Break, as defined and installed per the California Green Building Standards,

with a Vapor Retarder. Barriers for environmental purposes should be designed as in the companion Environmental Report (Group Delta, 2019b).

7.7 Earth Retaining Structures

Permanent retaining walls are planned to create the Service Level that is located within the western and southern portions of the Stadium. This level will be underground and below the Main Concourse. It will be constructed using free-standing or embedded retaining walls with compacted soil backfill to tie into newly formed fill slope platforms. Additional retaining walls will reconfigure an existing loading ramp for the SDCCU stadium. This ramp will be removed when the SDCCU stadium is demolished. The maximum height of the walls will range from about 25 to 30 feet. The following types of retaining walls may be suitable:

- A free-standing cast-in-place reinforced concrete retaining wall with compacted soil backfill. Counterforts may be necessary within the higher segments of the wall.
- A free-standing geogrid reinforced Segmental block Retaining Wall (SRW). This wall could allow the Service Level walls to be designed for structural loads only with no consideration of earth loads. There would be a minimal horizontal space between the face of the SRW and the face of Service Level structural wall.
- An embedded “king post” retaining wall with compacted soil backfill. The wall would consist of drilled and concreted H-piles (soldier piles) with wood lagging between the soldier piles. Where needed for lateral restraint, anchors would be installed in the fill as it placed behind the wall. The anchors could be concrete blocks embedded in the wall backfill and tied to the face of the wall with steel bars (referred to as Deadman anchors). The wall would have a permanent reinforced shotcrete facing constructed over the exposed wood lagging.

The following preliminary geotechnical recommendations are provided below:

- Retaining wall may be designed using the earth pressure diagram in Figure 9A, Lateral Earth Pressures for Yielding Retaining Walls (*to follow*) where they are able to rotate a horizontal distance at the top of the wall that is at least 0.5 percent of the wall height.
- Retaining walls may be designed using the earth pressure diagram in Figure 9B, Lateral Earth Pressures for Restrained Retaining Walls (*to follow*) where they are restrained from horizontal movement at the top.
- Retaining walls may be designed using the earth pressure diagram in Figure 9C, Lateral Earth Pressures for Anchored Retaining Walls (*to follow*), where single or multiple levels of anchors for lateral restraint. This figure provides geotechnical parameters to design the anchors and embedded portion of the walls (soldier piles).

- Current CBC requires seismic design for all earth retaining structures over six feet high. CSU Seismic Requirements (2016) states that seismic lateral earth pressures shall be considered one-half of the site adjusted MCE PGA value as the design acceleration. Seismic pressure and the seismic pressure increments *will be provided* in the earth pressure diagrams.
- Foundations for free standing retaining walls can be designed using the recommendations in the *Shallow Foundations* section of this report.
- Subsurface drainage should be provided to relieve hydrostatic pressure if not included in the wall design. Figure 9D, Wall Drain Details (*to follow*) provides typical subsurface draining details.
- SRWs should be designed by specialist designer according to the National Concrete Masonry Association, Segmental Retaining Walls Best Practice Guide (NCMA, 2016), or similar methodologies. For walls greater than 20 feet high, NCMA recommends soil placed in the reinforced zone to have a maximum particle size of 1 inch, a maximum fines content (silt and clay) of 15 percent and Plasticity Index less than 6. It may be necessary to selectively import or screen, process and stockpile on site materials to meet these characteristics. For preliminary design, we recommend using an internal friction angle of 30 degrees for soils placed and compacted in the reinforced and retained zones.

7.8 Asphalt Concrete Pavements

New interior streets will be 6-Lane Major, 4-Lane Major and 2-Lane Collectors with Traffic Indices of 9.0, 10.5 and 11.0 that are covered with asphalt concrete pavement and constructed according to City of San Diego Standard Drawings, Schedule J, Pavement Design Standards. Temporary surface parking covered with asphalt concrete or gravel is planned for Opening Day in areas north, west and south of the Stadium.

An R-Value of 20 should be assumed for preliminary assessment of Asphalt Concrete surfaced pavements or landscaping type of surfaces. Based on our review of the available geotechnical information, the subgrade R-Value within the upper 36 inches of subgrade could range from 20 to 40 or more, assuming some selective placement of fill to from the subgrade. The design subgrade R-Value should be confirmed by R-Value testing of the actual pavement subgrade soils during fine grading operations within the pavement areas.

Schedule J provides the standard sections for the range of subgrade R-Values for Traffic Indices representative of the planned streets and surface parking. Alternative pavement sections designed in accordance with the Caltrans Design Method, Topic 633.1 (Caltrans, 2018b) that use aggregate base rather than the cement treated base used in the Schedule J are summarized in the table below. A 20-year pavement design life was assumed for the analyses.

PRELIMINARY ASPHALT CONCRETE PAVEMENT SECTIONS

Traffic Index	Asphalt Section	Base Section (R-Value ~20)
9.0	5 Inches	17 Inches
10.5	7 Inches	20 Inches
11.0	7 Inches	22 Inches

7.9 Underground Utilities

The Stadium construction include new sewer (8- to 18-inch diameter PVC), storm drain (18- to 36-inch diameter RCP and temporary 30-inch diameter CMP), water and fireline (12-inch diameter), and dry utilities. Gravity flow utilities mostly have a minimum gradient of 0.5 percent. The following sections provide preliminary geotechnical recommendations for design and construction.

7.9.1 Settlement

New and existing underground utilities below new fill will experience time dependent consolidation settlement depending on the timing of their installation following grading. Some form of mitigation will be needed if the utility cannot tolerate the total and differential settlement estimated in the Compressible Soils section. Mitigation could be delaying the installation until the settlement is substantially complete, preloading the utility alignment area (prior to utility installation) with a fill surcharge or the various forms of Ground improvement discussed in this report.

7.9.2 Soil Loads

A soil unit weight of 130 pounds per cubic (pcf) may be used to evaluate soil loads for pipe above groundwater. The permissible depth of cover should be checked were new fill will be placed over underground utilities that will remain.

7.9.3 Thrust Blocks

Lateral resistance for thrust blocks may be determined by a passive pressure value of 200 pounds per square foot (psf) per foot of embedment, assuming a triangular distribution. This value may be used for thrust blocks embedded into the soils in the Surficial Soils - Undifferentiated unit described in this report that are above groundwater.

7.9.4 Modulus of Soil Reaction

The modulus of soil reaction (E') is used to characterize the stiffness of soil backfill placed along the sides of buried flexible pipelines. To evaluate deflection due to the load associated with trench backfill over the pipe, we recommend using 1,000 pounds per square inch (psi) assuming granular bedding material is placed around the pipe.

7.9.5 Pipe Bedding

Typical pipe bedding as specified in the *Standard Specifications for Public Works Construction* or *City of San Diego Standard Drawings* may be used. We recommend using a filter fabric separator (such as Mirafi 140N or an approved similar product) between the soil and open graded rock used for bedding and/or backfill where the alignment is within roadways or near settlement sensitive improvements. The use of a filter fabric separator may be waived by the Geotechnical Engineer based on site specific soil conditions observed in the trench excavation.

7.9.6 Existing Utilities

The permissible depth of cover and settlement tolerances should be evaluated where new fill will be placed over underground utilities that will remain. The permissible depth of cover and settlement tolerances for construction traffic and equipment loads should also be evaluated.

8.0 CONSTRUCTION CONSIDERATIONS

Construction of the project will need to manage substantial variability within the subsurface materials. Summarized below are the primary geotechnical-related construction considerations known at this time.

- The materials encountered in construction excavations could vary significantly across the site. Excavations should be prepared to encounter thick layers of gravel and cohesionless soils that are prone to caving and/or sloughing.
- Subgrade stabilization may be needed anywhere in the project area. The Contractor should anticipate the need for stabilization of the subgrade using geotextiles or gravel as recommended in the *Site Preparation* section of this report.
- Settlement monuments should be installed in all fill areas where construction needs to be delayed. Settlement instrumentation and monitoring can be conducted per the latest version of California Test Method 112 (Caltrans, 2012). Figures 10A and 10B, Settlement Monument Details – Surface Monument and Riser Plate provide details for the instrumentation.
- The variability of the soil physical characteristics, the pervasive gravel, and the observation of the mineral mica and its corresponding structure in the soil can complicate the use of ground improvement at the site, as outlined in the *Ground Improvement* section of this report.
- Displacement pile (Steel H-Pile or similar) cross sections needs to be slender enough to drive through the surface gravel with the least resistance and be robust enough to sustain high driving stresses.
- The installation method(s) for replacement piles (CIDH piles or similar) need to manage shallow ground water and caving soils.

- For base resistance to be included in the total axial capacity, the bottom of the CIDH pile shaft requires proper cleaning and inspection and the end bearing needs to be verified by a full-scale load test.
- The diameter and type of drilling tool for replacement piles needs to be able to remove gravel, cobbles and boulders without difficulty.
- Piles should be installed after the settlement is substantially complete to avoid static downdrag loads.
- The Piling Contractor should independently review the exploration logs in this report to assess pile installation conditions.
- Pile drivability studies, method testing, and load testing should be considered if deep foundations are adopted for construction. Drivability studies are necessary for all displacement types of piles. Method testing should be considered wherever propriety replacement (augered) piling systems are proposed, such as Auger-Cast-In-Place or Drilled Displacement piles. Advance Pile Load Testing (APLT) program is often completed where there is a desire to obtain additional information to further assess axial pile capacities, potentially reduce pile lengths and/or trial the method of pile installation.

9.0 LIMITATIONS

The recommendations in this report are preliminary and subject to revision from changes that occur during design development or from the results of field testing or actual subsurface conditions encountered during construction. Group Delta needs to continue to be part of the project design and construction for these recommendations to remain valid. If another geotechnical consultant provides these services, they should prepare a letter indicating their intent to assume the responsibilities of the project Geotechnical Engineer-of-Record. This letter should also indicate their concurrence with the recommendations in the report or revise them as needed to assume the role of the project Geotechnical Engineer-of-Record.

This report was prepared using the degree of care and skill ordinarily exercised, under similar circumstances, by reputable geotechnical consultants practicing in similar localities. No warranty, express or implied, is made as to the conclusions and professional opinions included in this report.

The findings of this report are valid as of the present date. However, changes in the condition of a property can occur with the passage of time, whether due to natural processes or the work of humans on this or adjacent properties. In addition, changes in applicable or appropriate standards of practice may occur from legislation or the broadening of knowledge. Accordingly, the findings of this report may be invalidated wholly or partially by changes outside our control. Therefore, this report is subject to review and should not be relied upon after a period of three years.

10.0 REFERENCES

- AECOM (2015). *Geotechnical and Geologic Evaluation Report for the Stadium Reconstruction Project, San Diego, California*, July 29.
- American Concrete Institute (2015). *ACI 302.1R-15 Guide for Concrete Floor and Slab Construction*.
- American Concrete Institute (2006). *ACI 360-06 Design of Slabs-on-Ground*.
- American Society of Civil Engineers (2016). *ASCE 7-16 Minimum Design Loads for Buildings and Other Structures*. American Society of Civil Engineers.
- American Society of Civil Engineers (2010). *ASCE 7-10 Minimum Design Loads for Buildings and Other Structures*. American Society of Civil Engineers.
- American Society for Testing and Materials (2018). *Annual Book of ASTM Standards, Section 4, Construction, Volume 04.08 Soil and Rock (I); Volume 04.09 Soil and Rock (II); Geosynthetics*, March.
- Boulanger, R.W. and Idriss, I.M. (2014). *CPT and SPT Based Liquefaction Triggering Procedures*, Center for Geotechnical Modeling, Department of Civil & Environmental Engineering, College of Engineering, University of California at Davis, Report No. UCD/CGM-14/01, dated April.
- Boulanger, Ross W. and Idriss, I.M. (2006). *Liquefaction Susceptibility Criteria for Silts and Clays*, Journal of Geotechnical and Geoenvironmental Engineering, American Society of Civil Engineers, Vol. 132 (11), pp. 1413-1426.
- Bray, Jonathan D. and Sancio, Rodolfo B. (2006). *Assessment of the Liquefaction Susceptibility of Fine-Grained Soils*, Journal of Geotechnical and Geoenvironmental Engineering, American Society of Civil Engineers, Vol. 132 (9), pp. 1165-1177.
- California Building Standards Commission (CBSC), (2016). *2016 California Building Code (CBC)*, California Code of Regulations, Title 24, Part 2, Volumes 1 and 2, dated: July 1.
- California Department of Conservation, Division of Mines and Geology (1992). *Fault Rupture Hazard Zones in California, Alquist-Priolo Special Studies Zone Act of 1972*: California Division of Mines and Geology, Special Publication 42.
- California Department of Conservation, Division of Mines and Geology (1993). *The Rose Canyon Fault Zone, Southern California*, CDMG OFR 93-02.

- California Emergency Management Agency (2009). *Tsunami Inundation Map for Emergency Planning, Point Loma Quadrangle*, June 1.
http://www.conservation.ca.gov/cgs/Tsunami/Inundation_Maps/SanDiego/Documents/Tsunami_Inundation_PointLoma_Quad_SanDiego.pdf
- California Geological Survey (2008). *Guidelines for Evaluating and Mitigating Seismic Hazards in California*, Special Publication 117A.
- California State University (2016). *CSU Seismic Requirements*, Office of the Chancellor, November 1.
- CAL/EPA (2001). *Department of Toxic Substances Control Information Advisory – Clean Imported Fill Material*.
- CAL/OSHA (2018). *Title 8 Regulations, Subchapter 4. Construction Safety Orders, Article 6. Excavations*. https://www.dir.ca.gov/title8/1541_1.html
- Caltrans (2018a). *Corrosion Guidelines, Version 3.0, Division of Engineering Services, Materials Engineering and Testing Services, Corrosion Branch*: dated March.
- Caltrans (2018b). *Highway Design Manual, 6th Edition*, dated July 2.
- Caltrans (2016). *Permissible Horizontal Load for Standard Plan and Steel HP Pile, Bridge Design Aid 12-2*, May.
- Caltrans (2012). *Method for Installation and Use of Embankment Settlement Devices, California Test 112*.
- City of San Diego (2008). *Seismic Safety Study, Geologic Hazards and Faults*, City of San Diego Development Services Department Grids 16 and 17, April 3.
- City of San Diego (2018). *Guidelines for Geotechnical Reports*.
- County of San Diego (2018). *Dam Failure Hazard Mitigation Planning, Draft*.
https://www.sandiegocounty.gov/oes/docs/DRAFT_COSD_DamFailure1.pdf
- Ensoft, Inc. (2016). *LPILE, A Program for Analyzing Stress and Deformation of Individual Piles or Drilled Shafts Under Lateral Load*, Version 2016.9.01, release dated: January 11.
- Federal Emergency Management Agency (FEMA), 2012, *Flood Insurance Rate Map (FIRM), San Diego County, California*, Panels 1880 and 1885 of 2375, Map Numbers 06073C1880G and -1885G, Scale 1:6,000, dated May 16.

Federal Highway Administration (FHWA), 2017. *Ground Modification Methods Reference Manual – Volume I*, Publication No. FHWA-NHI-16-027 (FHWS GEC 013), Dated April.

Geocon Incorporated (2016). *Geotechnical Reconnaissance, San Diego Stadium, SDCCU Stadium Property, San Diego, California*, November 1.

GeoLogismiki (2018) *CLiq, Version 2.0*, CPT Soil Liquefaction Software.

Gillingham Water and CH2M (2018). *Mission Valley Groundwater Feasibility Study 2018 Summary Report*, August.

Google, Inc. (2018). *Google Earth Pro* application, <https://www.google.com/earth/desktop/>: accessed September.

Group Delta Consultants (2019a). *Proposal for Geotechnical Services: 1. Geotechnical Evaluation of Stadium, 2. Geotechnical and Environmental Evaluation for Remainder of Site, San Diego State University Mission Valley Campus, San Diego, California*, January 16.

Group Delta Consultants (2019b). *Report of Geotechnical Investigation, Site Development, SDSU Mission Valley, San Diego, California*, May 10.

Group Delta Consultants (2019c). *Environmental Investigation Report, SDSU Mission Valley, San Diego, California*, April 5.

Hartley, J.D., and Duncan, J.M. (1987). *E' and Its Variation with Depth*, American Society of Civil Engineers (ASCE), *Journal of Transportation Engineering*, Vol. 113, Issue 5: dated September.

Kennedy, M. P., and Tan, S. S. (2008). *Geologic Map of the San Diego 30'x60' Quadrangle, California*: California Geologic Survey, Scale 1:100,000.

National Concrete Masonry Association (NCMA, 2016). *Segmental Retaining Walls Best Practices Guide*, NCMA Publication No. TR308, Ed. 1, revised March 18.

Populous (2018). *New Football Stadium Study, San Diego State University*, January 22.

- Pradel, Daniel (1998). *Procedure to Evaluate Earthquake-Induced Settlements in Dry Sandy Soils*, Journal of Geotechnical and Geoenvironmental Engineering, Volume 124 (4), pp. 364-368.
- Rick Engineering Company (2019a). *Phase 1A Grading and & Utilities, 100% DD Site Development Package, San Diego State University Mission Valley Campus*, April 29.
- Rick Engineering Company (2019b). *Grading and Improvements Conceptual Phasing Plan, SDSU Mission Valley*, February 12.
- Strategic Highway Research Program (2012). *Deep Dynamic Compaction Fact Sheet*, November.
- Structural Engineers Association of California and Office of Statewide Health Planning and Development (SEAOC/OSHPD, 2019). *Seismic Design Maps Online Tool*, <https://seismicmaps.org/>, accessed March 4.
- Tokimatsu, Kohji and Seed, H. Bolton (1987). *Evaluation of Settlements in Sands due to Earthquake Shaking*, Journal of Geotechnical Engineering, Vol. 113 (8), pp. 861-878.
- United States Department of the Interior (1903). *Topographic Map, La Jolla Quadrangle, San Diego County, California*, United States Geological Survey, Scale 1:62,500, dated December.
- United States Geological Survey (USGS, 2019). *topoView Online Tool*, National Geologic Map Database project, <https://ngmdb.usgs.gov/topoview/>, accessed March 4.
- United States Geological Survey (USGS, 2018a). *7.5-Minute Series Topographic Maps, La Jolla, La Mesa, Point Loma and National City Quadrangles*, Scale 1:24,000.
- United States Geological Survey (USGS, 2018b). *Earthquake Hazards Program, Unified Hazard Tool*. <https://earthquake.usgs.gov/hazards/interactive/>.
- United States Geological Survey (USGS, 2006). *Quaternary Fault and Fold Database for the United States*, <http://earthquake.usgs.gov/hazards/qfaults/>, accessed March 4, 2019.
- Youd, R.R. and Idriss, I.M (2001). *Liquefaction Resistance of Soils: Summary Report from the 1996 NCEER and 1998 NCEER/NSF Workshops on Evaluation of Liquefaction Resistance of Soils*, Journal of Geotechnical and Environmental Engineering of the American Society of Civil Engineers, Vol. 127, Issue 5.

D


FIGURES

R

A

F

T




REFERENCE: LA JOLLA, LA MESA, POINT LOMA AND NATIONAL CITY 7.5 MINUTE UAD (USGS, 2018)

SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA


SITE LOCATION

PROJECT NUMBER: SD605	FIGURE NUMBER: 1



**PROPOSED AZTEC
STADIUM**


REFERENCE: RIC ENGINEERING (2019). GRADING AND IMPROVEMENTS CONCEPTUAL PHASING PLAN, SDSU MISSION VALLEY, FEBRUARY 12.



SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

**PROPOSED
DEVELOPMENT**

PROJECT NUMBER: SD605	FIGURE NUMBER: 2



ABBREVIATED EXPLANATION
 Approximate stratigraphic relationships only, see pamphlet and CMU (Plate 2) for more detailed information.

MODERN SURFICIAL DEPOSITS

- af Artificial fill (late Holocene)

YOUNG SURFICIAL DEPOSITS

- Qya Young alluvial flood-plain deposits (Holocene and late Pleistocene)
- Qyc Young colluvial deposits (Holocene and late Pleistocene)

OLD SURFICIAL DEPOSITS

- Qoa Old alluvial flood-plain deposits, undivided (late to middle Pleistocene)

VERY OLD SURFICIAL UNITS

- Qvea Very old alluvial flood-plain deposits, undivided (middle to early Pleistocene)
- Qvop Very old palaeic deposits, undivided (middle to early Pleistocene)

Qvop7	Unit 7	Qvop13	Unit 13	Qvop14	Unit 14a
Qvop6	Unit 6	Qvop12	Unit 12	Qvop10a	Unit 10a
Qvop5	Unit 5	Qvop11	Unit 11	Qvop9a	Unit 9a
Qvop4	Unit 4	Qvop10	Unit 10	Qvop8a	Unit 8a
Qvop3	Unit 3	Qvop9	Unit 9		
Qvop2	Unit 2	Qvop8	Unit 8		
Qvop1	Unit 1	Qvop7	Unit 7		

SEDIMENTARY AND VOLCANIC BEDROCK UNITS

- Tsd San Diego Formation (early Pleistocene and late Pliocene)
 - Tsd - undivided
 - Tsdop - transitional marine and nonmarine pebbles and cobbles conglomerate
 - Tsdss - marine sandstone
 - Tsdpc - Pomeroy Conglomerate (middle Eocene)
 - Tsm - Mission Sandstone Member
- Tmv Mission Valley Formation (middle Eocene)
- Tat Statikum Conglomerate (middle Eocene)
- Tf Fries Formation (middle Eocene)


JURASSIC AND CRETACEOUS METAMORPHOSED AND UNMETAMORPHOSED VOLCANIC AND SEDIMENTARY ROCKS

- Msv Metamorphosed and unmetamorphosed volcanic and sedimentary rocks, undivided (Mesozoic)
- Mku Undivided metamorphic rocks in offshore region (Mesozoic)

ONSHORE MAP SYMBOLS

- Contact - Contact between geologic units: dotted where concealed.
- Fault - Solid where accurately located, dashed where approximately located, dotted where concealed. U = upthrown block, D = downthrown block. Arrow and number indicate direction and angle of dip of fault plane.
- Anticline - Solid where accurately located; dashed where approximately located; dotted where concealed. Arrow indicates direction of axial plunge.
- Syncline - Solid where accurately located; dotted where concealed. Arrow indicates direction of axial plunge.
- Landslide - Arrows indicate principal direction of movement; Curved white line indicates questionable.

REFERENCE: KENNEDY, M. P., AND TAN, S. S. (2008). GEOLOGIC MAP OF THE SAN DIEGO 30'X60' QUADRANGLE, CALIFORNIA: CALIFORNIA GEOLOGIC SURVEY, SCALE 1:1000,000.




SDSU MISSION VALLEY
 SAN DIEGO, CALIFORNIA

GEOLOGIC MAP

GROUP DELTA

PROJECT NUMBER: SD605

FIGURE NUMBER: 3




LEGEND

Geologic Hazard Categories

- FAULT ZONES**
 - 12 Potentially Active, Inactive, Presumed Inactive, or Activity Unknown
- SLIDE-PRONE FORMATIONS**
 - 23 Friars: neutral or favorable geologic structure
- LIQUEFACTION**
 - 31 High Potential -- shallow groundwater major drainages, hydraulic fills
 - 32 Low Potential -- fluctuating groundwater minor drainages
- OTHER TERRAIN**
 - 52 Other level areas, gently sloping to steep terrain, favorable geologic structure, Low risk
 - 53 Level or sloping terrain, unfavorable geologic structure, Low to moderate risk
- Water (Bays and Lakes)**
 - Water bodies
- FAULTS**
 - Fault
 - Inferred Fault
 - Concealed Fault
 - Shear Zone

REFERENCE: CITY OF SAN DIEGO SEISMIC SAFETY STUDY GEOLOGIC HAZARDS AND FAULTS, 04.03.2008



SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

SEISMIC SAFETY MAP

GROUP DELTA

PROJECT NUMBER: SD605 FIGURE NUMBER: 4

Historical Seismicity


- M6 E
- M6-M5
- M5-M4

Seismic Faults

- Historical <150yrs
- < 15,000 yrs
- < 130,000 yrs
- Blind Thrust



REFERENCE: U.S. GEOLOGICAL SURVEY AND CALIFORNIA GEOLOGICAL SURVEY, 2006, QUATERNARY FAULT AND FOLD DATABASE FOR THE UNITED STATES, ACCESSED 3/4/2019, FROM USGS WEB SITE: www.usgs.gov/




SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

FAULT MAP

PROJECT NUMBER: SD605	FIGURE NUMBER: 5

UNDIFFERENTIATED SURFICIAL SOILS



PROJECT NAME

**SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA**

FIGURE NAME

PARAMETER PLOTS



GROUP DELTA


PROJECT NUMBER

SD605

FIGURE NUMBER

6A

UNDIFFERENTIATED SURFICIAL SOILS



PROJECT NAME

**SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA**

FIGURE NAME

PARAMETER PLOTS



GROUP DELTA

PROJECT NUMBER

SD605

FIGURE NUMBER

6B

D


PLATES

R

A

F

T



EXPLANATION

-  SCPT-13 APPROXIMATE LOCATION OF SEISMIC CONE PENETRATION TEST
-  CPT-31 APPROXIMATE LOCATION OF CONE PENETRATION TEST
-  S-13 APPROXIMATE LOCATION OF AZTEC STADIUM GEOTECHNICAL BORING
-  B-17 APPROXIMATE LOCATION OF SITE DEVELOPMENT GEOTECHNICAL BORING
-  RW-111/R-81AD APPROXIMATE LOCATION OF PREVIOUS ENVIRONMENTAL BORING OR MONITORING WELL DATA USED IN THIS REPORT (ALL BORINGS/WELLS NOT INCLUDED)
-  APPROXIMATE LOCATION AND LETTER DESIGNATION OF GEOLOGIC CROSS SECTION
-  SURFICIAL SOILS - UNDIFFERENTIATED

REFERENCE: TOPO MAP AND OVERALL SITE, PROVIDED BY RICK ENGINEERING, 03/04/2019

SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA


GEOTECHNICAL MAP



PROJECT NUMBER: SD605
PLATE NUMBER: 1

V:\103168_103168\Projects\SDSU Mission Valley Campus - Geotechnical and Environmental\111_Drafting\SD605_Eng_1_Plate_1.dwg, 1/20/2019 10:36:35 AM, DWG TO PDF.plt

\\192.168.10.3\files\Projects\SD605_Geotech\SDSU Mission Valley Campus - Geotechnical and Environmental\11_Drafting\SD605_Cross_Section.dwg, 5/10/2019 6:42:22 AM, DWG to PDF.pc3



EXPLANATION

STANDARD PENETRATION TEST (SPT) SAMPLE
 MODIFIED CALIFORNIA (MC) SAMPLE
 USCS GRAPHIC SYMBOL
 GEOLOGIC FORMATION (USCS GROUP SYMBOL WHERE APPLICABLE)

BULK SAMPLE
 91/11"


GROUNDWATER LEVEL MEASURED DURING DRILLING
 Tf (SP)

$N_{60} = C_s \cdot N_{meas} \cdot C_{ref} \cdot (E_r/60)$
 $C_s = \text{SAMPLER TYPE CORRECTION} = 1.0 \text{ (SPT)} \& 0.67 \text{ (MC)}$
 $E_r = \text{HAMMER EFFICIENCY (\%)}$

EQUIVALENT SPT N_{60} CORRECTED FOR SAMPLER EFFICIENCY AND SAMPLER TYPE (EXCEPTION NOTED IN BLOWCOUNT CONVENTION, SEE BELOW)
 BLOWCOUNT CONVENTION:
 58 = # OF BLOWS FOR FINAL 12" OF 18" DRIVE X C_s X $(E_r/60)$
 91/11" = # OF BLOWS TO DRIVE THE INDICATED PENETRATION AFTER THE FIRST 6" (i.e., UNCORRECTED N_{meas})
 REF = =50 BLOWS REQUIRED TO DRIVE THE FIRST 4"
 ~ = INACCURATE BLOWCOUNT (i.e., PACKED SAMPLER, GRAVEL STUCK IN SAMPLER)

BEARING PRESSURE AT CPT CONE TIP
 RATIO OF CPT SLEEVE FRICTION TO BEARING PRESSURE ON CONE TIP
 TIP BEARING GREATER THAN 400 tsf TRUNCATED AT 400 tsf MAX

S_u - SURFICIAL SOILS - UNDIFFERENTIATED (INCLUDES UNDOCUMENTED FILL, SLOPEWASH, COLLUVIUM, ALLUVIUM)
 Tf - TERTIARY FRIARS FORMATION
 --- INTERPRETED GEOLOGIC CONTACT (DASHED WHERE UNCERTAIN)




SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

GEOLOGIC
CROSS SECTION A1-A1'

GROUP DELTA

PROJECT NUMBER: SD605
 PLATE NUMBER: 2A1

\\192.168.10.31\hies\Projects\SD605\Gate SDSU Mission Valley Campus - Geotechnical and Environmental\11_Drafting\SD605_Cross_Section.dwg, 5/10/2019 6:16:17 AM, DWG To PDF.pc3



EXPLANATION


[Symbol] STANDARD PENETRATION TEST (SPT) SAMPLE
 [Symbol] MODIFIED CALIFORNIA (MC) SAMPLE
 [Symbol] USCS GRAPHIC SYMBOL
 [Symbol] GEOSC. FORMATION (USCS GROUP SYMBOL WHERE APPLICABLE)
 [Symbol] TI (SP-SM)
 [Symbol] TI (SM)

[Symbol] USCS GROUP SYMBOL
 [Symbol] BULK SAMPLE
 [Symbol] 91/11" EQUIVALENT SPT N_{60} CORRECTED FOR HAMMER EFFICIENCY AND SAMPLER TYPE (EXCEPTION NOTED IN BLOWCOUNT CONVENTION, SEE BELOW)
 [Symbol] 38 BLOWCOUNT CONVENTION: 38 = (# OF BLOWS FOR FINAL 12" OF 18" DRIVE) $C_s \times (E_r/60)$
 [Symbol] 91/11" = (# OF BLOWS TO DRIVE THE INDICATED PENETRATION AFTER THE FIRST 6" (i.e., UNCORRECTED N_{60}))
 [Symbol] REF = = 50 BLOWS REQUIRED TO DRIVE THE FIRST 6"
 [Symbol] * = INACCURATE BLOWCOUNT (i.e., PACKED SAMPLER, GRAVEL STUCK IN SAMPLER)

$N_{60} = C_s \times M_{CORRECTED} (E_r/60)$
 $C_s = \text{SAMPLER TYPE CORRECTION} = 1.0 \text{ (SPT)} \& 0.87 \text{ (MC)}$
 $E_r = \text{HAMMER EFFICIENCY (\%)}$

[Symbol] GROUND WATER LEVEL MEASURED DURING DRILLING
 [Symbol] BEARING PRESSURE AT CPT CONE TIP
 [Symbol] RATIO OF CPT SLEEVE FRICTION TO BEARING PRESSURE ON CONE TIP
 [Symbol] TIP BEARING GREATER THAN 400 lbf TRUNCATED AT 400 lbf MAX

[Symbol] S_u - SURFICIAL SOILS - UNDIFFERENTIATED (INCLUDES UNDOCUMENTED FILL, SLOPEWASH, COLLOIDAL, ALLUVIUM)
 [Symbol] T_f - TERTIARY FRACTURED FORMATION
 [Symbol] - - - INTERPRETED GEOLOGIC CONTACT (DASHED WHERE UNCERTAIN)




SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

GEOLOGIC
CROSS SECTION A2-A2'

PROJECT NUMBER: SD605

PLATE NUMBER: 2A2

\\192.168.103\files\Projects\SD605\Garke SDSU Mission Valley Campus - Geotechnical and Environmental\11_Drafting\SD605_Cross_Section.dwg, 5/10/2019 6:16:52 AM, DWG To PDF.pc3



EXPLANATION

STANDARD PENETRATION TEST (SPT) SAMPLE
 MODIFIED CALIFORNIA (MC) SAMPLER
 USCS GRAPHIC SYMBOL
 GEOLOGIC FORMATION (USCS GROUP SYMBOL WHERE APPLICABLE)

BULK SAMPLE
 91/11" SAMPLER
 GROUND WATER LEVEL MEASURED DURING DRILLING
 TIP BEARING (tsf)

$N_{60} = C_e \cdot N_{measured} \cdot (E_r / 60)$
 $C_e = \text{SAMPLER TYPE CORRECTION} = 1.0 \text{ (SPT) \& } 0.67 \text{ (MC)}$
 $E_r = \text{HAMMER EFFICIENCY (\%)}$

EQUIVALENT SPT N_{60} CORRECTED FOR HAMMER EFFICIENCY AND SAMPLER TYPE (EXCEPTION NOTED IN BLOWCOUNT CONVENTION, SEE BELOW)
 BLOWCOUNT CONVENTION:
 $38 = (\# \text{ OF BLOWS FOR FINAL } 12" \text{ OF } 18" \text{ DRIVE}) \times C_e \times X \text{ (E}_r \text{ / } 60)$
 $91/11" = \# \text{ OF BLOWS TO DRIVE THE INDICATED PENETRATION AFTER THE FIRST } 6" \text{ (E}_r \text{, UNCORRECTED } N_{measured})$
 REF = ≥ 50 BLOWS REQUIRED TO DRIVE THE FIRST 6"
 ^ = INACCURATE BLOWCOUNT (i.e., PACKED SAMPLER, GRAVEL STUCK IN SAMPLER)

BEARING PRESSURE AT CPT CONE TIP
 RATIO OF OPT SLEEVE FRICTION TO BEARING PRESSURE ON CONE TIP
 TIP BEARING GREATER THAN 400 tsf TRUNCATED AT 400 tsf MAX

S_u - SURFICIAL SOILS - UNDIFFERENTIATED (INCLUDES UNDOCUMENTED FILL, SLOPEWASH, COLLUVIUM, ALLUVIUM)
T_f - TERTIARY FIRES FORMATION
 --- INTERPRETED GEOLOGIC CONTACT (DASHED WHERE UNCERTAIN)

SCALE (FT):
 0' 20' 40'


**SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA**

**GEOLOGIC
CROSS SECTION B-B'**

GROUP DELTA

PROJECT NUMBER: **SD605** PLATE NUMBER: **2B**

\\192.168.10.31\hes\Projects\SD605\Garde\SDSU Mission Valley Campus - Geotechnical and Environmental\11_Drafting\SD605_Cross_Section.dwg, 5/10/2019 6:17:36 AM, DWG To PDF.pc3



EXPLANATION

<p>STANDARD PENETRATION TEST (SPT) SAMPLE</p> <p>MODIFIED CALIFORNIA (MC) SAMPLE</p> <p>USCS GRAPHIC SYMBOL</p> <p>GEOLOGIC FORMATION (USCS GROUP SYMBOL WHERE APPLICABLE)</p>	<p>USCS GROUP SYMBOL</p> <p>91/11" BULK SAMPLE</p> <p>38 GROUND WATER LEVEL MEASURED DURING DRILLING</p> <p>55</p>	<p>EQUIVALENT SPT N_{60} CORRECTED FOR HAMMER EFFICIENCY AND SAMPLER TYPE (EXCEPTION NOTED IN BLOWCOUNT CONVENTION, SEE BELOW)</p> <p>BLOWCOUNT CONVENTION:</p> <p>38 = (# OF BLOWS FOR FINAL 12" OF 18" DRIVE) X C_s X (ER/80)</p> <p>91/11" = (# OF BLOWS TO DRIVE THE INDICATED PENETRATION AFTER THE FIRST 6" (i.e., UNCORRECTED) MEASURED)</p> <p>REF = = 50 BLOWS REQUIRED TO DRIVE THE FIRST 6"</p> <p>~ = INACCURATE BLOWCOUNT (i.e., PACKED SAMPLER, GRAVEL STUCK IN SAMPLER)</p>
--	--	--

<p>BEARING PRESSURE AT CPT CONE TIP</p> <p>RATIO OF CPT SLEEVE FRICTION TO BEARING PRESSURE ON CONE TIP</p> <p>TIP BEARING GREATER THAN 400 lbf TRUNCATED AT 400 lbf MAX</p>	<p>8.0 4.0 0 200 400</p> <p>Friction Ratio (%)</p> <p>Tip Bearing (lbf)</p>	<p>$N_{60} = C_s \times \text{MEASURED } (ER/80)$</p> <p>$C_s = \text{SAMPLER TYPE CORRECTION} = 1.0 \text{ (SPT)} \ \& \ 0.87 \text{ (MC)}$</p> <p>$ER_1 = \text{HAMMER EFFICIENCY } (\%)$</p>
--	---	--

<p>Su - SURFICIAL SOILS - UNDIFFERENTIATED (INCLUDES UNDOCUMENTED FILL, SLOPEWASH, COLLUVIUM, ALLUVIUM)</p> <p>Tf - TERTIARY FRARS FORMATION</p> <p>--- INTERPRETED GEOLOGIC CONTACT (DASHED WHERE UNCERTAIN)</p>	<p>SCALE (FT):</p> <p>0' 20' 40'</p>
---	--------------------------------------

<p>SDSU MISSION VALLEY SAN DIEGO, CALIFORNIA</p>		<p>GEOLOGIC CROSS SECTION C-C'</p>		<p>GROUP DELTA</p>
<p>PROJECT NUMBER: SD605</p>		<p>PLATE NUMBER: 2C</p>		

V:\192168_102\Drawings\192168_SDSU_Mission_Valley_Campus_Geotechnical_and_Environmental\11_Drawing\SD605_Plate_4.dwg, 5/20/2019, 11:10 AM, DWG To PDF, 6/2

S-1		S-2	
Elevation of Friars Formation (ft, NAVD 88)	26	Elevation of Friars Formation (ft, NAVD 88)	23
Fill Placement (ft)	5	Fill Placement (ft)	20
Duration of Consolidation Settlement (months)	N/A	Duration of Consolidation Settlement (months)	8-24
Consolidation Settlement (in)	N/A	Consolidation Settlement (in)	4.5
Liquefaction Settlement (in)	1	Liquefaction Settlement (in)	2

S-4	
Elevation of Friars Formation (ft, NAVD 88)	34
Fill Placement (ft)	20
Duration of Consolidation Settlement (months)	3-9
Consolidation Settlement (in)	4
Liquefaction Settlement (in)	1

S-3	
Elevation of Friars Formation (ft, NAVD 88)	30
Fill Placement (ft)	10
Duration of Consolidation Settlement (months)	<0.5
Consolidation Settlement (in)	<0.5
Liquefaction Settlement (in)	2

S-5	
Elevation of Friars Formation (ft, NAVD 88)	4
Fill Placement (ft)	25
Duration of Consolidation Settlement (months)	1-3
Consolidation Settlement (in)	5.5
Liquefaction Settlement (in)	4

S-6	
Elevation of Friars Formation (ft, NAVD 88)	34
Fill Placement (ft)	Cut
Duration of Consolidation Settlement (months)	--
Consolidation Settlement (in)	--
Liquefaction Settlement (in)	--

S-8	
Elevation of Friars Formation (ft, NAVD 88)	-4
Fill Placement (ft)	20
Duration of Consolidation Settlement (months)	<0.5-1
Consolidation Settlement (in)	2
Liquefaction Settlement (in)	5

S-7	
Elevation of Friars Formation (ft, NAVD 88)	32
Fill Placement (ft)	Cut
Duration of Consolidation Settlement (months)	--
Consolidation Settlement (in)	--
Liquefaction Settlement (in)	1

S-9	
Elevation of Friars Formation (ft, NAVD 88)	29.5
Fill Placement (ft)	5
Duration of Consolidation Settlement (months)	N/A
Consolidation Settlement (in)	N/A
Liquefaction Settlement (in)	2

S-10	
Elevation of Friars Formation (ft, NAVD 88)	-4
Fill Placement (ft)	15
Duration of Consolidation Settlement (months)	2-6
Consolidation Settlement (in)	1.5
Liquefaction Settlement (in)	4

S-11	
Elevation of Friars Formation (ft, NAVD 88)	24
Fill Placement (ft)	5
Duration of Consolidation Settlement (months)	4-12
Consolidation Settlement (in)	1.5
Liquefaction Settlement (in)	2

S-12	
Elevation of Friars Formation (ft, NAVD 88)	34
Fill Placement (ft)	Cut
Duration of Consolidation Settlement (months)	--
Consolidation Settlement (in)	--
Liquefaction Settlement (in)	2



B-14	
Elevation of Friars Formation (ft, NAVD 88)	26
Fill Placement (ft)	5
Duration of Consolidation Settlement (months)	N/A
Consolidation Settlement (in)	N/A
Liquefaction Settlement (in)	2

B-15	
Elevation of Friars Formation (ft, NAVD 88)	23
Fill Placement (ft)	5
Duration of Consolidation Settlement (months)	N/A
Consolidation Settlement (in)	N/A
Liquefaction Settlement (in)	4

B-17	
Elevation of Friars Formation (ft, NAVD 88)	14
Fill Placement (ft)	5
Duration of Consolidation Settlement (months)	N/A
Consolidation Settlement (in)	N/A
Liquefaction Settlement (in)	4

B-16	
Elevation of Friars Formation (ft, NAVD 88)	0
Fill Placement (ft)	Cut
Duration of Consolidation Settlement (months)	--
Consolidation Settlement (in)	--
Liquefaction Settlement (in)	1

S-13	
Elevation of Friars Formation (ft, NAVD 88)	-0.5
Fill Placement (ft)	10
Duration of Consolidation Settlement (months)	N/A
Consolidation Settlement (in)	N/A
Liquefaction Settlement (in)	4



REFERENCE: TOPO MAP AND OVERALL SITE, PROVIDED BY RICK ENGINEERING, 03/04/2019

SDSU MISSION VALLEY
SAN DIEGO, CALIFORNIA

ESTIMATED
SETTLEMENTS SUMMARY

GROUP DELTA

PROJECT NUMBER: SD605
PLATE NUMBER: 4

D


APPENDIX A
PREVIOUS BORING RECORDS

R

A

F

T



Permit #:
 Casing elevation:
 Date well drilled: 6/11/02
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-40AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Permit #:
 Casing elevation:
 Date well drilled: 6/11/02
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-40AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA




DRAFT

Permit #:
 Casing elevation:
 Date well drilled: 6/11/02
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION

	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-40AD (CONTINUED)



Permit #:
 Casing elevation:
 Date well drilled: 6/8/02
 LFR Field Staff: Rodney Crother
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-41AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA




DRAFT

Permit #:
 Casing elevation:
 Date well drilled: 6/8/02
 LFR Field Staff: Rodney Crother
 Approved by:

EXPLANATION

	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-41AD (CONTINUED)



Permit #:
 Casing elevation:
 Date well drilled: 6/17/02
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-42AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Permit #:
 Casing elevation:
 Date well drilled: 6/17/02
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-42AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Approx. Water Level

Continued

Date well drilled: 2/16/03 - 2/17/03
 LFR Field Staff: Adelo Derilo
 Approved by:

EXPLANATION


	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-45 AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained


Date well drilled: 2/16/03 - 2/17/03
 LFR Field Staff: Adelo Derilo
 Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-45 AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Approx. Water Level

Continued

EXPLANATION

- Clay
- Silt
- Sand
- Gravel
- Interval Sampled
- Sample Retained


Date well drilled: 2/19/03 - 2/20/03
 LFR Field Staff: Adelo Derilo
 Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-47 AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained

Date well drilled: 2/19/03 - 2/20/03
 LFR Field Staff: Adelo Derilo
 Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-47 AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA

Depth, feet	Graphic Log	Visual Description	ID of Samples Analyzed	P I D (ppm)/ Penetration Rate (blows/ft.)
Continued				
75				
80		<p>FRIAR SANDSTONE (SS), gray (5Y-6/1), moist, fine grained, friable.</p>		

Bottom of well at 77 feet bgs.
Bottom of boring at 81 feet bgs.

- Materials used:
- Filter Pack
 - 3 bags #2/12 sand
 - Annular Seal
 - 2 bags bentonite chips
 - 6 bags bentonite grout

EXPLANATION

- Clay
- Silt
- Sand
- Gravel
- Interval Sampled
- Sample Retained


Date well drilled: 2/19/03 - 2/20/03
LFR Field Staff: Adelo Derilo
Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-47 AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Approx. Water Level

Continued

EXPLANATION

- Clay
- Silt
- Sand
- Gravel
- Interval Sampled
- Sample Retained


Date well drilled: 2/21/03 - 2/22/03
 LFR Field Staff: Adelo Derilo/Charlotte Berghoffer
 Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-48 AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained

Date well drilled: 2/21/03 - 2/22/03
 LFR Field Staff: Adelo Derilo/Charlotte Berghoffer
 Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-48 AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA

Depth, feet	Graphic Log	Visual Description	ID of Samples Analyzed	P I D (ppm)/ Penetration Rate (blows/ft.)
Continued				
.....	#2/12 Sand		
.....	2-inch dia. SCH40 PVC Screen (0.010" slot)		
.....	Silt Trap		
75		FRIAR SANDSTONE (SS) , dark gray (5Y-4/1), moist, fine grained sand.	75	
.....	Bentonite Chips		
80			80	
.....	Slough		
85			85	

Bottom of well at 75.5 feet bgs.
Bottom of boring at 86 feet bgs.

- Materials used:
- Filter Pack
 - 3 bags #2/12 sand
 - Annular Seal
 - 2 bags bentonite chips
 - 6 bags bentonite grout

EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained


Date well drilled: 2/21/03 - 2/22/03
LFR Field Staff: Adelo Derilo/Charlotte Berghoffer
Approved by:

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-48 AD (CONTINUED)

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained

Date well drilled: 4/28/05
 LFR Field Staff: Adelo Derilo
 Approved by: *C. Wells CARCE 0-66471*

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-66AD (CONTINUED)

WELL CONSTRUCTION	LITHOLOGY	SAMPLING DATA
-------------------	-----------	---------------

Depth, feet	Graphic Log	Visual Description	ID of Samples Analyzed	P I D (ppm)/ Penetration Rate (blows/ft.)
-------------	-------------	--------------------	------------------------	---



Bottom of boring at 72 feet bgs.
 Bottom of well at 71 feet bgs.

- Materials used:
- Filter Pack
 - 1.519 cubic feet of #2/12 sand
 - Annular Seal
 - 1.05 cubic feet of bentonite pellets transition seal
 - 9.45 cubic feet of bentonite grout
 - 0.525 cubic feet of concrete surface seal

Drilling Method - Sonic Drilling
 Drilling Company - Prosonic Corporation


DRAFT

EXPLANATION

	Clay	<div style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; background-color: white; margin-right: 5px;"></div> Interval Sampled
	Silt	<div style="display: inline-block; width: 10px; height: 10px; border: 1px solid black; background-color: white; margin-right: 5px;"></div> Sample Retained
	Sand	
	Gravel	

Date well drilled: 4/28/05
 LFR Field Staff: Adelo Derilo
 Approved by: *C. Wells CARCE C-66471*

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-66AD (CONTINUED)



EXPLANATION

	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		


Date well drilled: 4/27/05
 LFR Field Staff: Adelo Derilo
 Approved by: *C. Wall CARCE 0-66471*

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-67AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



EXPLANATION

-  Clay
-  Silt
-  Sand
-  Gravel
-  Interval Sampled
-  Sample Retained

Date well drilled: 4/27/05
LFR Field Staff: Adelo Derilo


Approved by: *C. Wells* CARCE 0-66471

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-67AD (CONTINUED)

WELL CONSTRUCTION		LITHOLOGY		SAMPLING DATA		
Depth, feet	Graphic Log	Visual Description	ID of Samples Analyzed	P I D (ppm)/ Penetration Rate (blows/ft.)		
.....		FRIAR SANDSTONE (SS) , gray (5Y-6/1).			
.....					
.....				
.....				
75			75		
.....				
		Bottom of boring at 77 feet bgs. Bottom of well at 68 feet bgs.				
		Materials used: Filter Pack - 1.519 cubic feet of #2/12 sand Annular Seal - 1.05 cubic feet of bentonite pellets transition seal - 9.1 cubic feet of bentonite grout - 0.525 cubic feet of concrete surface seal				
		Drilling Method - Sonic Drilling Drilling Company - Prosonic Corporation				
		EXPLANATION 				

Date well drilled: 4/27/05
 LFR Field Staff: Adelo Derilo
 Approved by: *C. Derilo* CARCE 0-66471

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-67AD (CONTINUED)



EXPLANATION

	Clay		Interval Sampled
	Silt		Sample Retained
	Sand		
	Gravel		


Date well drilled: 4/26/05
 LFR Field Staff: Adelo Derilo
 Approved by: *C. Hall CARCE 0-66471*

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-68AD

WELL CONSTRUCTION

LITHOLOGY

SAMPLING DATA



Bottom of boring at 67 feet bgs.
 Bottom of well at 63 feet bgs.

Materials used:

- Filter Pack
 - 1.42 cubic feet of #2/12 sand
- Annular Seal
 - 1.05 cubic feet of bentonite pellets transition seal
 - 8.225 cubic feet of bentonite grout
 - 0.525 cubic feet of concrete surface seal

Drilling Method - Sonic Drilling
 Drilling Company - Prosonic Corporation

EXPLANATION

- Clay
- Silt
- Sand
- Gravel
- Interval Sampled
- Sample Retained

Date well drilled: 4/26/05
 LFR Field Staff: Adelo Derilo

Approved by: *C. Wall CARCE 0-66471*

WELL CONSTRUCTION AND LITHOLOGY FOR WELL R-68AD (CONTINUED)

PROJECT NAME Mission Valley Terminal - Qualcomm Stadium

WELL NUMBER RW-49

CLIENT Kinder Morgan Energy Partners

PAGE 1 OF 3

PROJECT LOCATION 9449 Friars Rd, San Diego, CA

DRILLING CONTRACTOR Boart Longyear

PROJECT NUMBER 002-10180-78-001

DRILLING METHOD Sonic Drilling

LOCATION Southwest Parking Lot

STAMP (IF APPLICABLE) AND/OR NOTES

Developed on 5/6/08 using Smeal Development rig.
Purged approximately 475 gallons.

OVA EQUIPMENT Mini Rae 2000

GROUND ELEVATION 56.56 ft-msl HOLE DIAMETER 10 inches

TOP OF CASING ELEVATION NA HOLE DEPTH 66.0 ft

▽ FIRST ENCOUNTERED WATER 17.0 ft bgs/ Elev 39.6 ft

▼ STABILIZED WATER 17.67 ft bgs/ Elev 38.9 ft

LOGGED BY James Gonzales DATE 2/6/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
5				5.0	Air knife to 5 feet bgs.	51.6		Concrete vault	5
10		GM		15.0	WELL GRADED GRAVEL (GM), dark brown (10YR 3/3), moist, some areas damp, no dry strength, loose, coarse gravel (up to 5" dia.), some silt, very low plasticity, gray to brown mottled gravel, subrounded to subangular cobbles.	6.7		Cement Grout	10
15		SP		41.6	POORLY GRADED SAND (SP) with silt and gravel, dark brown to gray mottled, moist, no dry strength, soft, loose, fine to medium subrounded sand with trace coarse sand, non-plastic, non-cohesive, quartz and micas.	3.1		6" dia. SCH40 PVC Blank Casing	15
20					▽ ▼			Hydrated Bentonite Chips	20
								#2/16 Sand	
								6" dia. SS Wire-wrap Screen (0.010" slot)	
								10" dia. Borehole	

(Continued Next Page)

APPROVED BY:

C. CARCE CARCE C-66471

DATE: 8/6/08



BORING+WELL 2006 002-10180-78-GPJ LFR SEPT 2006.GDT 5/14/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
25		SP		26.0	POORLY GRADED SAND (SP) with silt and gravel, dark brown to gray mottled, moist, no dry strength, soft, loose, fine to medium subrounded sand with trace coarse sand, non-plastic, non-cohesive, quartz and micas.	30.6	5.8		25
30		SM		32.0	SILTY SAND (SM), black (10YR 2/2) to brown mottled, wet, medium soft, loose, fine to medium subrounded sand, some coarse sand, very low plasticity to no plasticity, poorly graded, micas and quartz.	24.6	9.7		30
35		SP			POORLY GRADED SAND (SP) with silt and gravel (up to 6" dia.), dark brown to gray mottled, wet, no dry strength, soft, loose, fine to medium subrounded sand with trace coarse sand, non-plastic, non-cohesive.		12.1		35
40		SP					11.0		40
		SM		41.5	SILTY SAND (SM), black (10YR 2/2) to brown mottled, wet, medium soft, loose, fine to medium subrounded sand, some coarse sand, very low plasticity to no plasticity, poorly graded, micas and quartz.	15.1	7.9		

MATERIALS USED

(Continued Next Page)

APPROVED BY: CSMell CARCE C-66471 DATE: 8/6/08



BORING+WELL 2006 002-10180-78.GPJ LFR SEPT 2006.GDT 5/14/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
45		SM			SILTY SAND (SM), black (10YR 2/2) to brown mottled, wet, medium soft, loose, fine to medium subrounded sand, some coarse sand, very low plasticity to no plasticity, poorly graded, micas and quartz. (continued) -as above, with trace gravel.				45
50		SW		50.0	WELL GRADED SAND WITH GRAVEL (SW), brown to gray mottling, wet, soft, loose, no dry strength, medium to coarse subrounded sand, trace silt, cobbles (6 to 7" dia.), micas and quartz. -as above, increase gravel with depth.	6.6			50
55									55
60									60
65		SS		64.0	FRIARS FORMATION (SS), gray sandstone, hard, arenite, cemented, weathered interface.	-7.4			65
				66.0	Bottom of boring at 66 feet bgs. Bottom of well at 65 feet bgs.	-9.4			

MATERIALS USED

- Filter pack - 18.5 cubic feet of #2/16 sand
- Annular Seal - 1.0 cubic foot of bentonite chips
- 1.5 cubic feet of cement grout

APPROVED BY: C. Small CARCE C-66471 DATE: 8/6/08



BORING+WELL 2006 002-10180-78.GPJ LFR SEPT 2006.GDT 5/14/08

PROJECT NAME Mission Valley Terminal

WELL NUMBER RW-99

CLIENT KMEP

PAGE 1 OF 4

PROJECT LOCATION Qualcomm Stadium

DRILLING CONTRACTOR Boart Longyear

PROJECT NUMBER 002-10180-92

DRILLING METHOD Sonic Drilling

LOCATION Qualcomm - West Parking Lot

STAMP (IF APPLICABLE) AND/OR NOTES

OVA EQUIPMENT Mini Rae 2000

Developed on 5/7/08 using Smeal Development rig.
Purged approximately 500 gallons.


GROUND ELEVATION 67.90 ft-msl HOLE DIAMETER 10 inches

TOP OF CASING ELEVATION NA HOLE DEPTH 87.0 ft

▽ FIRST ENCOUNTERED WATER 33.0 ft bgs/ Elev 34.9 ft

▼ STABILIZED WATER 29.3 ft bgs/ Elev 38.6 ft

LOGGED BY Dana Brodie DATE 5/1/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
					Air knife to 5 feet bgs.				
5				5.0		62.9	>9999		5
10		CL			SANDY GRAVELLY CLAY (CL), mottled brown (10YR 5/3) and olive gray (5Y 5/2), moist, hard, no plasticity, fine to coarse grained sand, gravel to cobbles (4" dia.). -as above, dark grayish brown (10YR 4/2), more coarse grained sand. -as above, mottled very dark grayish brown (2.5Y 3/2), very dark brown (10YR 2/2) and dark olive gray (5Y 3/2).		>9999		10
15							>9999		15
20		CL		16.5	GRAVELLY SANDY CLAY (CL), mottled dark brown (10YR 3/3) and dark olive gray (5Y 3/2), moist, hard, no plasticity, fine to medium grained sand. -as above, pale yellow (2.5Y 8/2), moist, no plasticity, fine to coarse grained sand, gravel to cobbles (4" dia.).	51.4			20

(Continued Next Page)

APPROVED BY: CARCE C-66471 DATE: 8/6/08



BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
		CL		24.0	GRAVELLY SANDY CLAY (CL), pale yellow (2.5Y 8/2), moist, no plasticity, fine to coarse grained sand, gravel to cobbles (4" dia.).	43.9		<p>Bentonite Chips</p> <p>6" dia. SCH40 PVC Blank Casing</p> <p>10" dia. Borehole</p> <p>6" dia Stainless Steel Well Screen (0.010" slot)</p> <p>#2/12 Sand</p>	
25		SC		29.5	CLAYEY SAND (SC), dark olive gray (5Y 3/2), moist, fine grained, trace medium grained, poorly graded. -as above, trace coarse grained.	>9999			25
30		SM		38.4	SILTY SAND (SM), gray (2.5Y 6/1), moist, fine to medium grained, poorly graded. ▽ -as above, olive gray (5Y 5/2), wet.	5115			30
35					-as above, more coarse grained, trace gravel.	>9999			35
40		SP		38.5	POORLY GRADED SAND (SP), gray (10YR 5/1), wet, fine to medium grained, few coarse grained. -as above, more coarse grained. -as above, gravel (1" dia.).	29.4	2134		40

MATERIALS USED

(Continued Next Page)

APPROVED BY: C. CARCE C-66471 DATE: 8/6/08



BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
45		SP		45.0	POORLY GRADED SAND (SP), very dark gray (5Y 3/1), wet, fine to medium grained, trace clay.	20.9	853	<p>10" dia. Borehole</p> <p>6" dia Stainless Steel Well Screen (0.010" slot)</p> <p>#2/12 Sand</p>	45
50		CL		47.0	SANDY CLAY (CL), dark gray (10YR 4/1), wet, soft, moderate plasticity, fine to medium grained sand.	20.9	8.0		50
55		SM		54.0	SILTY SAND (SM), very dark gray (10YR 3/1), wet, fine grained, poorly graded.	13.9			55
		SW		54.2	WELL GRADED SAND (SW), gray (10YR 5/1), wet, fine to coarse grained.	13.7			
		SM		55.0	SILTY SAND (SM), dark gray (10YR 3/1), fine to medium grained sand, poorly graded, trace cobbles. -as above, fine to medium grained.	12.9	14.4		
60		SW		58.5	GRAVELLY SAND (SW), dark gray (10YR 3/1), fine to medium grained sand, few coarse grained sand, moderately graded, gravel (1 to 3" dia.), trace fines. -as above, more coarse grained sand.	9.4	6.7	60	
65							20.3	65	

MATERIALS USED

(Continued Next Page)

APPROVED BY: _____

C. Hall CARCE C-66471

DATE: 8/6/08



BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
70		SW		70.0	GRAVELLY SAND (SW), dark gray (10YR 3/1), fine to medium grained sand, more coarse grained sand, moderately graded, gravel (1 to 3" dia.).	-4.1		<p>10" dia. Borehole</p> <p>6" dia Stainless Steel Well Screen (0.010" slot)</p> <p>#2/12 Sand</p> <p>Bottom Cap</p> <p>Bentonite Chips</p> <p>Slough</p>	70
		SM		73.5	SILTY SAND (SM), gray (10YR 5/1), wet, medium to coarse grained sand, few fine grained sand, poorly graded, trace gravel.	-5.6			80
75		SW		77.5	GRAVELLY SAND (SW), gray (10YR 5/1), wet, fine to coarse grained, gravel (up to 3" dia.), trace fines. -as above, gravel to cobbles (6" dia.).	-9.6			85
80		SS			FRIARS FORMATION (SS), gray (10YR 5/1), weathered sandstone.				
85				87.0	Bottom of boring at 87 feet bgs. Bottom of well at 78 feet bgs.	-19.1			

MATERIALS USED

Filter Pack - 18.7 cubic feet of #2/12 Sand
 Transition Seal - 1.8 cubic foot of bentonite chips
 Annular Seal - 5.8 cubic feet of bentonite grout
 Bottom Plug - 2.7 cubic feet of bentonite chips

APPROVED BY: C. Small CARCE C-66471 DATE: 8/6/08



BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

PROJECT NAME Mission Valley Terminal

CLIENT KMEP

WELL NUMBER RW-100

PAGE 1 OF 3

PROJECT LOCATION Qualcomm Stadium

DRILLING CONTRACTOR Boart Longyear

PROJECT NUMBER 002-10180-92

DRILLING METHOD Sonic Drilling

LOCATION Qualcomm - SW Parking Lot

STAMP (IF APPLICABLE) AND/OR NOTES

OVA EQUIPMENT Mini Rae 2000

Developed on 5/8/08 using Smeal Development rig.
Purged approximately 490 gallons.

GROUND ELEVATION 53.14 ft-msl HOLE DIAMETER 10 inches

TOP OF CASING ELEVATION NA HOLE DEPTH 67.0 ft

▽ FIRST ENCOUNTERED WATER 15.0 ft bgs/ Elev 38.1 ft

▼ STABILIZED WATER 14.3 ft bgs/ Elev 38.9 ft

LOGGED BY Tania Alarcon DATE 5/5/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
					Air knife to 5 feet bgs.			Concrete Vault	
5		GC		5.0	CLAYEY GRAVEL WITH SAND (GC), brown (10YR 5/3), moist, coarse to subrounded gravel, cobbles (up to 3.5" dia.), some fine to medium grained sand.	48.1		Bentonite Chips	5
		GM		7.0	SILTY GRAVEL WITH SAND (GM), light olive brown (2.5Y 5/4), moist, fine to coarse gravel, angular to subrounded (up to 3" dia.), fine to medium grained sand, some fines.	46.1	3.8		
10		CL		9.5	-as above, brown to light olive gray (5Y 6/2) mottled, cobbles (up to 4" dia.). SANDY CLAY (CL), dark brown (10YR 3/3), moist, hard, medium plasticity, fine grained sand with gravel (up to 1.5" dia.).	43.6	1.1	6" dia. SCH40 PVC Blank Casing	10
		SM		12.5	-as above, dark brown to dark gray mottled, cobbles (up to 5" dia.), with some medium grained sand. SILTY SAND (SM), dark gray (10YR 4/1), moist, fine to medium grained sand, poorly graded, some clay, some gravel (up to 3" dia.).	40.6		#2/12 Sand	
15		CL		13.5	SANDY CLAY (CL), dark brown to dark gray mottled, moist, firm, medium plasticity, fine to coarse grained sand, with gravel and cobbles (up to 5" dia.).	39.6			
		SP		15.0	POORLY GRADED SAND (SP), very dark gray (10YR 3/1), wet, fine to medium grained, some fines, trace gravel and cobbles (up to 5" dia.). -as above, dark gray (10YR 4/1), fine to coarse grained, pocket of clay at 16.5 feet bgs, black (10YR 2/1), plastic. -as above, less fines and more coarse grained sand with depth, some gravel (up to 2" dia.).	38.1	0.0	6" dia. Stainless Steel Well Screen (0.010" slot)	15
20								10" dia. Borehole	20

BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

(Continued Next Page)

APPROVED BY: CAROL CARCE C-66471 DATE: 8/6/08



DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)
		SP		21.0	-as above, trace fine gravel.	32.1	3.4		
		ML		22.0	SILT (ML), very dark gray (10YR 3/1), very soft, low plasticity, some clay, trace fine grained sand.	31.1			
		CL		22.5	CLAY (CL), black (10YR 2/1), firm, medium plasticity.	30.6			
		SW		24.5	WELL GRADED SAND (SW), light gray to light brown mottled, fine to coarse grained.	28.6			
25		ML		29.5	SILT (ML), very dark gray (10YR 3/1), firm, medium plasticity, trace clay. -as above, very soft, some fine grained sand, trace clay, less sand with depth.	31.4			
		SP		35.0	POORLY GRADED SAND (SP), dark gray (10YR 4/1), fine to medium grained, trace coarse sand, trace fines. -as above, no fines.	23.6	1.2		
30		ML		36.0	SILT (ML), very dark gray (10YR 3/1), soft, medium plasticity, some clay.	18.1	36.6		
		SW		37.0	GRAVELLY SAND (SW), dark gray (10YR 4/1), fine to coarse grained, trace subrounded gravel (up to 1.5" dia.), some fines.	17.1			
		SM		39.5	SILTY SAND WITH GRAVEL (SM), very dark to dark gray, fine to coarse grained, trace gravel (up to 2" dia.), low plasticity. -as above, fine to medium grained sand, gravel (up to 3" dia.).	16.1			
35		GW		41.0	WELL GRADED GRAVEL WITH SAND (GW) mixture, very dark grayish brown (10YR 3/2), fine to coarse subangular to rounded cobbles (up to 6" dia.).	13.6	1.3		
		SW			WELL GRADED SAND (SW), very dark grayish brown (10YR 3/2), fine to coarse grained, trace angular to subrounded gravel (up to 2" dia.). -as above, trace rounded gravel (up to 1" dia.). -as above, increase coarse grained sand with depth, gravel (up to 3" dia.).	12.1			

MATERIALS USED

(Continued Next Page)

APPROVED BY: _____

C. Hall CARCE C-66471

DATE: 8/6/08



BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

DEPTH (feet)	SAMPLE TYPE NUMBER	U.S.C.S.	GRAPHIC LOG	DEPTHS	LITHOLOGIC DESCRIPTION	ELEVATIONS	PID (ppm)	WELL DIAGRAM	DEPTH (feet)	
45		SW			-as above, cobbles (up to 3.5" dia.).		2.8	<p>#2/12 Sand</p> <p>10" dia. Borehole</p> <p>6" dia. Stainless Steel Well Screen (0.010" slot)</p> <p>Bottom Cap</p>	45	
		SM		46.0	SILTY SAND (SM), very dark gray (10YR 3/1), fine grained sand.	7.1				
		SW		47.0	GRAVELLY SAND (SW), very dark grayish brown (10YR 3/2), fine to coarse grained, with gravel (up to 3" dia.), increasing gravel with depth.	6.1				
50				50.0	WELL GRADED GRAVEL WITH SAND (GW), very dark grayish brown (10YR 3/2), increasing gravel and cobble size with depth, fine to coarse grained sand.	3.1	2.7			50
					-as above, cobbles (up to 6.5" dia.).					
55					-as above, cobbles (up to 6" dia.). -as above, gravel (up to 3" dia.), increasing gravel and cobble size with depth.		2.0			55
		GW			-as above, cobbles (up to 4" dia.).		5.4			60
60					-as above, cobbles (up to 4" dia.).					
					-as above, cobbles (up to 4" dia.).					
65					-as above, cobbles (up to 5" dia.).		3.5			65
		SS		65.5	FRIARS FORMATION (SS), gray (10YR 5/1), iron staining at 66 feet bgs.	-12.4				
				67.0		-13.9				
					Bottom of boring at 67 feet bgs. Bottom of well at 66 feet bgs.					

MATERIALS USED

Filter Pack - 20.7 cubic feet of #2/12 Sand
 Annular Seal - 1.4 cubic feet of bentonite chips

BORING+WELL 2006 002-10180-92.GPJ LFR SEPT 2006.GDT 5/19/08

APPROVED BY: C. Wall CARCE C-66471 DATE: 8/6/08



Date Start/Finish: 4/14/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrell
Rig Type: Sonic Drill

Northing: 1865761.16
Easting: 6293593.55
Casing Elevation: NA
Borehole Depth: 74' bgs
Borehole Diameter: 8.5"
Surface Elevation: 63.11' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-109P (Pilot Boring)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Steve C Beedle* PG 6129

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
0								Air knife to 5' bgs on 4/12/11. Soil logged from air knife cuttings.	
5			0.0/NA			GM		SILTY GRAVEL (GM), fine to coarse subangular gravel, subrounded cobbles (up to 5" dia.), some fine grained sand with trace medium to coarse grained sand, poorly sorted, trace clay, low plasticity silt, no dilatancy, dry, medium dense, mottled gray to brown coloring.	
10			0.3/0.0					No recovery from 10' to 16' bgs.	Borehole backfilled with Bentonite Grout / Chips
15			0.4/0.0					Slough from 16' to 18' bgs, interpreted as SILTY GRAVEL (GM) with cobbles.	
45			0.2/0.0			GM		SILTY GRAVEL (GM), mostly fine to coarse subangular gravel, subrounded cobbles (up to 5" dia.), some fine grained sand with trace medium to coarse grained sand, poorly sorted, trace clay, low plasticity silt, no dilatancy, dry, medium dense, mottled	



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 66 feet NE of well RW-109.

Material Used: 59 cubic feet of Bentonite Grout / Chips.
 Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/14/11	27' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 74' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
20			1.4/0.0			GM		gray to brown coloring.	<p>Borehole backfilled with Bentonite Grout / Chips</p>
								No recovery from 20' to 22' bgs.	
40						GM		SILTY GRAVEL (GM) as above, moist.	
25			0.0/0.0			SP		POORLY GRADED SAND WITH GRAVEL (SP), mostly fine to coarse grained, subrounded, some fine to coarse subrounded gravel, trace subrounded gravel, trace silt, dry, gray (2.5Y 5/1) sand, brown to gray gravel and cobbles.	
								-as above, wet.	
35			0.0/0.0			SP-SW		Slough from 28' to 30' bgs, interpreted as POORLY GRADED SAND WITH GRAVEL (SP) to WELL GRADED SAND (SW).	
30			0.0/0.0			SM		SILTY SAND (SM), mostly fine sand, low plasticity silt, medium dense, olive brown (2.5Y 4/3).	
30						SW		WELL GRADED SAND (SW), mostly fine to coarse grained, subrounded, poorly sorted, trace silt, trace subangular fine gravel, wet, loose, soft, olive brown (2.5Y 4/3), micaceous.	
35			1.3/2.4			SM		SILTY SAND (SM), low plasticity silt, no dilatancy, fine subrounded sand, olive brown (2.5Y 4/3).	
25								No recovery from 38' to 44' bgs.	

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 66 feet NE of well RW-109.

Material Used: 59 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/14/11	27' ATD	NA

Depth measured from top of casing



Site Location:

Borehole Depth: 74' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
40								No recovery from 38' to 44' bgs.	
45		RW-109-46	0.9/1.1		X	SW		WELL GRADED SAND (SW), fine to coarse grained, subrounded, poorly sorted, trace silt, trace subangular fine gravel, wet, loose, soft, olive brown (2.5Y 4/3), micaceous.	
50		RW-109-50	0.1/0.9		X	SM		SILTY SAND (SM), low plasticity silt and fine to medium subrounded sand, low density, loose, dark olive brown (2.5Y 3/3).	Borehole backfilled with Bentonite Grout / Chips
55						SM-SW		Slough from 50' to 52' bgs, interpreted as SILTY SAND (SM) to WELL GRADED SAND WITH GRAVEL (SW).	
60								WELL GRADED SAND WITH GRAVEL (SW), fine to coarse subrounded sand, some subangular to subrounded fine to coarse gravel (up to 2" dia.), wet, loose, soft, dark olive brown (2.5Y 3/3), brown to gray mottled coloring.	
65		RW-109-56	0.0/0.0		X	SW			

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 66 feet NE of well RW-109.

Material Used: 59 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/14/11	27' ATD	NA
Depth measured from top of casing		



Site Location:

Borehole Depth: 74' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
								-as above, wet.	
60		RW-109-62		0.4/1.3	X			WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, trace silt, wet, loose, soft, micaceous.	
0									
65		RW-109-67			X	SW		WELL GRADED SAND WITH GRAVEL (SW), fine to coarse grained sand, subrounded, some fine to coarse subangular gravel, trace cobbles (up to 3.5" dia.), trace silt, loose, soft.	
-5									
70				2.2/1.9				-as above, wet.	
-10		RW-109-73			X				
						SS		FRIARS SANDSTONE (SS), gray.	
75									
-15									

Borehole backfilled with Bentonite Grout / Chips



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 66 feet NE of well RW-109.

Material Used: 59 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/14/11	27' ATD	NA

Depth measured from top of casing

Date Start/Finish: 6/3/11 - 6/4/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrel
Rig Type: Sonic Drill

Northing: 1865726.60
Easting: 6293537.80
Casing Elevation: NA
Borehole Depth: 71' bgs
Borehole Diameter: 10"
Surface Elevation: 60.15' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-109 (GWE Well)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Steve C Beedle PG 6129*

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
60								Air knife to 5' bgs on 4/12/11. Soil logged from air knife cuttings.	
55						GM		SILTY GRAVEL (GM) with cobbles, mostly silt and fine grained sand, mostly fine to coarse subangular gravel, subrounded cobbles (up to 5" dia.), trace medium to coarse grained sand, poorly sorted, trace clay, low plasticity, no dilatancy, dry, medium dense, mottled gray to brown coloring.	<ul style="list-style-type: none"> Concrete Vault (0-4' bgs) Concrete (4-7' bgs) Bentonite Chips (7-9' bgs) 10" Dia. Borehole 6" Dia. SCH40 PVC Blank Casing (1-50' bgs) Bentonite Grout (9-40' bgs)
10	50							No recovery from 10' to 16' bgs.	
15	45							Slough from 16' to 18' bgs, interpreted as SILTY GRAVEL (GM) with cobbles.	
						GM		SILTY GRAVEL (GM) with cobbles, mostly silt and fine grained sand, mostly fine to coarse subangular gravel, subrounded cobbles (up to 5" dia.), trace medium to coarse grained sand, poorly sorted, trace clay, low plasticity, no dilatancy, dry,	

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 66 feet SW of pilot boring RW-109P. Lithology determined from pilot boring RW-109P. Actual Friars Sandstone contact determined from well RW-109.

Material Used: 18 cubic ft of Sand, 27 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 71' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
20	40					GM		medium dense, mottled gray to brown coloring.	10" Dia. Borehole
								No recovery from 20' to 22' bgs.	
						GM		SILTY GRAVEL (GM) as above, moist.	Bentonite Grout (9-40' bgs)
25	35					SP		POORLY GRADED SAND WITH GRAVEL (SP), mostly fine to coarse grained, subrounded, some fine to coarse subrounded gravel, trace subrounded gravel, trace silt, dry, gray (2.5Y 5/1) sand, brown to gray gravel and cobbles.	
								-as above, wet.	
						SP-SW		Slough from 28' to 30' bgs, interpreted as POORLY GRADED SAND WITH GRAVEL (SP) to WELL GRADED SAND (SW).	6" Dia. SCH40 PVC Blank Casing (1-50' bgs)
30	30					SM		SILTY SAND (SM), mostly fine sand and silt, low plasticity, medium dense, olive brown (2.5Y 4/3).	
						SW		WELL GRADED SAND (SW), mostly fine to coarse grained, subrounded, poorly sorted, trace silt, trace subangular fine gravel, wet, loose, soft, olive brown (2.5Y 4/3), micaceous.	
						SM		SILTY SAND (SM), mostly low plasticity silt, no dilatency, some fine subrounded sand, olive brown (2.5Y 4/3).	
35	25							No recovery from 38' to 44' bgs.	

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 66 feet SW of pilot boring RW-109P. Lithology determined from pilot boring RW-109P. Actual Friars Sandstone contact determined from well RW-109.

Material Used: 18 cubic ft of Sand, 27 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 71' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
40	20							No recovery from 38' to 44' bgs.	
45	15					SW	WELL GRADED SAND (SW), mostly fine to coarse grained, subrounded, poorly sorted, trace silt, trace subangular fine gravel, wet, loose, soft, olive brown (2.5Y 4/3), micaceous.		
50	10					SM	SILTY SAND (SM), low plasticity silt and fine to medium subrounded sand, low density, loose, dark olive brown (2.5Y 3/3).		
55	5					SM-SW	Slough from 50' to 52' bgs, interpreted as SILTY SAND (SM) to WELL GRADED SAND WITH GRAVEL (SW).		
							SW	WELL GRADED SAND WITH GRAVEL (SW), mostly fine to coarse subrounded sand, some subangular to subrounded fine to coarse gravel (up to 2" dia.), wet, loose, soft, dark olive brown (2.5Y 3/3), brown to gray mottled coloring.	

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 66 feet SW of pilot boring RW-109P. Lithology determined from pilot boring RW-109P. Actual Friars Sandstone contact determined from well RW-109.

Material Used: 18 cubic ft of Sand, 27 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 71' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
60	0							-as above, wet. WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, trace silt, wet, loose, soft, micaceous.	
65	-5				SW		WELL GRADED SAND WITH GRAVEL (SW) and cobbles, fine to coarse grained sand, subrounded, some fine to coarse subangular gravel, trace cobbles (up to 3.5" dia.), trace silt, loose, soft.		
70	-10						-as above, wet. FRIARS SANDSTONE (SS) at 71' bgs, gray.		
75	-15								



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 66 feet SW of pilot boring RW-109P. Lithology determined from pilot boring RW-109P. Actual Friars Sandstone contact determined from well RW-109.

Material Used: 18 cubic ft of Sand, 27 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.

Date Start/Finish: 4/15/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrel
Rig Type: Sonic Drill

Northing: 1865429.40
Easting: 6293489.21
Casing Elevation: NA
Borehole Depth: 68' bgs
Borehole Diameter: 8.5"
Surface Elevation: 54.56' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-110P (Pilot Boring)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Steve C Beadle PG 6129*

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
5						GM		Air knife to 5' bgs on 4/12/11. Soil logged from air knife cuttings. SILTY GRAVEL (GM), fine to coarse subangular gravel, cobbles (up to 3-4" dia.), some fine grained sand with some medium and coarse grained sand, low plastic silt, dry to moist, brown to gray mottled coloring.	
10			0.9/0.0					No recovery from 10' to 14' bgs, interpreted as SILTY GRAVEL (GM).	Borehole backfilled with Bentonite Grout / Chips
15			6.3/0.2			GM		SILTY GRAVEL (GM) as above.	



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

 Drilled approximately 115 ft east of well RW-110.

 Material Used: 54 cubic feet of Bentonite Grout / Chips.
 Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/15/11	19' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 68' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
35								WELL GRADED SAND (SW), fine to coarse grained, subrounded, trace silt, moderate dilatancy, wet, low density, loose, dark olive brown (2.5Y 3/3), micaceous.	
20						SW			
25			0.3/0.0			SP		POORLY GRADED SAND (SP), mostly medium to coarse grained sand, some fine grained sand, subrounded, rapid dilatancy, wet, low density, dark olive brown (2.5Y 3/3), micaceous.	
30								No recovery from 30' to 37' bgs.	Borehole backfilled with Bentonite Grout / Chips
25			0.5/0.0						
30									
35						SW		WELL GRADED SAND (SW), mostly fine to medium grained sand, subrounded, some coarse subrounded sand, moderate dilatancy, trace silt, trace subangular gravel.	



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 115 ft east of well RW-110.

Material Used: 54 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/15/11	19' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 68' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
15									
40		RW-110-42		0.7/0.0		SW		-decreasing fines, increasing coarse grained sand with depth, increasing subangular and subrounded gravel.	
								-as above, wet.	
		RW-110-44		0.2/0.0		SM		SILTY SAND (SM), fine subrounded sand, slow dilatancy, low plastic silt, well sorted, medium to low density, black (2.5Y 2.5/1).	
45								-as above, decreasing fines.	
		RW-110-47		0.3/0.0				WELL GRADED SAND (SW), fine to medium grained sand, subrounded, moderate to rapid dilatancy.	
								-as above, mostly medium to coarse grained sand, subrounded, rapid dilatancy, trace subangular fine gravel, low density, black (2.5Y 2.5/1).	
50								-as above, wet.	
								Poor recovery from 54' to 56' bgs.	Borehole backfilled with Bentonite Grout / Chips
55		RW-110-56		0.2/0.0		SW			
		RW-110-58						-as above, fine to coarse grained, moderate to rapid dilatancy, non-cohesive, loose, soft, black (2.5Y 2.5/1).	

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 115 ft east of well RW-110.

Material Used: 54 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/15/11	19' ATD	NA
Depth measured from top of casing		



Site Location:

Borehole Depth: 68' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
60	-5					SW		FRIARS SANDSTONE (SS), weathered gray sandstone, weakly cemented, moist, light to dark gray.	
65	-10					SS			
70	-15								
75	-20								

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 115 ft east of well RW-110.

Material Used: 54 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/15/11	19' ATD	NA

Depth measured from top of casing



Date Start/Finish: 6/1/11 - 6/2/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrell
Rig Type: Sonic Drill

Northing: 1865424.21
Easting: 6293374.76
Casing Elevation: NA
Borehole Depth: 63' bgs
Borehole Diameter: 10"
Surface Elevation: 50.48' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-110 (GWE Well)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Steve Beadle PG 6129*

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
50								Air knife to 5' bgs on 4/12/11. Soil logged from air knife cuttings. SILTY GRAVEL (GM) with cobbles, mostly low plastic silt and fine grained sand, fine to coarse subangular gravel, cobbles (up to 3-4" dia.), some medium and coarse grained sand, dry to moist, brown to gray mottled coloring.	
5	45					GM		No recovery from 10' to 14' bgs, interpreted as SILTY GRAVEL (GM).	
10	40							SILTY GRAVEL (GM) with cobbles as above.	
15	35					GM			

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level
 Drilled approximately 115 ft west of pilot boring RW-110P. Lithology determined from pilot boring RW-110P. Actual Friars Sandstone contact determined from well RW-110.
 Material Used: 21 cubic ft of #8 Sand, 20 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 63' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
20	30					SW		WELL GRADED SAND (SW), fine to coarse grained, subrounded, trace silt, moderate dilatancy, wet, low density, loose, dark olive brown (2.5Y 3/3), micaceous.	10" Dia. Borehole
25	25					SP		POORLY GRADED SAND (SP), mostly medium to coarse grained sand, some fine grained sand, subrounded, rapid dilatancy, wet, low density, dark olive brown (2.5Y 3/3), micaceous.	Bentonite Grout (9-30' bgs)
30	20							No recovery from 30' to 37' bgs.	6" Dia. SCH40 PVC Blank Casing (1-40' bgs)
35	15					SW		WELL GRADED SAND (SW), mostly fine to medium grained sand, subrounded, some coarse subrounded sand, moderate dilatancy, trace silt, trace subangular gravel.	Bentonite Chips (30-35' bgs)
									#8 Mesh Sand (35-63' bgs)

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 115 ft west of pilot boring RW-110P. Lithology determined from pilot boring RW-110P. Actual Friars Sandstone contact determined from well RW-110.

Material Used: 21 cubic ft of #8 Sand, 20 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 63' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
40	10					SW		-decreasing fines, increasing coarse grained sand with depth, increasing subangular and subrounded gravel. -as above, wet.	6" Dia. SCH40 PVC Blank Casing (1-40' bgs)
45	5					SM		SILTY SAND (SM), fine subrounded sand, slow dilatancy, low plastic silt, well sorted, medium to low density, black (2.5Y 2.5/1). -as above, decreasing fines.	#8 Mesh Sand (35-63' bgs)
50	0					SW		WELL GRADED SAND (SW), fine to medium grained sand, subrounded, moderate to rapid dilatancy. -as above, mostly medium to coarse grained sand, subrounded, rapid dilatancy, trace subangular fine gravel, low density, black (2.5Y 2.5/1). -as above, wet.	6" Dia. SS Wire-wrapped Well Screen 0.040" Slot (40-60' bgs)
55	-5					SW		Poor recovery from 54' to 56' bgs. WELL GRADED SAND (SW), fine to coarse grained, moderate to rapid dilatancy, non-cohesive, loose, soft, black (2.5Y 2.5/1).	10" Dia. Borehole

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 115 ft west of pilot boring RW-110P. Lithology determined from pilot boring RW-110P. Actual Friars Sandstone contact determined from well RW-110.

Material Used: 21 cubic ft of #8 Sand, 20 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 63' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
60	-10					SW		WELL GRADED SAND (SW), fine to coarse grained, moderate to rapid dilatancy, non-cohesive, loose, soft, black (2.5Y 2.5/1).	<p>Integrated Bottom Cap</p> <p>#8 Mesh Sand (35-63' bgs)</p>
						SS		FRIARS SANDSTONE (SS), weathered gray sandstone, weakly cemented, moist, light to dark gray.	
65	-15								
70	-20								
75	-25								

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 115 ft west of pilot boring RW-110P. Lithology determined from pilot boring RW-110P. Actual Friars Sandstone contact determined from well RW-110.

Material Used: 21 cubic ft of #8 Sand, 20 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Date Start/Finish: 4/19/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrel
Rig Type: Sonic Drill

Northing: 1865177.82
Easting: 6293419.52
Casing Elevation: NA
Borehole Depth: 65' bgs
Borehole Diameter: 8.5"
Surface Elevation: 49.61' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-111P (Pilot Boring)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Steve C Beadle* PG 6129

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
0								Air knife to 5' bgs on 4/14/11. Soil logged from air knife cuttings. Asphalt at surface.	
5			1.4/0.1			GM		SILTY GRAVEL (GM), low to medium plastic silt, no dilatancy, subrounded to subangular fine to coarse gravel, some subrounded to subangular cobbles (up to 3-4" dia.), poorly sorted, moist, dense, mottled gray to brown coloring. -as above, moist. -as above, dark yellowish brown (10YR 4/4).	
10			1.7/0.3			GW		WELL GRADED GRAVEL WITH SAND (GW), fine to coarse grained sand, subrounded, moderate dilatancy, fine to coarse subangular gravel, some silt, trace subrounded cobbles, poorly sorted, wet, very dark brown (10YR 2/2). -as above, moist.	Borehole backfilled with Bentonite Grout / Chips
15			0.2/0.0			SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, some coarse subrounded sand, some non-plastic silt, moderately sorted, very dark brown (10YR 2/2), micaceous.	
						SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, trace subrounded fine to coarse gravel, trace silt, moderately sorted, wet, loose, soft, dark yellowish brown (10YR 3/4). -as above, increasing silt content.	



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

 Drilled approximately 7 ft east of well RW-111.

 Material Used: 52 cubic feet of Bentonite Grout / Chips.
 Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/19/11	13-17' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 65' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
30						SW			
20			0.0/0.0			SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, wet, medium dense, medium loose, very dark brown (10YR 2/2).	
25						SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, some non-plastic silt, moderately to well sorted, wet, low density, loose, very dark brown (10YR 2/2).	
25			0.0/0.0			SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, wet, medium dense, very dark brown (10YR 2/2), micaceous.	
20						SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, trace coarse sand, some non-plastic silt, moderately to well sorted, loose, soft, dark brown (10YR 3/3).	
30			0.0/0.0			SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, dark brown.	
						SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, some fine to coarse subrounded gravel, trace silt, dark brown.	
						SM		SILTY SAND (SM), non-plastic silt and fine sand, no dilatancy, well sorted, wet, dense, very dark brown (10YR 2/2).	
35			1.9/0.0			SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, some fine to coarse subrounded to subangular gravel, trace subrounded cobbles (up to 2-3" dia.), wet, loose, dark yellowish brown (10YR 3/4), micaceous.	
		RW-111-37				SW			Borehole backfilled with Bentonite Grout / Chips



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 7 ft east of well RW-111.

Material Used: 52 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/19/11	13-17' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 65' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
10									
40		RW-111-42	0.5/0.0		X	SW		-as above, increasing cobbles.	
45								-as above, some fine gravel, soft, dark yellowish brown (10YR 3/4).	
		RW-111-47	0.0/0.0		X				
50						GW		WELL GRADED GRAVEL WITH SAND (GW), fine to coarse grained sand, subrounded, moderate dilatancy, fine to coarse subrounded to subangular gravel, some subrounded cobbles (up to 3-4" dia.), trace to some non-plastic silt, very poorly sorted, wet, loose, mottled gray to brown coloring.	Borehole backfilled with Bentonite Grout / Chips
55		RW-111-55			X			No recovery from 55' to 60' bgs.	



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 7 ft east of well RW-111.

Material Used: 52 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data

Date	Depth	Elev.
4/19/11	13-17' ATD	NA
Depth measured from top of casing		

Site Location:

Borehole Depth: 65' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
60	-10			0.0/0.0				No recovery from 55' to 60' bgs.	<p>Borehole backfilled with Bentonite Grout / Chips</p>
65	-15					SS	FRIARS SANDSTONE (SS), partially cemented siltstone to sandstone, weathered gray.		
70	-20								
75	-25								



Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level; ATD = At Time of Drilling

Drilled approximately 7 ft east of well RW-111.

Material Used: 52 cubic feet of Bentonite Grout / Chips. Surface capped with cold asphalt.

Water Level Data		
Date	Depth	Elev.
4/19/11	13-17' ATD	NA
Depth measured from top of casing		

Date Start/Finish: 5/25/11
Drilling Company: Cascade Drilling
Driller's Name: Val Godoy
Drilling Method: Rotary Sonic
Sampling Method: 10' x 6" Dia. Sonic Core Barrel
Rig Type: Sonic Drill

Northing: 1865175.32
Easting: 6293426.34
Casing Elevation: NA
Borehole Depth: 57.5' bgs
Borehole Diameter: 10"
Surface Elevation: 49.73' MSL
Descriptions By: James Gonzales

Well/Boring ID: RW-111 (GWE Well)
Client: Kinder Morgan Energy Partners
Location: Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108
Reviewed By: *Stuart Beedle PG 6129*

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
0								Air knife to 5' bgs on 4/14/11. Soil logged from air knife cuttings. Asphalt at surface.	
5	45					GM		SILTY GRAVEL (GM), low to medium plastic silt, no dilatancy, subrounded to subangular fine to coarse gravel, some subrounded to subangular cobbles (up to 3-4" dia.), poorly sorted, moist, dense, mottled gray to brown coloring. -as above, moist. -as above, dark yellowish brown (10YR 4/4).	Concrete Vault (0-4' bgs) Concrete (4-7' bgs)
10	40					GW		WELL GRADED GRAVEL WITH SAND (GW), fine to coarse grained sand, subrounded, moderate dilatancy, fine to coarse subangular gravel, some silt, trace subrounded cobbles, poorly sorted, wet, very dark brown (10YR 2/2). -as above, moist.	Bentonite Chips (7-9' bgs)
15	35					SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, some coarse subrounded sand, some non-plastic silt, moderately sorted, very dark brown (10YR 2/2), micaceous.	6" Dia. SCH40 PVC Blank Casing (1-37' bgs)
						SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, trace subrounded fine to coarse gravel, trace silt, moderately sorted, wet, loose, soft, dark yellowish brown (10YR 3/4). -as above, increasing silt content.	Bentonite Grout (9-27' bgs) 10" Dia. Borehole

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

 Drilled approximately 7 ft west of pilot boring RW-111P. Lithology determined from pilot boring RW-111P. Actual Friars Sandstone contact determined from well RW-111.

 Material Used: 18 cubic ft of #8 Sand, 18 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 57.5' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
20	30					SW			
						SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, wet, medium dense, medium loose, very dark brown (10YR 2/2).	10" Dia. Borehole
						SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, some non-plastic silt, moderately to well sorted, wet, low density, loose, very dark brown (10YR 2/2).	Bentonite Grout (9-27' bgs)
25	25					SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, wet, medium dense, very dark brown (10YR 2/2), micaceous.	6" Dia. SCH40 PVC Blank Casing (1-37' bgs)
						SP		POORLY GRADED SAND (SP), fine to medium grained sand, subrounded, moderate dilatancy, trace coarse sand, some non-plastic silt, moderately to well sorted, loose, soft, dark brown (10YR 3/3).	
						SM		SILTY SAND (SM), fine to medium subrounded sand, slow to moderate dilatancy, non-plastic silt, moderately sorted, dark brown.	Bentonite Chips (27-32' bgs)
30	20					SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, some fine to coarse subrounded gravel, trace silt, dark brown.	
						SM		SILTY SAND (SM), non-plastic silt and fine sand, no dilatancy, well sorted, wet, dense, very dark brown (10YR 2/2).	
						SW		WELL GRADED SAND (SW), fine to coarse grained sand, subrounded, rapid dilatancy, some fine to coarse subrounded to subangular gravel, trace subrounded cobbles (up to 2-3" dia.), wet, loose, dark yellowish brown (10YR 3/4), micaceous.	#8 Mesh Sand (32-57.5' bgs)
35	15					SW			6" Dia. SS Wire-wrapped Well Screen 0.040" Slot (37-57' bgs)

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 7 ft west of pilot boring RW-111P. Lithology determined from pilot boring RW-111P. Actual Friars Sandstone contact determined from well RW-111.

Material Used: 18 cubic ft of #8 Sand, 18 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



Site Location:

Borehole Depth: 57.5' bgs

Mission Valley Terminal - Qualcomm Stadium
 9950 San Diego Mission Rd
 San Diego, CA 92108

DEPTH	ELEVATION	Sample ID	Recovery (feet)	PID/FID (ppm)	Sieve Analysis Sample	USCS Code	Geologic Column	Stratigraphic Description	Well/Boring Construction
40	10					SW		-as above, increasing cobbles. -as above, some fine gravel, soft, dark yellowish brown (10YR 3/4).	10" Dia. Borehole #8 Mesh Sand (32-57.5' bgs)
45	5					GW		WELL GRADED GRAVEL WITH SAND (GW), fine to coarse grained sand, subrounded, moderate dilatancy, fine to coarse subrounded to subangular gravel, some subrounded cobbles (up to 3-4" dia.), trace to some non-plastic silt, very poorly sorted, wet, loose, mottled gray to brown coloring.	6" Dia. SS Wire-wrapped Well Screen 0.040" Slot (37-57' bgs)
50	0							No recovery from 55' to 57' bgs.	
55	-5					SS		FRIARS SANDSTONE (SS), weathered, gray.	Integrated Bottom Cap

Remarks: ft bgs = feet below ground surface; NA = Not Applicable/Available; MSL = Mean Sea Level

Drilled approximately 7 ft west of pilot boring RW-111P. Lithology determined from pilot boring RW-111P. Actual Friars Sandstone contact determined from well RW-111.

Material Used: 18 cubic ft of #8 Sand, 18 cubic ft of Bentonite Grout/Chips, 2 cubic ft of Concrete Seal.



D

APPENDIX B
CURRENT EXPLORATION RECORDS

R

A

F

T

APPENDIX B

CURRENT EXPLORATION RECORDS

Field exploration included a visual reconnaissance of the site, the drilling of 17 exploratory borings, and the advancement of five cone penetration tests (CPTs). The borings were drilled between February 11 and March 15, 2019 and the CPTs were advanced on March 18 and April 8, 2019. The maximum depth of exploration was about 101½ feet below surrounding grades. The approximate exploration locations are shown in Plate 1. Logs of the explorations are provided in Figures B-01 through B-23, immediately after the Boring Record Legends.

The exploratory borings were advanced by Pacific Drilling and Tri-County Drilling using several truck mounted drill rigs. Disturbed samples were collected from the borings using a 2-inch outside diameter unlined Standard Penetration Test (SPT) sampler. Less disturbed samples were collected using a 3-inch outside diameter ring lined sampler (a modified California sampler). Bulk samples were also collected. The samples were sealed in plastic bags, labeled, and returned to the laboratory for testing. A summary of the exploratory boring locations, elevations and depths is shown on the following page.

The drive samples were collected from the exploratory borings using several different automatic hammers with average Energy Transfer Ratios (ETR) ranging from approximately 79 to 85 percent. For each sample, the 6-inch incremental blowcounts was recorded on the logs. The field blow counts (N) were normalized to approximate the standard 60 percent ETR, as shown on the logs (N_{60}). The California ring samples were also corrected for the 3-inch sampler diameter using Burmister's correction factor. Blowcounts that were influenced by flowing/heaving sands, gravel and cobbles are noted on the logs with a caret (^) as being inaccurate. Where sampler refusal was encountered (i.e., unable to drive the sampler more than the first six inches with 50 hammer blows), the blowcount is denoted as "REF".

The exploratory borings were logged using the Caltrans Soil and Rock Logging, Classification and Presentation Manual (2010) as a guideline. The Friars Formation materials are described in general accordance with Section 2.6.1.3 (i.e., Description of Poorly Indurated Rock) of the Caltrans Manual (2010).

The CPT soundings were advanced by Kehoe Testing and Engineering in general accordance with ASTM D5778. The CPT soundings were carried out by KTE using an integrated electronic cone system manufactured by Vertek. The CPTs were advanced using a 30-ton CPT rig. The cone used during the program was a 15 cm² cone and recorded the following parameters at approximately 2.5 cm depth intervals:

- Cone Resistance (q_c)
- Sleeve Friction (f_s)
- Dynamic Pore Pressure (u)
- Inclination
- Penetration Speed

APPENDIX B

CURRENT EXPLORATION RECORDS (Continued)

CPT-2 initially encountered refusal at a depth of about 25 feet due to gravel and cobbles causing flexure of the CPT rods. A second CPT was advanced a few feet away and was able to be advanced to a depth of about 45 feet. SCPT-7 and CPT-11 both encountered relatively shallow refusal on gravel and cobbles at about 17 feet.

At locations SCPT-5, SCPT-7 and SCPT-13, shear wave velocity measurements were obtained at various depths. The shear wave was generated using an air-actuated hammer located inside the front jack of the CPT rig. The cone was equipped with a triaxial geophone, which recorded the shear wave signal generated by the air hammer. The above parameters were recorded and viewed in real time using a laptop computer. A summary of the collected shear wave measurements is presented in Figure B-22. Note: SCPT-13 was intentionally advanced through the previously grouted borehole of boring S-13 to obtain shear wave velocity measurements. Therefore, the CPT parameters (q_c , f_s and u) are not representative of the actual soil conditions at that location and are not presented in this report.

Note: the exploration locations were measured in the field using a Garmin GPSMAP 64st Global Positioning System (GPS) receiver and by visually estimating, pacing or taping distances from nearby landmarks, if available. The exploration elevations were estimated by interpolation using the referenced plans provided by Rick Engineering (see Plate 1). The locations and elevations provided should not be considered more accurate than is implied by the scale of the map and the accuracy of the equipment used to locate the explorations. The lines designating the interface between differing soil materials on the logs may be abrupt or gradational. Further, soil conditions at locations between the explorations may be substantially different from those at the specific locations we explored. The Boring Records are part of a geotechnical report which must be considered in its entirety.

APPENDIX B

CURRENT EXPLORATION RECORDS (Continued)

Exploratory Borings Summary (see Plate 1)						
Exploration ID	Latitude [°]	Longitude [°]	Top Elevation NAVD 88 [FT]	Exploration Depth [FT]	Bottom Elevation NAVD 88 [FT]	Figure No.
S-1	32.78583	-117.12281	83	60	23	B-1
S-2	32.78575	-117.12112	66	61	5	B-2
S-3	32.78518	-117.12293	74	46.5	28	B-3
S-4	32.78519	-117.12216	68	40.5	28	B-4
S-5	32.78506	-117.12130	63	61	2	B-5
S-6	32.78473	-117.12305	69	41.5	28	B-6
S-7	32.78427	-117.12239	57	100.9	-44	B-7
S-8	32.78454	-117.12129	69	75.5	-7	B-8
S-9	32.78409	-117.12310	59	36.5	23	B-9
S-10	32.78382	-117.12202	66	71.3	-5	B-10
S-11	32.78364	-117.12323	54	36.5	18	B-11
S-12	32.78345	-117.12271	58	41.5	17	B-12
S-13	32.78324	-117.12156	75	101.5	-27	B-13
B-14	32.78253	-117.12331	51	31.5	23	B-14
B-15	32.78151	-117.12375	51	36.3	5	B-15
B-16	32.78221	-117.12111	78	85	28	B-16
B-17	32.78121	-117.12114	64	71.5	28	B-17

Exploratory Cone Penetration Test Soundings Summary (see Plate 1)						
Exploration ID	Latitude	Longitude	Top Elevation NAVD 88 [FT]	Exploration Depth [FT]	Bottom Elevation NAVD 88 [FT]	Figure No.
CPT-2	32.78570	-117.12109	67	45.5	21	B-18
SCPT-5	32.78504	-117.12129	63	57.4	6	B-19
SCPT-7	32.78428	-117.12239	57	17.5	40	B-20
CPT-11	32.78365	-117.12322	54	17.5	36	B-21
SCPT-13	32.78324	-117.12156	75	66.8	8	--

SOIL IDENTIFICATION AND DESCRIPTION SEQUENCE

Sequence	Identification Components	Refer to Section		Required	Optional
		Field	Lab		
1	Group Name	2.5.2	3.2.2	●	
2	Group Symbol	2.5.2	3.2.2	●	
	Description Components				
3	Consistency of Cohesive Soil	2.5.3	3.2.3	●	
4	Apparent Density of Cohesionless Soil	2.5.4		●	
5	Color	2.5.5		●	
6	Moisture	2.5.6		●	
7	Percent or Proportion of Soil	2.5.7	3.2.4	●	○
	Particle Size	2.5.8	2.5.8	●	○
	Particle Angularity	2.5.9			○
	Particle Shape	2.5.10			○
8	Plasticity (for fine-grained soil)	2.5.11	3.2.5		○
9	Dry Strength (for fine-grained soil)	2.5.12			○
10	Dilatency (for fine-grained soil)	2.5.13			○
11	Toughness (for fine-grained soil)	2.5.14			○
12	Structure	2.5.15			○
13	Cementation	2.5.16		●	
14	Percent of Cobbles and Boulders	2.5.17		●	
	Description of Cobbles and Boulders	2.5.18		●	
15	Consistency Field Test Result	2.5.3		●	
16	Additional Comments	2.5.19			○

Describe the soil using descriptive terms in the order shown

Minimum Required Sequence:

USCS Group Name (Group Symbol); Consistency or Density; Color; Moisture; Percent or Proportion of Soil; Particle Size; Plasticity (optional).

○ = optional for non-Caltrans projects

Where applicable:

Cementation; % cobbles & boulders;
Description of cobbles & boulders;
Consistency field test result

HOLE IDENTIFICATION

Holes are identified using the following convention:

H – YY – NNN

Where:

H: Hole Type Code

YY: 2-digit year

NNN: 3-digit number (001-999)

Hole Type Code and Description

Hole Type Code	Description
A	Auger boring (hollow or solid stem, bucket)
R	Rotary drilled boring (conventional)
RC	Rotary core (self-cased wire-line, continuously-sampled)
RW	Rotary core (self-cased wire-line, not continuously sampled)
P	Rotary percussion boring (Air)
HD	Hand driven (1-inch soil tube)
HA	Hand auger
D	Driven (dynamic cone penetrometer)
CPT	Cone Penetration Test
O	Other (note on LOTB)

Description Sequence Examples:

SANDY lean CLAY (CL); very stiff; yellowish brown; moist; mostly fines; some SAND, from fine to medium; few gravels; medium plasticity; PP=2.75.

Well-graded SAND with SILT and GRAVEL and COBBLES (SW-SM); dense; brown; moist; mostly SAND, from fine to coarse; some fine GRAVEL; few fines; weak cementation; 10% GRANITE COBBLES; 3 to 6 inches; hard; subrounded.

Clayey SAND (SC); medium dense, light brown; wet; mostly fine sand; little fines; low plasticity.

REFERENCE: Caltrans Soil and Rock Logging, Classification, and Presentation Manual (2010).



Project No. SD605

SDSU Mission Valley
Football Stadium

BORING RECORD LEGEND #1

GROUP SYMBOLS AND NAMES

Graphic / Symbol	Group Names	Graphic / Symbol	Group Names
	Well-graded GRAVEL		Lean CLAY
	Well-graded GRAVEL with SAND		Lean CLAY with SAND Lean CLAY with GRAVEL SANDY lean CLAY
	Poorly graded GRAVEL		SANDY lean CLAY SANDY lean CLAY with GRAVEL GRAVELLY lean CLAY GRAVELLY lean CLAY with SAND
	Poorly graded GRAVEL with SAND		SILTY CLAY SILTY CLAY with SAND SILTY CLAY with GRAVEL SANDY SILTY CLAY SANDY SILTY CLAY with GRAVEL GRAVELLY SILTY CLAY GRAVELLY SILTY CLAY with SAND
	Well-graded GRAVEL with SILT		SILT SILT with SAND SILT with GRAVEL SANDY SILT SANDY SILT with GRAVEL GRAVELLY SILT GRAVELLY SILT with SAND
	Well-graded GRAVEL with SILT and SAND		ORGANIC lean CLAY ORGANIC lean CLAY with SAND ORGANIC lean CLAY with GRAVEL SANDY ORGANIC lean CLAY GRAVELLY ORGANIC lean CLAY GRAVELLY ORGANIC lean CLAY with SAND
	Well-graded GRAVEL with CLAY (or SILTY CLAY)		ORGANIC SILT ORGANIC SILT with SAND ORGANIC SILT with GRAVEL SANDY ORGANIC SILT SANDY ORGANIC SILT with GRAVEL GRAVELLY ORGANIC SILT GRAVELLY ORGANIC SILT with SAND
	Well-graded GRAVEL with CLAY and SAND (or SILTY CLAY and SAND)		ORGANIC fat CLAY ORGANIC fat CLAY with SAND ORGANIC fat CLAY with GRAVEL SANDY ORGANIC fat CLAY GRAVELLY ORGANIC fat CLAY GRAVELLY ORGANIC fat CLAY with SAND
	Poorly graded GRAVEL with SILT		ORGANIC elastic SILT ORGANIC elastic SILT with SAND ORGANIC elastic SILT with GRAVEL SANDY elastic SILT SANDY elastic SILT with GRAVEL GRAVELLY ORGANIC elastic SILT GRAVELLY ORGANIC elastic SILT with SAND
	Poorly graded GRAVEL with SILT and SAND		ORGANIC fat CLAY ORGANIC fat CLAY with SAND ORGANIC fat CLAY with GRAVEL SANDY ORGANIC fat CLAY GRAVELLY ORGANIC fat CLAY GRAVELLY ORGANIC fat CLAY with SAND
	Poorly graded GRAVEL with CLAY (or SILTY CLAY)		ORGANIC elastic SILT ORGANIC elastic SILT with SAND ORGANIC elastic SILT with GRAVEL SANDY elastic ELASTIC SILT SANDY ORGANIC elastic SILT with GRAVEL GRAVELLY ORGANIC elastic SILT GRAVELLY ORGANIC elastic SILT with SAND
	Poorly graded GRAVEL with CLAY and SAND (or SILTY CLAY and SAND)		ORGANIC SOIL ORGANIC SOIL with SAND ORGANIC SOIL with GRAVEL SANDY ORGANIC SOIL SANDY ORGANIC SOIL with GRAVEL GRAVELLY ORGANIC SOIL GRAVELLY ORGANIC SOIL with SAND
	SILTY GRAVEL		ORGANIC SOIL ORGANIC SOIL with SAND ORGANIC SOIL with GRAVEL SANDY ORGANIC SOIL SANDY ORGANIC SOIL with GRAVEL GRAVELLY ORGANIC SOIL GRAVELLY ORGANIC SOIL with SAND
	SILTY GRAVEL with SAND		COBBLES COBBLES and BOULDERS BOULDERS
	CLAYEY GRAVEL		
	CLAYEY GRAVEL with SAND		
	SILTY, CLAYEY GRAVEL		
	SILTY, CLAYEY GRAVEL with SAND		
	Well-graded SAND		
	Well-graded SAND with GRAVEL		
	Poorly graded SAND		
	Poorly graded SAND with GRAVEL		
	Well-graded SAND with SILT		
	Well-graded SAND with SILT and GRAVEL		
	Well-graded SAND with CLAY (or SILTY CLAY)		
	Well-graded SAND with CLAY and GRAVEL (or SILTY CLAY and GRAVEL)		
	Poorly graded SAND with SILT		
	Poorly graded SAND with SILT and GRAVEL		
	Poorly graded SAND with CLAY (or SILTY CLAY)		
	Poorly graded SAND with CLAY and GRAVEL (or SILTY CLAY and GRAVEL)		
	SILTY SAND		
	SILTY SAND with GRAVEL		
	CLAYEY SAND		
	CLAYEY SAND with GRAVEL		
	SILTY, CLAYEY SAND		
	SILTY, CLAYEY SAND with GRAVEL		
	PEAT		

FIELD AND LABORATORY TESTING

- C Consolidation (ASTM D 2435)
- CL Collapse Potential (ASTM D 5333)
- CP Compaction Curve (CTM 216)
- CR Corrosion, Sulfates, Chlorides (CTM 643, CTM 417, CTM 422)
- CU Consolidated Undrained Triaxial (ASTM D 4767)
- DS Direct Shear (ASTM D 3080)
- EI Expansion Index (ASTM D 4829)
- M Moisture Content (ASTM D 2216)
- OC Organic Content (ASTM D 2974)
- P Permeability (CTM 220)
- PA Particle Size Analysis (ASTM D 422)
- PI Liquid Limit, Plastic Limit, Plasticity Index (AASHTO T 99, AASHTO T 90)
- PL Point Load Index (ASTM D 5731)
- PM Pressure Meter
- R R-Value (CTM 301)
- SE Sand Equivalent (CTM 217)
- SG Specific Gravity (AASHTO T 100)
- SL Shrinkage Limit (ASTM D 427)
- SW Swell Potential (ASTM D 4546)
- UC Unconfined Compression - Soil (ASTM D 2166)
- UU Unconfined Compression - Rock (ASTM D 2938)
- UU Unconsolidated Undrained Triaxial (ASTM D 2850)
- UW Unit Weight (ASTM D 4787)
- 200 Passing No. 200 Sieve (ASTM D 1140)

SAMPLER GRAPHIC SYMBOLS

- Standard Penetration Test (SPT)
- Standard California Sampler
- Modified California Sampler (2.4" ID, 3" OD)
- Shelby Tube
- Piston Sampler
- NX Rock Core
- HQ Rock Core
- Bulk Sample
- Other (see remarks)

DRILLING METHOD SYMBOLS

- Auger Drilling
- Rotary Drilling
- Dynamic Cone or Hand Driven
- Diamond Core

WATER LEVEL SYMBOLS

- First Water Level Reading (during drilling)
- Static Water Level Reading (after drilling, date)

Definitions for Change in Material

Term	Definition	Symbol
Material Change	Change in material is observed in the sample or core and the location of change can be accurately located.	
Estimated Material Change	Change in material cannot be accurately located either because the change is gradational or because of limitations of the drilling and sampling methods.	
Soil / Rock Boundary	Material changes from soil characteristics to rock characteristics.	

REFERENCE: Caltrans Soil and Rock Logging, Classification, and Presentation Manual (2010).



Project No. SD605

SDSU Mission Valley
Football Stadium

BORING RECORD LEGEND #2

CONSISTENCY OF COHESIVE SOILS

Description	Shear Strength (tsf)	Pocket Penetrometer, PP Measurement (tsf)	Torvane, TV, Measurement (tsf)	Vane Shear, VS, Measurement (tsf)
Very Soft	Less than 0.12	Less than 0.25	Less than 0.12	Less than 0.12
Soft	0.12 - 0.25	0.25 - 0.5	0.12 - 0.25	0.12 - 0.25
Medium Stiff	0.25 - 0.5	0.5 - 1	0.25 - 0.5	0.25 - 0.5
Stiff	0.5 - 1	1 - 2	0.5 - 1	0.5 - 1
Very Stiff	1 - 2	2 - 4	1 - 2	1 - 2
Hard	Greater than 2	Greater than 4	Greater than 2	Greater than 2

APPARENT DENSITY OF COHESIONLESS SOILS

Description	SPT N ₆₀ (blows / 12 inches)
Very Loose	0 - 5
Loose	5 - 10
Medium Dense	10 - 30
Dense	30 - 50
Very Dense	Greater than 50

MOISTURE

Description	Criteria
Dry	No discernable moisture
Moist	Moisture present, but no free water
Wet	Visible free water

PERCENT OR PROPORTION OF SOILS

Description	Criteria
Trace	Particles are present but estimated to be less than 5%
Few	5 - 10%
Little	15 - 25%
Some	30 - 45%
Mostly	50 - 100%

PARTICLE SIZE

Description	Size (in)	
Boulder	Greater than 12	
Cobble	3 - 12	
Gravel	Coarse	3/4 - 3
	Fine	1/5 - 3/4
Sand	Coarse	1/16 - 1/5
	Medium	1/64 - 1/16
	Fine	1/300 - 1/64
Silt and Clay	Less than 1/300	

CEMENTATION

Description	Criteria
Weak	Crumbles or breaks with handling or little finger pressure.
Moderate	Crumbles or breaks with considerable finger pressure.
Strong	Will not crumble or break with finger pressure.

Plasticity

Description	Criteria
Nonplastic	A 1/8-in. thread cannot be rolled at any water content.
Low	The thread can barely be rolled and the lump cannot be formed when drier than the plastic limit.
Medium	The thread is easy to roll and not much time is required to reach the plastic limit. The thread cannot be rerolled after reaching the plastic limit. The lump crumbles when drier than the plastic limit.
High	It takes considerable time rolling and kneading to reach the plastic limit. The thread can be rerolled several times after reaching the plastic limit. The lump can be formed without crumbling when drier than the plastic limit.

REFERENCE: Caltrans Soil and Rock Logging, Classification, and Presentation Manual (2010), with the exception of consistency of cohesive soils vs. N₆₀.

CONSISTENCY OF COHESIVE SOILS

Description	SPT N ₆₀ (blows/12 inches)
Very Soft	0 - 2
Soft	2 - 4
Medium Stiff	4 - 8
Stiff	8 - 15
Very Stiff	15 - 30
Hard	Greater than 30

Ref: Peck, Hansen, and Thornburn, 1974, "Foundation Engineering," Second Edition.

Note: Only to be used (with caution) when pocket penetrometer or other data on undrained shear strength are unavailable. Not allowed by Caltrans Soil and Rock Logging and Classification Manual, 2010.



Project No. SD605

SDSU Mission Valley
Football Stadium

BORING RECORD LEGEND #3

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-1
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D120		BORING DIA. (in) 8	TOTAL DEPTH (ft) 60
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 83	DEPTH/ELEV. GROUNDWATER (ft) ▼ 34.0 / 49.0

NOTES
ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
80			B1				12.2	-	PA			UNDIFFERENTIATED SURFICIAL SOILS: CLAYEY SAND (SC); brown; moist; mostly fine sand; some fines; trace gravel; low to medium plasticity. (2% Gravel; 52% Sand; 46% Fines)
5			S1	7 18 50^	^	^	4.2	-	-200			Poorly-graded SAND with silt and gravel (SP-SM); light brown; moist; mostly fine to medium sand; few fines; little gravel and cobbles; nonplastic; trace mica. (10% fines) Gravel stuck in sampler shoe.
75												Slow and difficult drilling on GRAVELS and COBBLES (Estimated 20 to 30% COBBLES).
10												
70												
15												
65												
20			S2	7 13 15	28	42	18.3	-	-200			Sandy SILT (ML); dense; brown to dark brown; moist; mostly fines; some fine to medium sand; few gravel. (55% Fines)
60												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-1 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-1

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/8/2019

FINISH
3/8/2019

SHEET NO.
2 of 3

DRILLING COMPANY
Tri-County Drilling

DRILLING METHOD
Hollow Stem Auger

LOGGED BY
J. Sanders

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D120

BORING DIA. (in)
8

TOTAL DEPTH (ft)
60

GROUND ELEV (ft)
83

DEPTH/ELEV. GROUNDWATER (ft)
▼ 34.0 / 49.0

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
55			S3	4 6 9	15	22	19.4	-	PA			UNDIFFERENTIATED SURFICIAL SOILS (continued): Clayey SAND (SC); medium dense; dark brown; moist; mostly fine to medium sand; some fines; medium to high plasticity; some iron oxide staining. (52% Sand; 48% Fines)
30			S4	3 8 15	23	34	18.3	-	-200			Silty SAND (SM); medium dense; dark brown; moist; mostly fine sand; some fines; nonplastic; trace mica; no bedding. (43% Fines)
50			S5	5 7 8	15	22	25.6	-	-200			Wet; micaceous. (30% Fines)
35			S6	26 50/3"	^	^	16.7	-	PA			Well-graded SAND with silt and gravel (SW-SM); brown; wet; mostly fine to coarse sand; little coarse gravel; few fines; nonplastic; trace mica. (16% Gravel; 78% Sand; 6% Fines)
40												Slow and difficult drilling on GRAVELS and COBBLES (Estimated 20% COBBLES)
45												
40												
35												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-1 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-1
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D120		BORING DIA. (in) 8	TOTAL DEPTH (ft) 60
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 83	DEPTH/ELEV. GROUNDWATER (ft) ▼ 34.0 / 49.0

NOTES
ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
30												<p>UNDIFFERENTIATED SURFICIAL SOILS (continued): Slow and difficult drilling on GRAVELS and COBBLES (Estimated 20% COBBLES)</p>
55		⊗	S7	75/6"	REF	REF	17.5	-	-200	55		
25		⊗	S8	40 50/3"	50/3"	>100	17.3	-	-200	60		<p>FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; yellowish brown; moist; moderately weathered; very soft; unfractured (Silty SAND (SM); very dense; mostly fine to medium sand; little fines; low plasticity; mottled; weakly cemented). (18% Fines)</p> <p>Total Depth = 60 feet (Target depth reached).</p> <p>Groundwater measured during drilling at a depth of 34 feet.</p> <p>Boring backfilled on 3/8/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcounts.</p> <p>All soils encountered may include up to 10% COBBLES (subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 10 to 15 feet thick.</p> <p>*Geologic Description; (Disturbed Soil Description).</p>
60												
65												
20												
70												
10												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-1 c

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-2

SITE LOCATION
9449 Friars Road, San Diego, California

START
2/19/2019

FINISH
2/19/2019

SHEET NO.
1 of 3

DRILLING COMPANY

Pacific Drilling

DRILLING METHOD

Hollow Stem Auger

LOGGED BY

S. Narveson

CHECKED BY

C. Vonk

DRILLING EQUIPMENT

Diedrich D50

BORING DIA. (in)

8

61

TOTAL DEPTH (ft)

66

GROUND ELEV (ft)

23.8 / 42.2

SAMPLING METHOD

Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES

ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
	65		B1									PAVEMENT: Approximately 3 inches of ASPHALT CONCRETE.
			S2	2 2 6	8	11	16.2	-	PA EI CR			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); medium dense; brown (10YR 4/3); moist; mostly fine to coarse sand; some fines; few gravel; medium plasticity; micaceous. PID=0.6 ppm (10% Gravel; 56% Sand; 34% Fines)
5			B1									PID= 0.5 ppm
	60		R3	10 10 16	26	23						
			S4	3 5 5	10	13	19.8	-	-200 PI			Sandy lean CLAY (CL); stiff; dark grayish brown (2.5Y 4/2); moist; mostly fines; some fine to medium sand; trace fine gravel; medium plasticity. PP=1.25 tsf; PID=0.5 ppm (51% Fines)
10	55		S5	2 3 5	8	11	21.3	-				No gravel; micaceous. PP=1.25 tsf; PID=0.6 ppm
15	50		S6	2 3 4	7	9	19.7	-				Medium stiff; trace fine gravel; iron oxide staining. PP=0.75 tsf; PID=0.4 ppm
20	45											

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-2 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-2
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/19/2019	FINISH 2/19/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 61
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 66	DEPTH/ELEV. GROUNDWATER (ft) ▼ 23.8 / 42.2

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
40		✖	R7	3 4 7	11	10	22.8	-	-200 PI			UNDIFFERENTIATED SURFICIAL SOILS (continued): Sandy lean CLAY (CL); soft to medium stiff; dark grayish brown (2.5Y 4/2); wet; mostly fines; some fine to medium sand; trace fine gravel; medium plasticity; sample disturbed. PP=0.5 tsf; PID=0.3 ppm (58% Fines)
30	35	⊗	S8	4 5 7	12	16	19.0	-				Lean CLAY with sand (CL); medium stiff; dark grayish brown (10YR 4/2); mostly fines; little fine to medium sand; trace fine gravel; medium plasticity. PP=0.5 tsf; PID=0.8 ppm
35	30	⊗	S9	15 4 5	9	12	15.8	-	-200			Clayey SAND (SC); medium dense; dark grayish brown (10YR 4/2); wet; mostly fine to medium sand; some fines; trace fine gravel; medium plasticity. PID=0.3 ppm (35% Fines)
40	25	⊗	S10	5 3 3	6	8	24.7	-	-200			Loose; grayish brown (10YR 5/2); mostly medium to coarse sand; low to medium plasticity. PID=0.3 ppm (38% Fines)
45	20	✖	R11-1 R11-2	12 14 15	29	26	22.4	102	DS			FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (2.5YR 5/1); highly weathered; very soft; unfractured; (poorly graded SAND with silt (SP-SM); medium dense; wet; mostly fine to coarse sand; few to little fines; trace gravel; nonplastic; weakly cemented; iron oxide staining).

GDC_LOG_BORING_MM_X_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-2 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-2
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/19/2019	FINISH 2/19/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 61
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 66	DEPTH/ELEV. GROUNDWATER (ft) ▼ 23.8 / 42.2

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
15		X	S12-1 S12-2	25 35 50/5"	85/11"	>100	17.5	-	PI			FRIARS FORMATION (continued): *Poorly-indurated CLAYSTONE; fine grained; massive; gray (2.5Y 5/1); moderately weathered; very soft; unfractured (fat CLAY with sand (CH); hard; moist; mostly fines; few to little fine sand; high plasticity). PID=0.1 ppm
55	10	X	S13	20 28 50/3"	78/9"	>100	17.4	-		55		*POORLY INDURATED SANDSTONE; fine to coarse grained; massive; gray (2.5YR 5/1); moderately weathered; very soft; unfractured; (silty SAND (SM); very dense; wet; mostly fine sand; some fines; nonplastic, weakly to moderately cemented). PID=0 ppm
60	5	X	S14	30 50/6"	50/6"	>100	17.3	-	-200	60		(Little fines.) (18% Fines)
65	0									65		Total Depth = 61 feet (Target depth reached). Groundwater measured during drilling at a depth of 23.8 feet. Boring backfilled on 2/19/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. *Geologic Description; (Disturbed Soil Description).
70	-5									70		

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-2 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-3
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/26/2019	FINISH 3/1/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-36') / Casing Advance (36-45')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 46.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 74	DEPTH/ELEV. GROUNDWATER (ft) ▼ 28.2 / 45.8

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
			B1				11.1	-	PA			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); dark yellowish brown (10YR 4/4); moist; mostly fine to coarse sand; some fines; trace gravel; low plasticity. (0% Gravel; 68% Sand; 32% Fines).
5	70											Slow and difficult drilling on GRAVELS and COBBLES.
			S2	15 14 23	37	49	10.1	-				Silty SAND (SM); dense; yellowish brown (10YR 5/4); moist; mostly fine to coarse sand; little fines; trace gravel; nonplastic. PID=0.6 ppm
			R3-1 R3-2	9 16 23	39	34	18.3	107	-200 PI			Sandy lean CLAY (CL); brown (10YR 5/3); moist; mostly fines; some fine sand; trace gravel; medium plasticity; trace iron oxide staining. Hard. PP=4.0 tsf (59% Fines)
			S4	4 5 9	14	18	18	-				Very stiff; very dark grayish brown (10YR 3/2); micaceous. PP=3.0 tsf; PID=0.5 ppm
			R5-1 R5-2	9 8 36	44	39	16.6	113	-200			Clayey SAND (SC); dense; dark yellowish brown (10YR 4/4); moist; mostly fine sand; some fines; low plasticity. (44% Fines)
												Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 10-20% COBBLES). Equipment failure (sheared drive cap).

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-3 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-3

SITE LOCATION
9449 Friars Road, San Diego, California

START
2/26/2019

FINISH
3/1/2019

SHEET NO.
2 of 3

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
HSA (0-36') / Casing Advance (36-45')

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8

TOTAL DEPTH (ft)
46.5

GROUND ELEV (ft)
74

DEPTH/ELEV. GROUNDWATER (ft)
▼ 28.2 / 45.8

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
45												UNDIFFERENTIATED SURFICIAL SOILS (continued): Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 10 to 20% COBBLES).
30		X	S6	22^ 25^ 47^	^	^			PA	30		Silty SAND with gravel (SM); grayish brown (10YR 5/2); wet; mostly fine to coarse sand; some gravel; little fines; nonplastic. (34% Gravel; 52% Sand; 14% Fines). Gravel in sampler; PID=0
40		X	B10									Sandy lean CLAY (CL); dark yellowish brown (10YR 4/4); wet; mostly fines; some fine to coarse sand; trace gravel; medium plasticity. (59% Fines).
35		X	S7	100/6"	REF	REF			-200 PI	35		Clayey GRAVEL with sand (GC); wet; dark yellowish brown (10YR 4/4); mostly gravel; some fine to coarse sand and fines; low plasticity.
40		X	S8	100/6"	REF	REF				40		Equipment failure (sheared drive cap at 36 ft). Switch to casing advancement with tri-cone drill bit. (Estimated 30-40% COBBLES).
45		X	S9	23 37 34	71	>100			-200	45		FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; gray (2.5Y 6/1); wet; moderately weathered; very soft; unfractured (Clayey SAND (SC); very dense; mostly fine to medium sand; little fines; trace fine gravel; low plasticity; weakly cemented). (16% Fines).
25												Total Depth = 46.5 feet (Target Depth Reached). Hollow stem auger (0 to 36 ft); Casing advancement (36 to 46.5 ft).

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-3 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-3
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/26/2019	FINISH 3/1/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-36') / Casing Advance (36-45')	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 46.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 74	DEPTH/ELEV. GROUNDWATER (ft) ▼ 28.2 / 45.8

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
0												
5												
10												
15												
20												
28.2												Groundwater measured during drilling at a depth of 28.2 feet.
30												Boring backfilled on 3/1/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.
35												This Boring Record is part of a geotechnical report which must be considered in its entirety.
40												^ = Inaccurate blowcounts.
45												All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 5 to 10 feet thick.
46.5												*Geologic Description; (Disturbed Soil Description).

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-3 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-4
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2018	FINISH 3/8/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D120		BORING DIA. (in) 8	TOTAL DEPTH (ft) 40.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 68	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 47.0

NOTES
ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
65			B1				15.6	-	PA			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); brown; moist; mostly fine sand; little fines; trace fine gravel; low plasticity. (1% Gravel; 78% Sand; 21% Fines)
5			S1	4 6 7	13	19	19.5	-		5		Medium dense; trace mica.
60												Lean CLAY with sand (CL); brown; moist; mostly fines; little to some sand; medium to high plasticity.
10			S2	4 6 8	14	21	20.2	-	-200 PI	10		Stiff; brown; interbedded. PP=1.75 tsf (71% Fines)
55												
15			S3	2 7 7	14	21	18.8	-	PA	15		Sandy lean CLAY (CL); stiff to very stiff; brown; moist; mostly fines; some sand; medium plasticity; thin layers; trace mica; some mottling. (0% Gravel; 41% Sand; 59% Fines)
50												
20			S4	3 7 7	14	21	19.8	-	-200 PI	20		Very stiff; dark brown; low to medium plasticity; no bedding; organics present. PP=2.75 tsf (59% Fines)
45												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-2 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-4
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2018	FINISH 3/8/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D120		BORING DIA. (in) 8	TOTAL DEPTH (ft) 40.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 68	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 47.0

NOTES
ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION	
40		⊗	S5	18 [^] 50/2" ^	^	^	11.9	-				<p>UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND with gravel and cobbles (SP); brown; wet; mostly medium to coarse sand; little to some gravel and cobbles; trace mica; sampler refusal on cobbles.</p> <p>Slow and difficult drilling on GRAVEL and COBBLES. Water and polymer added to hole to mitigate caving soils. (Estimated 20% COBBLES)</p>	
35		⊗	S6	17 34 50	84	>100	16.6	-	PA				<p>FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; yellow brown; wet; moderately weathered; very soft; unfractured; *(Silty SAND (SM); very dense; mostly fine to medium sand; little fines; nonplastic; moderately cemented).</p> <p>(0% Gravel; 82% Sand; 18% Fines)</p>
40		⊗	S7	50/6"	REF	REF	17.8	-					<p>Total Depth = 40.5 feet (Target depth reached).</p> <p>Groundwater measured after drilling at a depth of 21 feet.</p> <p>Polymer/water mixture added down hollow stem for heaving sand.</p> <p>Boring backfilled on 3/8/19 with bentonite grout and capped with black dyed rapid set concrete.</p> <p>^ = Inaccurate blowcount.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated</p>

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-2 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-4
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2018	FINISH 3/8/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	LOGGED BY J. Sanders
DRILLING EQUIPMENT Diedrich D120		BORING DIA. (in) 8	TOTAL DEPTH (ft) 40.5
		GROUND ELEV (ft) 68	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 47.0

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)	NOTES ETR ~ 89%, $N_{60} = 1.48N_{SPT} = 0.99N_{MC}$
--	--

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
15										55		based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 5 to 10 feet thick. *Geologic Description; (Disturbed Soil Description).
55										60		
60										65		
65										70		
70												

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
 9245 Activity Road, Suite 103
 San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
 B-2 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-5
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-40') / Mud Rotary (40-61')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 61
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 63	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 42.0

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
60			B1				11.0	-	PA PI			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND with gravel (SC); yellowish brown (10YR 5/4); moist; mostly fine to coarse sand; some fines; little gravel; medium plasticity. (19% Gravel; 46% Sand; 35% Fines) Rig chatter at 3.5 ft on gravel and potential cobble layer. Loose; trace organics (plant roots).
5			S2	4 3 4	7	9						
55												
10			R3	5 7 9	16	14	12.2	95	-200			Silty SAND (SM); medium dense; brown (7.5 YR 5/2); moist; mostly fine sand; few to little fines; nonplastic; grading to poorly-graded SAND. (20% Fines)
50												Poorly-graded SAND (SP); medium dense; brown (7.5YR 5/2); moist; mostly fine sand; trace fines; nonplastic.
15			S4	1 1 2	3	4	34.5	-				Lean CLAY with sand (CL); soft; dark grayish brown (10YR 4/2); moist; mostly fines; little fine sand; medium to high plasticity. PP=0.25 tsf; PID=0.6 ppm
45												
20			R5-1 R5-2	2 3 4	7	6	41.6	79	-200 PI C			Medium stiff; dark gray (Gley 4/N); wet; medium plasticity. PP=0.5 tsf; TV=0.4 tsf PID=0.2 ppm (75% fines)
40												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-5 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-5
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-40') / Mud Rotary (40-61')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 61
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 63	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 42.0

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
35		X	S6	2 3 5	8	11	24.0	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND (SP); medium dense; gray (10YR 5/1); wet; mostly fine to medium sand; trace fines; nonplastic; micaceous. PID=0.8 ppm (1% Fines)
30		X	S7	1 2 8	10	13	21.9	-	-200			Poorly-graded SAND with silt (SP-SM); medium dense; gray (10YR 5/1); wet; mostly fine to medium sand; few to little fines; nonplastic; trace mica. PID=5.2 ppm (12% Fines)
30												Difficult drilling on GRAVEL and COBBLES from 32 to 34 ft. (Estimated 10-20% COBBLES)
35		X	S8	9 11 12	23	30	21.6	-	-200			Well-graded SAND with silt (SW-SM); dense; very dark gray (7.5YR 3/1); wet; mostly fine to medium sand; few to little fines; nonplastic; trace mica. (12% Fines) PID=0.3 ppm
40		X	S9	10 10 9	19	25	14.5	-	PA			Heaving sands. Switch to mud rotary (Tricone rotary drill bit) Medium dense; yellowish brown (10YR 5/4); few to little fine to medium gravel; few fines. (14% Gravel; 76% Sand; 10% Fines)
45		X	S10	8 8 9	17	22	21.0	-	-200			No gravel; micaceous; trace oxide staining. (9% Fines)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-5 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-5
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-40') / Mud Rotary (40-61')	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 61
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 63	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.0 / 42.0

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION	
13		⊗	S11	13	39	51	16.0	-				<p>UNDIFFERENTIATED SURFICIAL SOILS (continued): Well-graded SAND with silt (SW-SM); very dense; gray (75YR 5/1); wet; mostly fine to medium sand; few gravel; trace fines; nonplastic; trace mica.</p>	
18				18									<p>Slow and difficult drilling on GRAVEL and COBBLES from 53 to 59 ft. (Estimated 10 to 20% COBBLES)</p>
21				21									
55										55		<p>FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; gray (2.5YR 6/1); moderately weathered; very soft; unfractured (Silty SAND (SM); mostly fine to medium sand; some fines; low plasticity; weakly to moderately cemented). (48% Fines)</p>	
60		⊗	S12	24	50/6"	>100	20.2	-	-200	60			
65										65		<p>Total Depth = 61.0 feet (Target depth reached).</p> <p>Groundwater measured during drilling at a depth of 21 feet.</p> <p>Boring backfilled on 3/8/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcount.</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 2 to 10 feet thick.</p> <p>*Geologic Description; (Disturbed Soil Description).</p>	
70										70			
-10													

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-5 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-6
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/7/2019	FINISH 3/7/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 41.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 69	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.3 / 46.7

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
5	65		B1				19.5	-	PA CR EI	5		UNDIFFERENTIATED SURFICIAL SOILS: Lean CLAY with sand (CL); dark yellowish brown (10YR 4/6); moist; mostly fines; some fine sand; low plasticity. (0% Gravel; 28% Sand; 72% Fines) PID= 0.6 ppm Few gravel.
			R2	9 15 26	41	36						Sandy SILT (ML); dense; dark yellowish brown (10YR 4/5); moist; mostly fines; some fine sand; nonplastic. PID= 0.3 ppm
10	60		R3-1 R3-2	5 8 13	21	19	29.0	93	-200			Lean CLAY (CL); medium stiff to very stiff; dark yellowish brown (10YR 4/4); moist; mostly fines; few to little fine sand; low plasticity. PP=3.75 tsf; TV=0.33 tsf; PID=0 (87% Fines)
15	55		S5	4 9 11	20	26	6.7	-	PA			Silty SAND (SM); medium dense; grayish brown (10YR 5/2); moist; mostly fine to medium sand; few to little fine; trace fine gravel; nonplastic; trace mica. PID=0 (0% Gravel; 87% Sand; 13% Fines)
20	50		S6	3 4 6	10	13	20.3	-	-200 PI			Sandy lean CLAY (CL); stiff; very dark grayish brown (10YR 3/2); moist; mostly fines; little to some fine sand; trace gravel; medium plasticity; trace mica. PP=1.5 tsf; TV=0.70 tsf PID=0.3 ppm (66% Fines)
												Slow and difficult drilling on GRAVEL and COBBLES from 22 to 35 feet. (Estimated 10-20% COBBLES)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-6 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-6

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/7/2019

FINISH
3/7/2019

SHEET NO.
2 of 3

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
Hollow Stem Auger

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8

TOTAL DEPTH (ft)
41.5

GROUND ELEV (ft)
69

DEPTH/ELEV. GROUNDWATER (ft)
▼ 22.3 / 46.7

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
			S7	39^ 22^ 30^	^	^	12.3	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Silty GRAVEL with sand (GM); yellowish brown (10YR 5/4); wet; mostly fine to coarse gravel; some fine to coarse sand; little fines; nonplastic. (Estimated 10 to 20% COBBLES)
30			S8	50/5" ^	REF	REF				30		Sampler refusal on gravel and cobbles.
35			S9	19 25 50	75	99	7.5	-	-200	35		FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; grayish brown (10YR 5/2); wet; moderately weathered; very soft; unfractured; (Silty SAND (SM); very dense; mostly fine to medium sand; some fines; nonplastic; weakly cemented; Iron oxide staining.) (32% Fines) Gray (7.5YR 5/1); little fines. (26% Fines)
40			S10	19 25 50	75	99	18.5	-	-200	40		
45										45		Total Depth = 41.5 feet (Target depth reached). Groundwater measured during drilling at a depth of 22.3 feet. Boring backfilled on 3/7/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. ^ = Inaccurate blowcount. All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-6 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-6
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/7/2019	FINISH 3/7/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 41.5
		GROUND ELEV (ft) 69	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.3 / 46.7

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)	NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$
--	--

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
55	15									55		based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 10 to 13 feet thick. *Geologic Description; (Disturbed Soil Description).
60	10									60		
65	5									65		
70	0									70		
	-5											

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC. 9245 Activity Road, Suite 103 San Diego, California 92126	THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.	FIGURE B-6 c
--	--	----------------------------

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-7
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/11/2019	FINISH 3/11/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	DEPTH/ELEV. GROUNDWATER (ft) ▼ 16.8 / 40.2
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		TOTAL DEPTH (ft) 100.9	GROUND ELEV (ft) 57

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
0												PAVEMENT: Approximately 3 inches of ASPHALT CONCRETE.
0-5			B1				12.9	-	PA PI CR EI	5		UNDIFFERENTIATED SURFICIAL SOILS: Sandy lean CLAY (CL); dark brown (7.5YR 3/2); moist; mostly fines; some fine to coarse sand; trace gravel; low plasticity; grades finer with depth. (1% Gravel; 34% Sand; 65% Fines) Little gravel.
5			R2	2^ 11^ 23^	^	^	17.8	-		5		Stiff to very stiff; trace iron oxide staining; gravel in sampler. PP=1.0 tsf
5-10			S3	6 5 6	11	14	17.8	-		10		Sandy lean CLAY (CL); stiff; dark yellowish brown (10YR 4/6); moist; mostly fines; some fine sand; trace gravel; low plasticity; trace mica. PP=1.5 tsf
10-15			S4	15 6 6	12	16	19.6	-	-200	15		Silty SAND (SM); medium dense; yellowish brown (10YR 5/4); moist; mostly fine sand; little to some fines; nonplastic; trace mica. (28% Fines)
15-20			R5	50/6"	REF	REF				20		No recovery; wet.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-7 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-7

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/11/2019

FINISH
3/11/2019

SHEET NO.
2 of 5

DRILLING COMPANY

Pacific Drilling

DRILLING METHOD

Hollow Stem Auger

LOGGED BY

S. Narveson

CHECKED BY

C. Vonk

DRILLING EQUIPMENT

Diedrich D50

BORING DIA. (in)

8

TOTAL DEPTH (ft)

100.9

GROUND ELEV (ft)

57

DEPTH/ELEV. GROUNDWATER (ft)

▼ 16.8 / 40.2

SAMPLING METHOD

Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES

ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
30		X	S6	8 18 24	42	55	18.7	-	PA			FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; brownish gray (10Y 5/2); wet; moderately to highly weathered; very soft; unfractured (Silty SAND (SM)); very dense; mostly fine to medium sand; few to little fines; nonplastic; trace mica; weakly cemented). (86% Sand; 14% Fines)
30		⊠	R7	50/6"	REF	REF				30		No recovery; possible moderately to strongly cemented material.
35		X	S8	18 27 34	61	80	18.0	-	-200	35		Little fines; weakly to moderately cemented. (17% Fines)
40		X	S9	40 50/3"	50/3"	>100	11.5	-		40		Gray (10YR 5/1); (Clayey SAND with gravel (SC)); little gravel; low plasticity.
45		X	S10	25 37 50/4"	87/10"	>100	18.0	-		45		Thinly bedded.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-7 b

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-7

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/11/2019

FINISH
3/11/2019

SHEET NO.
3 of 5

DRILLING COMPANY

Pacific Drilling

DRILLING METHOD

Hollow Stem Auger

LOGGED BY

S. Narveson

CHECKED BY

C. Vonk

DRILLING EQUIPMENT

Diedrich D50

BORING DIA. (in)

8

TOTAL DEPTH (ft)

100.9

GROUND ELEV (ft)

57

DEPTH/ELEV. GROUNDWATER (ft)

▼ 16.8 / 40.2

SAMPLING METHOD

Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES

ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
5		◆	R11	43 50/5"	50/5"	>100			-200			FRIARS FORMATION, (continued): *Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (10YR 5/1); wet; moderately weathered; very soft; unfractured; (Clayey SAND (SC); very dense; wet; mostly fine sand; few to little fines; nonplastic; weakly to moderately cemented). (17% Fines)
55		⊗	S12	17 50/1"	50/1"	>100	20.7	-		55		Friable.
60		◆	R13	50/4"∧	REF∧	REF				60		Sampler refusal on strongly cemented concretion (3 inch diameter concretion stuck in sampler).
70		⊗	S14	35 50/3"	50/3"	>100				70		No recovery; possible moderately to strongly cemented material.

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-7 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-7
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/11/2019	FINISH 3/11/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 100.9
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 57	DEPTH/ELEV. GROUNDWATER (ft) ▼ 16.8 / 40.2

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
-20												<p>FRIARS FORMATION (continued): *Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (Gley 6/N); wet; moderately weathered; very soft; unfractured; (Clayey SAND (SC); very dense; mostly fine sand; little fines; low plasticity; weakly cemented).</p>
70-80		X	S15	23 30 40	70	92	22.6	-		80		
-25												<p>(Trace gravel; laminated.)</p>
85-90		X	S16	37 40 50	90	>100	16.2	-		90		
-30												
-35												
-40												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-7 d

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-7
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/11/2019	FINISH 3/11/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	DEPTH/ELEV. GROUNDWATER (ft) ▼ 16.8 / 40.2

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)	NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$
---	---

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
		⊗	S17	45 50/5"	50/5"	>100	26.5	-				<p>FRIARS FORMATION, (continued): *Poorly-indurated SANDSTONE; fine to coarse grained; laminated; gray (Gley 6/N); wet; moderately weathered; very soft; unfractured; (Clayey SAND (SC); very dense; mostly fine sand; little fines; low plasticity; weakly to moderately cemented).</p> <p>Total Depth = 100.9 feet (Target depth reached).</p> <p>Groundwater measured during drilling at a depth of 16.8 feet.</p> <p>Boring backfilled on 3/11/19 with bentonite grout and capped with cold patch asphalt.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcount.</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings.</p> <p>*Geologic Description; (Disturbed Soil Description).</p>

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC. 9245 Activity Road, Suite 103 San Diego, California 92126	THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.	FIGURE B-7 e
--	--	----------------------------

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-8

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/14/2019

FINISH
3/14/2019

SHEET NO.
2 of 4

DRILLING COMPANY

Pacific Drilling

DRILLING METHOD

Hollow Stem Auger

LOGGED BY

S. Narveson

CHECKED BY

C. Vonk

DRILLING EQUIPMENT

Diedrich D50

BORING DIA. (in)

8

TOTAL DEPTH (ft)

75.5

GROUND ELEV (ft)

69

DEPTH/ELEV. GROUNDWATER (ft)

▼ 22.4 / 46.6

SAMPLING METHOD

Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES

ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
			S8-1 S8-2	3 2 3	5	7	12.7 35.2	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Well graded SAND (SW); loose; grayish brown (10YR 5/2); wet; mostly fine to coarse sand; trace fines; nonplastic; trace mica. PID=0.6 ppm (4% Fines).
30			S9	5 [^] 8 [^] 12 [^]	^	^	13.4	-	PA	30		Sandy lean CLAY (CL); medium stiff; very dark gray (10YR 3/2); wet; mostly fines; some fine sand; medium plasticity; micaceous. PID=0.4 ppm; PP=0.75 tsf
35			S10	7 6 4	10	13	21.4	-	-200	35		Poorly-graded SAND (SP); gray (10YR 5/1); wet; mostly fine to medium sand; few gravel; trace fines; nonplastic; trace mica. Packed sampler. PID=6.7 ppm (9% Gravel; 87% Sand; 4% Fines).
40			R11-1 R11-2	6 7 20	27	24	34.4 20.8	86 106	-200 PI	40		Medium dense; trace mica. PID=24.1 ppm (5% Fines)
45			S12	8 [^] 8 [^] 11 [^]	^	^	24.1	-	-200	45		Fat CLAY (CH); medium stiff; dark gray (10YR 4/1); wet; mostly fines; little fine sand; high plasticity; grading to silty sand. PP=1 tsf; TV= 0.25 tsf (86% Fines)
												Silty SAND (SM); medium dense; dark gray (10YR 4/1); wet; mostly fine sand; some fines; nonplastic; grading to sand with silt.
												Poorly-graded SAND with silt (SP-SM); dark gray (10YR 5/1); wet; mostly fine to medium sand; few fines; nonplastic; micaceous. Packed sampler. PID=1.0 ppm (6% Fines)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-8 b

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-8

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/14/2019

FINISH
3/14/2019

SHEET NO.
3 of 4

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
Hollow Stem Auger

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8



TOTAL DEPTH (ft)
75.5

GROUND ELEV (ft)
69

DEPTH/ELEV. GROUNDWATER (ft)
▼ 22.4 / 46.6

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
			S13	8 15 22	37	49	15.0	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Clayey SAND (SC); dense; dark gray (10YR 5/1); wet; mostly fine to medium sand; little fines; trace gravel; low plasticity; micaceous. PID=0.3 ppm (19% Fines)
55			S14	8^ 12^ 14^	^	^	13.6	-	-200	55		Silty SAND (SM); dark gray (10YR 5/1); wet; mostly fine to medium sand; few fines and gravel; low plasticity; micaceous. Sampler packed. PID=0.8 ppm (12% Fines)
60			S15	19^ 18^ 12^	^	^	9.1	-		60		Moderately difficult drilling on GRAVELS and COBBLES from 56ft to 62ft. Poorly-graded GRAVEL (GP); dark grayish brown (2.5YR 4/2); wet; mostly gravel; few sand; trace fines; nonplastic; trace mica. (Estimated 10 to 20% COBBLES).
65										65		Slow and difficult drilling on GRAVELS and COBBLES from 62ft to 73ft. (Estimated 20 to 30% COBBLES)
70			S16	50/3"	REF	REF				70		No recovery; sampler refusal on gravel and cobbles.
-5												FRIARS FORMATION: *Poorly indurated SANDSTONE; (see next page)

GDC_LOG_BORING_MMX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-8 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-8
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/14/2019	FINISH 3/14/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 75.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 69	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.4 / 46.6

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
		⊗	S17	50/6"	REF	REF	20.5	-	-200			<p>FRIARS FORMATION (continued): *Poorly-indurated SANDSTONE; fine grained; massive; gray (7.5YR 5/1); moderately weathered; very soft; unfractured (Silty SAND (SM); very dense; wet; mostly fine sand; few fines; nonplastic; weakly to moderately cemented). (46% Fines)</p> <p>Total Depth = 75.5 feet (Target depth reached).</p> <p>Groundwater measured during drilling at a depth of 22.4 feet.</p> <p>Boring backfilled on 3/14/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcounts.</p> <p>*Geologic Description; (Disturbed Soil Description).</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 10 to 20 feet thick.</p>

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-8 d

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-9

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/4/2019

FINISH
3/5/2019

SHEET NO.
1 of 2

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
HSA (0-13') / Casing Advance (13-36.5')

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8/4

TOTAL DEPTH (ft)
36.5

GROUND ELEV (ft)
59

DEPTH/ELEV. GROUNDWATER (ft)
▼ NM / na

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
5	55		B1	3 8 [^] 13 [^]	^	^	7.7	-	PA	5		UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND with gravel (SC); brown (7.5YR 4/4); moist; mostly fine to coarse sand; some fines; little gravel; low plasticity. PID=1.3 ppm (17% Gravel; 48% Sand; 35% Fines) Increasing gravel content; difficult drilling from 3 to 4 feet on GRAVELS and COBBLES. Medium plasticity; gravel in sampler. PID=0.6 ppm
10	50		S2	15 [^] 29 [^] 29 [^]	^	^				10		Slow and difficult drilling from 7 to 19 feet on GRAVEL and COBBLES from 7 to 19 ft. Clayey GRAVEL (GC); brown (7.5 YR 4/2); moist; mostly gravel; little sand; little fines; nonplastic. (Estimated 20 to 30% COBBLES).
15	45		S3							15		Equipment failure- sheared drive cap at 11 ft. Switch to rotary casing advancement due to slow and difficult drilling.
20	40		S4	6 [^] 15 [^] 39 [^]	^	^				20		Poorly graded SAND with silt (SP-SM); wet; gray (7.5 YR 6/1); mostly fine sand; few fines; trace fine gravel; nonplastic. Packed sampler. PID=0.4 ppm
35												

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-9 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-9
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/4/2019	FINISH 3/5/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-13') / Casing Advance (13-36.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 36.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 59	DEPTH/ELEV. GROUNDWATER (ft) ▼ NM / na

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
			S5	18^ 25^ 32^	^	^	19.0	-	PA			UNDIFFERENTIATED SURFICIAL SOILS (continued): Silty SAND (SM); brown (7.5Y 5/4); wet; mostly fine to medium sand; little fines; nonplastic; trace mica; iron oxide staining throughout sample. (0% Gravel; 78% Sand; 22% Fines)
			S6-1 S6-2	19 20 34	54	71	24.3 18.6	- -	-200 PI	30		FRIARS FORMATION: *Poorly-indurated CLAYSTONE; fine grained; massive; dark gray (10YR 4/1); wet; moderately weathered; very soft; unfractured (FAT CLAY (CH); hard; mostly fines; trace sand; highly plastic). PP>4 tsf; PID=1.8 ppm (95% Fines)
			S7	20 26 35	61	80	20.6	-		35		*Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (10YR 5/1); wet; moderately weathered; very soft; unfractured (Poorly-graded SAND with silt (SP-SM); very dense; mostly fine sand; few fines; nonplastic; weakly cemented). PID=1.4 ppm
												Total Depth = 36.5 feet (Target depth reached). Groundwater was not measured during drilling because fluid was added to the hole prior to encountering groundwater. Boring backfilled on 3/6/19 with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. ^ = Inaccurate blowcount. All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 10 to 13 feet thick. *Geologic Description; (Disturbed Soil Description).

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-9 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-10
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/12/2019	FINISH 3/12/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 71.3
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 66	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.1 / 43.9

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
65												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
5			B1						PA PI CR EI	5		UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND with gravel (SC); yellowish brown (10YR 5/4); moist; mostly fine to coarse sand; some fines; few to little gravel; low to medium plasticity. (19% Gravel; 47% Sand; 34% Fines) Dark gray (7.5YR 4/1).
60			S2	23^ 22^ 14^	^	^	11.9	-				Light brownish gray (10YR 6/2); gravel in sampler. PP=1.25 tsf; PID=1.5 ppm
10			R3	10 12 11	23	20	7.8	107				Poorly-graded SAND with silt (SP-SM); medium dense; gray (10YR 5/1); moist; mostly fine sand; few fines; nonplastic. PID=1.4 ppm
15			S4	9 8 8	16	21						No recovery.
20			S5	3 3 4	7	9	19.5	-	PA			Poorly-graded SAND (SP); loose; grayish brown (10YR 5/2); moist; mostly fine to medium sand; trace fines; nonplastic; micaceous. PID=6.2 ppm (0% Gravel; 97% Sand; 3% Fines)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-10 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-10
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/12/2019	FINISH 3/12/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.1 / 43.9

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)	NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$
---	---

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
40		✖	R6	7 13 20	33	29	16.7	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND with silt (SP-SM); medium dense; grayish brown (10YR 5/2); wet; mostly fine sand; few fines; nonplastic. 9% Fines
30	35	⊗	S7	3 2 3	5	7	19.7	-	-200			Well-graded SAND (SW); loose; grayish brown (10YR 6/1); wet; mostly fine to coarse sand; trace fines and fine gravel; nonplastic; trace mica. PID=1.9 ppm (1% Fines)
35	30	⊗	S8	15 7 6	13	17	22.7	-	-200 PI			Sandy lean CLAY (CL); medium stiff to stiff; very dark gray (2.5Y 3/1); wet; mostly fines; little sand; few gravel; medium plasticity; trace mica. PP=1.0 tsf; TV=0.4 tsf; PID=1.1 ppm (62% Fines)
40	25	⊗	S9	3 3 3	6	8	24.1	-				Medium Stiff. PP=0.5 tsf; TV=0.3 tsf; PID=1.3 ppm
45	20	⊗	S10	7 6 7	13	17	24.9	-	-200 PI			Medium stiff to stiff; no gravel; trace mica. PP=1.0 tsf; TV=0.5 tsf; PID=1.2 ppm (62% Fines)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-10 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-10
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/12/2019	FINISH 3/12/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 71.3
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 66	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.1 / 43.9

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
15		X	S11	10 15 13	28	37	22.5	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND with silt (SP-SM); dense; dark gray (10YR 5/1); wet; mostly fine sand; few to little fines; nonplastic; micaceous. PID=0.6 ppm (11% Fines)
55	10	X	S12	10^ 22^ 49^	^	^	16.6	-		55		Slow and difficult drilling on GRAVEL and COBBLES from 54 feet and 60 feet. Silty GRAVEL with sand (GM); wet; dark gray (10YR 5/1); mostly gravel; little to some sand; little fines; nonplastic; trace mica. PID=1.4 ppm (Estimated 20% COBBLES)
65	0	X	S13	19^ 20^ 13^	^	^	16.1	-		65		Poorly-graded SAND with silt (SP-SM); dark gray (10YR 5/1); wet; mostly fine sand; few to little fines; nonplastic. Packed sampler.
70	-5	X	S14	25 37 50/3"	87/9"	>100	16.2	-	PA	70		FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine grained; massive; gray (7.5YR 5/1); wet; moderately weathered; very soft; unfractured; (Silty SAND (SM); very dense; wet; mostly fine sand; some fines; nonplastic; weakly cemented). (0% Gravel; 61% Sand; 39% Fines)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-10 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605		BORING S-10	
SITE LOCATION 9449 Friars Road, San Diego, California			START 3/12/2019	FINISH 3/12/2019	SHEET NO. 4 of 4
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger		LOGGED BY S. Narveson	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 71.3	GROUND ELEV (ft) 66	DEPTH/ELEV. GROUNDWATER (ft) ▼ 22.1 / 43.9

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)			NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$		
--	--	--	--	--	--

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
	-10											<p>Total Depth = 71.3 feet (Target depth reached).</p> <p>Groundwater measured during drilling at a depth of 22.1 feet.</p> <p>Boring backfilled on 3/12/19 with bentonite grout and capped with black dyed rapid set concrete.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcount.</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings.</p> <p>*Geologic Description; (Disturbed Soil Description).</p>
	-15									80		
	-20									85		
	-25									90		
	-30									95		

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC. 9245 Activity Road, Suite 103 San Diego, California 92126		THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.	FIGURE B-10 d
--	--	--	-----------------------------

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605		BORING S-11	
SITE LOCATION 9449 Friars Road, San Diego, California			START 3/6/2019		FINISH 3/7/2019
DRILLING COMPANY Pacific Drilling			DRILLING METHOD HSA (0-30') / Mud Rotary (30-36.5')		LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50			BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 36.5	GROUND ELEV (ft) 54
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)			NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$		

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
25			S6	50/3	REF	REF						UNDIFFERENTIATED SURFICIAL SOILS (continued): Silty SAND (SM); gray (2.5Y 5/1); wet; mostly fine sand; little fines; trace fine gravel; nonplastic; no recovery; heaving/flowing sands.
30			S7	20 22 36	58	76	18.9	--	-200			FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; gray (2.5Y N/5/1); wet; moderately weathered; very soft; unfractured; (Silty SAND (SM)); very dense; mostly fine to medium sand; little fines; nonplastic; weakly cemented). PID=0.1 ppm (22% Fines)
35			S8	23 27 37	64	84	20.7	--				Switch to mud rotary at 30 feet (tricone rotary drill bit). PID=0.2 ppm
40												Total Depth = 36.5 feet (Target depth reached). Groundwater measured during drilling at a depth of 10 feet. Boring backfilled on 3/7/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. . Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 1 to 2 feet thick. ^=Inaccurate blowcount. *Geologic Description (Disturbed Soil Description)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-11 b

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-12

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/8/2019

FINISH
3/8/2019

SHEET NO.
1 of 2

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
Hollow Stem Auger

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8

TOTAL DEPTH (ft)
41.5

GROUND ELEV (ft)
58

DEPTH/ELEV. GROUNDWATER (ft)
▼ 21.8 / 36.2

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE
5	55		B1				13.2	--	PA EI	5		UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); brown (10YR 4/3); mostly fine to coarse sand; some fines; few gravel; low to medium plasticity. PID=1.2 ppm (5% Gravel; 48% Sand; 47% Fines) Very dark gray (10YR3/1).
			S2	2 4 9	13	17	10.3	--				Medium dense; yellowish brown (10YR 5/4); little fines; low plasticity; trace mica. PID=3.2 ppm
10	50		R3	11^ 22^ 38^	^	^	9.1	--	-200	10		Clayey GRAVEL (GC); moist; dark grayish brown (10YR 4/2); mostly fine to coarse gravel; some fines; little sand; medium plasticity; gravel stuck in sampler. (47% Fines)
15	45		S4	13^ 14^ 14^	^	^	15.9	--	PA	15		Clayey SAND with gravel (SC); dark grayish brown (10YR 4/2); moist; mostly fine to coarse sand; little gravel; little to some fines; low plasticity; trace mica. PID= 1.4 ppm (18% Gravel; 54% Sand; 28% Fines)
20	40		S5	14^ 29^ 15^	^	^	10.0	--		20		Silty GRAVEL with sand (GM); dark grayish brown (10YR 4/2); wet; mostly fine to medium gravel; some sand; little fines; nonplastic; trace mica. PID=0.9 ppm
35												FRIARS FORMATION: *Poorly indurated SANDSTONE; (see next page)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-12 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-12
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/8/2019	FINISH 3/8/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8	TOTAL DEPTH (ft) 41.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 58	DEPTH/ELEV. GROUNDWATER (ft) ▼ 21.8 / 36.2

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
30		X	S6	45 25 39	64	84	14.7	--	-200			FRIARS FORMATION (continued): *Poorly-indurated SANDSTONE; fine grained; massive; gray (7.5YR 6/1); wet; moderately weathered; very soft; unfractured; (Silty SAND (SM)); very dense; wet; mostly fine sand; little fines; nonplastic; weakly cemented). PID=0.7 ppm. (23% Fines)
30		X	S7	22 31 50	81	>100	26.0	--				Gray (7.5YR 5/1); (Clayey SAND (SC)); little fines; low plasticity). PID=0.3 ppm
35		X	S8-1 S8-2	7 16 22	38	50	21.7 17.6	-- --	-200 PI -200			*Poorly-indurated CLAYSTONE; fine grained; massive; dark gray (2.5Y 4/1); wet; unfractured; moderately weathered; very soft; (Sandy fat CLAY (CH)); hard; mostly fines; few fine sand; high plasticity). PID=0.5 ppm; (61% Fines)
40		X	S9	16 24 50	74	97	20.3	--				*Poorly-indurated SANDSTONE; fine grained; massive; dark gray (2.5Y 4/1); wet; moderately weathered; very soft; unfractured; (Silty SAND (SM)); dense; mostly fine sand; some fines; nonplastic; weakly cemented). (35% Fines) Very dense; PID=0 ppm
Total Depth = 41.5 feet (Target depth reached). Groundwater measured during drilling at a depth of 21.8 feet. Boring backfilled on 3/8/19 with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. ^= Inaccurate blowcount. *Geologic Description; (Disturbed Soil Description).												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-12 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-13
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/25/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-101.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 101.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 75	DEPTH/ELEV. GROUNDWATER (ft) ▼ NM / NM

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 3 inches of ASPHALT CONCRETE.
			B1						PI			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); grayish brown (10YR 5/2); moist; mostly fine sand; little fines; little gravel; medium plasticity. PID=3.3 ppm (23% Gravel; 56% Sand; 21% Fines)
			S2	25 16 10	26	34	12.9	-	PA			
5	70		B1							5		Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20% COBBLES).
			S3	18 15^ 29^	^	^	12.2	-				Clayey GRAVEL (GC); dense; grayish brown (10YR 5/2); moist; mostly gravel and gravel-sized freshly broken rock fragments; little to some fines; little sand; medium plasticity.
10	65		S4	11 24^ 18^	^	^				10		
15	60		S5	7 20^ 24^	^	^				15		No recovery.
20	55		S6	7 50/3" ^	^	^				20		Sandy lean CLAY with gravel (CL); grayish brown; moist; mostly fines; some sand; little gravel. (Estimated 10 to 20% COBBLES).
												Slow and difficult drilling on GRAVEL and COBBLES from 20 to 30 ft. Clayey GRAVEL (GC); very dense; dark grayish brown; wet; mostly fine to coarse gravel; some sand; little fines; medium plasticity. Gravel stuck in sampler. PID=0.4 ppm (Estimated 20% COBBLES)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-13 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
S-13

SITE LOCATION
9449 Friars Road, San Diego, California

START
2/13/2019

FINISH
2/25/2019

SHEET NO.
2 of 5

DRILLING COMPANY

Pacific Drilling

DRILLING METHOD

HSA (0-45') / Mud Rotary (45-101.5')

LOGGED BY

S. Narveson

CHECKED BY

C. Vonk

DRILLING EQUIPMENT

Diedrich D50

BORING DIA. (in)

8/4

TOTAL DEPTH (ft)

101.5

GROUND ELEV (ft)

75

DEPTH/ELEV. GROUNDWATER (ft)

▼ NM / NM

SAMPLING METHOD

Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES

ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
			S7	50/1"	REF	REF						UNDIFFERENTIATED SURFICIAL SOILS (continued): No recovery. Clayey GRAVEL (GC) (continued).
30	45		S8	50/4"	REF	REF						No recovery.
35	40		S9	15 9 15	24	32	23.2	-	PA	35		Poorly-graded SAND with silt (SP-SM); wet; gray (7.5YR 5/1); mostly fine to medium sand; few fines; trace gravel; nonplastic; micaceous.
40	35		S10	6 7 10	17	22	18.0	-	-200	40		Dense; no gravel; trace mica. PID=0.8 ppm (0% Gravel; 94% Sand; 6% Fines)
45	30		R11	6 5 8	13	11	27.6	-		45		Medium dense; trace iron oxide staining. PID=0.8 ppm (7% Fines)
												Switch to mud rotary drilling (Tricone rotary drill bit). Dark gray (2.5Y 4/1); wet. PID=4.8 ppm

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-13 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-13
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/25/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-101.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 101.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 75	DEPTH/ELEV. GROUNDWATER (ft) ▼ NM / NM

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
		X	S12	9 10 10	20	26						UNDIFFERENTIATED SURFICIAL SOILS (continued): Clayey SAND (SC); medium dense; dark gray (7.5YR 4/1); wet; mostly fine to coarse sand; some fines; few gravel; low plasticity; trace mica. PID=0.2 ppm
55	20	X	S13	17^ 17^ 16^	^	^	15.0	-	-200	55		Well-graded SAND with silt and gravel (SW-SM); dense; dark gray (7.5YR 4/1); wet; mostly fine to coarse sand; few fines; little gravel; nonplastic. PID=0 (9% Fines)
60	15	X	S14	50/5"	REF	REF				60		Sampler refusal; gravel stuck in shoe of sampler. PID=1.8 ppm Slow and difficult drilling on GRAVELS and COBBLES from 60 to 75 ft. (Estimated 20% COBBLES).
65	10											
70	5	X	S15	50/5.5"	REF	REF				70		PID=0

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126




THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-13 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-13
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/25/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-101.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 101.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 75	DEPTH/ELEV. GROUNDWATER (ft) ▼ NM / NM

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
80	-5	⊗	S16	15 17 24	41	54	25.8	-	-200	80		<p>FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (2.5Y 6/1); moderately to highly weathered; very soft; unfractured; (Clayey SAND (SC); dense; wet; mostly fine sand; little fines; low plasticity; weakly to moderately cemented).</p> <p>Very dense. PID=0 (25% Fines)</p> <p>Slow and difficult drilling 82 to 84 ft; moderately to strongly cemented SANDSTONE and possible concretions.</p>
90	-15	⊗	S17	50/2"	REF	REF				90		<p>Slow and difficult drilling from 89 to 92 ft; moderately to strongly cemented SANDSTONE and made possible concretions. No recovery; possible concretions.</p>
95	-20									95		<p>Slow and difficult drilling from 97 to 98 ft; moderately to strongly cemented SANDSTONE and possible concretions.</p>

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-13 d

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING S-13
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/25/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-101.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 101.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 75	DEPTH/ELEV. GROUNDWATER (ft) ▼ NM / NM

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
		X	S18	34 32 38	70	92	19.6	-			•••••	<p>FRIARS FORMATION (continued): *Poorly-indurated SANDSTONE; fine to coarse grained; massive; gray (2.5Y 6/1); moderately to highly weathered; very soft; unfractured; (Silty SAND (SM); very dense; wet; mostly fine to coarse sand; little fines; low plasticity; weakly to moderately cemented.</p> <p>Total Depth = 101.5 feet (Target depth reached).</p> <p>Groundwater not measured.</p> <p>Boring backfilled on 2/25/19 and 2/26/19 with bentonite grout and capped with cold patch asphalt.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcount</p> <p>All soils encountered may include up to 10% COBBLES (granitic, subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 10 to 20 feet thick.</p> <p>*Geologic Description; (Disturbed Soil Description).</p>
105	-30									105		
110	-35									110		
115	-40									115		
120	-45									120		

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 01 - STADIUM.GPJ GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-13 e

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
B-14

SITE LOCATION
9449 Friars Road, San Diego, California

START
3/13/2019

FINISH
3/13/2019

SHEET NO.
1 of 2

DRILLING COMPANY
Tri-County Drilling

DRILLING METHOD
Hollow Stem Auger

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
CME 75

BORING DIA. (in)
8

TOTAL DEPTH (ft)
31.5

GROUND ELEV (ft)
51

DEPTH/ELEV. GROUNDWATER (ft)
▼ NM / NM

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 85%, $N_{60} = 1.42N_{SPT} = 0.95N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
0	50	ASPHALT CONCRETE	B1						EI	0		PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
0	49		S2	6	18	26	9.0	-	PA	0		UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); brown (7.5YR 4/3); moist; mostly fine to medium sand; some fines; few gravel; low plasticity.
0	49		B3	9						0		Medium dense; dark gray (10YR 5/1); little fines; trace gravel; micaceous.
5	45		S4	3	11	16	18.5	-	-200 PI	5		(1% Gravel; 86% Sand; 13% Fines) PID= 0.8 ppm. PID=0.5 ppm.
5	45		S4	5						5		Lean CLAY with sand (CL); stiff to very stiff; reddish brown (5YR 4/4); moist; mostly fines; little fine sand; trace fine gravel; medium plasticity; trace mica. PP= 2.5 tsf; TV= 0.9 tsf; PID=0.6 ppm (66% Fines)
5	45		S4	6						5		
10	40		S5	16^	^	^				10		Clayey GRAVEL with sand (GC); reddish brown (5YR 4/3) and gray (10YR 5/1) gravels; moist; mostly gravel with fresh broken rock fragments; little sand; little fines; low plasticity. Gravel in sampler. Polymer/water mix added to hollow stem. PID=1 ppm. Slow and difficult drilling on GRAVEL and COBBLES from 7ft to 25ft. (Estimated 10 to 30% COBBLES)
10	40		S5	25^						10		
10	40		S5	29^						10		
15	35		S6	16^	^	^	11.1	-	-200	15		Poorly graded GRAVEL with silt and sand (GP-GM); dense; brown (10YR 4/3); wet; mostly gravel; some sand; few fines; nonplastic. Gravel in sampler. PID=0.9 ppm. (10% Fines) (Estimated 20% COBBLES)
15	35		S6	17^						15		
15	35		S6	18^						15		
20	30		S7	45^	^	^				20		No recovery; sampler refusal on gravel and cobbles.
20	30		S7	50/2" ^						20		5-inch diameter cobble in spoils.

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-14 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-14
SITE LOCATION 9449 Friars Road, San Diego, California		START 3/13/2019	FINISH 3/13/2019
DRILLING COMPANY Tri-County Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT CME 75		BORING DIA. (in) 8	TOTAL DEPTH (ft) 31.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 51	DEPTH/ELEV. GROUNDWATER (ft) ∇ NM / NM

NOTES
ETR ~ 85%, $N_{60} = 1.42N_{SPT} = 0.95N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
25		X	S8	20 30 47	77	>100	18.0	-	PA			FRIARS FORMATION: *Poorly-indurated SANDSTONE; fine to medium grained; massive; pinkish gray (7.5YR 6/2); highly weathered; very soft; unfractured (Silty SAND (SM)); very dense; wet; mostly fine to medium sand; little fines; nonplastic; weakly cemented). (79% Sand; 21% Fines) PID = 0.9 ppm
30	20	X	S9	14 30 44	74	>100	17.6	-	-200	30		*Poorly-indurated CLAYSTONE; fine grained; massive; redish gray (5YR 5/2); moderately weathered; very soft; unfractured (sandy lean CLAY (CL)); hard; wet; mostly fines; some fine sand; medium to high plasticity).
35	15									35		*Poorly-indurated SANDSTONE; fine to medium grained; massive; pinkish gray (7.5YR 6/2); highly weathered; very soft; unfractured (Silty SAND (SM)); very dense; wet; mostly fine to medium sand; little fines; nonplastic; weakly cemented). PID=0.3 ppm (19% Fines)
40	10									40		Total Depth = 31.5 feet (Target depth reached). Groundwater was not measured during drilling because Polymer/water mix added down hollow stem to control heaving sands prior to encountering groundwater. Boring backfilled on 3/13/2019 shortly after drilling with neat portland cement and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. ^ = Inaccurate blowcounts. *Geologic Description; (Disturbed Soil Description).
45	5									45		All soils encountered may include up to 10% COBBLES (subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 15 to 20 feet thick.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-14 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-15
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/11/2019	FINISH 3/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Unimog Marl M5 & Deidrich D50		BORING DIA. (in) 6	TOTAL DEPTH (ft) 36.3
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 51	DEPTH/ELEV. GROUNDWATER (ft) ▼ 12.2 / 38.8

NOTES
ETR ~ 81% (Marl M5) / 79% (Deidrich D50)

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N ₆₀	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
50												PAVEMENT: Approximately 5 inches of ASPHALT CONCRETE.
5			B1				11.4	-	PA			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND with gravel (SC); light brown (10YR 5/3); moist; mostly fine to coarse sand; some fines; little to some gravel and gravel-sized freshly broken rock fragments; medium plasticity. (26% Gravel; 44% Sand; 30% Fines)
45			R2-1 R2-2	12 [^] 29 [^] 22 [^]	^	^	12.0 10.9	-	-200 PI			Brown (7.5YR 4/3); little to some fines; approximately ~2.5-inch diameter gravel clast in sample number R2-1. PP=2.25 tsf; PID=0.3 ppm (27% Fines)
10			S3	2 3 5	8	11	22.4	-				Silty SAND (SM); medium dense; dark gray (2.5Y 4/1); moist; mostly fine to coarse sand; some fines; nonplastic; trace mica. PID=0.7 ppm
15			S4	12 [^] 14 [^] 12 [^]	^	^	15.5	-				Clayey SAND with gravel (SC); dense; grayish brown (10YR 5/2); wet; mostly fine to coarse sand; some fines; little gravel; medium plasticity. Gravel in sampler. PID=1.0 ppm
20			S5	16 [^] 23 [^] 20 [^]	^	^	8.4	-				Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 10 to 20% COBBLES)
30												Silty SAND with gravel (SM); yellowish brown (10YR 5/4); wet; mostly fine to coarse sand; some fines; little gravel; nonplastic. Gravel in sampler. PID=10.1 ppm

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-15 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-15
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/11/2019	FINISH 3/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD Hollow Stem Auger	CHECKED BY C. Vonk
DRILLING EQUIPMENT Unimog Marl M5 & Deidrich D50		BORING DIA. (in) 6	TOTAL DEPTH (ft) 36.3
		GROUND ELEV (ft) 51	DEPTH/ELEV. GROUNDWATER (ft) ▼ 12.2 / 38.8

SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)	NOTES ETR ~ 81% (Marl M5) / 79% (Deidrich D50)
---	---

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N ₆₀	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
25		⊗	S6	10 50/3" ^	^	^						UNDIFFERENTIATED SURFICIAL SOILS (continued): Silty SAND with gravel (SM); dark grayish brown (10YR 6/2); wet; mostly fine to coarse sand; some fines; little gravel; nonplastic; gravel in bottom of sample.
30	20	⊗	S7	8 16 24	40	53	19.4	-		30		FRIARS FORMATION: *Poorly indurated SANDSTONE; fine grained; massive; light brownish gray (10YR 6/2); highly weathered; very soft; unfractured (Silty SAND (SM); very dense; wet; mostly fine sand; little fines; nonplastic; weakly cemented).
35	15	⊗	R8-1 R8-2	10 33 50/4"	83/10"	88	6.1	120	PA DS	35		Gray (10YR 6/1); strongly cemented concretion in sampler. (0% Gravel; 86% Sand; 14% Fines)
40	10									40		Total Depth = 36.3 feet (Target depth reached). Groundwater measured during drilling at a depth of 12.2 feet on 2/11/19. Marl M5 (0 to 26.3 feet); Deidrich D50 (26.3 to 36.3 feet). Boring backfilled on 2/11/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete. Boring redrilled on 3/15/19, backfilled with bentonite grout and capped with black-dyed rapid set concrete. This Boring Record is part of a geotechnical report which must be considered in its entirety. ^ = Inaccurate blowcounts. *Geologic Description; (Disturbed Soil Description). All soils encountered may include up to 10% COBBLES (subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 1 to 5 feet thick.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC. 9245 Activity Road, Suite 103 San Diego, California 92126	THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.	FIGURE B-15 b
--	--	----------------------

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-16
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-85')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 85
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 78	DEPTH/ELEV. GROUNDWATER (ft) ▼ 39.9 / 38.1

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 3 inches of ASPHALT CONCRETE over 6 inches of AGGREGATE BASE.
75			S1	5	11	14	13.6	-				UNDIFFERENTIATED SURFICIAL SOILS: Silty SAND (SM); medium dense; grayish brown (2.5Y 5/2); moist; mostly fine to medium sand; some fines; trace gravel and cobbles; nonplastic.
5			B2	5			13.1	-	PA			Clayey SAND (SC); medium dense; grayish brown (2.5Y 5/2); moist; mostly fine to medium sand; some fines; trace gravel and cobbles; low plasticity. PID=0.0 ppm (4% Gravel; 57% SAND; 39% fines)
			R3	8	26	23	16.4	109	CR			
70			S4	6 [^] 15 [^] 15 [^]	^	^	13.1	-	-200			Clayey SAND with gravel (SC); dense; dark grayish brown (10YR 4/2); moist; mostly fine sand; some fines; few to little gravel and gravel-sized freshly broken rock fragments; low plasticity. PID=0.0 ppm (38% Fines)
15			R5	50/2" ^	REF	REF						Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20% COBBLES) No recovery; sampler refusal.
60			S6	3 10 20	30	40	13.2	-	-200	PI		Clayey SAND (SC); dense; moist; mostly fine sand; some fines; few to little gravel; low to medium plasticity. PP=1.0 tsf (35% Fines)
20												
55												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-16 a

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-16
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-85')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 85
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 78	DEPTH/ELEV. GROUNDWATER (ft) ▼ 39.9 / 38.1

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
50		☒	R7	50/5" ^	REF	REF						UNDIFFERENTIATED SURFICIAL SOILS (continued): Hard drilling on GRAVEL and COBBLES. No recovery; sampler refusal. (Estimated 20-30% COBBLES)
30		☒	S8	16 7 9	16	21	16.4	-	PA	30		Silty SAND (SM); medium dense; dark gray (5YR 4/1); moist; mostly fine sand; some fines; few gravel; nonplastic; micaceous; 1/2 inch clay lense in bottom 1/3rd of sample. PID=0.3 ppm (6% Gravel; 62% Sand; 32% Fines)
35		☒	R9	18 30 26	56	49				35		No recovery; dense.
40		☒	S10-1 S10-2	6 3 2	5	7	18.5 45.6	- -	-200 PI	40		Loose; dark gray (2.5Y 4/1); wet; mostly medium to coarse sand; trace mica. PID=13.6 ppm
35												Sandy fat CLAY (CH); medium stiff; black (5Y 2.5/1); wet; mostly fines; some fine sand; high plasticity. PID=26.4 ppm (57% Fines)
45		☒	R11-1 R11-2	14 20 33	53	47	13.6	116	-200	45		Poorly-graded SAND with silt (SP-SM); dense; dark grayish brown (10YR 4/2); wet; mostly medium to coarse sand; few fines; trace gravel; nonplastic; well-graded in bottom rings of sample. PID=0.0 ppm (9% Fines) Switch to mud rotary drilling (Tricone rotary drill bit) at 45 feet.

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-16 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-16
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-85')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 85
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 78	DEPTH/ELEV. GROUNDWATER (ft) ▼ 39.9 / 38.1

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
25		⊗	S12	12 8 11	19	25	24.6	-	-200			UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND (SP); medium dense; gray (10YR 5/1); wet; mostly fine to medium sand; trace fines and fine gravel; nonplastic; trace mica. PID=41.2 ppm (4% Fines)
55		⊗	R13	27 ^ 50/4" ^	^	^	16.6	-		55		Heaving sands; packed sampler PID=0.0 ppm
60										60		Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20-30% COBBLES)
65		⊗	S14	25 ^ 30 ^ 50/5" ^	^	^	12.2	-		65		Silty GRAVEL with sand (GM); very dense; dark grayish brown (2.5Y 4/2); wet; mostly gravel, cobbles and gravel-sized freshly broken rock fragments; little fines; little to some fine to coarse sand; nonplastic. PID=1.4 ppm
70										70		Very slow and difficult drilling on GRAVEL and COBBLES (caving; drill bit getting stuck downhole). (Estimated 30% COBBLES)

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-16 c

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-16
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/13/2019	FINISH 2/15/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-45') / Mud Rotary (45-85')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 85
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV (ft) 78	DEPTH/ELEV. GROUNDWATER (ft) ▼ 39.9 / 38.1
NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$		CHECKED BY C. Vonk	
SHEET NO. 4 of 4			

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
0		⊗	S15	30^ 30^ 35^	^	^	21.8	-		0		UNDIFFERENTIATED SURFICIAL SOILS (continued): Silty GRAVEL with sand (GM); very dense; light olive brown (2.5Y 5/3); wet; mostly gravel and gravel-sized freshly broken rock fragments; little fines; little to some fine to coarse sand; nonplastic. (Estimated 20% COBBLES) PID=0.0 ppm
80		⊗	S16	21 29 50	79	>100	19.3	-		80		FRIARS FORMATION: *Poorly indurated SANDSTONE; fine to coarse grained; massive; gray (2.5Y 5/1); moderately to highly weathered; very soft; unfractured; (Poorly graded SAND with clay (SP-SC); very dense; wet; mostly fine sand; few to little fines; low plasticity; weakly cemented). PID=0.0 ppm
85										85		Unable to sample at 85 feet due to gravel caving into borehole.
90										90		Total Depth = 85 feet (Target depth reached). Groundwater measured during drilling at a depth of 39.9 feet. Boring backfilled on 2/15/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.
95										95		This Boring Record is part of a geotechnical report which must be considered in its entirety.
-15										-15		^ = Inaccurate blowcounts. *Geologic Description; (Disturbed Soil Description).
-20										-20		All soils encountered may include up to 10% COBBLES (subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 3 to 20 feet thick.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-16 d

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
B-17

SITE LOCATION
9449 Friars Road, San Diego, California

START
2/12/2019

FINISH
2/12/2019

SHEET NO.
1 of 4

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
HSA (0-25') / Mud Rotary (25-71.5')

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8/4

TOTAL DEPTH (ft)
71.5

GROUND ELEV. (ft)
64

DEPTH/ELEV. GROUNDWATER (ft)
▼ 23.6 / 40.4

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
												PAVEMENT: Approximately 4 inches of ASPHALT CONCRETE.
			B1				13.8	-	PA CR			UNDIFFERENTIATED SURFICIAL SOILS: Clayey SAND (SC); yellowish brown (10YR 5/4); moist; mostly fine to coarse sand; some fines; trace gravel; low to medium plasticity; few cobbles. PID=0.0 ppm (1% Gravel; 61% Sand; 38% Fines)
5			R2	20^ 25^ 17^	^	^	17.5	106	-200 PI	5		Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 10% COBBLES)
			S3	28^ 24^ 22^	^	^				10		Clayey SAND with gravel (SC); dense; dark yellowish brown (10YR 4/2); moist; mostly fine to coarse sand, gravel, and gravel-sized freshly broken rock fragments; some fines; medium plasticity; sample disturbed in upper 12 inches. PP=1.75 tsf; PID=34.0 ppm (43% Fines)
			R4-1 R4-2	7 7 22^	^	^	18.8	105	-200	15		Clayey GRAVEL (GC); very dense; yellowish brown (10 YR 5/4); moist; mostly gravel; some fines; little sand; low plasticity; low recovery. Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20% COBBLES)
			S5	14 9 8	17	22	13.5	-	-200 PI	20		Sandy lean CLAY to clayey SAND (CL to SC); very stiff/"medium dense"; dark yellowish brown (10YR 4/2); moist; mostly fines and fine to coarse sand; few gravel; low to medium plasticity; 2 inch diameter gravel in sampler shoe. PP=2.5 tsf; PID=1.4 ppm (60% Fines)
												PID=11.1 ppm (38% Fines)
												Poorly-graded SAND with silt (SP-SM); dark grayish brown (2.5Y 4/2); wet; mostly medium sand; little fines; few gravel; nonplastic.

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-17 a

BORING RECORD

PROJECT NAME
SDSU Mission Valley

PROJECT NUMBER
SD605

BORING
B-17

SITE LOCATION
9449 Friars Road, San Diego, California

START
2/12/2019

FINISH
2/12/2019

SHEET NO.
2 of 4

DRILLING COMPANY
Pacific Drilling

DRILLING METHOD
HSA (0-25') / Mud Rotary (25-71.5')

LOGGED BY
S. Narveson

CHECKED BY
C. Vonk

DRILLING EQUIPMENT
Diedrich D50

BORING DIA. (in)
8/4

TOTAL DEPTH (ft)
71.5

GROUND ELEV (ft)
64

DEPTH/ELEV. GROUNDWATER (ft)
▼ 23.6 / 40.4

SAMPLING METHOD
Hammer: 140 lbs., Drop: 30 in. (Automatic)

NOTES
ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
		▲	R6	29 50/5"	^	^						UNDIFFERENTIATED SURFICIAL SOILS (continued): Poorly-graded SAND with silt (SP-SM); very dense; dark grayish brown (2.5Y 4/2); wet; mostly medium sand; few fines; few gravel; nonplastic; trace mica; few cobbles. PID=11.7 ppm Switch to mud rotary drilling (Tricone rotary drill bit) at 25 feet.
35												
30		⊗	S7	6 10 14	24	32	26.3	-	-200	30		Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20% COBBLES) Silty SAND (SM); dense; dark gray (2.5Y 4/1); wet; mostly medium to coarse sand; little fines; nonplastic; micaceous. PID=0 ppm (17% Fines)
30												
35		▲	R8-1 R8-2	4 4 6	10	9	28.7	95	-200	35		Very dark gray (2.5Y 3/1); mostly fine sand; some fines; trace mica. PID=0.4 ppm (36% Fines)
25												
40		⊗	S9	3 2 5	7	9	20.8	-	-200	40		Dark grayish brown (10YR 4/2); micaceous. (34% Fines)
20												
45										45		Slow and difficult drilling on GRAVEL and COBBLES. (Estimated 20 to 30% COBBLES) Interbedded COBBLES, GRAVEL, and SAND.
15												

GDC_LOG_BORING_MMXX_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-17 b

BORING RECORD

PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605	BORING B-17
SITE LOCATION 9449 Friars Road, San Diego, California		START 2/12/2019	FINISH 2/12/2019
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-25') / Mud Rotary (25-71.5')	LOGGED BY S. Narveson
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 71.5
SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)		GROUND ELEV. (ft) 64	DEPTH/ELEV. GROUNDWATER (ft) ▼ 23.6 / 40.4
NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$		CHECKED BY C. Vonk	

DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
10		⊗	S10	30 50/1"	50/1"	>100	15.5	-	PA			FRIARS FORMATION: *Poorly indurated SANDSTONE; fine to coarse grained; massive; gray (7.5YR 6/1); moderately weathered; very soft; unfractured; (Silty SAND (SM); very dense; wet; mostly fine sand; little fines; nonplastic; weakly to moderately cemented). PID=0 ppm (78% Sand; 22% Fines)
55		⊗	S11	23 26 38	64	84	20.0	-		55		(Trace gravel; iron oxide staining). PID=0 ppm
60		⊗	R12-1 R12-2	40 50/5"	50/5"	>100	18.0 19.7	109 105	-200 DS	60		Poorly-indurated CLAYSTONE.
65										65		*Poorly indurated SANDSTONE; fine to coarse grained; massive; blueish gray (Gley 10B 5/1); moderately weathered; very soft; unfractured; (Poorly-graded SAND with silt (SP-SM); very dense; wet; mostly medium sand; few to little fines; nonplastic; weakly cemented). PID=0 ppm (11% Fines)
70		⊗	S13	25 35 43	78	>100	22.0	-		70		Thinly bedded. PID=0 ppm
-10												Total Depth = 71.5 feet (Target depth reached). Groundwater measured during drilling at a depth of 23.6'.

GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC.
9245 Activity Road, Suite 103
San Diego, California 92126

THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.

FIGURE
B-17 c

BORING RECORD


PROJECT NAME SDSU Mission Valley		PROJECT NUMBER SD605		BORING B-17	
SITE LOCATION 9449 Friars Road, San Diego, California			START 2/12/2019	FINISH 2/12/2019	SHEET NO. 4 of 4
DRILLING COMPANY Pacific Drilling		DRILLING METHOD HSA (0-25') / Mud Rotary (25-71.5')		LOGGED BY S. Narveson	CHECKED BY C. Vonk
DRILLING EQUIPMENT Diedrich D50		BORING DIA. (in) 8/4	TOTAL DEPTH (ft) 71.5	GROUND ELEV (ft) 64	DEPTH/ELEV. GROUNDWATER (ft) ▼ 23.6 / 40.4


SAMPLING METHOD Hammer: 140 lbs., Drop: 30 in. (Automatic)			NOTES ETR ~ 79%, $N_{60} = 1.32N_{SPT} = 0.88N_{MC}$		
--	--	--	--	--	--


DEPTH (feet)	ELEVATION (feet)	SAMPLE TYPE	SAMPLE NO.	PENETRATION RESISTANCE (BLOWS / 6 IN)	BLOW/FT "N"	N_{60}	MOISTURE (%)	DRY DENSITY (pcf)	OTHER TESTS	DEPTH (feet)	GRAPHIC LOG	DESCRIPTION AND CLASSIFICATION
80	-15									80		<p>Boring backfilled on 2/12/19 shortly after drilling with bentonite grout and capped with black-dyed rapid set concrete.</p> <p>This Boring Record is part of a geotechnical report which must be considered in its entirety.</p> <p>^ = Inaccurate blowcounts.</p> <p>*Geologic Description; (Disturbed Soil Description).</p> <p>All soils encountered may include up to 10% COBBLES (subrounded, 3- to 12-inch diameter), estimated based on drill rig chatter, excessive auger inclination, and visual evaluation of drill cuttings. Percent COBBLES greater than 10% are noted in the boring record description and classification, where encountered. Cobble-rich layers encountered in this exploration were approximately 1 to 8 feet thick.</p>
85	-20									85		
90	-25									90		
95	-30									95		
	-35											


GDC_LOG_BORING_MMV_SOIL_SD_SD605_LOGS - PHASE 02 - SITE.GPJ_GDCLOG.GDT 5/9/19

GROUP DELTA CONSULTANTS, INC. 9245 Activity Road, Suite 103 San Diego, California 92126		THIS SUMMARY APPLIES ONLY AT THE LOCATION OF THIS BORING AND AT THE TIME OF DRILLING. SUBSURFACE CONDITIONS MAY DIFFER AT OTHER LOCATIONS AND MAY CHANGE AT THIS LOCATION WITH THE PASSAGE OF TIME. THE DATA PRESENTED IS A SIMPLIFICATION OF THE ACTUAL CONDITIONS ENCOUNTERED.	FIGURE B-17 d
--	--	--	-----------------------------









SDSU Mission Valley
San Diego, CA

CPT Shear Wave Measurements

Location	Tip Depth (ft)	Geophone Depth (ft)	Travel Distance (ft)	S-Wave Arrival (msec)	S-Wave Velocity from Surface (ft/sec)	Interval S-Wave Velocity (ft/sec)
SCPT-5	4.99	3.99	6.40	6.40	999.51	
	10.01	9.01	10.30	11.22	918.39	810.68
	14.99	13.99	14.86	17.86	831.84	685.58
	20.05	19.05	19.70	27.92	705.42	480.97
	25.00	24.00	24.52	37.48	654.09	504.19
	30.02	29.02	29.45	44.32	664.43	721.09
	35.01	34.01	34.38	51.80	663.62	658.82
	40.03	39.03	39.35	58.66	670.80	724.98
	45.01	44.01	44.29	64.64	685.23	826.78
	50.07	49.07	49.32	72.24	682.78	661.97
	54.99	53.99	54.22	76.64	707.48	1112.94
	57.35	56.35	56.57	77.92	726.02	1836.22
SCPT-7	5.05	4.05	6.43	5.10	1261.66	
	9.97	8.97	10.27	10.16	1010.77	757.89
	14.99	13.99	14.86	14.12	1052.17	1158.39
	17.52	16.52	17.26	16.36	1055.02	1072.96
SCPT-13	4.99	3.99	6.40	6.10	1048.67	
	10.10	9.10	10.38	11.36	914.01	757.85
	14.99	13.99	14.86	15.08	985.19	1202.55
	20.08	19.08	19.72	19.04	1035.94	1229.19
	25.00	24.00	24.52	23.24	1054.88	1140.72
	30.02	29.02	29.45	27.84	1057.74	1072.24
	35.01	34.01	34.38	34.04	1009.86	794.84
	40.06	39.06	39.38	40.44	973.76	781.74
	44.98	43.98	44.26	45.16	980.14	1034.87
	50.00	49.00	49.25	50.84	968.81	878.72
	55.02	54.02	54.25	57.48	943.82	752.48
	60.07	59.07	59.28	63.04	940.37	904.74
66.83	65.83	66.02	71.40	924.64	806.03	

S-Wave Velocity from Surface = Travel Distance/S-Wave Arrival
Interval S-Wave Velocity = (Travel Dist2-Travel Dist1)/(Time2-Time1)

D

APPENDIX C
LABORATORY TESTING

R

A

F

T

APPENDIX C

LABORATORY TESTING

Laboratory testing was conducted in a manner consistent with the level of care and skill ordinarily exercised by members of the profession currently practicing under similar conditions and in the same locality. No warranty, express or implied, is made as to the correctness or serviceability of the test results, or the conclusions derived from these tests. Where a specific laboratory test method has been referenced, such as ASTM or Caltrans, the reference only applies to the specified laboratory test method, which has been used only as a guidance document for the general performance of the test and not as a "Test Standard". A brief description of the tests follows.

Classification: Soils were visually classified according to the Unified Soil Classification System as established by the American Society of Civil Engineers per ASTM D2487. The soil classifications are shown on the boring logs in Appendix C.

Particle Size Analysis: Particle size analyses were performed in general accordance with ASTM D422, and were used to supplement visual classifications. The test results are summarized on the Boring Records in Appendix B and are presented in detail in Figures C-1.1 through C-1.37.

Atterberg Limits: ASTM D4318 was used to determine the liquid and plastic limits, and plasticity index of selected soil samples. The test results are presented with the associated gradation analyses in Figures C-1.1 through C-1.37 and are also summarized in Figure C-1.38 and C-1.39.

Expansion Index: The expansion potential of selected soil samples was estimated in general accordance with ASTM D4829. The test results are summarized in Figure C-2, along with a summary of previous expansion index tests we conducted at the site. Figure C-2 also presents common criteria for evaluating the expansion potential based on the expansion index.


pH and Resistivity: To assess the potential for reactivity with buried metals, selected soil samples were tested for pH and minimum resistivity using Caltrans test method 643. The corrosivity test results are summarized in Figure C-3, along with previous corrosion tests we conducted on site.

Sulfate Content: To assess the potential for reactivity with concrete, selected soil samples were tested for water soluble sulfate. The sulfate was extracted from the soil under vacuum using a 10:1 (water to dry soil) dilution ratio. The extracted solution was tested for water soluble sulfate in general accordance with ASTM D516. The test results are also presented in Figure C-3, along with common criteria for evaluating soluble sulfate content.

Chloride Content: Soil samples were also tested for water soluble chloride. The chloride was extracted from the soil under vacuum using a 10:1 (water to dry soil) dilution ratio. The extracted solution was then tested for water soluble chloride using a calibrated ion specific electronic probe in general accordance with ASTM D512. The test results are also shown in Figure C-3.

Direct Shear: The shear strength of selected partially intact samples of the soils from the site were assessed using direct shear testing performed in general accordance with ASTM D3080. The test results are shown in Figures C-4.1 through C-4.4.

Consolidation: The one-dimensional consolidation properties of a selected sample was evaluated in general accordance with ASTM D2435. The sample was inundated with water under a nominal seating load, allowed to swell, and then subjected to controlled stress increments while restrained laterally and drained axially. The test results are presented in Figure C-5.




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-1
SAMPLE DEPTH:	2' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-1
SAMPLE DEPTH:	25' - 26.5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-1
SAMPLE DEPTH:	40' - 40.8'

UNIFIED SOIL CLASSIFICATION:	SW-SM
DESCRIPTION:	WELL GRADED SAND WITH SILT AND GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-2
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-3
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-3
SAMPLE DEPTH:	30' - 31.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-4
SAMPLE DEPTH:	0.5' - 4'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE
SAMPLE NUMBER: S-4
SAMPLE DEPTH: 15' - 16.5'

UNIFIED SOIL CLASSIFICATION:	CL
DESCRIPTION:	SANDY LEAN CLAY

ATTERBERG LIMITS
LIQUID LIMIT: --
PLASTIC LIMIT: --
PLASTICITY INDEX: --




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-4
SAMPLE DEPTH:	35' - 36.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-5
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	38
PLASTIC LIMIT:	15
PLASTICITY INDEX:	23




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-5
SAMPLE DEPTH:	40' - 41.5'

UNIFIED SOIL CLASSIFICATION:	SW
DESCRIPTION:	WELL GRADED SAND WITH SILT

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-6
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	CL
DESCRIPTION:	LEAN CLAY WITH SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-6
SAMPLE DEPTH:	15' - 16.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-7
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	CL
DESCRIPTION:	SANDY LEAN CLAY

ATTERBERG LIMITS	
LIQUID LIMIT:	39
PLASTIC LIMIT:	14
PLASTICITY INDEX:	25




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-7
SAMPLE DEPTH:	25' - 26.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-8
SAMPLE DEPTH:	0.5' - 2.5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-8
SAMPLE DEPTH:	20' - 21.5'

UNIFIED SOIL CLASSIFICATION:	SP
DESCRIPTION:	POORLY GRADED SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-8
SAMPLE DEPTH:	30' - 31.5'

UNIFIED SOIL CLASSIFICATION:	SP
DESCRIPTION:	POORLY GRADED SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-9
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-9
SAMPLE DEPTH:	25' - 26.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-10
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	39
PLASTIC LIMIT:	15
PLASTICITY INDEX:	24




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-10
SAMPLE DEPTH:	20' - 21.5'

UNIFIED SOIL CLASSIFICATION:	SP
DESCRIPTION:	POORLY GRADED SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-10
SAMPLE DEPTH:	70' - 71.3'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-11
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	CL
DESCRIPTION:	SANDY LEAN CLAY

ATTERBERG LIMITS	
LIQUID LIMIT:	38
PLASTIC LIMIT:	13
PLASTICITY INDEX:	25




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-11
SAMPLE DEPTH:	15' - 16.5'

UNIFIED SOIL CLASSIFICATION:	SP-SM
DESCRIPTION:	POORLY GRADED SAND WITH SILT AND GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-12
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-12
SAMPLE DEPTH:	15' - 16.5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-13
SAMPLE DEPTH:	2.5' - 4'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	0
PLASTIC LIMIT:	0
PLASTICITY INDEX:	0




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	S-13
SAMPLE DEPTH:	35' - 36.5'

UNIFIED SOIL CLASSIFICATION:	SP-SM
DESCRIPTION:	POORLY GRADED SAND WITH SILT

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-14
SAMPLE DEPTH:	2.5' - 4'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-14
SAMPLE DEPTH:	25' - 26.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-15
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND WITH GRAVEL

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-15
SAMPLE DEPTH:	35.5' - 36'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-16
SAMPLE DEPTH:	2.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-16
SAMPLE DEPTH:	30' - 31.5'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--




COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-17
SAMPLE DEPTH:	0.5' - 5'

UNIFIED SOIL CLASSIFICATION:	SC
DESCRIPTION:	CLAYEY SAND

ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--



COARSE	FINE	COARSE	MEDIUM	FINE	SILT AND CLAY
GRAVEL		SAND			

SAMPLE	
BORING NUMBER:	B-17
SAMPLE DEPTH:	50' - 51'

UNIFIED SOIL CLASSIFICATION:	SM
DESCRIPTION:	SILTY SAND


ATTERBERG LIMITS	
LIQUID LIMIT:	--
PLASTIC LIMIT:	--
PLASTICITY INDEX:	--

ATTERBERG LIMITS RESULTS
(ASTM D4318)

SAMPLE	DESCRIPTION	LIQUID LIMIT	PLASTIC LIMIT	PLASTICITY INDEX
S-2 @ 10' – 11.5'	Sandy Lean CLAY (CL)	40	18	22
S-2 @ 26' – 26.5'	Sandy Lean CLAY (CL)	39	17	22
S-2 @ 50' – 51'	Fat CLAY with sand (CH)	51	24	27
S-3 @ 10.5' – 11'	Sandy Lean CLAY (CL)	42	18	24
S-3 @ 34' – 36'	Sandy Lean CLAY (CL)	42	14	28
S-4 @ 10' – 11.5'	Lean CLAY with sand (CL)	48	19	29
S-4 @ 20' – 21.5'	Lean CLAY with sand (CL)	42	16	26
S-5 @ 0.5' – 5'	Clayey SAND with gravel (SC)	38	15	23
S-5 @ 20.5' – 21'	Lean CLAY with sand (CL)	46	20	26
S-6 @ 20' – 21.5'	Sandy Lean CLAY (CL)	42	16	26
S-7 @ 0.5' – 5'	Sandy Lean CLAY (CL)	39	14	25
S-8 @ 40.5' – 41'	Fat CLAY (CH)	59	21	38
S-9 @ 30' – 31'	Fat CLAY (CH)	66	22	44
S-10 @ 0.5' – 5'	Clayey SAND with gravel (SC)	39	15	24
S-10 @ 35' – 36.5'	Sandy Lean CLAY (CL)	45	16	29
S-10 @ 45' – 46.5'	Sandy Lean CLAY (CL)	46	17	29
S-11 @ 0.5' – 5'	Sandy Lean CLAY (CL)	38	13	25
S-11 @ 10' – 11.5'	Sandy Lean CLAY (CL)	38	15	23
S-12 @ 35' – 36'	Sandy fat CLAY (CH)	53	21	32
S-13 @ 0.5' – 5'	Clayey SAND with gravel (SC)	40	17	23
B-14 @ 5' – 6.5'	Sandy Lean CLAY (CL)	40	17	23
B-15 @ 6' – 6.5'	Clayey SAND with gravel (SC)	36	19	17
B-16 @ 20' – 21.5'	Clayey SAND (SC)	34	17	17
B-16 @ 41' – 41.5'	Sandy Fat CLAY (CH)	55	28	27
B-17 @ 20' – 21.5'	Clayey SAND (SC)	35	16	19

ATTERBERG LIMITS RESULTS (CONTINUED)

(ASTM D4318)



EXPANSION TEST RESULTS
(ASTM D4829)

SAMPLE	DESCRIPTION	EXPANSION INDEX
S-2 @ 0.5' – 5'	Clayey SAND (SC)	26
S-6 @ 0.5' – 5'	Lean CLAY with sand (CL)	75
S-7 @ 0.5' – 5'	Sandy Lean CLAY (CL)	50
S-10 @ 0.5' – 5'	Clayey SAND with gravel (SC)	20
S-11 @ 0.5' – 5'	Sandy Lean CLAY (CL)	63
S-12 @ 0.5' – 5'	Clayey SAND (SC)	25
S-13 @ 0.5' – 5'	Clayey SAND (SC)	70
B-14 @ 0.5' – 2.5'	Clayey SAND (SC)	6
B-16 @ 2.5' – 5'	Clayey SAND (SC)	55

EXPANSION INDEX	POTENTIAL EXPANSION
0 to 20	Very low
21 to 50	Low
51 to 90	Medium
91 to 130	High
Above 130	Very High





CORROSIVITY TEST RESULTS
(ASTM D516, CTM 643)

SAMPLE	pH	RESISTIVITY [OHM-CM]	SULFATE CONTENT [%]	CHLORIDE CONTENT [%]
S-2 @ 0.5' – 5'	8.6	1,950	<0.01	<0.01
S-6 @ 0.5' – 5'	7.1	1,135	0.01	0.01
S-7 @ 0.5' – 5'	8.0	600	0.03	0.07
S-10 @ 0.5' – 5'	7.9	980	<0.01	0.06
S-11 @ 0.5' – 5'	8.2	940	<0.01	0.01
B-16 @ 2.5' – 5'	8.6	970	0.01	0.01
B-17 @ 0.5' – 5'	8.5	1,080	<0.01	<0.01

SULFATE CONTENT [%]	SULFATE EXPOSURE	CEMENT TYPE
0.00 to 0.10	Negligible	-
0.10 to 0.20	Moderate	II, IP(MS), IS(MS)
0.20 to 2.00	Severe	V
Above 2.00	Very Severe	V plus pozzolan

SOIL RESISTIVITY [OHM-CM]	GENERAL DEGREE OF CORROSIVITY TO FERROUS METALS
0 to 1,000	Very Corrosive
1,000 to 2,000	Corrosive
2,000 to 5,000	Moderately Corrosive
5,000 to 10,000	Mildly Corrosive
Above 10,000	Slightly Corrosive

CHLORIDE (Cl) CONTENT [%]	GENERAL DEGREE OF CORROSIVITY TO METALS
0.00 to 0.03	Negligible
0.03 to 0.15	Corrosive
Above 0.15	Severely Corrosive



SAMPLE: S-2 @ 46' - 46.5'

Description:
Clayey SAND (SC)

STRAIN RATE: 0.0020 IN/MIN
(Sample was consolidated and drained)

PEAK

ϕ'	29 °
C'	1,300 PSF

IN-SITU

γ_d	102.3 PCF
w_c	21.1 %

ULTIMATE

	27 °
	1,300 PSF

AS-TESTED



	102.3 PCF
	24.0 %



GROUP DELTA

DIRECT SHEAR TEST RESULTS

Project No. SD605
FIGURE C-4.1



SAMPLE: S-7 @ 50.4' - 50.9'

Description:
Silty SAND (SM)

STRAIN RATE: 0.0030 IN/MIN
(Sample was consolidated and drained)

PEAK

ϕ'	40 °
C'	0 PSF

IN-SITU

γ_d	103.2 PCF
w_c	22.0 %

ULTIMATE

ϕ'	36 °
C'	0 PSF

AS-TESTED



γ_d	103.2 PCF
w_c	23.3 %



GROUP DELTA

DIRECT SHEAR TEST RESULTS

Project No. SD605
FIGURE C-4.2



SAMPLE: B-15 @ 35.5' - 36'

Description:
Gray silty SAND (SM)

STRAIN RATE: 0.0030 IN/MIN
(Sample was consolidated and drained)

PEAK

ϕ' 35 °
 C' 1,100 PSF

IN-SITU

γ_d 119.7 PCF
 w_c 6.1 %

ULTIMATE

32 °
275 PSF

AS-TESTED



119.7 PCF
15.1 %



GROUP DELTA

DIRECT SHEAR TEST RESULTS

Project No. SD605
FIGURE C-4.3



SAMPLE: B-17 @ 60.5' - 70'

Description:
Poorly graded SAND with silt (SP-SM)

STRAIN RATE: 0.0030 IN/MIN
(Sample was consolidated and drained)

PEAK

ϕ'	35 °
C'	600 PSF

IN-SITU

γ_d	105.3 PCF
w_c	19.7 %

ULTIMATE

ϕ'	32 °
C'	350 PSF

AS-TESTED


γ_d	105.3 PCF
w_c	22.2 %



GROUP DELTA

DIRECT SHEAR TEST RESULTS

Project No. SD605
FIGURE C-4.4



BORING NUMBER/DEPTH: S-5 @ 21' - 21.5'

DESCRIPTION: Lean CLAY with sand (CL)

INITIAL	FINAL
1.0000	0.8410
72.2	85.9
2.96	2.96
1.56	1.16
50.1	39.0
95.0	100.0

SAMPLE HEIGHT [IN]
 DRY DENSITY [PCF]
 SPECIFIC GRAVITY (ASSUMED)
 VOID RATIO (e)
 WATER CONTENT [%]
 DEGREE OF SATURATION [%]



GROUP DELTA

CONSOLIDATION RESULTS

Project No. SD605

FIGURE C-5