




## **Rio Rockwell Residential Development Project**

### **Appendix H**

#### **Preliminary Geotechnical Investigation**

##### **Rio Rockwell Site**



***ALBUS-KEEFE & ASSOCIATES, INC.***

GEOTECHNICAL CONSULTANTS

---

December 19, 2018  
***Revised*** March 2, 2020  
J.N.: 2551.00

Mr. Steve Sheldon  
Sheldon Development, LLC  
901 Dove Street, Suite 140  
Newport Beach, California 92660

**Subject: Preliminary Geotechnical Investigation, Proposed Residential Development,  
Intersection of Old Grove Road and Frazee Road, Oceanside, California.**

Dear Mr. Sheldon,

*Albus-Keefe & Associates, Inc.* is pleased to present to you our preliminary geotechnical report for the proposed residential development at the subject site. This report presents the results of our aerial photo and literature review, subsurface exploration, laboratory testing, and engineering analyses. Conclusions relevant to the feasibility of the proposed site development are also presented herein based on the findings of our work. This version of our report reflects updates to recommendations pertaining to ground preparation as a result of addressing comments by the city of Oceanside. The previous version dated December 19, 2018 is superseded by this report.

We appreciate this opportunity to be of service to you. If you have any questions regarding the contents of this report, please do not hesitate to call.

Sincerely,

***ALBUS-KEEFE & ASSOCIATES, INC.***

David E. Albus  
Principal Engineer



**PRELIMINARY GEOTECHNICAL INVESTIGATION,  
PROPOSED RESIDENTIAL DEVELOPMENT,  
INTERSECTION OF OLD GROVE ROAD AND FRAZEE ROAD,  
OCEANSIDE, CALIFORNIA**

**VOLUME 1**

***Dated:***

December 19, 2018

***Revised***

March 2, 2020

***Prepared for:***

Mr. Steve Sheldon  
Sheldon Development, LLC  
901 Dove Street, Suite 140  
Newport Beach, California 92660

***Prepared by:***

Albus-Keefe & Associates, Inc.  
J.N. 2551.00

**TABLE OF CONTENTS**

<b>1.0 INTRODUCTION.....</b>	<b>1</b>
1.1 PURPOSE AND SCOPE .....	1
1.2 SITE LOCATION AND DESCRIPTION.....	1
1.3 PROPOSED DEVELOPMENT .....	3
<b>2.0 INVESTIGATION.....</b>	<b>3</b>
2.1 RESEARCH .....	3
2.2 SUBSURFACE INVESTIGATION.....	3
2.3 LABORATORY TESTING .....	4
<b>3.0 SUBSURFACE CONDITIONS.....</b>	<b>4</b>
3.1 SOIL CONDITIONS .....	4
3.2 GROUNDWATER.....	5
3.3 FAULTING .....	5
<b>4.0 ANALYSES .....</b>	<b>5</b>
4.1 SEISMICITY.....	5
4.2 STATIC SETTLEMENT .....	5
4.3 LIQUEFACTION.....	6
<b>5.0 CONCLUSIONS .....</b>	<b>13</b>
5.1 FEASIBILITY OF PROPOSED DEVELOPMENT.....	13
5.2 GEOLOGIC HAZARDS.....	13
5.2.1 Ground Rupture .....	13
5.2.2 Ground Shaking .....	13
5.2.3 Liquefaction .....	13
5.3 STATIC SETTLEMENT .....	14
5.4 MATERIAL CHARACTERISTICS .....	14
5.5 SHRINKAGE AND SUBSIDENCE.....	14
5.6 SOIL EXPANSION.....	15
<b>6.0 RECOMMENDATIONS.....</b>	<b>15</b>
6.1 EARTHWORK.....	15
6.1.1 General Earthwork and Grading Specifications .....	15
6.1.2 Pre-Grade Meeting and Geotechnical Observation .....	15
6.1.3 Site Clearing.....	15
6.1.4 Ground Preparation.....	16
6.1.5 Fill Placement .....	16
6.1.6 Import Materials.....	17
6.1.7 Temporary Excavations .....	17
6.2 SEISMIC DESIGN PARAMETERS .....	17
6.3 FOUNDATION DESIGN .....	17
6.3.1 General.....	17
6.3.2 Soil Expansion .....	18
6.3.3 Static and Seismic Settlement.....	18
6.3.4 Allowable Bearing Value.....	18
6.3.5 Lateral Resistance .....	19
6.3.6 Residential Post-Tension Slabs.....	19
6.3.7 Foundation Observations .....	20
6.4 RETAINING AND SCREENING WALLS.....	20

**TABLE OF CONTENTS**

6.4.1	General.....	20
6.4.2	Allowable Bearing Value and Lateral Resistance .....	20
6.4.3	Footing Reinforcing and Wall Jointing.....	20
6.4.4	Active Earth Pressure.....	21
6.4.5	Drainage and Moisture-Proofing .....	22
6.4.6	Footing Observations.....	22
6.4.7	Retaining Wall Backfill .....	22
6.5	EXTERIOR FLATWORK .....	22
6.6	CONCRETE MIX DESIGN.....	23
6.7	PRELIMINARY PAVEMENT DESIGN .....	23
6.7.1	Preliminary Pavement Structural Sections.....	23
6.7.2	Subgrade Preparation.....	23
6.7.3	Aggregate Base .....	23
6.7.4	Asphaltic Concrete.....	24
6.7.5	Concrete Paver .....	24
6.7.6	Portland Cement Concrete .....	25
6.8	POST GRADING CONSIDERATIONS .....	25
6.8.1	Site Drainage and Irrigation.....	25
6.8.2	Utility Trenches .....	26
6.9	PLAN REVIEW AND CONSTRUCTION SERVICES.....	26
<b>7.0</b>	<b>LIMITATIONS.....</b>	<b>27</b>
	<b>REFERENCES.....</b>	<b>28</b>

**FIGURES AND PLATES**

Figure 1 - Site Location Map

Plate 1 – Geotechnical Map

**APPENDICES****APPENDIX A - Exploratory Logs and Summary CPT Data**

Boring Logs - Plates A-1 through A-14

**APPENDIX B - Laboratory Test Program**

Table B-1 – Summary of Laboratory Test Results

Plates B-1 through B-5 – Grain-Size Distribution Plots

Plates B-6 and B-7 – Consolidation Test Plots

Plates B-8 and B-9 – Direct Shear Test Plot

**APPENDIX C – Exploratory Logs and Laboratory Test Results by Others****APPENDIX D – Liquefaction Analyses using CPT Data, and Analysis of Lateral Spread**

## **1.0 INTRODUCTION**

### **1.1 PURPOSE AND SCOPE**

The purposes of our work were to evaluate the feasibility of proposed site development as well as provide you preliminary recommendations for site development. The scope of our geotechnical investigation included the following:

- Review of historical aerial photographs for the site and surrounding
- Review of previous geotechnical reports by others for the site
- Review of published geologic and seismic data for the site and surrounding area
- Exploratory drilling and sampling
- Engineering analyses of data obtained from exploration and laboratory testing during previous investigations
- Preparation of this report

### **1.2 SITE LOCATION AND DESCRIPTION**

The site is located north of the intersection of Old Grove Road and Frazee Road within Oceanside, California. The property is bordered by Frazee Road to the southeast, Old Grove Road to the south, and by an undeveloped lot adjacent to the San Luis Rey River Valley to the north. Single-family residential tracts are also located in close vicinity to the subject site to the east, south, and west. The location of the site and its relationship to the surrounding areas is shown on Figure 1, Site Location Map.

The irregular-shaped site encompasses approximately 8.4 acres of land and is currently undeveloped. A concrete-lined storm drain culvert abuts the site at the east and west corner of the property. The storm drain culverts measure approximately 15 feet below adjacent grades and drain in a northerly direction away from the site. According to the referenced report by Christian Wheeler Engineering (dated May 13, 2005), a 24-inch-diameter storm drain line also runs in the east-west direction adjacent the north property line of the site. The report states the north property line is located within the center of a 40-foot-wide easement associated with the subject storm drain improvements.

Topographically, elevations range from approximately 58 feet to 69 feet above Mean Sea Level (MSL). In general, the site is situated approximately 2 feet to 8 feet below the adjacent streets. Drainage is generally directed as sheet flow towards the north. Vegetation within the site consists of minor shrubs and medium-size trees scattered throughout the site.



© 2018 Google

### SITE LOCATION MAP

Sheldon Development, LLC  
Proposed Residential Development  
Old Grove Road and Frazee Road  
Oceanside, California

NOT TO SCALE

**FIGURE 1**

### **1.3 PROPOSED DEVELOPMENT**

We anticipate the proposed site development will consist of 83 single-family, 2-story residential structures. We anticipate the development will be constructed on grade with associated interior driveways, parking bays, decorative hardscape, landscaping elements and underground utilities.

No grading or structural plans were available in preparing of this report. However, we anticipate that rough grading of the site will be required to achieve future surface configurations.

## **2.0 INVESTIGATION**

### **2.1 RESEARCH**

We have reviewed the referenced geologic publications and maps (see references). Data from these sources were utilized to develop some of the findings and conclusions presented herein.

We have also reviewed historical aerial photographs from our in-house library. Based on this firm's review of the referenced aerial photographs, the site is located within the old flood plain of the San Luis Rey River. Since 1938, the southeast portion of the site was utilized for agricultural purposes. Sometime between 1980 and 1989, residential tracts, Frazee Road, and Old Grove Road were constructed adjacent to the site. The site was also cleared and left undeveloped. In 2003, storm drain improvements were installed at the eastern and western portions of the site. The site and surrounding area has remained relatively unchanged since 2003.

We have also reviewed the referenced geotechnical investigation report by Christian Wheeler Engineering dated May 13, 2005, conducted in the southeast triangular portion of the site flanked by Old Grove Road and Frazee Road. Their investigation included three (3) hollow-stem auger borings, laboratory testing of selected soil samples, and engineering analyses. The borings were excavated using a hollow-stem auger drill rig to depths ranging from 20 feet to 50 feet below existing ground surfaces. Pertinent exploratory and laboratory data presented by Christian Wheeler Engineering were utilized in developing some of the findings and conclusions presented herein and are included in Appendix C of the present report. The approximate locations of the exploratory excavations completed by Christian Wheeler Engineering are also indicated on the enclosed Geotechnical Map, Plate 1.

### **2.2 SUBSURFACE INVESTIGATION**

Subsurface exploration for this investigation was conducted by this firm in several phases on November 10, 2016, June 12, 2018, and October 23, 2018 through October 25, 2018. The subsurface exploration consisted of drilling a total of six (6) geotechnical borings and fifty-five (55) cone penetration test (CPT) soundings to the maximum depth of approximately 50 feet below the existing ground surface (bgs). The CPT soundings were advanced using a 30-ton CPT truck. The geotechnical borings were drilled using a truck-mounted, continuous flight, hollow-stem-auger drill rig. Representatives of *Albus-Keefe & Associates, Inc.* logged the exploratory borings. Visual and tactile identifications were made of the materials encountered, and their descriptions are presented in the Exploration Logs in Appendix A. The approximate locations of the exploratory excavations

completed by this firm are shown on the enclosed Geotechnical Map, Plate 1. As indicated in this plate, four zones labeled Zone 1 through 4 are defined, each including certain CPT clusters.

Bulk, relatively undisturbed, and Standard Penetration Test (SPT) samples were obtained at selected depths within the exploratory borings for subsequent laboratory testing. Relatively undisturbed samples were obtained using a 3-inch O.D., 2.5-inch I.D., California split-spoon soil sampler lined with brass rings. SPT samples were obtained from the boring using a standard, unlined SPT soil sampler. During each sampling interval, the sampler was driven 18 inches with successive drops of a 140-pound automatic hammer free falling approximately 30 inches. The number of blows required to advance the split-spoon sampler was recorded for each six inches of advancement. The total blow count for the lower 12 inches of advancement per soil sample is recorded on the exploration logs. Samples were placed in sealed containers or plastic bags and transported to our laboratory for analyses. The borings were backfilled with cement and bentonite upon completion of sampling.

## **2.3 LABORATORY TESTING**

Selected samples of representative earth materials from the borings excavated at the site were tested in the laboratory. Tests consisted of in-situ moisture content and dry density, maximum dry density and optimum moisture content, Atterberg limits, R-value, expansion index, soluble sulfate, direct shear strength, grain-size analysis, minus #200 wash, and consolidation/collapse tests. Descriptions of laboratory test criteria and a summary of the test results are presented in Appendix B and on the boring logs in Appendix A.

## **3.0 SUBSURFACE CONDITIONS**

### **3.1 SOIL CONDITIONS**

Descriptions of the earth materials encountered during our investigation are summarized below and are presented in detail on the Exploration Logs presented in Appendix A.

Soil materials encountered at the site consisted of artificial fill materials and alluvial deposits to the maximum depth explored, 51.5 feet below the ground surface (bgs). The artificial fill materials typically consisted of grayish brown to tan silty sand and sandy silt with occasional layers of cohesive material in the upper 5 feet within portions of the site. These materials are typically dry to damp and loose/soft to medium stiff/medium dense. The alluvial deposits typically consist of brown, gray, and light gray with orange sand and silty sand in the upper 18 to 25 feet (bgs). These materials are typically damp to wet and very loose to medium dense/soft to stiff. Between approximately 25 and 40 feet below the ground surface (bgs), the alluvial deposits generally consist of interlayered medium brown, grayish brown, and gray sandy silt, silty sand, silt, and clay. These materials are typically wet to saturated and loose/very soft to medium dense/medium stiff. Below 40 feet, the alluvial deposits typically consist of brown to grayish brown sand and silty sand with occasional layers of increased silt. These materials are typically wet to saturated and medium dense to dense/very stiff.



### 3.2 GROUNDWATER

Groundwater was encountered during this firm's exploration to the depth of approximately 13 to 24 feet below the existing ground surface. The referenced geotechnical report by Christian Wheeler Engineering indicated groundwater at depths 10 to 12 feet below ground surface. Search of well records from the Water Data Library of the California Department of Water Resources resulted in sparse historical groundwater data for this area, mostly indicating groundwater deeper than 60 feet below ground surface. As a result, a groundwater depth of 10 feet below ground surface is adopted as the historically high groundwater level.

### 3.3 FAULTING

Based on our review of the referenced publications and seismic data, no faults are known to project through or immediately adjacent the site and the site does not lie within an "Earthquake Fault Zone" as defined by the State of California in the Alquist-Priolo Earthquake Fault Zoning Act. Table 3.1 presents a summary of known active faults within 10 miles of the site, based on the 2008 U.S.G.S. National Seismic Hazard Maps.

**TABLE 3.1**  
**Summary of Faults**

<b>Name</b>	<b>Dist. (miles)</b>	<b>Slip Rate (mm/yr.)</b>	<b>Preferred Dip (degrees)</b>	<b>Slip Sense</b>	<b>Rupture Top (km)</b>	<b>Fault Length (km)</b>
Newport Inglewood Connected alt 1	8.95	1.3	89	strike slip	0	208
Newport Inglewood Connected alt 2	8.95	1.3	90	strike slip	0	208
Newport-Inglewood (Offshore)	8.95	1.5	90	strike slip	0	66

## 4.0 ANALYSES

### 4.1 SEISMICITY

We have performed probabilistic seismic analyses utilizing the U.S. Seismic Design Maps web application by the U.S. Geological Survey (USGS). From our analyses, we obtain a PGA of 0.397 in accordance with Figure 22-7 of ASCE 7-10. The site coefficient,  $F_{PGA}$ , for Site Class D in this range of PGA is 1.103. Therefore, the  $PGAM = 1.103 \times 0.397 = 0.438g$ . The mean event associated with a probability of exceedance equal to 2% over 50 years has a moment magnitude of 6.64 and the mean distance to the seismic source is 13.5 miles.

### 4.2 STATIC SETTLEMENT

Results of our laboratory testing indicate portions of the alluvial soils have a potential for hydro-collapse (consolidation upon wetting) in the upper 12 feet. We estimate that residential footings founded upon these soils in their in-situ condition could settle several inches if they became wetted



after construction. Limited test results are available to provide a quantitative estimate of settlement due to these materials. However, the data available does indicate the existing fill soils are generally poorly compacted and likely exhibit hydrocollapse properties.

If the existing artificial fill and alluvium located within the upper 6 feet of current ground surface were re-compacted as engineered fill, we estimate total and differential settlement potential of residential footings would be reduced to a maximum of 1 inch and ½ inch over 30 feet, respectively.

### **4.3 LIQUEFACTION**


Engineering research of soil liquefaction potential (Youd, et al., 2001) indicates that generally three basic factors must exist concurrently in order for liquefaction to occur. These factors include:

- A source of ground shaking, such as an earthquake, capable of generating soil mass distortions.
- A relatively loose silty and/or sandy soil.
- A relative shallow groundwater table (within approximately 50 feet below ground surface) or completely saturated soil conditions that will allow positive pore pressure generation.


The liquefaction susceptibility of the onsite subsurface soils was evaluated by analyzing the potential concurrent occurrence of the above-mentioned three basic factors and using the computer program CLiq. These analyses were completed under the guidance of Special Publication 117A: Guidelines for Evaluating and Mitigating Seismic Hazards in California (CDMG, 2008). CPT data from our site investigations of November 10, 2016, June 20 2018, and October 23 through October 26, 2018 were used for this purpose. Among the methods available in this program for analysis of liquefaction potential, Robertson (NCEER 2001) was used for the current project. The seismic event was defined by peak ground acceleration of  $PGA=0.44g$  and mean moment magnitude of 6.64 discussed in Section 4.1. Groundwater was assumed at depth 10 feet below ground surface, as discussed in Section 3.2.

All of the 55 CPT probes performed at the site under the supervision of our company reached a depth of at least 50 feet below ground surface, making them usable for liquefaction analysis per SP 117 A. Among these, CPT-39 showed unreliable data and was thus excluded from the analyses. Appendix C includes the related CLiq report, based on Robertson (NCEER 2001). In these results, factors of safety smaller than 1.3 indicate potential liquefaction.


Cliq analyses were also performed to evaluate the potential for seismic settlement from liquefied soils. The results of seismic-induced settlement using Robertson (NCEER 2001) method are summarized in Figures 4.1 through 4.4, for Zone 1 through 4, respectively. The estimated maximum total settlement is approximately 10.5 inches.




**Figure 4.1 Liquefaction Settlement using CPT Data within Zone 1 and its Vicinity**



**Figure 4.2 Liquefaction Settlement using CPT Data within Zone 2 and its Vicinity**




**Figure 4.3 Liquefaction Settlement using CPT Data within Zone 3 and its Vicinity**




**Figure 4.4 Liquefaction Settlement using CPT Data within Zone 4 and its Vicinity**

Figures 4.5 through 4.8 show contour plots of liquefaction settlements for Zone 1 through 4, respectively. Earlier CPT data (CPT-1 through CPT-7) are not included in these figures to eliminate potential distortion of the contour plots that may be caused by the use of a different set of CPT equipment. These contour plots were generated by employing the Kriging gridding method, as available in the computer program Surfer (Version 16.0330). In these figures, horizontal and vertical axes are distances in feet from the origin of a local coordinate system used for each zone. The contours are labeled in values of inches. Each figure shows the line segment with maximum differential settlement slope, expressed in inches over a distance of 40 feet. Based on these plots, the maximum estimated differential seismic settlement is 2 inches over 40 feet.




**Figure 4-5 Contour Plot of Liquefaction Settlements; Zone 1**




**Figure 4-6 Contour Plot of Liquefaction Settlements; Zone 2**





**Figure 4-7 Contour Plot of Liquefaction Settlements; Zone 3**



**Figure 4-8 Contour Plot of Liquefaction Settlements; Zone 4**

The potential for lateral spreading was evaluated using the procedures developed by Youd, et al., (2002). Lateral spreading is a phenomenon that can occur during and shortly after triggering of liquefaction. A gentle slope in the ground surface or the presence of a slope face nearby can cause the ground to slide or spread on layers of liquefied soil. The general slope of ground in the area was found to be less than 2% toward the north and the nearest free face slope was the creek located between the site and the San Luis River Trail north of the site, with a maximum elevation difference of 12 feet and toe distance of 140 feet (based on GoogleEarth 2018). The procedure requires providing the

earthquake magnitude and distance to the seismic source. For this, the magnitude and distance to the source as discussed in Section 4.1 of this report were used, i.e., M6.64 at 13.5 miles. The conservative assumption was made that all layers between liquefaction groundwater at depth 10 feet and depth 50 feet were liquefiable. Soils descriptions (boring logs of Appendix A) and grain size distribution curves (Appendix B) were used for particle size input parameters needed by this method. A printout of this analysis is provided in Table D-1 (at the end of Appendix D). From our analyses, we estimate a lateral spread of 0.9 and 1.1 feet for free-face condition and sloping ground condition, respectively. These calculated values include a factor of safety equal to 2 as recommended by Youd, et al. (2002). The sloping ground condition was estimated using a slope of 4% that is twice the slope reported above.

## **5.0 CONCLUSIONS**

### **5.1 FEASIBILITY OF PROPOSED DEVELOPMENT**

From a geotechnical point of view, the proposed site development is considered feasible provided the recommendations presented in this report are incorporated into the design and construction of the project. Furthermore, it is also our opinion that the proposed development will not adversely impact the stability of adjoining properties. Key geotechnical issues that should be mitigated for proposed site development are discussed in the following sections of this report.

### **5.2 GEOLOGIC HAZARDS**

#### **5.2.1 Ground Rupture**

No active faults are known to project through the site nor does the site lie within the boundaries of an “Earthquake Fault Zone” as defined by the State of California in the Alquist-Priolo Earthquake Fault Zoning Act. The closest known active fault is the Newport Inglewood fault located about 8.95 miles from the site. Therefore, potential for ground rupture due to an earthquake beneath the site is considered very low.

#### **5.2.2 Ground Shaking**

The site is situated in a seismically active area that has historically been affected by generally moderate to occasionally high levels of ground motion. The site lies in relative close proximity to several active faults; therefore, during the life of the proposed structures, the property will probably experience similar moderate to occasionally high ground shaking from these fault zones, as well as some background shaking from other seismically active areas of the Southern California region. Potential ground accelerations have been estimated for the site and are presented in Section 4.1 of this report. Design and construction in accordance with the current California Building Code (CBC) requirements is anticipated to address the issues related to potential ground shaking at the site.

#### **5.2.3 Liquefaction**

Based on our engineering analyses discussed previously, a number of thin and thick layers of granular soils below groundwater are susceptible to liquefaction. Summary results provided in Section 4.3 indicate that settlement due to liquefaction ranges between about 4 and 10.5 inches. The maximum differential settlement due to liquefaction is limited to 2 inches over 40 feet. We anticipate a sufficient



thickness of non-liquefiable soils to be present below the foundations to preclude a loss of bearing while deeper soils are liquefied.

Liquefaction-triggered lateral spread in the range of 0.9 ft (due to free face) to 1.1 ft (due to ground slope) to is estimated, in which a factor of safety of 2 has been used.

Based on the State of California Special Publication 117A, hazards from liquefaction should be mitigated to the extent required to reduce seismic risk to “acceptable levels”. The acceptable level of risk means, “that level that provides reasonable protection of the public safety” [California Code of Regulations Title 14, Section 3721 (a)]. The use of well-reinforced foundations, such as post-tensioned slabs, grade beams with structural slabs, or mat foundations have been proven to adequately provide basal support for structures similar to those proposed for the site during comparable liquefaction events. Specific recommendations for the design and construction of such foundation are provided in later sections of this report.

### **5.3 STATIC SETTLEMENT**

As indicated in Section 4.2, existing fills and the upper portions of the alluvial soils are prone to hydroconsolidation. Footings founded on these soils could undergo several inches of settlement if wetted after construction. If existing fills and the alluvium located within the upper 6 feet of ground surface is recompacted as engineered fill, we expect total and differential settlement potential of residential footings would be reduced to a maximum total and differential settlement of 1 inch and ½ inch over 30 feet, respectively. These estimated settlements are considered within tolerable limits of proposed structures and site improvements.

### **5.4 MATERIAL CHARACTERISTICS**

Subsurface soils are anticipated to be relatively easy to excavate with conventional heavy earthmoving equipment. Most of the existing fill materials and upper portion of alluvial soils are generally below optimum moisture content. These soils may require the addition of water prior to reuse as compacted fills depending on weather conditions at the time of grading.

If buried debris, onsite disposal systems, clarifiers, and other underground improvements are encountered during future demolition or rough grading, these improvements will require proper abandonment or removal.

### **5.5 SHRINKAGE AND SUBSIDENCE**

Volumetric changes in earth quantities will occur when excavated onsite soil materials are replaced as properly compacted fill. The earth materials within the upper 10 feet vary somewhat in material types and degree of porosity from various points of exploration. In general, we estimate the existing artificial fill and the upper 6 feet of the alluvial soils could shrinkage approximately 15 to 25 percent. Reprocessing of removal bottoms is anticipated to result in a general subsidence of approximately 0.2 foot. The estimates of shrinkage and subsidence are approximate and are intended as an aid for project engineers in determining earthwork quantities.

## **5.6 SOIL EXPANSION**

Based on laboratory test results and the USCS visual manual classification, the near-surface soils within the site are generally anticipated to possess a **Very Low** expansion potential (UBC 18-2). Design and construction considerations for expansive soils are anticipated to be nominal. Additional testing for soil expansion will be required subsequent to rough grading and prior to construction of foundations and other concrete work to confirm these conditions.

## **6.0 RECOMMENDATIONS**

### **6.1 EARTHWORK**

#### **6.1.1 General Earthwork and Grading Specifications**

All earthwork and grading should be performed in accordance with applicable requirements of Cal/OSHA, applicable specifications of the Grading Codes of the City of Oceanside, California in addition to the recommendations presented herein.

#### **6.1.2 Pre-Grade Meeting and Geotechnical Observation**

Prior to commencement of grading, we recommend a meeting be held between the developer, City Inspector, grading contractor, civil engineer, and geotechnical consultant to discuss the proposed grading and construction logistics. We also recommend a geotechnical consultant be retained to provide soil engineering and engineering geologic services during site grading and foundation construction. This is to observe compliance with the design specifications and recommendations and to allow for design changes in the event that subsurface conditions differ from those anticipated. If conditions are encountered that appear to be different than those indicated in this report, the project geotechnical consultant should be notified immediately. Design and construction revisions may be required.

#### **6.1.3 Site Clearing**

All existing site improvements, including asphaltic concrete paving, structural foundations and underground utilities, should be removed from the areas to be developed prior to any grading activities. Existing underground utility lines within the project area that will be protected in place and that fall within a 1 to 1 (H:V) plane projected down from the edges of footings may be subject to surcharge loads. Under such conditions, this office should be made aware of these conditions for evaluation of potential surcharging. Supplemental recommendations may be required to protect such improvements in place.

The project geotechnical consultant should be notified at the appropriate times to provide observation services during clearing operations to verify compliance with the above recommendations. Voids created by clearing and excavation should be left open for observation by the geotechnical consultant. Should any unusual soil conditions or subsurface structures be encountered during site clearing or grading that are not described or anticipated herein, these conditions should be brought to the immediate attention of the project geotechnical consultant for corrective recommendations as needed.

The presence of the existing offsite improvements may limit removals of unsuitable materials adjacent the property lines. Special grading techniques, such as shoring may be required adjacent to the property lines where offsite structures are nearby. Specific recommendations should be developed once more detail development plans are prepared.

Temporary construction equipment (office trailers, power poles, etc.) should be positioned to allow adequate room for clearing and recommended ground preparation to be performed for proposed structures, pavements, and hardscapes.

#### **6.1.4 Ground Preparation**

In general, all artificial fill and near-surface compressible alluvium is considered unsuitable for support of proposed engineered fill and site improvements. These materials should be removed from proposed building pads and any other “structural” areas, and replaced as engineered compacted fill. The depth of removal of unsuitable soils is anticipated to generally extend to a depth of approximately 6 feet but may reach up to about 10 feet below existing grades. In addition to general removal of unsuitable soils, the existing soils should be over-excavated to a depth of at least 10 feet below finish pad grade within the limits of residential structures and extend at least 10 feet horizontally beyond the edges of pads.

Locally deeper removal may be required in the areas of previously existing improvements. The actual depth of removal should be determined by the geotechnical consultant during grading.

Within the limits of pavement and free-standing retaining walls over 3 feet in height, the existing fill soils should be removed to a minimum depth of 1 foot below subgrade or footing, whichever is deeper.

The removals should extend laterally a distance of at least 5 feet beyond the limits of the proposed structures or a 1:1 projection down and away from the bottom of the footings, whichever is greater. Removals for pavement and free-standing retaining walls may be limited to the edge of the foundations or pavement where lateral restrictions to removals are present such as property lines. The actual depth of removals should be verified by the geotechnical consultant during site grading.

Where removals are limited by existing structures, protected trees or property lines, special considerations may be required in the construction of affected improvements. Under such conditions, specific recommendations should be provided by this firm.

All removal excavations should be evaluated by the geotechnical consultant during grading to confirm the exposed conditions are as anticipated and to provide supplemental recommendations if required.

Following removals/overexcavation, the exposed grade should first be scarified to a depth of 6 inches, brought to at least 100 percent of the optimum moisture content, and then compacted to at least 90 percent of the laboratory standard (ASTM D 1557).

#### **6.1.5 Fill Placement**

Materials excavated from the site may be reused as fill provided they are free of deleterious materials and particles greater than 4 inches in maximum dimension (oversized materials). Asphaltic and

concrete debris generated during site demolition can be incorporated within fill soils during earthwork operations provided they are reduced to no more than 4 inches in maximum dimension. Such materials should be mixed thoroughly with fill soils to prevent nesting. All fill should be placed in lifts no greater than 8 inches in loose thickness, moisture conditioned to at least 100 percent of the optimum moisture content, then compacted in place to at least 90 percent of the laboratory standard. Each lift should be treated in a similar manner. Subsequent lifts should not be placed until the project geotechnical consultant has approved the preceding lift.

#### **6.1.6 Import Materials**

If import materials are required to achieve the proposed finish grades, the proposed import soils should have an Expansion Index (EI, ASTM D 4829) less than 20 and possess negligible soluble sulfate concentrations. Import sources should be indicated to the geotechnical consultant prior to hauling the materials to the site so that appropriate testing and evaluation of the fill materials can be performed in advance.

#### **6.1.7 Temporary Excavations**

Temporary construction slopes or trench excavations in site materials may be cut vertically up to a height of 3 feet provided that no surcharging of the excavations is present. Temporary slopes over 3 feet in height but no greater than 10 feet should be laid back to 1.5:1 (H:V) or flatter and evaluated by the geotechnical consultant.

Excavations should not be left open for prolonged periods of time. The project geotechnical consultant should observe all temporary cuts to confirm anticipated conditions and to provide alternate recommendations if conditions dictate. All excavations should conform to the requirements of CAL OSHA.

Where temporary excavations cannot accommodate a 1.5:1 9H:V0 layback or where surcharging occurs, shoring, underpinning, or other methods should be used. Specific recommendations for other options if considered should be provided by the geotechnical consultant based on review of the final design plans.

### **6.2 SEISMIC DESIGN PARAMETERS**

For design of the project in accordance with Chapter 16 of the 2016 CBC, seismic design factors are summarized in Table 6.1.

### **6.3 FOUNDATION DESIGN**

#### **6.3.1 General**

The following recommendations are provided for preliminary design purposes. These recommendations have been based on the site materials exposed during our investigation, our understanding of the proposed development, and the assumption that the recommendations presented herein are incorporated into the design and construction of the project. Our preliminary recommendations include conventional shallow spread footings and post-tension slabs on grade. Final

recommendations should be provided by the project geotechnical consultant following review of final foundation plans as well as observation and testing of site materials during grading. Depending upon the design plans and actual site conditions, the recommendations provided herein may require modification.

**TABLE 6.1**  
**2016 CBC Seismic Design Parameters**

Parameter	Value
Site Class	D
Importance Factor	I, II, III
Mapped $MCE_R$ Spectral Response Acceleration, short periods, $S_s$	1.059
Mapped $MCE_R$ Spectral Response Acceleration, at 1-sec. period, $S_1$	0.413
Site Coefficient, $F_a$	1.076
Site Coefficient, $F_v$	1.587
Adjusted $MCE_R$ Spectral Response Acceleration, short periods, $S_{MS}$	1.140
Adjusted $MCE_R$ Spectral Response Acceleration, at 1-sec. period, $S_{M1}$	0.656
Design Spectral Response Acceleration, short periods, $S_{DS}$	0.760
Design Spectral Response Acceleration, at 1-sec. period, $S_{D1}$	0.437
$MCE_R$ = Risk-Targeted Maximum Considered Earthquake	

### 6.3.2 Soil Expansion

The recommendations presented herein are based on soils with a **Very Low** expansion potential. Following site grading, additional testing of site soils should be performed by the project geotechnical consultant to confirm the basis of these recommendations. If site soils with higher expansion potentials are encountered or imported to the site, the recommendations contained herein may require modification.

### 6.3.3 Static and Seismic Settlement

Foundations should be designed for static total and differential settlement up to 1 inch and ½-inch over 30 feet, respectively. Total seismic settlements could be up to 10.8 inches and differential seismic settlement could be up to 2 inches over 40 feet (equivalent to 1.5 inches over 30 feet). Design for seismic settlement need not meet the same criteria as static settlement. Design for seismic settlement should provide for the safety of occupants during a strong seismic event as well as safe exit from the building following such an event. Design need not prevent damage to the structure. Design recommendations provide for foundations in the following sections include consideration of mitigation of seismic settlement.

### 6.3.4 Allowable Bearing Value

A bearing value of 2,000 pounds per square foot (psf) can be used for continuous and isolated footings founded at a minimum depth of 12 inches below the lowest adjacent grade and having a minimum width of 12 inches and 24 inches, respectively. The bearing value may be increased by 270 psf and

670 psf for each additional foot in width and depth, respectively, up to a maximum value of 3,500 psf. Recommended allowable bearing values include both dead and live loads, and may be increased by one-third for wind and seismic forces.

### **6.3.5 Lateral Resistance**

Provided site grading is performed in accordance with the recommendations provided by the project geotechnical consultant, a passive earth pressure of 240 pounds per square foot per foot of depth up to a maximum value of 1,200 pounds per square foot may be used to determine lateral bearing for beams. This value may be increased by one-third when designing for wind and seismic forces. A coefficient of friction of 0.35 times the dead load forces may also be used between concrete and the supporting soils to determine lateral sliding resistance. No increase in the coefficient of friction should be used when designing for wind and seismic forces.

Where lateral removals may be restricted, such as along property lines, the above-noted values should be reduced by 50%.

The above values are based on footings placed directly against compacted fill or competent native soils. In the case where footing sides are formed, all backfill against the footings should be compacted to at least 90 percent of the laboratory standard (ASTM D 1557).

### **6.3.6 Residential Post-Tension Slabs**

Perimeter edge beams should be founded at a minimum depth of 18 inches below the lowest adjacent final ground surface. If a post-tensioned mat is used, the outer 12 inches should be thickened to provide a minimum embedment of 8 inches below lowest grade, or to the depth of the underlying sand, whichever is deeper. Interior beams may be founded at a minimum depth of 12 inches below the tops of the finish floor slabs.

The thickness of the floor slab/mat should be determined by the project structural engineer. However, we recommend a minimum slab thickness of 4 inches. Design of the slab may be based on a modulus of subgrade reaction ( $K_v1$ ) of 27 pounds per cubic inch (pci). The modulus is based on an effective loading area of 1 foot by 1 foot. The modulus may be adjusted for other effective loading areas using the equation provided below.

$$k_b(\text{pci}) = 27 \left\{ \frac{b+1}{2b} \right\}^2 \quad \text{where "b" is the effective width of loading (minimum dimension) in feet.}$$

All dwelling area floor slabs constructed on-grade should be underlain with a minimum of 10-mil moisture vapor retarder conforming to ASTM E 1745, Class A. The membrane should be properly lapped, sealed, and underlain with at least two (2) inches of sand having a sand equivalent (SE) no less than 30. One inch of this sand may be placed over the membrane to aid in the uniform curing of the concrete slab. This vapor retarder system is anticipated to be suitable for most flooring finishes that can accommodate some vapor emissions. However, this system may emit more than 4 pounds of water per 1000 sq. ft. and therefore, may not be suitable for all flooring finishes. Additional steps should be taken if such vapor emission levels are too high for anticipated flooring finishes. Where a mat is utilized, the sand may be reduced to 1 inch provided the mat is at least 8 inches thick.

Prior to placing concrete, subgrade soils below slab-on-grade/mat areas should be thoroughly moistened to provide at least 100 percent of the optimum moisture content to a depth of 12 inches.

Based on the guidelines provided in the “Design of Post-Tensioned Slabs-on-Ground” 3rd Edition by Post-Tensioning Institute, the *em* and *ym* values for soil conditions are summarized in Table 6.2. These values also consider the estimated potential differential settlement due to seismic settlement discussed previously.

**TABLE 6.2**  
**PTI Design Parameters**

Parameter	Value
Edge Lift Moisture Variation Distance, <i>em</i>	4.7 feet
Edge Lift, <i>ym</i>	1.2 inches
Center Lift Moisture Variation Distance, <i>em</i>	9.0 feet
Center Lift, <i>ym</i>	0.7 inches

### **6.3.7 Foundation Observations**

Foundation excavations should be observed by the project geotechnical consultant to verify that they have been excavated into competent bearing soils and to the minimum embedment recommended above. These observations should be performed prior to placement of forms or reinforcement. The excavations should be trimmed neat, level and square. Loose, sloughed or moisture-softened materials and debris should be removed prior to placing concrete.

## **6.4 RETAINING AND SCREENING WALLS**

### **6.4.1 General**

The following preliminary design and construction recommendations are provided for general retaining and screen walls supported by engineered compacted fill or competent native soils. Final wall designs specific to the site development should be provided for review once completed. The structural engineer and architect should provide appropriate recommendations for sealing at all joints and applying moisture-proofing material on the back of the walls.

### **6.4.2 Allowable Bearing Value and Lateral Resistance**

Design of retaining and screen walls may utilize the bearing and lateral resistance values provided in Section 0 and 6.3.5.

### **6.4.3 Footing Reinforcing and Wall Jointing**


All continuous footings should be reinforced with a minimum of two No. 4 bars, one top and one bottom. Where removals of unsuitable soils are limited laterally due to property line constraints, the footings should be reinforced with a minimum of four No. 4 bars, two top and two bottom. The structural engineer may require different reinforcement and should dictate if greater than the recommendations herein.

Retaining and screen walls should be provided with cold joint through the wall stem at a spacing not exceeding approximately 40 feet on center. Where removals of unsuitable soils are limited laterally due to property line constraints, this spacing should be reduced to 20 feet. The joint should not continue through the footing.

#### 6.4.4 Active Earth Pressure

Static and seismic earth pressures for level and 2:1 (H:V) backfill conditions are provided in the Table 6.3. Seismic earth pressures provided herein are based on the method provided by Seed & Whitman (1970) using a peak ground acceleration (PGA) of 0.29g. This acceleration is based on a 10% probability of exceedance in 50 years. Based on the 2016 CBC, walls that retain less than 6 feet need not be designed for seismic earth pressures. The values provided in the following table are based on typical site materials on drained backfill conditions and do not consider hydrostatic pressure. Retaining walls should be designed to support adjacent surcharge loads imposed by other nearby footings or traffic loads in addition to the earth pressure.

**TABLE 6.3  
SEISMIC EARTH PRESSURES**



**Active Earth Pressure Values**

Value	Backfill Condition	
	Level	2H:1V Slope
<b>A</b>	38H	70H
<b>B</b>	9H	9H
<b>C</b>	24H	40H

Note:  
H is in feet and resulting pressure is in psf. Design may utilize either the sum of the static component and the seismic component force diagrams or the total force diagram above. SEAOSC has suggested using a load factor of 1.7 for the static component and 1.0 for the seismic component. The actual load factors should be determined by the structural engineer.



#### **6.4.5 Drainage and Moisture-Proofing**

Retaining walls should be constructed with a perforated pipe and gravel subdrain to prevent entrapment of water in the backfill. The perforated pipe should consist of 4-inch-diameter, ABS SDR-35 or PVC Schedule 40 with the perforations laid down. The pipe should be embedded in  $\frac{3}{4}$ - to  $1\frac{1}{2}$ -inch open-graded gravel wrapped in filter fabric. The gravel should be at least one foot wide and extend at least one foot up the wall above the footing and drainage outlet. Drainage gravel and piping should not be placed below outlets and weepholes. Filter fabric should consist of Mirafi 140N, or equal. Outlet pipes should be directed to positive drainage devices.

The use of weepholes may be considered in locations where aesthetic issues from potential nuisance water are not a concern. Weepholes should be 2 inches in diameter and provided at least every 6 feet on center. Where weepholes are used, perforated pipe may be omitted from the gravel subdrain.

Retaining walls supporting backfill should also be coated with a moisture-proofing compound or covered with such material to inhibit infiltration of moisture through the walls. Moisture-proofing material should cover any portion of the back of wall that will be in contact with soil and should lap over and cover the top of footing. A drainage panel should be provided between the water proofing and soil backfill. The panel should extend from the top of the subdrain gravel to within 12 inches of finish grade. The top of footing should be finished smooth with a trowel to inhibit the infiltration of water through the wall. The project structural engineer should provide specific recommendations for moisture-proofing, water stops, and joint details.

#### **6.4.6 Footing Observations**

Footing excavations should be observed by the project geotechnical consultant to verify that they have been excavated into competent bearing soils and to the minimum embedment recommended herein. These observations should be performed prior to placement of forms or reinforcement. The excavations should be trimmed neat, level, and square. Loose, sloughed or moisture-softened materials and debris should be removed prior to placing concrete.

#### **6.4.7 Retaining Wall Backfill**

Onsite soils may be used to backfill retaining walls. The project geotechnical consultant should approve all backfill used for retaining walls. Wall backfill should be moisture-conditioned to slightly over the optimum moisture content; placed in lifts no greater than 12 inches in thickness, and then mechanically compacted with appropriate equipment to at least 90 percent of the laboratory standard. Hand-operated compaction equipment should be used to compact the backfill placed immediately adjacent the wall to avoid damage to the wall. Flooding or jetting of backfill material is not recommended.

### **6.5 EXTERIOR FLATWORK**

Exterior flatwork should be a minimum 4 inches thick. Cold joints or saw cuts should be provided at least every 10 feet in each direction. Special jointing detail should be provided in areas of block-outs, notches, or other irregularities to avoid cracking at points of high stress. Subgrade soils below flatwork should be moistened to achieve a minimum of 100 percent of optimum moisture content to a depth of

12 inches. Moistening should be accomplished by lightly spraying the area over a period of a few days just prior to pouring concrete. The geotechnical consultant should observe and verify the density and moisture content of subgrade soils prior to pouring concrete to ensure that the required compaction and pre-moistening recommendations have been met.

Drainage from flatwork areas should be directed to local area drains or other appropriate collection devices designed to carry runoff water to the street or other approved drainage structures. Flatwork adjacent entry points to structures should have a minimum slope of 0.5% away from the structure.

## **6.6 CONCRETE MIX DESIGN**

Laboratory testing of near-surface soils for soluble sulfate content indicates soluble sulfate concentration of up to 0.003%. We recommend following the procedures provided in ACI 318, Section 4.3, Table 4.3.1 for **negligible** sulfate exposure. Upon completion of rough grading, an evaluation of as-graded conditions and further laboratory testing should be completed for the site to confirm or modify the recommendations provided in this section.

## **6.7 PRELIMINARY PAVEMENT DESIGN**

### **6.7.1 Preliminary Pavement Structural Sections**

Based on the soil conditions present at the site and estimated traffic index, preliminary pavement structural sections are recommended in Table 6.4. Based on the onsite soil description and results of lab tests, “R-value” of 25 was utilized for the near-surface soil in this preliminary pavement design. The sections provided below are for planning purposes only and should be re-evaluated subsequent to site grading. Final pavement sections should be based on actual R-value testing of in-place soils and analysis of anticipated traffic.

### **6.7.2 Subgrade Preparation**

Prior to placement of pavement elements, subgrade soils should be moisture-conditioned to at least 100 percent of the optimum moisture content then compacted to at least 90 percent of the laboratory determined maximum dry density. Areas observed to pump or yield under vehicle traffic should be removed and replaced with firm and unyielding compacted soil or aggregate base materials.

### **6.7.3 Aggregate Base**

Aggregate base should be moisture conditioned to slightly over the optimum moisture content, placed in lifts no greater than 6 inches in thickness, then compacted to at least 95 percent of the laboratory standard (ASTM D 1557). Aggregate base materials should be Class 2 Aggregate Base conforming to Section 26-1 of the latest edition of the Caltrans Standard Specifications, Crushed Aggregate Base conforming to Section 200-2.2 of the latest edition of the Standard Specifications for Public Works Construction (Greenbook) or Crushed Miscellaneous Base conforming to Section 200-2.4 of the Greenbook.

**TABLE 6.4**  
**PRELIMINARY PAVEMENT STRUCTURAL SECTIONS**

Location	Traffic Index	Asphaltic Concrete (inches)	Portland Cement Concrete (inches)	Concrete Pavers (mm)	Aggregate Base (inches)
Entryway and Driveway	6.0	3.0	--	--	10.0
		4.0	--	--	8.0
		--	--	80	10.0
		--	7.0	--	--
Side Streets	5.0	3.0	--	--	7.0

#### 6.7.4 Asphaltic Concrete

Aggregate base should be moisture conditioned to slightly over the optimum moisture content, placed in lifts no greater than 6 inches in thickness, then compacted to at least 95 percent of the laboratory standard (ASTM D 1557). Aggregate base materials should be Class 2 Aggregate Base conforming to Section 26-1 of the latest edition of the Caltrans Standard Specifications, Crushed Aggregate Base conforming to Section 200-2.2 of the latest edition of the Standard Specifications for Public Works Construction (Greenbook) or Crushed Miscellaneous Base conforming to Section 200-2.4 of the Greenbook.

#### 6.7.5 Concrete Paver

Aggregate Concrete pavers should conform to the requirements of ASTM C 936. Construction of the pavers, including bedding sand, should follow manufacturer's specifications. Typical thickness of bedding sand is about 1 inch. The gradation of bedding sand should meet the requirement in Table 6.5.

**TABLE 6.5**  
**Gradation for Sand Bedding**

Sieve Size	Percent Passing
$\frac{3}{8}$ "	100
<b>No. 4</b>	95 - 100
<b>No. 8</b>	80 - 100
<b>No. 16</b>	50 - 85
<b>No. 30</b>	25 - 60
<b>No. 50</b>	5 - 30
<b>No. 100</b>	0 - 10
<b>No. 200</b>	0 - 1

### **6.7.6 Portland Cement Concrete**

Portland cement concrete used to construct concrete paving should conform to Section 201 of the Greenbook and should have a minimum compressive strength of 3,250 pounds per square inch (psi) at 28 days. Reinforcement and jointing of concrete pavement sections should be designed according to the minimum recommendations provided by the Portland Cement Association (PCA). For rigid pavement, transverse and longitudinal contraction joints should be provided at spacing no greater than 15 feet. Score joints may be constructed by saw cutting to a depth of  $\frac{1}{4}$  of the slab thickness. Expansion/cold joints may be used in lieu of score joints. Such joints should be properly sealed and provided with a key or dowels. Where traffic will traverse over edges of concrete paving (not including joints), the edges should be thickened by 20% of the design thickness toward the edge over a horizontal distance of 5 feet.

Trash pickup areas should be provided with a concrete slab where the bins will be picked up and extend at least 3 feet past the front wheel landing areas. The slab should be at least 7 inches thick and be reinforced with No. 4 bars spaced at 24 inches on centers, both ways. The slabs should be provided transverse and longitudinal joints spacing as specified above. Dowels or a keyway should be provided at all cold joints.

## **6.8 POST GRADING CONSIDERATIONS**

### **6.8.1 Site Drainage and Irrigation**

The ground immediately adjacent to foundations should be provided with positive drainage away from the structures in accordance with 2016 CBC, Section 1804.3. However, the minimum ground slope may be reduced to 2% in consideration of soils and climatic factors. No rain or excess water should be allowed to pond against structures such as walls, foundations, flatwork, etc.

Excessive irrigation water can be detrimental to the performance of the proposed site development. Water applied in excess of the needs of vegetation will tend to percolate into the ground. Such percolation can lead to nuisance seepage and shallow perched groundwater. Seepage can form on slope faces, on the faces of retaining walls, in streets, or other low-lying areas. These conditions could lead to adverse effects such as the formation of stagnant water that breeds insects, distress or damage of trees, surface erosion, slope instability, discoloration and salt buildup on wall faces, and premature failure of pavement. Excessive watering can also lead to elevated vapor emissions within buildings that can damage flooring finishes or lead to mold growth inside the home.

Key factors that can help mitigate the potential for adverse effects of overwatering include the judicious use of water for irrigation, use of irrigation systems that are appropriate for the type of vegetation and geometric configuration of the planted area, the use of soil amendments to enhance moisture retention, use of low-water demand vegetation, regular use of appropriate fertilizers, and seasonal adjustments of irrigation systems to match the water requirements of vegetation. Specific recommendations should be provided by a landscape architect or other knowledgeable professional.

### **6.8.2 Utility Trenches**

Trench excavations should be constructed in accordance with the recommendations contained in Section 6.1.7 of this report. Trench excavations must also conform to the requirements of Cal/OSHA.

Trench backfill materials and compaction criteria should conform to the requirements of the local municipalities. As a minimum, utility trench backfill should be compacted to at least 90 percent of the laboratory standard. Trench backfill should be brought to moisture content slightly over optimum, placed in lifts no greater than 12 inches in thickness, and then mechanically compacted with appropriate equipment to at least 90 percent of the laboratory standard. The project geotechnical consultant should perform density testing, along with probing, to test compaction. Site conditions are generally not suitable for jetting of trench backfill and jetting should not be completed without prior approval from the project geotechnical consultant.

Within shallow trenches (less than 18 inches deep) where pipes may be damaged by heavy compaction equipment, imported clean sand having a SE of 30 or greater may be utilized. The sand should be placed in the trench, thoroughly watered, and then compacted with a vibratory compactor. For utility trenches located below a 1:1 (H:V) plane projecting downward from the outside edge of the adjacent footing base or crossing footing trenches, concrete or slurry should be used as trench backfill.

## **6.9 PLAN REVIEW AND CONSTRUCTION SERVICES**

We recommend *Albus-Keefe & Associates, Inc.* be engaged to review any future development plans, including civil plans (grading plans), foundation plans, and proposed structural loads, prior to construction. This is to verify that the assumptions of this report are valid and that the preliminary conclusions and recommendations contained in this report have been properly interpreted and are incorporated into the project plans and specifications. If we are not provided the opportunity to review these documents, we take no responsibility for misinterpretation of our preliminary conclusions and recommendations.

We recommend that a geotechnical consultant be retained to provide soil engineering services during construction of the project. These services are to observe compliance with the design, specifications or recommendations, and to allow design changes in the event that subsurface conditions differ from those anticipated prior to the start of construction.

If the project plans change significantly from the assumed development described herein, the project geotechnical consultant should review our preliminary design recommendations and their applicability to the revised construction. If conditions are encountered during construction that appear to be different than those indicated in this report or subsequent design reports, the project geotechnical consultant should be notified immediately. Design and construction revisions may be required.

## 7.0 LIMITATIONS

This report is based on the proposed development and geotechnical data as described herein. The materials described in other literature are believed representative of the total project area, and the conclusions and recommendations contained in this report are presented on that basis. However, soil materials can vary in characteristics between points of exploration, both laterally and vertically, and those variations could affect the conclusions and recommendations contained herein. As such, observation and testing by a geotechnical consultant during the grading and construction phases of the project are essential to confirming the basis of this report.

This report has been prepared consistent with that level of care being provided by other professionals providing similar services at the same locale and time period. The contents of this report are professional opinions and as such, are not to be considered as a guaranty or warranty.

This report should be reviewed and updated after a period of one year or if the site ownership or project concept changes from that described herein.

This report has been prepared for the exclusive use of **Sheldon Development, LLC** to assist the project consultants in the design of the proposed development. This report has not been prepared for use by parties or projects other than those named or described herein. This report may not contain sufficient information for other parties or other purposes.


This report is subject to review by the controlling governmental agency.

Respectfully submitted,

***ALBUS-KEEFE & ASSOCIATES, INC***

  
Bidjan Ghahreman  
Associate Engineer  
G.E. 3111



  
David E. Albus  
Principal Engineer  
G.E. 2455



## REFERENCES


### Publications

- California Geologic Survey, Special Publication 117A, Guidelines for Evaluating and Mitigating Seismic Hazards in California, 2008.
- NCEER, "Proceedings of the NCEER Workshop on Evaluation of Liquefaction Resistance of Soils", Technical Report NCEER-97-0022, December 31, 1997.
- Saxton, K.E., W.J. Rawls, J.S. Romberger, and R.I. Papendick, "Estimating Generalized Soil-Water Characteristics From Texture," Soil Science Society of America, Journal 50(4), pg. 1031-1103, 1986.
- Seed, R.B., Cetin, K.O., Moss, R.E.S., Kammerer, A.M., Wu, J., Pestana, J.M., Riemer, M.F., Sancio, R.B., Bray, J.D., Kayen, R.E., and Faris, A., "Recent Advances in Soil Liquefaction Engineering: A Unified and Consistent Framework", 26<sup>th</sup> Annual ASCE Los Angeles Geotechnical Spring Seminar, Long Beach, California, April 30, 2003.
- Seed, H.B., Idriss, I.M., "Ground Motions and Soil Liquefaction During Earthquakes," published by the EERI, dated December 1982.
- Southern California Earthquake Center (SCEC), University of Southern California, "Recommended Procedures for Implementation of DMG Special Publication 117 Guidelines for Analyzing and Mitigating Liquefaction Hazards in California", March 1999.
- U.S.G.S., U.S. Seismic Design Maps, Version 3.1.0, July 2013.
- Tokimatsu, K. & Seed, H.B., "Evaluation of Settlement in Sands Due to Earthquake Shaking," Journal of Geotechnical Engineering, Vol. 113, No. 8, August, 1987.
- Idriss, I. M. (1995). H. B. Seed Memorial Lecture, University of California, Berkeley
- Youd, T.L., Hansen, C.M., and Bartlett, S.F., "Revised Multilinear Regression Equations for Prediction of Lateral Spread Displacement", ASCE Journal of Geotechnical and Geoenvironmental Engineering, December 2002.
- Youd, T.L., Idriss, I.M., Andrus, R.D., Arango, I., Castro, G., Christian, J., Dobry, R., Finn, W.D.L., Harder, L.F., Hynes, M.E., Ishihara, K., Koester, J.P., Liao, S.S.C., Marcuson, W.F., Martin, G.R., Mitchell, J.K., Moriwaki, Y., Power, M.S., Robertson, P.K., Seed, R.B., and Stokoe, K.H., "Liquefaction Resistance of Soils: Summary Report from the 1996 NCEER and 1998 NCEER/NSF Workshops on Evaluation of Liquefaction Resistance of Soils", Journal of Geotechnical and Geoenvironmental Engineering, October, 2001.

**Reports**

“Report of Preliminary Geotechnical Investigation, Proposed Condominium Complex, Old Grove Road and Frazee Road, Oceanside, California,” Prepared by Christian Wheeler Engineering (Project No. CWE 2050171.01), dated May 13, 2005.






SMALL LOT DETACHED  
83 UNITS  
1,660 - 1,820 - 1,940 S.F. - 2,037 S.F.  
61 GUEST STALLS  
2.73 STALLS/UNIT

OLD GROVE - FRAZEE DETACHED HOMES

CONCEPTUAL SITE PLAN

SEPTEMBER 22, 2017



**SUMMA**  
ARCHITECTURE  
5256 S. Mission Road, Suite 404  
Bonsall, CA 92003  
www.summarch.com  
760.724.1198

EXPLANATION	
(Locations Approximate)	
	- Exploratory Boring (this report)
	- Cone Penetration Test (CPT)(this report)
	- Percolation Well (this report)
	- Exploratory Boring (Christian Wheeler Eng. (05/13/2005))

ALBUS-KEEFE & ASSOCIATES, INC. GEOTECHNICAL CONSULTANTS		
GEOTECHNICAL MAP		
Job No.: 2551.00	Date: 12/19/18	Plate: 1



**APPENDIX A**  
**EXPLORATORY LOGS**

# EXPLORATION LOG

Project:				Location:				
Address:				Elevation:				
Job Number:		Client:		Date:				
Drill Method:		Driving Weight:		Logged By:				
Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests		
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)
<div style="text-align: center;">5</div> <div style="text-align: center;">10</div> <div style="text-align: center;">15</div> <div style="text-align: center;">20</div>		<b><u>EXPLANATION</u></b>  <div style="border: 1px solid black; padding: 5px; margin: 5px 0;">Solid lines separate geologic units and/or material types.</div> <div style="border: 1px dashed black; padding: 5px; margin: 5px 0;">Dashed lines indicate unknown depth of geologic unit change or material type change.</div> <p><b>Solid black rectangle</b> in Core column represents California Split Spoon sampler (2.5in ID, 3in OD).</p> <p><b>Double triangle</b> in core column represents SPT sampler.</p> <p><b>Vertical Lines</b> in core column represents Shelby sampler.</p> <p><b>Solid black rectangle</b> in Bulk column represents large bag sample.</p> <p><b><u>Other Laboratory Tests:</u></b>            Max = Maximum Dry Density/Optimum Moisture Content            EI = Expansion Index            SO4 = Soluble Sulfate Content            DSR = Direct Shear, Remolded            DS = Direct Shear, Undisturbed            SA = Sieve Analysis (1" through #200 sieve)            Hydro = Particle Size Analysis (SA with Hydrometer)            200 = Percent Passing #200 Sieve            Consol = Consolidation            SE = Sand Equivalent            Rval = R-Value            ATT = Atterberg Limits</p>						

**Albus-Keefe & Associates, Inc.**
Plate A-1





# EXPLORATION LOG

Project:					Location: B-1		
Address: 391 Frazee Rd, Oceanside, CA 92057					Elevation: 65.1		
Job Number: 2551.00		Client: Sheldon Development, LLC			Date: 11/10/2016		
Drill Method: Hollow-Stem Auger		Driving Weight: 140 lbs / 30 in			Logged By: MP		
Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests	
				Blows Per Foot	Core Bulk	Moisture Content (%)	Dry Density (pcf)  Other Lab Tests
		<b>ARTIFICIAL FILL (Af)</b> <u>Silty Sand (SM)</u> : Grayish brown, dry, loose, fine grained sand, trace fine gravel, trace organics, mica					Max EI SO4 DS
				6		1.6	Dist. 200
5		<b>ALLUVIUM (Qal)</b> <u>Silty Sand (SM)</u> : Gray, damp, loose, fine to medium grained sand, trace silt, mica		6		1.6	94
				6		11	92.3 200
		<u>Silt (ML)</u> : Medium brown, damp, medium stiff, trace clay, mica		7		1.8	87.6
10		<u>Silty Sand (SM)</u> : Gray, damp, loose, fine grained sand, trace silt, mica		6		7.4	Dist. SA
				7		1.2	91.7
				7		1.8	92.1
15		@ 15', Dark grayish brown, moist, fine to medium grained sand		8		18.1	86.7
		<u>Sand (SP)</u> : Gray, moist, medium dense, fine to medium grained sand, trace fine gravel, mica		16		3	96.4
20				15		3.7	86.3 SA
				8		36.8	85.5
		<u>Silt (ML)</u> : Medium brown, saturated, medium stiff, fine to medium grained sand, some clay, few sand, mica				30.4	91.5

# EXPLORATION LOG


Project:					Location: B-1				
Address: 391 Frazee Rd, Oceanside, CA 92057					Elevation: 65.1				
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 11/10/2016			
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: MP			

Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests		
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)
30		@ 30 ft, very soft to soft, fine grained sand, increased sand content, some sand		2				ATT
35		<u>Sandy Silt (ML)</u> : Medium brown, saturated, medium stiff		6				
40		<u>Silty Sand (SM)</u> : Medium grayish brown, saturated, medium dense, fine grained sand, mica		16				200
45				17				

**Albus-Keefe & Associates, Inc.**
Plate A-3

# EXPLORATION LOG

Project:						Location: B-1					
Address: 391 Frazee Rd, Oceanside, CA 92057						Elevation: 65.1					
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 11/10/2016					
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: MP					
Depth (feet)	Lith- ology	Material Description	Water	Samples			Laboratory Tests				
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests		
		<u>Silty Sand (SM)</u> : Brown, saturated, medium dense, fine to medium grained sand, mica		15							
		End of boring at 51.5 feet. Groundwater encountered at 24 feet. Backfilled with cement and bentonite.									











# EXPLORATION LOG

[illegible]

# EXPLORATION LOG

Project:				Location: B-2			
Address: 391 Frazee Rd, Oceanside, CA 92057				Elevation: 72.5			
Job Number: 2551.00		Client: Sheldon Development, LLC		Date: 11/10/2016			
Drill Method: Hollow-Stem Auger		Driving Weight: 140 lbs / 30 in		Logged By: MP			

Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests		
				Blows Per Foot	Core Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests
30		<u>Silt (ML)</u> : Medium brown, saturated, medium stiff, fine grained sand, trace sand, mica		6				
								
35		<u>Sandy Silt (ML)</u> : Medium brown, saturated, medium stiff, some silt, mica		4				ATT
								
40		<u>Silty Sand (SM)</u> : Medium brown, saturated, medium dense, fine grained sand, trace sand, mica		13				200
								
45		@ 40', Grayish brown, saturated		8				200
								
		<u>Sand with Silt (SP-SM)</u> : Grayish brown, saturated, medium dense, fine grained sand, mica		16				200
								

Albus-Keefe & Associates, Inc.
Plate A-6



# EXPLORATION LOG

Project:						Location: B-2					
Address: 391 Frazee Rd, Oceanside, CA 92057						Elevation: 72.5					
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 11/10/2016					
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: MP					
Depth (feet)	Lith- ology	Material Description	Water	Samples			Laboratory Tests				
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests		
				14							
		End of Boring at 51.5 feet. Groundwater at 25 feet. Backfilled with cement and bentonite									





# EXPLORATION LOG

[illegible]

# EXPLORATION LOG

Project:					Location: B-3				
Address: 391 Frazee Rd, Oceanside, CA 92057					Elevation: 68.1				
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 6/12/2018			
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: DDA			








Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests			
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests
30		<u>Sand (SP):</u> Gray, wet, loose, fine to coarse grained sand		4					
		<u>Silty Sand / Sandy Silt (SM/ML):</u> Grayish brown, wet, loose / soft to medium stiff, fine grained sand		4					
		Total Depth 31.5 feet Ground water at 17 feet Boring backfilled with bentonite 0-31.5 feet							

**Albus-Keefe & Associates, Inc.**
Plate A-9

# EXPLORATION LOG

Project:				Location: B-4			
Address: 391 Frazee Rd, Oceanside, CA 92057				Elevation: 61.7			
Job Number: 2551.00		Client: Sheldon Development, LLC		Date: 6/12/2018			
Drill Method: Hollow-Stem Auger		Driving Weight: 140 lbs / 30 in		Logged By: DDA			

Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests		
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)
		<u>Silty Sand (SM)</u> : Light gray, dry, fine grained sand						
		<u>Sand (SP)</u> : Light gray, damp, loose, fine to coarse grained sand		11			1.2	Dist.
		@ 4 ft, , damp to moist		7			2.2	93.8
5		@ 6 ft, , moist		8			3.2	95.1
		@ 10 ft, , very moist to wet, medium dense		15			24.3	90.6
15		<u>Silty Sand (SM)</u> : Gray, wet, loose to medium dense, fine to coarse grained sand		8				
		@ 15.5 ft, Ground water						
20		<u>Sand (SP)</u> : Gray, wet, loose, fine to coarse grained sand		5				
		Total Depth 21.5 feet Ground water at 15.5 feet Boring backfilled with bentonite 0-20 feet						

**Albus-Keefe & Associates, Inc.**
Plate A-10




# EXPLORATION LOG

Project:					Location: B-5				
Address: 391 Frazee Rd, Oceanside, CA 92057					Elevation: 58.7				
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 6/12/2018			
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: DDA			
Depth (feet)	Lith- ology	Material Description	Water	Samples			Laboratory Tests		
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests
		<u>Silty Sand (SM):</u> Light gray, damp, fine grained sand							
		<u>Sand (SP):</u> Gray, moist, medium dense, fine to coarse grained sand		20			2.7	99.9	
5				18			4.6	96.3	
		@ 6 ft, , very moist		15			24.4	91.6	
10		@ 10 ft, , wet		16			24	95.2	
		@ 11.5 ft, Ground water							
15		<u>Sand trace Silt (SP):</u> Gray, wet, medium dense, fine to medium grained sand		9					
20		@ 20 ft, loose to medium dense		8					
		Total Depth 21.5 feet Ground water at 11.5 feet Boring backfilled with bentonite 0-21.5 feet							

Albus-Keefe & Associates, Inc.

Plate A-11

# EXPLORATION LOG

Project:						Location: B-6					
Address: 391 Frazee Rd, Oceanside, CA 92057						Elevation: 63.4					
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 6/12/2018					
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: DDA					
Depth (feet)	Lith- ology	Material Description	Water	Samples			Laboratory Tests				
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests		
5		<b>ARTIFICIAL FILL (Af)</b> <u>Silty Sand (SM)</u> : Tan to light gray, dry to damp, fine grained sand		12			11	85.9	Max EI SO4 DS		
		<u>Sandy Silt / Interbedded Sand (ML/SP)</u> : Tan to light gray, damp, medium stiff / loose, fine grained sand, some debris									
		<b>ALLUVIUM (Qal)</b> <u>Sand (SP)</u> : Light gray, damp to moist, loose, fine to coarse grained sand									
		@ 7.5 ft, , very moist, very loose									
		@ 10 ft, , wet									
		@ 13 ft, Ground water									
		<u>Sand with Silt (SP-SM)</u> : Gray, wet, loose to medium dense, fine to medium grained sand, some coarse grained sand									
		@ 20 ft, medium dense, fine to coarse grained sand									

Albus-Keefe & Associates, Inc.

Plate A-12

# EXPLORATION LOG

Project:				Location: B-6			
Address: 391 Frazee Rd, Oceanside, CA 92057				Elevation: 63.4			
Job Number: 2551.00		Client: Sheldon Development, LLC		Date: 6/12/2018			
Drill Method: Hollow-Stem Auger		Driving Weight: 140 lbs / 30 in		Logged By: DDA			

Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests		
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)
30		<u>Silty Sand (SM)</u> : Grayish brown, wet, loose to medium dense, fine grained sand		8				200
35		<u>Sandy Silt (ML)</u> : Grayish brown, wet, soft, fine grained sand		3				200
40		<u>Sand with Silt (SP)</u> : Gray, wet, very loose, fine to medium grained sand		3				200
45		@ 40 ft, medium dense to dense		14				
		@ 45 ft, medium dense		12				200

**Albus-Keefe & Associates, Inc.**
Plate A-13

# EXPLORATION LOG

Project:					Location: B-6				
Address: 391 Frazee Rd, Oceanside, CA 92057					Elevation: 63.4				
Job Number: 2551.00			Client: Sheldon Development, LLC			Date: 6/12/2018			
Drill Method: Hollow-Stem Auger			Driving Weight: 140 lbs / 30 in			Logged By: DDA			
Depth (feet)	Lith- ology	Material Description	Water	Samples		Laboratory Tests			
				Blows Per Foot	Core	Bulk	Moisture Content (%)	Dry Density (pcf)	Other Lab Tests
				11					
		Total Depth 51.5 feet Ground water at 13.0 feet Boring backfilled with bentonite 0-51.5 feet							
<div> <div>Albus-Keefe &amp; Associates, Inc.</div> <div>Plate A-14</div> </div>									



**APPENDIX B**

**LABORATORY TEST PROGRAM**

## **LABORATORY TESTING PROGRAM**

### **Soil Classification**

Soils encountered within the exploratory borings were initially classified in the field in general accordance with the visual-manual procedures of the Unified Soil Classification System (Test Method ASTM D 2488). The samples were re-examined in the laboratory and classifications reviewed and then revised where appropriate. The assigned group symbols are presented in the Boring Logs, Appendix A.

### **In Situ Moisture and Density**

Moisture content and unit dry density of in-place soil materials were determined in representative strata. Test data are summarized in the Boring Logs, Appendix A.

### **Laboratory Maximum Dry Density**

Maximum dry density and optimum moisture content of onsite soils were determined for a selected soil sample in general accordance with Method A of ASTM D 1557. Pertinent test values are given on Table B-1.

### **Grain Size Analysis**

Grain size was performed on selected samples to verify visual classifications performed in the field. The test was performed in accordance with ASTM D 422. Test results are graphically presented on Plate B-1 through B-5.

### **Expansion Potential**

An Expansion Index test was performed on a selected sample in accordance with Test Method ASTM D-4829. The expansion potential classification was determined on the basis of the expansion index value. The test result and expansion potential are presented on Table B-1.

### **Soluble Sulfate Analysis**

A chemical analysis was performed on a selected sample to determine soluble sulfate content in accordance with Test Method No performed this test. California 417. Their test result is included on Table B-1.

### **Direct Shear**

The Coulomb shear strength parameters, angle of internal friction and cohesion, were determined for bulk samples obtained from our borings. Our laboratory performed the test in general conformance with Test Method ASTM D 3080. The samples were remolded to 90 percent of maximum dry density and 2 percentage points over optimum. Three specimens were prepared for each test, artificially saturated, and then sheared under varied loads at an appropriate constant rate of strain. Results are graphically presented on Plate B-8 and B-9.


**Consolidation**

Consolidation Tests were performed in general conformance with Test Method ASTM D 2435. Axial loads were applied in several increments to a laterally restrained 1-inch-thick sample. Loads were applied in geometric progression by doubling the previous load, and the resulting deformations were recorded at selected time intervals. The test samples were inundated at a selected surcharge loading in order to evaluate the effects of a sudden increase in moisture content. Results of these tests are graphically presented on Plates B-6 and B-7.

**TABLE B-1  
SUMMARY OF LABORATORY TEST RESULTS**

<b>Boring No.</b>	<b>Sample Depth (ft)</b>	<b>Soil Description</b>	<b>Test Results</b>	
B-1	0-5	Silty Sand (SM)	Maximum Dry Density: Optimum Moisture Content: Expansion Index: Expansion Potential: Soluble Sulfate Content: Sulfate Exposure: Percent Passing #200 Sieve:	122.5 pcf 11.0% 0 Very Low 0.000% Negligible 19.2
B-1	6	Silty Sand (SM)	Percent Passing #200 Sieve:	24.0
B-1	40	Silty Sand (SM)	Percent Passing #200 Sieve:	24.9
B-2	4	Sand (SP)	Percent Passing #200 Sieve:	1.7
B-2	8	Sand (SP)	Percent Passing #200 Sieve:	2.2
B-2	30	Sandy Silt (ML)	Liquid Limit: Plasticity Index:	39% 7%
B-2	35	Silty Sand (SM)	Percent Passing #200 Sieve:	48.2
B-2	40	Silty Sand (SM)	Percent Passing #200 Sieve:	20.8
B-2	45	Sand with Silt (SP-SM)	Percent Passing #200 Sieve:	8.4
B-6	0-5	Silty Sand (SM)	Maximum Dry Density: Optimum Moisture Content: Expansion Index: Expansion Potential: Soluble Sulfate Content: Sulfate Exposure:	121.0 pcf 11.0% 0 Very Low 0.003% Negligible
B-6	15	Sand with Silt (SP-SM)	Percent Passing #200 Sieve:	10.2
B-6	20	Sand with Silt (SP-SM)	Percent Passing #200 Sieve:	6.4
B-6	25	Silty Sand (SM)	Percent Passing #200 Sieve:	40.2
B-6	30	Sandy Silt (ML)	Percent Passing #200 Sieve:	77.4
B-6	35	Sand with Silt (SP-SM)	Percent Passing #200 Sieve:	8.2
B-6	45	Sand with Silt (SP-SM)	Percent Passing #200 Sieve:	7.1
P-1	0-5	Silty Sand (SM)	R-value	73


GRAIN SIZE DISTRIBUTION



Job Number	Location	Depth	Description
2551.00	B-1	10 feet	Silty Sand (SM)

# GRAIN SIZE DISTRIBUTION

COBBLES	GRAVEL		SAND			SILT AND CLAY
	COARSE	FINE	COARSE	MEDIUM	FINE	




Job Number	Location	Depth	Description
2551.00	B-1	20 feet	Sand trace Silt (SP)

# GRAIN SIZE DISTRIBUTION

COBBLES	GRAVEL		SAND			SILT AND CLAY
	COARSE	FINE	COARSE	MEDIUM	FINE	


U.S. Standard Sieve Sizes



# GRAIN SIZE DISTRIBUTION

COBBLES	GRAVEL		SAND			SILT AND CLAY
	COARSE	FINE	COARSE	MEDIUM	FINE	

U.S. Standard Sieve Sizes




Job Number	Location	Depth	Description
2551.00	P-1	9 feet	Silty Sand (SM)

# GRAIN SIZE DISTRIBUTION

COBBLES	GRAVEL		SAND			SILT AND CLAY
	COARSE	FINE	COARSE	MEDIUM	FINE	

U.S. Standard Sieve Sizes




Job Number	Location	Depth	Description
2551.00	P-2	6 feet	Sand trace Silt (SP)




# CONSOLIDATION TEST - ASTM D2435

Boring / Sample No.	B-2	Depth:	2.0'	Date	11-15-16
---------------------	-----	--------	------	------	----------






CONSOLIDATION



Job Number	Location	Depth	Description
2551.00	B-3	6	Sandy Silt / Sand with Silt


Initial Dry Density (pcf)	Initial Moisture Content (%)	Final Moisture Concent (%)
50.8	94.6	55.5

Specimen No.	1	2	3
Normal Stress (ksf)	1	2	4
Peak Shear Stress (ksf)	0.648	1.32	2.376
Peak Displacement (in)	0.004	0.006	0.008
Ultimate Shear Stress (ksf)	0.636	1.296	2.376
Ultimate Displacement (in)	0.25	0.25	0.25
Initial Dry Density (pcf)	110.3	110.3	110.3
Initial Moisture Content (%)	11	11	11
Strain Rate (in/min)	0.01		






Strain Legend	
◆	1
●	2
▲	4

Strength Legend	
□	Peak
○	Ultimate

SAMPLE LOCATION	SAMPLE TYPE	SAMPLE DESCRIPTION
B-1 @ 0-5 feet	90% of 122.5 pcf @ 11%	Sandy Clay (CL)
 <b>ALBUS-KEEFE &amp; ASSOCIATES, INC.</b> GEOTECHNICAL CONSULTANTS		Job No: 2551.00
		Plate No: B-8


**DIRECT SHEAR**

Specimen No.	1	2	3
Normal Stress (ksf)	1	2	4
Peak Shear Stress (ksf)	1.296	2.016	3.384
Peak Displacement (in)	0.011	0.005	0.003
Ultimate Shear Stress (ksf)	1.044	1.512	2.904
Ultimate Displacement (in)	0.25	0.25	0.25
Initial Dry Density (pcf)	108.8	108.8	108.8
Initial Moisture Content (%)	11.1	11.1	11.1
Strain Rate (in/min)	0.01		



Strain Legend	
◆	1
●	2
▲	4

Strength Legend	
□	Peak
○	Ultimate

SAMPLE LOCATION	SAMPLE TYPE	SAMPLE DESCRIPTION
B-6 @ 0-5 feet	90% of 121 pcf @ 11%	Sandy Clay (CL)
 <b>ALBUS-KEEFE &amp; ASSOCIATES, INC.</b> GEOTECHNICAL CONSULTANTS		Job No: 2551.00
		Plate No: B-9

**DIRECT SHEAR**

## **APPENDIX C**


### **EXPLORATORY LOGS AND LABORATORY TEST RESULTS BY OTHERS**

**(Christian Wheeler Engineering, May 13, 2005)**

## LOG OF TEST BORING NUMBER B-1

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
		<u>Topsoil</u> : Medium brownish-gray, moist, loose, SILTY SAND (SM).						
2		<u>Alluvium (Qal)</u> : Medium gray, moist, loose to medium dense, SILTY SAND (SM), very fine to fine-grained, micaceous.	CK		21	14.8	110.2	SS
4		Light to medium gray, moist, loose to medium dense, SILTY SAND (SM), micaceous, friable.  At 10 feet becomes medium dense.  Groundwater at 12 feet.	SPT		12			SA, MD,
6			Cal		27	5.9	87.6	SS, DS
8								
10			Cal		10			
12			Cal		30			
14		Light to medium gray, saturated, medium dense, POORLY GRADED SAND (SP).	SPT		22			SA
16			Cal		41	19.4	105.7	
18								
20			SPT		23			

Boring continued on Plate No. 3.

  
 CHRISTIAN WHEELER  
 ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY: HF	DATE: April 2005
JOB NO.: 2050171	PLATE NO.: 2

## LOG OF TEST BORING NUMBER B-1 (Continued)

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
22		<u>Alluvium (Qal)</u> : Light to medium gray, saturated, medium dense, SILTY SAND (SM), micaceous, friable.  At 2½ feet becomes loose.	Cal		22			
24		Medium gray, saturated, very soft, SANDY SILT (ML), very fine-grained, micaceous, with trace clay.  At 8½ feet becomes soft.	SPT		3			SA
26								
28								
30			SPT		4			
32								
34			SPT		4			
36								
38								
40		Medium gray, saturated, medium dense, SILTY SAND (SM), very fine to fine-grained, micaceous.	SPT		19			

Boring continued on Plate No. 4.

\* No sample recovery.



CHRISTIAN WHEELER  
ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY:	HF	DATE:	April 2005
JOB NO.:	2050171	PLATE NO.:	3

## LOG OF TEST BORING NUMBER B-1 (Continued)

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
42		<u>Alluvium (Qal)</u> : Medium brown, saturated, medium dense, SILTY SAND (SM), very fine to fine-grained, micaceous.						
44		At 43½ feet becomes medium dense to dense.	SPT		33			SA
46								
48		At 48½ feet becomes medium dense.	SPT		28			
50		Boring terminated at 50 feet.						
52								
54								
56								
58								
60								

  
**CHRISTIAN WHEELER**  
 ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY: HF  
 JOB NO.: 2050171


DATE: April 2005  
 PLATE NO.: 4



## LOG OF TEST BORING NUMBER B-2

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
		<u>Topsoil:</u> Medium brownish-gray, moist, loose, SILTY SAND (SM).						
2		<u>Alluvium (Qal):</u> Medium gray, moist, medium dense, SILTY SAND (SM), very fine to fine-grained, micaceous.	Cal		29	18.9	93.2	
4		Light to medium gray, moist, medium dense, SILTY SAND (SM), micaceous, friable.  At 10½ feet becomes wet.    Groundwater at 12 feet.	SPT		14			
6			Cal		23	8.2	100.0	
8								
10			SPT		15			
12			Cal		25	4.4	93.7	
14								
16			SPT		16			
18			Cal		33	24.7	94.3	
20		At 19½ feet becomes loose.	SPT		9			

Boring continued on Plate No. 6.



### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY: HF

DATE: April 2005

JOB NO.: 2050171

PLATE NO.: 5

## LOG OF TEST BORING NUMBER B-2 (continued)

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
22		<u>Alluvium (Qal)</u> : Light to medium gray, saturated, loose to medium dense, SILTY SAND (SM), micaceous, friable.	Cal		14	32.2	86.6	
24		Medium gray, saturated, soft, SANDY SILTY (ML) very fine-grained, micaceous, with trace clay.						
26								
28								
30			SPT*		4			
32								
34								
36								
38								
40			SPT*		3			

Boring continued on Plate No. 7.

\* No sample recovery.



CHRISTIAN WHEELER  
ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY:	HF	DATE:	April 2005
JOB NO.:	2050171	PLATE NO.:	6

## LOG OF TEST BORING NUMBER B-2 (continued)

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 12 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
42		<u>Alluvium (Qal)</u> : Medium gray, saturated, very soft to soft, SANDY SILT (ML), very fine-grained, micaceous, with trace clay.						
44								
46								
48								
50		At 49 feet becomes medium stiff.	SPT		19			
52		Boring terminated at 50 feet.						
54								
56								
58								
60								

  
**CHRISTIAN WHEELER**  
 ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California


BY: HF  
 JOB NO.: 2050171

DATE: April 2005  
 PLATE NO.: 7

## LOG OF TEST BORING NUMBER B-3

Date Excavated: 3/8/2005  
 Equipment: A-300  
 Existing Elevation: N/A  
 Finish Elevation: N/A

Logged by: AKN  
 Project Manager: CHC  
 Depth to Water: 10 feet  
 Drive Weight: 140 lbs./30"

DEPTH (feet)	GRAPHIC LOG	SUMMARY OF SUBSURFACE CONDITIONS	SAMPLES		PENETRATION (blows/foot)	MOISTURE (%)	DRY UNIT WT. (pcf)	LABORATORY TESTS
			SAMPLE TYPE	BULK				
2		<u>Topsoil</u> : Medium brownish-gray, moist, loose to medium dense, SILTY SAND (SM), with roots.						SS
4		<u>Alluvium (Qal)</u> : Light to medium gray, moist, medium dense, SILTY SAND-POORLY GRADED SAND (SM-SP), poorly graded, micaceous, friable.	Cal		19	17.6	87.7	SA, SS,
6			Cal		22	4.8	94.4	MD, DS
8		At 8½ feet becomes very moist.						
10		Groundwater at 10 feet.	Cal		25	4.8	94.0	
12								
14								
16								
18								
20			Cal		33	21.2	103.6	

Boring terminated at 20 feet.

  
 CHRISTIAN WHEELER  
 ENGINEERING

### PROPOSED RETAIL CENTER

Frazee Road & Old Grove Road, Oceanside, California

BY: HF	DATE: April 2005
JOB NO.: 2050171	PLATE NO.: 8

# LABORATORY TEST RESULTS

PROPOSED CONDOMINIUM COMPLEX  
OLD GROVE ROAD AND FRAZEE ROAD  
OCEANSIDE, CALIFORNIA

## MAXIMUM DRY DENSITY AND OPTIMUM MOISTURE CONTENT (ASTM D1557)

<b>Sample Location</b>	<b>Boring B-1 @ 4'-9'</b>	<b>Boring B-3 @ 1½'-5'</b>
Sample Description	Lt. gray, silty sand	Lt. gray, silty sand
Maximum Density	117.0 pcf	115.0 pcf
Optimum Moisture	11.8 %	11.0 %

## DIRECT SHEAR (ASTM D3080)

<b>Sample Location</b>	<b>Boring B-1 @ 4'-9'</b>	<b>Boring B-3 @ 1½'-5'</b>
Sample Type	Remolded to 90 %	Remolded to 90 %
Friction Angle	31 °	32 °
Cohesion	125 psf	175 psf


## GRAIN SIZE DISTRIBUTION (ASTM D422)


<b>Sample Location</b>	<b>Boring B-1 @ 4'-9'</b>	<b>Boring B-1 @ 14'-15'</b>	<b>Boring B-1 @ 24'-25'</b>
<i>Sieve Size</i>	<i>Percent Passing</i>	<i>Percent Passing</i>	<i>Percent Passing</i>
3/8"			100
#4			98
#8	100	100	98
#16	97	98	98
#30	87	80	97
#50	89	32	95
#100	28	10	90
#200	14	4	78


<b>Sample Location</b>	<b>Boring B-1 @ 44'-45'</b>	<b>Boring B-3 @ 1½'-5'</b>
<i>Sieve Size</i>	<i>Percent Passing</i>	<i>Percent Passing</i>
#4		100
#8		99
#16	100	95
#30	97	80
#50	80	47
#100	49	21
#200	20	10

## SOLUBLE SULFATES (CALIFORNIA TEST 417)

<b>Sample Location</b>	<b>Boring B-1 @ 0'-4'</b>	<b>Boring B-1 @ 4'-9'</b>	<b>Boring B-3 @ 0-1½'</b>	<b>Boring B-3 @ 1½'-5'</b>
Soluble Sulfate	0.001 % (SO <sub>4</sub> )	0.001 % (SO <sub>4</sub> )	0.001 % (SO <sub>4</sub> )	0.001 % (SO <sub>4</sub> )



 <b>CHRISTIAN WHEELER</b> ENGINEERING	JOB NAME: CDC Administration Building	SAMPLE NO.: Boring B-1 @ 11.5'
	JOB NUMBER: 2050171	PLATE NUMBER: 10



JOB NAME:  
CDC Administration Building

SAMPLE NO.:  
Boring B-1 @ 21.5'

JOB NUMBER:  
2050171

PLATE NUMBER:  
11

**PRELIMINARY GEOTECHNICAL INVESTIGATION,  
PROPOSED RESIDENTIAL DEVELOPMENT,  
INTERSECTION OF OLD GROVE ROAD AND FRAZEE ROAD,  
OCEANSIDE, CALIFORNIA**

**VOLUME 2**

***Dated:***  
December 19, 2018

***Revised***  
March 2, 2020

***Prepared for:***

Mr. Steve Sheldon  
Sheldon Development, LLC  
901 Dove Street, Suite 140  
Newport Beach, California 92660

***Prepared by:***

Albus-Keefe & Associates, Inc.  
J.N. 2551.00



## **APPENDIX D**

### **LIQUEFACTION ANALYSES USING CPT DATA AND ANALYSIS OF LATERAL SPREAD**

## TABLE OF CONTENTS

<b>CPT-1 results</b>	
Summary data report	1
Vertical settlements summary report	4
<b>CPT-2 results</b>	
Summary data report	5
Vertical settlements summary report	8
<b>CPT-3 results</b>	
Summary data report	9
Vertical settlements summary report	12
<b>CPT-4 results</b>	
Summary data report	13
Vertical settlements summary report	16
<b>CPT-5 results</b>	
Summary data report	17
Vertical settlements summary report	20
<b>CPT-6 results</b>	
Summary data report	21
Vertical settlements summary report	24
<b>CPT-7 results</b>	
Summary data report	25
Vertical settlements summary report	28
<b>CPT-8 results</b>	
Summary data report	29
Vertical settlements summary report	32
<b>CPT-9 results</b>	
Summary data report	33
Vertical settlements summary report	36
<b>CPT-10 results</b>	
Summary data report	37
Vertical settlements summary report	40
<b>CPT-11 results</b>	
Summary data report	41
Vertical settlements summary report	44
<b>CPT-12 results</b>	
Summary data report	45
Vertical settlements summary report	48
<b>CPT-13 results</b>	
Summary data report	49
Vertical settlements summary report	52
<b>CPT-14 results</b>	
Summary data report	53
Vertical settlements summary report	56
<b>CPT-15 results</b>	
Summary data report	57
Vertical settlements summary report	60
<b>CPT-16 results</b>	
Summary data report	61

Vertical settlements summary report	64
<b>CPT-17 results</b>	
Summary data report	65
Vertical settlements summary report	68
<b>CPT-18 results</b>	
Summary data report	69
Vertical settlements summary report	72
<b>CPT-19 results</b>	
Summary data report	73
Vertical settlements summary report	76
<b>CPT-20 results</b>	
Summary data report	77
Vertical settlements summary report	80
<b>CPT-21 results</b>	
Summary data report	81
Vertical settlements summary report	84
<b>CPT-22 results</b>	
Summary data report	85
Vertical settlements summary report	88
<b>CPT-23 results</b>	
Summary data report	89
Vertical settlements summary report	92
<b>CPT-24 results</b>	
Summary data report	93
Vertical settlements summary report	96
<b>CPT-25 results</b>	
Summary data report	97
Vertical settlements summary report	100
<b>CPT-26 results</b>	
Summary data report	101
Vertical settlements summary report	104
<b>CPT-27 results</b>	
Summary data report	105
Vertical settlements summary report	108
<b>CPT-28 results</b>	
Summary data report	109
Vertical settlements summary report	112
<b>CPT-29 results</b>	
Summary data report	113
Vertical settlements summary report	116
<b>CPT-30 results</b>	
Summary data report	117
Vertical settlements summary report	120
<b>CPT-31 results</b>	
Summary data report	121
Vertical settlements summary report	124
<b>CPT-32 results</b>	
Summary data report	125
Vertical settlements summary report	128
<b>CPT-33 results</b>	

Summary data report	129
Vertical settlements summary report	132
<b>CPT-34 results</b>	
Summary data report	133
Vertical settlements summary report	136
<b>CPT-35 results</b>	
Summary data report	137
Vertical settlements summary report	140
<b>CPT-36 results</b>	
Summary data report	141
Vertical settlements summary report	144
<b>CPT-37 results</b>	
Summary data report	145
Vertical settlements summary report	148
<b>CPT-38 results</b>	
Summary data report	149
Vertical settlements summary report	152
<b>CPT-40 results</b>	
Summary data report	153
Vertical settlements summary report	156
<b>CPT-41 results</b>	
Summary data report	157
Vertical settlements summary report	160
<b>CPT-42 results</b>	
Summary data report	161
Vertical settlements summary report	164
<b>CPT-43 results</b>	
Summary data report	165
Vertical settlements summary report	168
<b>CPT-44 results</b>	
Summary data report	169
Vertical settlements summary report	172
<b>CPT-45 results</b>	
Summary data report	173
Vertical settlements summary report	176
<b>CPT-46 results</b>	
Summary data report	177
Vertical settlements summary report	180
<b>CPT-47 results</b>	
Summary data report	181
Vertical settlements summary report	184
<b>CPT-48 results</b>	
Summary data report	185
Vertical settlements summary report	188
<b>CPT-49 results</b>	
Summary data report	189
Vertical settlements summary report	192
<b>CPT-50 results</b>	
Summary data report	193
Vertical settlements summary report	196

<b>CPT-51 results</b>	
Summary data report	197
Vertical settlements summary report	200
<b>CPT-52 results</b>	
Summary data report	201
Vertical settlements summary report	204
<b>CPT-53 results</b>	
Summary data report	205
Vertical settlements summary report	208
<b>CPT-54 results</b>	
Summary data report	209
Vertical settlements summary report	212
<b>CPT-55 results</b>	
Summary data report	213
Vertical settlements summary report	216



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-1

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-2**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_\sigma$ applied:	Yes		





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-3


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-4

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

### Liquefaction analysis summary plot




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-5**

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry




## CPT basic interpretation plots (normaliz



## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-6**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

### Liquefaction analysis summary plot




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>c</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-7**

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_g$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-8**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-9


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		






## CPT basic interpretation plots (normaliz



## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-10

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



Zone A: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A2: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-11

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-12

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-13

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-14

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-15

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**


**CPT file : CPT-16**

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-17

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-18

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-19

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



## Liquefaction analysis summary plo




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 $FS$ : Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-20

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-21


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-22


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry

## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-23


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations


$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain







## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-25

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-26

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-27


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-28

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



### Liquefaction analysis summary plot




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-29**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_g$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-30


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

### Liquefaction analysis summary plot




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-31

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-32


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-33


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		








## CPT basic interpretation plots (normaliz



## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

### Liquefaction analysis summary plot




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-34

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		












## CPT basic interpretation plots (normaliz



### Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

### SBTn legend

	1. Sensitive fine grained		4. Clayey silt to silty		7. Gravely sand to sand
	2. Organic material		5. Silty sand to sandy silt		8. Very stiff sand to
	3. Clay to silty clay		6. Clean sand to silty sand		9. Very stiff fine grained



Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-35


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-36


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-37

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-38


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-40**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-41

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




**Project title : 2551.00**

**Location : Oceanside, CA**

**CPT file : CPT-42**


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-43

### Input parameters and analysis data


Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry



## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-44


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry

## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-45


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-46


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-47

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-48


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data


Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-49


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz






## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained

## Liquefaction analysis summary plo




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-50


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



Zone A<sub>1</sub>: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A<sub>2</sub>: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry

## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on $I_c$ value	$I_c$ cut-off value:	2.60	$K_o$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained



Liquefaction analysis summary plo




Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft



## Estimation of post-earthquake settlements



### Abbreviations

q<sub>c</sub>: Total cone resistance (cone resistance q<sub>c</sub> corrected for pore water effects)  
 I<sub>c</sub>: Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain

## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-51


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based





## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

q<sub>c</sub>: Total cone resistance (cone resistance q<sub>c</sub> corrected for pore water effects)  
 I<sub>c</sub>: Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-52

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




### Liquefaction analysis summary plot



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>o</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA

CPT file : CPT-53


### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



Zone A1: Cyclic liquefaction likely depending on size and duration of cyclic loading  
 Zone A2: Cyclic liquefaction and strength loss likely depending on loading and ground geometry  
 Zone B: Liquefaction and post-earthquake strength loss unlikely, check cyclic softening  
 Zone C: Cyclic liquefaction and strength loss possible depending on soil plasticity, brittleness/sensitivity, strain to peak undrained strength and ground geometry

## CPT basic interpretation plots (normaliz




## Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft




## Liquefaction analysis summary plo



### Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-54

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior	
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	applied:	Sands only
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	Limit depth:	50.00 ft
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes	MSF method:	Method based



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements



### Abbreviations

$q_c$ : Total cone resistance (cone resistance  $q_c$  corrected for pore water effects)  
 $I_c$ : Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## LIQUEFACTION ANALYSIS REPORT




Project title : 2551.00

Location : Oceanside, CA


CPT file : CPT-55

### Input parameters and analysis data

Analysis method:	NCEER (1998)	G.W.T. (in-situ):	11.50 ft	Use fill:	No	Clay like behavior applied:	Sands only
Fines correction method:	NCEER (1998)	G.W.T. (earthq.):	10.00 ft	Fill height:	N/A	Limit depth applied:	Yes
Points to test:	Based on Ic value	Average results interval:	3	Fill weight:	N/A	Limit depth:	50.00 ft
Earthquake magnitude $M_w$ :	6.64	Ic cut-off value:	2.60	Trans. detect. applied:	Yes	MSF method:	Method based
Peak ground acceleration:	0.44	Unit weight calculation:	Based on SBT	$K_0$ applied:	Yes		



## CPT basic interpretation plots (normaliz



## Input parameters and analysis data




Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	K <sub>0</sub> applied:	Yes
Earthquake magnitude M <sub>w</sub> :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## SBTn legend

1. Sensitive fine grained	4. Clayey silt to silty	7. Gravely sand to sand
2. Organic material	5. Silty sand to sandy silt	8. Very stiff sand to
3. Clay to silty clay	6. Clean sand to silty sand	9. Very stiff fine grained




Liquefaction analysis summary plo



Input parameters and analysis data

Analysis method:	NCEER (1998)	Depth to water table (erthq.):	10.00 ft	Fill weight:	N/A
Fines correction method:	NCEER (1998)	Average results interval:	3	Transition detect. applied:	Yes
Points to test:	Based on Ic value	Ic cut-off value:	2.60	$K_0$ applied:	Yes
Earthquake magnitude $M_w$ :	6.64	Unit weight calculation:	Based on SBT	Clay like behavior applied:	Sands only
Peak ground acceleration:	0.44	Use fill:	No	Limit depth applied:	Yes
Depth to water table (insitu):	11.50 ft	Fill height:	N/A	Limit depth:	50.00 ft

## Estimation of post-earthquake settlements




### Abbreviations

q<sub>c</sub>: Total cone resistance (cone resistance q<sub>c</sub> corrected for pore water effects)  
 I<sub>c</sub>: Soil Behaviour Type Index  
 FS: Calculated Factor of Safety against liquefaction  
 Volumetric strain: Post-liquefaction volumetric strain



## Procedure for the evaluation of soil liquefaction resistance, NCEER (1998)


Calculation of soil resistance against liquefaction is performed according to the Robertson & Wride (1998) procedure. The procedure used in the software, slightly differs from the one originally published in NCEER-97-0022 (Proceedings of the NCEER Workshop on Evaluation of Liquefaction Resistance of Soils). The revised procedure is presented below in the form of a flowchart<sup>1</sup>:



<sup>1</sup> "Estimating liquefaction-induced ground settlements from CPT for level ground", G. Zhang, P.K. Robertson, and R.W.I. Brachman

## Procedure for the evaluation of soil liquefaction resistance (all soils), Robertson (2010)


Calculation of soil resistance against liquefaction is performed according to the Robertson & Wride (1998) procedure. This procedure used in the software, slightly differs from the one originally published in NCEER-97-0022 (Proceedings of the NCEER Workshop on Evaluation of Liquefaction Resistance of Soils). The revised procedure is presented below in the form of a flowchart<sup>1</sup>:




<sup>1</sup> P.K. Robertson, 2009. "Performance based earthquake design using the CPT", Keynote Lecture, International Conference on Performance-based Design in Earthquake Geotechnical Engineering – from case history to practice, IS-Tokyo, June 2009



**Procedure for the evaluation of soil liquefaction resistance, Idriss & Boulanger (2008)**




**Procedure for the evaluation of soil liquefaction resistance (sandy soils), Moss et al. (2006)**







# Procedure for the evaluation of soil liquefaction resistance, Boulanger & Idriss(2014)



## Procedure for the evaluation of liquefaction-induced lateral spreading displacements



<sup>1</sup> Flow chart illustrating major steps in estimating liquefaction-induced lateral spreading displacements using the proposed approach



<sup>1</sup> Figure 1


$$LDI = \int_0^{Z_{max}} \gamma_{max} dz$$

<sup>1</sup> Equation [3]

<sup>1</sup> "Estimating liquefaction-induced ground settlements from CPT for level ground", G. Zhang, P.K. Robertson, and R.W.I. Brachman



## Procedure for the estimation of seismic induced settlements in dry sands



Robertson, P.K. and Lisheng, S., 2010, "Estimation of seismic compression in dry soils using the CPT" FIFTH INTERNATIONAL CONFERENCE ON RECENT ADVANCES IN GEOTECHNICAL EARTHQUAKE ENGINEERING AND SOIL DYNAMICS, Symposium in honor of professor I. M. Idriss, San Diego, CA

## Liquefaction Potential Index (LPI) calculation procedure

Calculation of the Liquefaction Potential Index (LPI) is used to interpret the liquefaction assessment calculations in terms of severity over depth. The calculation procedure is based on the methodology developed by Iwasaki (1982) and is adopted by AFPS.

To estimate the severity of liquefaction extent at a given site, LPI is calculated based on the following equation:

$$LPI = \int_0^{20} (10 - 0.5z) \times F_L \times dz$$

where:


$F_L = 1 - F.S.$  when F.S. less than 1

$F_L = 0$  when F.S. greater than 1

$z$  depth of measurement in meters

Values of LPI range between zero (0) when no test point is characterized as liquefiable and 100 when all points are characterized as susceptible to liquefaction. Iwasaki proposed four (4) discrete categories based on the numeric value of LPI:

- $LPI = 0$  : Liquefaction risk is very low
- $0 < LPI \leq 5$  : Liquefaction risk is low
- $5 < LPI \leq 15$  : Liquefaction risk is high
- $LPI > 15$  : Liquefaction risk is very high



**Graphical presentation of the LPI calculation procedure**



## References

- Lunne, T., Robertson, P.K., and Powell, J.J.M 1997. Cone penetration testing in geotechnical practice, E & FN Spon Routledge, 352 p, ISBN 0-7514-0393-8.
- Boulanger, R.W. and Idriss, I. M., 2007. Evaluation of Cyclic Softening in Silts and Clays. ASCE Journal of Geotechnical and Geoenvironmental Engineering June, Vol. 133, No. 6 pp 641-652
- Boulanger, R.W. and Idriss, I. M., 2014. CPT AND SPT BASED LIQUEFACTION TRIGGERING PROCEDURES. DEPARTMENT OF CIVIL & ENVIRONMENTAL ENGINEERING COLLEGE OF ENGINEERING UNIVERSITY OF CALIFORNIA AT DAVIS
- Robertson, P.K. and Cabal, K.L., 2007, Guide to Cone Penetration Testing for Geotechnical Engineering. Available at no cost at <http://www.geologismiki.gr/>
- Robertson, P.K. 1990. Soil classification using the cone penetration test. Canadian Geotechnical Journal, 27 (1), 151-8.
- Robertson, P.K. and Wride, C.E., 1998. Cyclic Liquefaction and its Evaluation based on the CPT Canadian Geotechnical Journal, 1998, Vol. 35, August.
- Youd, T.L., Idriss, I.M., Andrus, R.D., Arango, I., Castro, G., Christian, J.T., Dobry, R., Finn, W.D.L., Harder, L.F., Hynes, M.E., Ishihara, K., Koester, J., Liao, S., Marcuson III, W.F., Martin, G.R., Mitchell, J.K., Moriwaki, Y., Power, M.S., Robertson, P.K., Seed, R., and Stokoe, K.H., Liquefaction Resistance of Soils: Summary Report from the 1996 NCEER and 1998 NCEER/NSF Workshop on Evaluation of Liquefaction Resistance of Soils, ASCE, Journal of Geotechnical & Geoenvironmental Engineering, Vol. 127, October, pp 817-833
- Zhang, G., Robertson, P.K., Brachman, R., 2002, Estimating Liquefaction Induced Ground Settlements from the CPT, Canadian Geotechnical Journal, 39: pp 1168-1180
- Zhang, G., Robertson, P.K., Brachman, R., 2004, Estimating Liquefaction Induced Lateral Displacements using the SPT and CPT, ASCE, Journal of Geotechnical & Geoenvironmental Engineering, Vol. 130, No. 8, 861-871
- Pradel, D., 1998, Procedure to Evaluate Earthquake-Induced Settlements in Dry Sandy Soils, ASCE, Journal of Geotechnical & Geoenvironmental Engineering, Vol. 124, No. 4, 364-368
- Iwasaki, T., 1986, Soil liquefaction studies in Japan: state-of-the-art, Soil Dynamics and Earthquake Engineering, Vol. 5, No. 1, 2-70
- Papathanassiou G., 2008, LPI-based approach for calibrating the severity of liquefaction-induced failures and for assessing the probability of liquefaction surface evidence, Eng. Geol. 96:94–104
- P.K. Robertson, 2009, Interpretation of Cone Penetration Tests - a unified approach., Canadian Geotechnical Journal, Vol. 46, No. 11, pp 1337-1355
- P.K. Robertson, 2009. "Performance based earthquake design using the CPT", Keynote Lecture, International Conference on Performance-based Design in Earthquake Geotechnical Engineering - from case history to practice, IS-Tokyo, June 2009
- Robertson, P.K. and Lisheng, S., 2010, "Estimation of seismic compression in dry soils using the CPT" FIFTH INTERNATIONAL CONFERENCE ON RECENT ADVANCES IN GEOTECHNICAL EARTHQUAKE ENGINEERING AND SOIL DYNAMICS, *Symposium in honor of professor I. M. Idriss*, SAN diego, CA
- R. E. S. Moss, R. B. Seed, R. E. Kayen, J. P. Stewart, A. Der Kiureghian, K. O. Cetin, CPT-Based Probabilistic and Deterministic Assessment of In Situ Seismic Soil Liquefaction Potential, Journal of Geotechnical and Geoenvironmental Engineering, Vol. 132, No. 8, August 1, 2006
- I. M. Idriss and R. W. Boulanger, 2008. Soil liquefaction during earthquakes, Earthquake Engineering Research Institute MNO-12

**TABLE D-1**  
**Empirical Prediction of Liquefaction-Induced Lateral Spread**  
(Existing Conditions)

J.N.: 2551.00 Client: Sheldon Dev. Location: Oceanside Comments: Consider all layers liquifying Liquefiable Zone:10'-50' Zone of potential spread: Consider All		
<b>Characteristics of liquefiable soils having <math>(N_1)_{60} &lt; 15</math> bpf</b>		
Slope Height (ft)	12	
Distance from Toe of Slope (ft)	140	
Slope of Ground (%)	3.00	
Thickness of Liquefied Layer (ft)	40	
Depth to Liquefiable Layer (ft)	10	
Average Fine Content (%)	25	
Mean Grain Size, $D_{50}$ (mm)	0.3	
Typical Blow Count	5	
Distance to Seismic Source (mi)	13.5	
Earthquake Magnitude	6.64	
Free Face Ratio, W (%)	8.6	
Source Distance Correction, $R_0$ (mi)	1.2	
Lateral Spread, Free-Face (ft)	0.9	factor of x2 included
Lateral Spread, Ground Slope (ft)	1.1	factor of x2 included

**Reference:**

Youd, T.L., Hansen, C.M., and Bartlett, S.F., (2002), "Revised Multilinear Regression Equations for Prediction of Lateral Spread Displacement", ASCE, Journal of Geotechnical and Geoenvironmental Engineering, Vol.128, No.12, pp.1007-1017, December, 2002.