



**Air Quality Technical Study Report  
Draft Air Quality Technical Study  
for the Culver Drive and Alton Parkway  
Intersection Improvement Project (CIP  
311905) Irvine, California**

January 8, 2020

Prepared for:

City of Irvine  
One Civic Center Plaza  
Irvine, CA 92623-9575

Prepared by:


Stantec  
300 North Lake Avenue Suite 400  
Pasadena, CA 91101-4169

## **DRAFT AIR QUALITY TECHNICAL STUDY**


### **Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California**

January 8, 2020


This document entitled *Air Quality Technical Study Report* was prepared by Stantec Consulting Services Inc. ("Stantec") for the account of City of Irvine (the "Client"). Any reliance on this document by any third party is strictly prohibited. The material in it reflects Stantec's professional judgment in light of the scope, schedule and other limitations stated in the document and in the contract between Stantec and the Client. The opinions in the document are based on conditions and information existing at the time the document was published and do not take into account any subsequent changes. In preparing the document, Stantec did not verify information supplied to it by others. Any use which a third party makes of this document is the responsibility of such third party. Such third party agrees that Stantec shall not be responsible for costs or damages of any kind, if any, suffered by it or any other third party as a result of decisions made or actions taken based on this document.

Prepared by   
(signature)

**Nasrin Behmanesh, Ph.D., Air Quality and Climate Change Specialist**

Reviewed by   
(signature)

**Michael P. Weber, Principal Scientist**

Approved by   
(signature)

**Gilberto Ruiz, Principal Environmental Planner**

January 8, 2020

## **Table of Contents**

<b>ABBREVIATIONS .....</b>	<b>II</b>
----------------------------	-----------

<b>1.0 INTRODUCTION .....</b>	<b>1</b>
1.1 EXISTING SETTING .....	5
1.1.1 Climate and Meteorology .....	5
1.1.2 Regulatory Setting.....	6
1.1.3 Sensitive Receptors .....	10
1.1.4 Thresholds of Significance .....	11
<b>2.0 IMPACT ANALYSIS.....</b>	<b>12</b>
2.1 AVOIDANCE, MINIMIZATION, OR MITIGATION MEASURES .....	16
<b>3.0 REFERENCES.....</b>	<b>18</b>

### **LIST OF TABLES**

Table 1. National and California Ambient Air Quality Standards .....	7
Table 2. Attainment Status of Orange County within South Coast Air Basin .....	9
Table 3. SCAQMD Significance Thresholds for Mass Daily Emissions of Criteria Air Pollutants.....	11
Table 4. Project Construction Emissions in Comparison with SCAQMD Regional Significance Thresholds.....	13
Table 5. Project Construction Emissions in Comparison with SCAQMD Localized Significance Thresholds.....	14
Table 6. Comparison of Peak Hour Traffic Conditions at the Culver Drive/Alton Parkway with and without Project.....	15

### **LIST OF FIGURES**

Figure 1. Location Map.....	3
Figure 2. Preliminary Engineering Plan.....	4

### **LIST OF APPENDICES**

#### **APPENDIX A AIR POLLUTANTS AND GREENHOUSE GAS EMISSIONS**



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

## Abbreviations

CAA	Clean Air Act
CAAQS	California Ambient Air Quality Standards
CARB	California Air Resources Board
CEQA	California Environmental Quality Act
CO	Carbon monoxide
ICU	intersection capacity utilization
LOS	level of service
LST	localized significance thresholds
NAAQS	National Ambient Air Quality Standards
NO <sub>2</sub> , NO <sub>x</sub>	Nitrogen dioxide, oxides of nitrogen
O <sub>3</sub>	Ozone
Pb	Lead
PM <sub>10</sub> , and PM <sub>2.5</sub>	Respirable particulate matter, and fine particulate matter
ppb, ppm	parts per billion, parts per million
ROG	Reactive organic gases
SCAB	South Coast Air Basin
SCAQMD	South Coast Air Quality Management District
SIP	State Implementation Plan
SM	Standard Measures
SMAQMD	Sacramento Metro
SO <sub>2</sub> , and SO <sub>x</sub>	Sulfur dioxide and sulfur oxides
SRA	Source Receptor Area
TAC	Toxic air contaminants
USEPA	United States Environmental Protection Agency
VOC	Volatile organic compounds





## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

## 1.0 INTRODUCTION

The Culver Drive and Alton Parkway Intersection Improvement Project (proposed Project) is one of the mitigations identified in the *2015 Irvine Business Complex Vision Plan Traffic Study* and the *2016 Citywide Traffic Operation & Traffic Management Study* that would improve circulation in the City of Irvine (City). The proposed Project will provide capacity enhancements and improve circulation to the intersection. Culver Drive is a six-lane major arterial roadway, and Alton Parkway is a four-lane primary arterial east of Culver Drive and a six-lane major arterial west of Culver Drive in the City's roadway network within the intersection vicinity. Figure 1 (Project Location) shows the location of proposed Project.

The Project area is within the South Coast Air Basin (SCAB) and is under the jurisdiction of South Coast Air Quality Management District (SCAQMD). This air quality technical study report provides assessment of the potential impacts to local and regional air quality that are related to the proposed Project.

The proposed roadway layout and associated improvements, including revised geometries for the Culver Drive and Alton Parkway intersection are summarized below. Each location describes the approach to the intersection and for the purpose of this description, Culver Drive is considered a north-south roadway and Alton Parkway an east-west roadway.

Several alternatives were considered and studied for the proposed Project improvements. From the studied alternatives, two alternatives were determined to be viable as they provide improvements in the level of service (LOS) and intersection capacity utilization (ICU) to maintain the intersection at acceptable City requirements for traffic circulation through the buildout conditions (2035). One of these two alternatives is considered as the "preferred alternative" (see Figure 2) which include the following:

- Adding a fourth northbound through lane on Culver Drive
- Removing the southbound free right turn lane on Culver Drive and converting it to a standard right turn lane; and removal of the existing pedestrian island
- Adding southbound right turn overlap phasing on Culver Drive coordinated with the eastbound dual left turn phasing on Alton Parkway (prohibiting eastbound U-turn movement)
- Extending the eastbound and westbound left turn pockets in both directions on Alton Parkway approaching the intersection at Culver Drive
- Adding concrete bus pads at existing bus stops located at the northeast (Culver Drive), northwest (Alton Parkway) nearest the retail business at 3755 Alton Parkway, currently occupied by Olive Garden Italian restaurant, and southeast (Alton Parkway) corners of the intersection;
- Adding a new bus stop and bus pad on the northwest corner (Alton Parkway) of the intersection nearest to the retail business at 3995 Alton Parkway, currently occupied by Starbucks coffee shop;



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California


January 8, 2020

- Modify / improve supporting traffic signal, medians, sidewalks, and landscaping, where applicable and;
- Providing enhanced striping to the existing on-street bike lanes on all four (4) legs of the intersection.


Figure 2 shows the proposed roadway layout and associated improvements, including revised geometries for the Culver Drive and Alton Parkway intersection. The design features for proposed Project are as follows:

- New pavement, curb and gutter, sidewalk and pedestrian ramps.
- Lengthen the eastbound Alton Parkway left turn pocket by approximately 60 feet.
- Lengthen the westbound Alton Parkway left turn pocket by 150 feet.
- Remove and replace existing trees and ground cover in the Alton Parkway median on both legs of the intersection.
- Protect in place the existing monument sign, stone façade wall(s), and portions of landscaping on the southeast (Woodbridge) corner of the intersection.
- Modify the existing traffic signal at the intersection.
- Adjust and/or relocate various utility features (manholes, valves, vaults, etc.).
- Install Filterra biofiltration water quality facilities; of which three (3) will retrofit existing catch basin inlets at the northwest, southwest, and southeast legs of the intersection, and 2 facilities will retrofit the existing catch basin inlet at the northeast corner of the intersection.
- Relocation of existing street lighting, as required.
- Reconstruct parkways in three of the four quadrants of the intersection, summarized as follows:
  - Northwest Quadrant – Ten-foot wide curb adjacent sidewalk with landscaping behind along Alton Parkway. Eight-foot wide curb adjacent sidewalk with landscaping behind along Culver Drive.
  - Northeast Quadrant – Variable (8-foot- 10-foot) wide curb adjacent sidewalk with retaining curb at the back of walk along Culver Drive. Five-foot wide curb adjacent planting area with 5-foot wide sidewalk behind along Alton Parkway. A retaining curb will be constructed at the back of sidewalk.
  - Southeast Quadrant – Five-foot curb adjacent sidewalk with a landscape slope (4 to 1 maximum) to match existing behind the sidewalk along Culver Drive.
  - Southwest Quadrant – No improvements required (existing conditions to remain).





  Project Location





Project Location	Prepared by DL on 2019-12-20
Irvine, California	TR by
	IR by
Client/Project	2042557300
<b>City of Irvine</b>	
Alton Parkway and Culver Drive	
Intersection Improvement Project	
Figure No.	
<b>1</b>	

Title  
**Location Map**

**Notes**  
 1. Coordinate System: NAD 1983 StatePlane California VI FIPS 0406 Feet  
 2. Data Sources: Stantec 2019.  
 3. Background: USGS The National Map: National Boundaries Dataset, 3DEP Elevation Program, Geographic Names Information System, National Hydrography Dataset, National Land Cover Database, National Structures Dataset, and National





**Project Location** Prepared by DL on 2019-12-30  
Irvine, California TR by IR by  
**Client/Project** 2042558200

**City of Irvine**  
Alton Parkway and Culver Drive  
Intersection Improvement Project

**Figure No.**  
**2**

**Title**  
**Preliminary Engineering Plan**

January 8, 2020

## **1.1 EXISTING SETTING**

### **1.1.1 Climate and Meteorology**

The proposed Project is located in the SCAB which includes all of Orange County and the non-desert portions of Los Angeles, Riverside, and San Bernardino Counties. Its terrain and geographical location determine the distinctive climate of the air basin, as the Basin is a coastal plain with connecting broad valleys and low hills.

The southern California region lies in a semi-permanent high-pressure zone of the eastern Pacific. As a result, the climate is mild, tempered by cool sea breezes. Warm, dry summers, low precipitation, and mild winters characterize the overall climate in the SCAB. In the Project area, the average daily winter temperature is 54.5 degrees Fahrenheit (°F) and the average daily summer temperature is 73 °F. More than two-thirds of the annual rainfall occurs from December through March. The mean annual precipitation in the area is 14.4 inches. In nearly all months of the year, evaporation exceeds precipitation. Winds in the area are usually driven by the dominant land/sea breeze circulation system. Regional wind patterns are dominated by daytime onshore sea breezes from southwest. Average wind speed in the Project area is 5.4 miles per hour (mph). Occasionally during autumn and winter, “Santa Ana” conditions develop from a high-pressure zone to the east to bring dry, high-velocity winds from the deserts over Cajon Pass to the coastal region. These winds, gusting to more than 80 mph, can reduce relative humidity to less than 10 percent. Meteorological characteristics such as wind, sunlight, temperature, humidity, rainfall, and topography all impact the accumulation and/or dispersion of air pollutants throughout the Basin.

#### **Criteria Air Pollutants**

Criteria pollutants are defined by state and federal law as a risk to the health and welfare of the general public. In general, criteria air pollutants include the following compounds:

**Ozone.** Ozone (O<sub>3</sub>) is considered a photochemical oxidant, which is a chemical that is formed when volatile organic compounds (VOCs) and nitrogen oxides (NO<sub>x</sub>), both by-products of fuel combustion, react in the presence of ultraviolet light. Ozone is considered a respiratory irritant and prolonged exposure can reduce lung function, aggravate asthma, and increase susceptibility to respiratory infections. Children and those with existing respiratory diseases are at greatest risk from exposure to ozone.

**Reactive Organic Gases.** Reactive Organic Gases (ROGs) (also known as VOCs) are compounds composed primarily of hydrogen and carbon atoms. Internal combustion associated with motor vehicle usage is the major source of ROGs. Other sources of ROGs include evaporative emissions from paints and solvents, the application of asphalt paving, and the use of household consumer products such as aerosols. Adverse effects on human health are not caused directly by ROGs, but rather by reactions of ROGs to form secondary pollutants such as ozone.

**Carbon Monoxide.** Carbon Monoxide (CO) is a by-product of fuel combustion. CO is an odorless, colorless gas. CO affects red blood cells in the body by binding to hemoglobin and reducing the amount



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

of oxygen that can be carried to the body's organs and tissues. CO can cause health effects to those with cardiovascular disease and can also affect mental alertness and vision.

**Nitrogen Dioxide.** Nitrogen Dioxide (NO<sub>2</sub>) is also a by-product of fuel combustion and is formed both directly as a product of combustion and in the atmosphere through the reaction of nitrogen oxide (NO) with oxygen. NO<sub>2</sub> is a respiratory irritant and may affect those with existing respiratory illness, including asthma. NO<sub>2</sub> can also increase the risk of respiratory illness.

**Respirable Particulate Matter and Fine Particulate Matter.** Respirable particulate matter, or PM<sub>10</sub>, refers to particulate matter with an aerodynamic diameter of 10 microns or less. Fine particulate matter, or PM<sub>2.5</sub>, refers to particulate matter with an aerodynamic diameter of 2.5 microns or less. Particulate matter in these size ranges have been determined to have the potential to lodge in the lungs and contribute to respiratory problems. PM<sub>10</sub> and PM<sub>2.5</sub> arise from a variety of sources, including road dust, diesel exhaust, fuel combustion, tire and brake wear, construction operations, and windblown dust. PM<sub>10</sub> and PM<sub>2.5</sub> can increase susceptibility to respiratory infections and can aggravate existing respiratory diseases such as asthma and chronic bronchitis. PM<sub>2.5</sub> is considered to have the potential to lodge deeper in the lungs. Diesel particulate matter is classified a carcinogen by the California Air Resources Board (CARB).

**Sulfur dioxide.** Sulfur dioxide (SO<sub>2</sub>) is a colorless, reactive gas that is produced from the burning of sulfur-containing fuels such as coal and oil and by other industrial processes. Generally, the highest concentrations of SO<sub>2</sub> are found near large industrial sources. SO<sub>2</sub> is a respiratory irritant that can cause narrowing of the airways leading to wheezing and shortness of breath. Long-term exposure to SO<sub>2</sub> can cause respiratory illness and aggravate existing cardiovascular disease.

**Lead.** Lead (Pb) in the atmosphere occurs as particulate matter. With the phase-out of leaded gasoline, large manufacturing facilities are the sources of the largest amounts of lead emissions. Pb has the potential to cause gastrointestinal, central nervous system, kidney, and blood diseases upon prolonged exposure. Pb is also classified as a probable human carcinogen. The Proposed Project does not include a source of lead emissions.

### 1.1.2 Regulatory Setting

Regulatory oversight authority regarding air quality rests at the federal, state, and local levels with the, U.S. Environmental Protection Agency (USEPA), CARB, and SCAQMD, respectively. Plans, policies, and regulations that are relevant to the proposed Project are discussed in the following sections.

#### Federal

The federal Clean Air Act (CAA), which was passed in 1970 and last amended in 1990, forms the basis for the national air pollution control effort. The CAA delegates primary responsibility for clean air to the USEPA. The USEPA develops rules and regulations to preserve and improve air quality and delegates specific responsibilities to state and local agencies. Under the act, the USEPA has established the National Ambient Air Quality Standards (NAAQS) for six criteria air pollutants that are pervasive in urban environments and for which state and national health-based ambient air quality standards have been established. Ozone (O<sub>3</sub>), carbon monoxide (CO), nitrogen dioxide (NO<sub>2</sub>), sulfur dioxide (SO<sub>2</sub>), lead (Pb),



**DRAFT AIR QUALITY TECHNICAL STUDY****Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California**

January 8, 2020

and particulate matter (PM<sub>10</sub> – respirable particles less than 10 microns in diameter, and PM<sub>2.5</sub> – fine particles less than 2.5 microns in diameter) are the six criteria air pollutants. Ozone is a secondary pollutant, Nitrogen oxides (NO<sub>x</sub>) and volatile organic compounds (VOCs) are of particular interest as they are precursors to ozone formation. The NAAQS are divided into primary and secondary standards; the primary standards are set to protect human health within an adequate margin of safety, and the secondary standards are set to protect environmental values, such as plant and animal life. The standards for all criteria pollutants are presented in Table 1.

The CAA requires the USEPA to designate areas as attainment, nonattainment, or maintenance (previously nonattainment and currently attainment) for each criteria pollutant based on whether the NAAQS have been achieved. The act also mandates that the state submit and implement a State Implementation Plan (SIP) for areas not meeting the NAAQS. These plans must include pollution control measures that demonstrate how the standards will be met.

**Table 1. National and California Ambient Air Quality Standards**

Pollutant	Averaging Time	California Standards	National Standards	
			Primary	Secondary
Ozone (O <sub>3</sub> )	1 Hour	0.09 ppm (180 µg/m <sup>3</sup> )	--	Same as Primary
	8 Hour	0.070 ppm (137 µg/m <sup>3</sup> )	0.070 ppm (137 µg/m <sup>3</sup> )	
Respirable Particulate Matter (PM <sub>10</sub> )	24 Hour	50 µg/m <sup>3</sup>	150 µg/m <sup>3</sup>	Same as Primary
	Annual Mean	20 µg/m <sup>3</sup>	--	
Fine Particulate Matter (PM <sub>2.5</sub> )	24 Hour	--	35 µg/m <sup>3</sup>	Same as Primary
	Annual Mean	12 µg/m <sup>3</sup>	12.0 µg/m <sup>3</sup>	15 µg/m <sup>3</sup>
Carbon Monoxide (CO)	1 Hour	20 ppm (23 µg/m <sup>3</sup> )	35 ppm (40 mg/m <sup>3</sup> )	--
	8 Hour	9.0 ppm (10 mg/m <sup>3</sup> )	9 ppm (10 mg/m <sup>3</sup> )	--
Nitrogen Dioxide (NO <sub>2</sub> )	1 Hour	0.18 ppm (339 µg/m <sup>3</sup> )	100 ppb (188 µg/m <sup>3</sup> )	--
	Annual Mean	0.030 ppm (57 µg/m <sup>3</sup> )	0.053 ppm (100 µg/m <sup>3</sup> )	Same as Primary
Sulfur Dioxide (SO <sub>2</sub> )	1 Hour	0.25 ppm (655 µg/m <sup>3</sup> )	75 ppb (196 µg/m <sup>3</sup> )	--
	3 Hour	--	--	0.5 ppm (1300 µg/m <sup>3</sup> )
	24 Hour	0.04 ppm (105 µg/m <sup>3</sup> )	0.14 ppm	--
	Annual Mean	--	0.030 ppm	--
Lead (Pb)	30 Day Average	1.5 µg/m <sup>3</sup>	--	--
	Calendar Quarter	--	1.5 µg/m <sup>3</sup>	Same as Primary
	Rolling 3-Month Avg	--	0.15 µg/m <sup>3</sup>	Same as Primary



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

**Table 1. National and California Ambient Air Quality Standards**

Pollutant	Averaging Time	California Standards	National Standards	
			Primary	Secondary
Visibility reducing particles	8 Hour	10-mile visibility standard, extinction of 0.23 per kilometer	No National Standards	
Sulfates	24 Hour	25 µg/m <sup>3</sup>		
Hydrogen sulfide (H <sub>2</sub> S)	1 Hour	0.03 ppm (42 µg/m <sup>3</sup> )		
Vinyl chloride	24 Hour	0.01 ppm (265 µg/m <sup>3</sup> )		

Notes:

ppm = parts per million; ppb = parts per billion; µg/m<sup>3</sup> = micrograms per cubic meter; "--" = no standard.

Source: CARB Ambient Air Quality Standards Chart, CARB 2016

## State

The State began to set California ambient air quality standards (CAAQS) in 1969 under the mandate of the Mulford-Carrell Act. The California Clean Air Act was adopted by the CARB in 1988. The California Clean Air Act requires all air district of the state to achieve and maintain the CAAQS by the earliest practical date. Table 1 shows the CAAQS currently in effect for each of the criteria pollutants, as well as the other pollutants recognized by the state. As shown in Table 1, the CAAQS are generally more stringent than the corresponding federal standards and incorporate additional standards for sulfates, hydrogen sulfide, vinyl chloride, and visibility-reducing particles.

The CARB and local air districts are responsible for achieving CAAQS, which are to be achieved through district-level air quality management plans (AQMPs) that would be incorporated into the SIP. In California, the USEPA has delegated authority to prepare SIPs to CARB, which in turn, has delegated that authority to individual air districts. Other CARB duties include monitoring air quality (in conjunction with air monitoring networks maintained by air districts) and setting emissions standards for new motor vehicles and for other emission sources, such as consumer products and certain off-road equipment.

## Attainment Status

Depending on whether or not the applicable ambient air quality standards are met or exceeded, the air basin is classified as being in "attainment" or "nonattainment". The USEPA and CARB determine the air quality attainment status of designated areas by comparing ambient air quality measurements from state or local ambient air monitoring stations with the NAAQS and CAAQS. These designations are determined on a pollutant-by-pollutant basis. Consistent with federal requirements, an unclassifiable/ unclassified designation is treated as an attainment designation. Table 2 presents the federal and state attainment status for the Project area, which is in Orange County. As shown in the Table 2, the Proposed Project is in an area designated non-attainment for O<sub>3</sub> and PM<sub>2.5</sub> based on both the federal and State standards,





## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

and for PM<sub>10</sub>, based on the State standard. Because the Orange County (within SCAB) currently exceeds these State and federal ambient air quality standards, the SCAQMD is required to implement strategies to reduce pollutant levels to recognized acceptable standards.

**Table 2. Attainment Status of Orange County within South Coast Air Basin**

Pollutant	Federal Designation	State Designation
Ozone (O <sub>3</sub> )	Non-Attainment (Extreme)	Non-Attainment
Particulate Matter (PM <sub>10</sub> )	Attainment/Maintenance	Non-Attainment
Particulate Matter (PM <sub>2.5</sub> )	Non-Attainment (Moderate)	Non-Attainment
Carbon Monoxide (CO)	Attainment/Maintenance	Attainment
Nitrogen Dioxide (NO <sub>2</sub> )	Attainment/Maintenance	Attainment
Sulfur Dioxide (SO <sub>2</sub> )	Attainment	Attainment
Lead (Pb)	Attainment	Attainment
Hydrogen Sulfide (H <sub>2</sub> S)	*	Unclassified
Sulfates	*	Attainment
Visibility Reducing Particles	*	Unclassified

Source: SCAQMD, 2017a, and USEPA 2019 (area designation for criteria pollutants [Green Book])

Notes: (\*) = Not Applicable/ No Federal Standards.

**Toxic Air Contaminants Regulation.** California regulates toxic air contaminants (TACs) primarily through the Tanner Air Toxics Act (AB 1807) and the Air Toxics Hot Spots Information and Assessment Act of 1987 (AB 2588 – Connelly). In the early 1980s, the CARB established a statewide comprehensive air toxics program to reduce exposure to air toxics. In August 1998, CARB identified diesel particulate matter emissions from diesel-fueled engines as a TAC. In September 2000, CARB approved a comprehensive diesel risk reduction plan to reduce emissions from both new and existing diesel fueled engines and vehicles (CARB 2000). The goal of the plan is to reduce diesel PM<sub>10</sub> (inhalable particulate matter) emissions and the associated health risk by 75% in 2010 and by 85% by 2020.

## Local

**Applicable Air Quality Plans.** The SCAQMD in conjunction with the Southern California Association of Governments (SCAG), CARB, and USEPA prepares air quality management plans (AQMP) to lead the SCAB into attainment with federal and state standards, and to ensure that future emissions will be within these standards. The SCAQMD updates its plans on a regular basis. The most recent plan is the 2016 AQMP (SCAQMD 2017b). It provides a comprehensive and integrated program to lead the SCAB into compliance with the federal ozone and particulate matter standards.



## **DRAFT AIR QUALITY TECHNICAL STUDY**

### **Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California**

January 8, 2020

The 2016 AQMP accounts for projected population growth, predicted future emissions in energy and transportation demand, and determined control strategies for the eventual achievement of NAAQS attainment designation. These control strategies are either organized into the SCAQMD rules and regulations, or otherwise set forth as formal SCAQMD recommendations to other agencies. The 2016 AQMP includes policies that are consistent with the SCAQMD and specify review according to the recommendations of SCAQMD guidelines. Other policies are aimed at reducing transportation emissions and emissions from major stationary sources. The Proposed Project would be subject to the following general SCAQMD rules and regulations, and the Orange County Grading and Excavation Codes prior to issuance of grading permit:

#### **Regulatory IV – Prohibitions**

- Rule 401 – Visible Emissions: prohibits discharges of visible air contaminants that occlude the air beyond certain thresholds;
- Rule 402 – Nuisance: prohibits discharges of air contaminants that cause “injury, detriment, nuisance, or annoyance” to the public; and
- Rule 403 – Fugitive Dust: prohibits discharges of fugitive dust that exceed certain thresholds.
- Rule 1113 – Architectural Coating: limits the amount of VOCs from paving, asphalt, concrete curing, and cement coatings operations.

#### **1.1.3 Sensitive Receptors**

Some population groups are considered more sensitive to air pollution than the others. The degree of the greater sensitivity depends on several factors including pre-existing health problems, proximity to the emissions source, or duration of exposure to the air pollutants. For the purposes of a California Environmental Quality Act (CEQA) analysis, the SCAQMD considers a sensitive receptor to be a receptor such as a residence, school, hospital, or convalescent facility where people stay in extended amount of time during the day. Commercial and industrial facilities are not included in the definition of sensitive receptor, because employees typically are present for shorter periods of time, such as eight hours per day.

The surrounding land uses of the Proposed Project include Westpark Plaza (commercial) to the northwest, Mark Daily Athletic Field to the northeast, and residential uses to the southeast and southwest of the Culver Drive and Alton Parkway intersection. The nearest sensitive receptors to the Proposed Project site are the residences south of the intersection, and the closest residence is located about 65 feet from the edge of Culver Drive, southwest of the intersection and include the Woodbridge Master Homeowners Association and the Alders Homeowners Association and the San Marino Apartments, respectively. The Mark Daily Athletic Field (including bleacher seats) is approximately 85 feet from the edge of northbound Culver Drive. The closest school/day care center is the LePort Montessori Irvine Mandarin Immersion, located within Westpark Plaza at 3935 Alton Parkway, and is approximately 40 to 50 feet from the edge of southbound Culver Drive. However, the school site is about 350 feet northwest of the intersection and the major construction activities along the southbound Culver Drive would terminate



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

approximately 110 feet from the intersection. The other daycare facility in the vicinity of the Project is Jenny Hart Early Education Center located at 4445 Alton Parkway, approximately 0.4 mile southeast of the intersection.

#### 1.1.4 Thresholds of Significance

In addition to the significance criteria in Appendix G of CEQA Guidelines, the SCAQMD has adopted regional and localized significance thresholds (LSTs) to determine the significance of a project's potential air quality impacts. Separate thresholds of significance have been adopted for the construction and operation phases of projects.

The LSTs were developed by the SCAQMD to assist lead agencies in analyzing localized air quality impacts from projects. LSTs look-up tables for one-, two-, and five-acre proposed projects emitting CO, NO<sub>x</sub>, PM<sub>2.5</sub> or PM<sub>10</sub> were prepared for easy reference according to source receptor area. The LSTs methodology and associated mass rates are not applicable to mobile sources travelling over the roadways. LSTs for a pollutant are based on the ambient concentrations of that pollutant within the Project Source Receptor Area (SRA) and the distance to the nearest sensitive receptor. This proposed Project is within SRA 20. Table 3 presents the regional thresholds as well as LSTs applicable to the proposed Project construction and operational emissions.

The proposed Project construction is anticipated to be initiated in the Winter of 2021 and extend to Summer 2022 and take approximately 8-10 months to complete, although the total duration of actual construction would be about four months combined. The maximum daily area of disturbance at both sides of the intersection would be approximately 8,000 square feet per day or 0.18 acre. As determined through SCAQMD guidelines, a one-acre site size was used for Proposed Project LSTs and localized impact analysis. These LSTs are based on the one-acre project site with a 25-meter (82 feet) receptor distance (approximate distance of the nearest residences located southeast of the intersection and the Mark Daily athletic field on the northeast corner of the intersection).

**Table 3. SCAQMD Significance Thresholds for Mass Daily Emissions of Criteria Air Pollutants**

Component/ emission source	Emissions Threshold (lbs/day)					
	VOC	NO <sub>x</sub>	SO <sub>x</sub>	CO	PM <sub>10</sub>	PM <sub>2.5</sub>
<b>Regional Thresholds</b>						
Construction	75	100	150	550	150	55
Operation	55	55	150	550	150	55
<b>Localized Thresholds - Construction</b>						
Receptors within 25 meters	n/a	92	n/a	647	4	3
Receptors within 50 meters	n/a	93	n/a	738	13	5



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

Component/ emission source	Emissions Threshold (lbs/day)					
	VOC	NO <sub>x</sub>	SO <sub>x</sub>	CO	PM <sub>10</sub>	PM <sub>2.5</sub>
<b>Localized Thresholds - Operation</b>						
Receptors within 25 meters	n/a	92	n/a	647	1	1
Receptors within 50 meters	n/a	93	n/a	738	4	2

Source: SCAQMD Air Quality Significance (Mass Daily) Thresholds, 2015

SCAQMD Mass Rate LST Lookup Tables, Appendix C, 2008

Notes: Lbs/day = pounds per day

Localized significance thresholds are from the SCAQMD lookup tables for Source Receptor Area 20 assuming a one-acre project site and a distance to the nearest sensitive receptor of 50 meters. It should be noted the 25 meter is the distance from the edge of Culver Drive to the nearest residences along the southbound of Culver Drive, and the Mark Daily athletic field on the northeast corner of the intersection.

## 2.0 IMPACT ANALYSIS

### Impact AQ (a): Would the Project conflict with or obstruct implementation of the applicable air quality plan?

**Less Than Significant Impact.** A project is conforming with applicable adopted plans if it complies with the applicable local air district (SCAQMD) rules and regulations and emission control strategies as identified in the current air quality plan (2016 AQMP). Based on the traffic study results provided in the Traffic Analysis Memorandum (Stantec 2019), the proposed Project is not a capacity-increasing transportation project and would not generate additional traffic volumes compared with the no-project scenario/alternative.

The Project would comply with the applicable rules, including the use of standard mitigation measures for construction equipment and fugitive dust (SCAQMD Rules 401, 402, 403, and 1113).

Furthermore, the thresholds of significance, adopted by the air district (SCAQMD), determine compliance with the goals of attainment plans in the region. As such, emissions below the SCAQMD regional mass daily emissions thresholds presented in Table 3 would not conflict with or obstruct implementation of the applicable air quality plans. Emissions associated with the Project implementation would be short term, construction emissions and long-term operational. These are analyzed below.

### Construction Impact

Air pollutant emissions associated with construction activities include exhaust emissions generated by operation of on-site construction equipment; fugitive dust emissions related to grading, trenching and earthwork activities; and off-site emissions from construction worker vehicles trips and haul/delivery truck trips. Construction emissions vary from day to day, depending on the number of construction equipment operating on site, the type of construction activity occurring, and, for fugitive dust, prevailing weather conditions. These emissions would be temporary and limited to the immediate area surrounding the construction site.



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

Construction emissions were estimated for the proposed Project using the Road Construction Emissions Model version 8.1.0 (Roadmod) that was developed by the Sacramento Metro Air Quality Management District. Use of the model is consistent with SCAQMD and the City of Irvine CEQA guidance for linear construction projects. The proposed Project construction is anticipated to be initiated in the Winter of 2021 and extend to Summer 2022 and take approximately 8-10 months to complete, although the total duration of actual construction would be about four months combined. The construction phasing and activities with estimated approximate duration of each phase include: clear and grub and site preparation (2 weeks); asphalt demolition and grading (4 weeks); trenching and construction of sidewalks and roadway subgrade (5 weeks); paving, landscaping, and roadway restriping (1 week). The maximum disturbance area at any one time would be 0.18 acre and at both sides of the intersection. For the Project-specific data that are not available at this time, default assumptions (e.g., construction fleet activities) from Roadmod were used. Construction-related regional and localized emissions are presented in Tables 4 and 5, respectively. Calculations and Roadmod output are provided in Appendix A.

As shown in Tables 4 and 5, unmitigated construction emissions would not exceed the SCAQMD maximum daily emissions or localized emissions significance thresholds. Furthermore, the Project would comply with the SCAQMD applicable rules and regulations as stated above (Rules 401, 402, 403, and Rule 1113). Therefore, construction impacts would be less than significant and no mitigation measures are required.

**Table 4. Project Construction Emissions in Comparison with SCAQMD Regional Significance Thresholds**

Emissions Source/Component	Pollutant Emissions (lbs/day)					
	VOC	NOx	SOx	CO	PM <sub>10</sub> Total	PM <sub>2.5</sub> Total
Clear and Grub	0.75	8.68	0.01	5.44	2.37	0.74
Grading/Site Preparation	2.23	23.28	0.05	17.73	3.17	1.42
Construction of subgrade and Sidewalks	2.00	17.81	0.03	19.63	3.02	1.35
Paving and restriping	1.25	11.75	0.02	13.95	0.70	0.62
Maximum Daily Construction Emissions	2.2	23.28	0.05	19.6	3.2	1.4
SCAQMD Significance Threshold (lbs/day)	<b>75</b>	<b>100</b>	<b>150</b>	<b>550</b>	<b>150</b>	<b>55</b>
Exceed Threshold?	No	No	No	No	No	No

**Notes:**

Emissions estimated using Road Construction Emissions Model version 8.1.0 (Sacramento Metro Air Quality Management District 2016). Model output is provided in Appendix A.



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

**Table 5. Project Construction Emissions in Comparison with SCAQMD Localized Significance Thresholds**

Onsite Emissions Sources	Pollutant Emissions (lbs/day)				
	VOC	NOx	CO	PM <sub>10</sub>	PM <sub>2.5</sub>
Clear and Grub	0.72	8.50	4.92	2.34	0.73
Grading/Site Preparation	2.07	22.26	15.57	3.03	1.37
Construction of subgrade and Sidewalks	1.91	17.55	18.23	2.95	1.33
Paving and restriping	1.18	11.53	12.94	0.65	0.60
Maximum Daily Onsite Construction Emissions	2.1	22.3	18.2	3.0	1.4
SCAQMD LST within 25 meters distance (lbs/day)	n/a	<b>92</b>	<b>647</b>	<b>4</b>	<b>3</b>
Exceed Threshold?	n/a	No	No	No	No

Notes: n/a = not applicable, no threshold is set.

Localized significance thresholds are from the SCAQMD lookup tables for Source Receptor Area (SRA) 20 assuming a one-acre project site and a distance to the nearest sensitive receptor of 25 meters.

Based on proposed construction phasing and schedule, it is assumed that the maximum disturbance of 0.18 acre would occur per day of construction.

## Operational Emissions Impact

The proposed Project would improve the existing intersection of Culver Drive and Alton Parkway operations. Upon completion of construction activities, the Project would not result in a measurable increase in vehicle trips, as demonstrated in the proposed Project's Traffic Analysis Memorandum (Stantec 2019) and discussed below.

Based on the proposed Project's traffic analysis, with the proposed improvements, the LOS and ICU would be improved during PM (afternoon) peak hours, and the LOS would maintain at the acceptable level (D or better) through the buildout conditions. Table 6 shows the traffic analysis results. As described in Project's Traffic Analysis Memorandum, CEQA requires a roadway improvement project that would induce a measurable and substantial increase in vehicle travel to conduct a "vehicle miles travelled" analysis identifying the amount of vehicle travel produced by the project. However, the proposed Project would not be vehicle travel inducing. The proposed Project involves "spot" capacity improvements and while all alternatives provide at least one additional through lane at the intersection, these additional "through" (auxiliary) lanes are merged into existing through lanes beyond the intersection (within approximately 600 feet) without continuing to an adjacent intersection. Therefore, while the intersection operates more efficiently, no vehicle inducing capacity is added to roadway segments. Other improvements included in the proposed Project involve only turn lane modifications and would not cause change in traffic volume or fleet mix.



**DRAFT AIR QUALITY TECHNICAL STUDY****Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California**

January 8, 2020

**Table 6. Comparison of Peak Hour Traffic Conditions at the Culver Drive/Alton Parkway with and without Project**

Analysis Year and Scenario	AM Peak Hour		PM Peak Hour	
	LOS	ICU	LOS	ICU
<b>Existing Year</b>				
No Project	B	0.67	D	0.81
With Project (preferred alternative)	B	0.67	C	0.72
<b>Interim Year</b>				
No Project	C	0.80	D	0.86
With Project (preferred alternative)	C	0.80	C	0.76
<b>Buildout Year</b>				
No Project	C	0.80	E	0.92
With Project (preferred alternative)	C	0.80	D	0.81

Notes: AM = before noon; PM = afternoon; LOS = level of service; ICU = intersection capacity utilization

Source: Traffic Analysis Memorandum, Culver Drive and Alton Parkway Intersection Improvement Project (Stantec 2019)

As such, the operational capacity or fleet mix and associated emissions would not change because of the proposed Project improvements. The proposed Project would not result in an increase in long-term operational emissions of air pollutants compared to the no build alternative and would not result in an increase in regional operational emissions. In addition, with intersection LOS improvement, the localized emissions, primarily CO emissions would be lower than the no build alternative. As such, both regional and localized operational impacts from criteria pollutants would be less than significant, and no mitigation is required.

**Toxic Air Contaminants.** Proposed Project operational emissions would not change due to proposed improvements. The greatest potential for TAC emissions would be related to diesel particulate emissions from the exhaust of heavy-duty off-road equipment during proposed Project construction activities. According to SCAQMD methodology, health effects from carcinogenic TACs are usually described in terms of individual cancer risk, which is based on 30 to 70 years exposure to TACs. Given the construction schedule of four months and considering that operation of off-road heavy-duty diesel equipment would occur intermittently during different construction phases, the proposed Project would not result in a long-term substantial source of TAC emissions, with no residual emissions after construction and corresponding individual cancer risk. As such, potential impacts related to TAC emissions would be less than significant and no mitigation measures are required.

**Impact AQ (b): Would the Project result in a cumulatively considerable net increase of any criteria pollutant for which the Project region in non-attainment under and applicable federal or state ambient air quality standard?**

**Less Than Significant Impact.** The Project region is a federal and/or State nonattainment area for ozone, PM<sub>10</sub>, and PM<sub>2.5</sub>. The proposed Project would contribute particulates and the ozone precursors



## DRAFT AIR QUALITY TECHNICAL STUDY

### Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California

January 8, 2020

VOC and NOx to the area during short-term Project construction. As discussed in response to checklist AQ (a), the proposed Project would be consistent with the AQMP, which is intended to bring the SCAB into attainment with air quality standards for all criteria pollutants. In addition, estimated proposed Project emissions are below the applicable SCAQMD regional and localized mass emissions thresholds of significance. Therefore, proposed Project emissions would have a less than significant impact to non-attainment pollutants in the SCAB. As such, increases in pollutants for which the region is in nonattainment would not be cumulatively considerable and impacts would be less than significant, and no mitigation measures are required.

#### **Impact AQ (c): Would the Project expose sensitive receptors to substantial pollutant concentrations?**

**Less Than Significant Impact.** As discussed in responses to checklist AQ (a) and AQ (b) above, the proposed Project would improve intersection operations and it would not generate additional operational emissions that would affect nearby sensitive receptors. The proposed Project would not result in any substantial local concentrations of criteria pollutants. Emissions of diesel particulate matter from construction equipment exhaust would not be substantial and would last only four months. As such, the proposed Project would not expose sensitive receptors to substantial pollutant concentrations and the impact would be less than significant. No mitigation measures are required.

#### **Impact AQ (d): Would the Project result in other emissions such as those leading to odors adversely affecting a substantial number of people?**

**Less Than Significant Impact.** Land uses associated with odor complaints, as identified by SCAQMD, typically include agricultural uses (farming and livestock), wastewater treatment plants, food processing plants, chemical plants, composting operations, refineries, landfills, and dairies. The proposed Project does not contain land uses associated with emitting objectionable odors.

During proposed Project construction, potential sources of objectionable odors would be related to the operation of diesel-powered equipment and to off-gas emissions during activities such as paving and asphaltting. Such odors, however, would be short-term and limited to the area where the specific activity is occurring. The perception of these odors is dependent upon climatic conditions such as temperature, humidity, wind speed, and wind direction. Furthermore, SCAQMD Rules 402 (nuisance) and 1113 (Architectural Coatings) limits the VOC emissions from paving, asphalt, concrete curing, and cement coatings operations. Due to the short-term nature of construction odors, controlled access, and distance to the nearest receptors, odors are not likely to affect a substantial number of people. Impacts would be less than significant, and no mitigation is required.

## **2.1 AVOIDANCE, MINIMIZATION, OR MITIGATION MEASURES**

As described above, the proposed Project would not result in significant impacts during construction or operation and therefore, would not require mitigation measures. In addition, the proposed Project construction activities would also comply with all applicable rules and regulations including those





## **DRAFT AIR QUALITY TECHNICAL STUDY**

### **Culver Drive and Alton Parkway Intersection Improvement Project (CIP 311905) Irvine, California**

January 8, 2020

established by the SCAQMD. Although not considered mitigation, a summary of the measures included in the applicable Rules (standard measures [SM]) are listed below.

**SM AQ-1      SCAQMD Rule 403 (Fugitive Dust).** During clearing, grading, earthmoving, or excavation operations, fugitive dust emissions shall be controlled by using water, chemical stabilizers, or other dust preventive measures using the following procedures, as specified in the South Coast Air Quality Management District (SCAQMD) Rule 403 Table 1.

- All material excavated or graded will be sufficiently watered to prevent excessive amounts of dust. Watering shall occur with sufficient frequency for complete coverage.
- All material transported on- or off-site will be either sufficiently watered or securely covered to prevent excessive fugitive dust emission

**SM AQ-2      The following measures would further reduce VOCs (ROGs) during Project construction.**

- All construction equipment will be properly tuned and maintained in accordance with manufacturer's specifications.
- The construction equipment on construction site shall operate such that exhaust emissions are minimized. For example, idling shall be limited to 10 minutes or engines shall be turned off while in queues or while loading/unloading.
- Compliance with SCAQMD Rule 1113 on the use of architectural coatings (during paving and restriping) shall be implemented. Emissions associated with architectural coatings would be reduced by implementing such measures as low-VOC paint and asphalt material.

**SM AQ-3      SCAQMD Rule 402 (Nuisance).** Project-related construction activities shall not discharge from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health, or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property.



January 8, 2020

### **3.0 REFERENCES**

California Air Resources Board (CARB). 2016. Ambient Air Quality Standards Chart. May 4. Available at: <https://www.arb.ca.gov/research/aaqs/aaqs2.pdf>

California Air Resources Board (CARB). 2017. Attainment Status Area Designation Maps. Available at: <https://www.arb.ca.gov/desig/adm/adm.htm>

United States Environmental Protection Agency (USEPA). 2019. Nonattainment Areas for Criteria Pollutants (Green Book). Available at: <https://www.epa.gov/green-book>

South Coast Air Quality Management District, 2017b. Final 2016 Air Quality Management Plan, available at <http://www.aqmd.gov/docs/default-source/clean-air-plans/air-quality-management-plans/2016-air-quality-management-plan/final-2016-aqmp/final2016aqmp.pdf?sfvrsn=15>.

South Coast Air Quality Management District, 2008. Final Localized Significance Threshold Methodology, available at <http://www.aqmd.gov/docs/default-source/ceqa/handbook/localized-significance-thresholds/final-lst-methodology-document.pdf?sfvrsn=2>.

South Coast Air Quality Management District, 2008. Air Quality Significance Thresholds. Available at: <http://www.aqmd.gov/docs/default-source/ceqa/handbook/scaqmd-air-quality-significance-thresholds.pdf>.

Stantec 2019. Traffic Analysis Memorandum for the Culver Drive and Alton Parkway Intersection Improvement Project. November 2019.



## **Appendix A   AIR POLLUTANTS AND GREENHOUSE GAS EMISSIONS**

### **Emissions Calculation Summary Road Construction Emissions Model (RoadMod) Output**



Culver Drive and Alton Parkway Intersection Improvements Project

Construction Emissions Calculations Summary

Daily Emission Estimates for -> Culver Drive and Alton Parkway Intersection Improvements														
Project Phases (Pounds)	ROG (lbs/day)	CO (lbs/day)	NOx (lbs/day)	Total PM10 (lbs/day)	Exhaust PM10 (lbs/day)	Fugitive PM10 (lbs/day)	Total PM2.5 (lbs/day)	Exhaust PM2.5 (lbs/day)	Fugitive PM2.5 (lbs/day)	SOx (lbs/day)	CO2 (lbs/day)	CH4 (lbs/day)	N2O (lbs/day)	CO2e (lbs/day)
Grubbing/Land Clearing	0.75	5.44	8.68	2.37	0.37	2.00	0.74	0.32	0.42	0.01	1,431.11	0.37	0.02	1,445.38
Grading/Excavation	2.23	17.73	23.28	3.17	1.17	2.00	1.42	1.01	0.42	0.05	4,479.03	0.97	0.06	4,522.32
Drainage/Utilities/Sub-Grade	2.00	19.63	17.81	3.02	1.02	2.00	1.35	0.94	0.42	0.03	3,345.50	0.50	0.03	3,367.71
Paving	1.25	13.95	11.75	0.70	0.70	0.00	0.62	0.62	0.00	0.02	2,344.23	0.56	0.03	2,365.70
Maximum (pounds/day)	2.23	19.63	23.28	3.17	1.17	2.00	1.42	1.01	0.42	0.05	4,479.03	0.97	0.06	4,522.32
Total (tons/construction project)	0.08	0.69	0.73	0.11	0.04	0.07	0.05	0.04	0.01	0.00	138.21	0.03	0.00	139.36

126.4631 MT CO2e

Off-site Emissions - from Data Entry sheet

Grubbing/Land Clearing	0.03	0.52	0.17		0.03			0.01		0.00	298.08	0.00	0.01	300.13
Grading/Excavation	0.15	2.16	1.01		0.14			0.06		0.01	1,536.16	0.02	0.04	1,547.74
Drainage/Utilities/Sub-Grade	0.09	1.40	0.26		0.07			0.03		0.01	587.08	0.01	0.01	590.37
Paving	0.06	1.01	0.22		0.05			0.02		0.00	458.63	0.01	0.01	461.38

Onsite emissions

Grubbing/Land Clearing	0.72	4.92	8.50	2.34	0.34	2.00	0.73	0.31	0.42	0.01	1,133.03	0.37	0.01	1,145.25
Grading/Excavation	2.07	15.57	22.26	3.03	1.03	2.00	1.37	0.95	0.42	0.03	2942.88	0.95	0.03	2974.58
Drainage/Utilities/Sub-Grade	1.91	18.23	17.55	2.95	0.95	2.00	1.33	0.91	0.42	0.03	2758.42	0.49	0.02	2777.34
Paving	1.18	12.94	11.53	0.65	0.65	0.00	0.60	0.60	0.00	0.02	1885.60	0.55	0.02	1904.32
Maximum (pounds/day)	2.07	18.23	22.26	3.03	1.03		1.37	0.95		0.03	2942.88	0.95	0.03	2974.58

Daily Emission Estimates for -> Culver Drive and Alton Parkway Intersection Improvements														Total	Exhaust	Fugitive Dust	Total	Exhaust	Fugitive Dust				
Project Phases (Pounds)		ROG (lbs/day)	CO (lbs/day)	NOx (lbs/day)	PM10 (lbs/day)	PM10 (lbs/day)	PM10 (lbs/day)	PM2.5 (lbs/day)	PM2.5 (lbs/day)	PM2.5 (lbs/day)	SOx (lbs/day)	CO2 (lbs/day)	CH4 (lbs/day)	N2O (lbs/day)	CO2e (lbs/day)								
Grubbing/Land Clearing		0.75	5.44	8.68	2.37	0.37	2.00	0.74	0.32	0.42	0.01	1,431.11	0.37	0.02	1,445.38								
Grading/Excavation		2.23	17.73	23.28	3.17	1.17	2.00	1.42	1.01	0.42	0.05	4,479.03	0.97	0.06	4,522.32								
Drainage/Utilities/Sub-Grade		2.00	19.63	17.81	3.02	1.02	2.00	1.35	0.94	0.42	0.03	3,345.50	0.50	0.03	3,367.71								
Paving		1.25	13.95	11.75	0.70	0.70	0.00	0.62	0.62	0.00	0.02	2,344.23	0.56	0.03	2,365.70								
Maximum (pounds/day)		2.23	19.63	23.28	3.17	1.17	2.00	1.42	1.01	0.42	0.05	4,479.03	0.97	0.06	4,522.32								
Total (tons/construction project)		0.08	0.69	0.73	0.11	0.04	0.07	0.05	0.04	0.01	0.00	138.21	0.03	0.00	139.36								
Notes: Project Start Year -> 2021																							
Project Length (months) -> 4																							
Total Project Area (acres) -> 1																							
Maximum Area Disturbed/Day (acres) -> 0																							
Water Truck Used? -> Yes																							
		Total Material Imported/Exported Volume (yd³/day)		Daily VMT (miles/day)																			
Phase		Soil	Asphalt	Soil Hauling	Asphalt Hauling	Worker Commute	Water Truck																
Grubbing/Land Clearing		0	0	0	0	200	40																
Grading/Excavation		0	220	0	220	800	40																
Drainage/Utilities/Sub-Grade		0	0	0	0	560	40																
Paving		0	0	0	0	400	40																
PM10 and PM2.5 estimates assume 50% control of fugitive dust from watering and associated dust control measures if a minimum number of water trucks are specified.																							
Total PM10 emissions shown in column F are the sum of exhaust and fugitive dust emissions shown in columns G and H. Total PM2.5 emissions shown in Column I are the sum of exhaust and fugitive dust emissions shown in columns J and K.																							
CO2e emissions are estimated by multiplying mass emissions for each GHG by its global warming potential (GWP), 1, 25 and 298 for CO2, CH4 and N2O, respectively. Total CO2e is then estimated by summing CO2e estimates over all GHGs.																							
Total Emission Estimates by Phase for -> Culver Drive and Alton Parkway Intersection Improvements														Total	Exhaust	Fugitive Dust	Total	Exhaust	Fugitive Dust				
Project Phases (Tons for all except CO2e. Metric tonnes for CO2e)		ROG (tons/phase)	CO (tons/phase)	NOx (tons/phase)	PM10 (tons/phase)	PM10 (tons/phase)	PM10 (tons/phase)	PM2.5 (tons/phase)	PM2.5 (tons/phase)	PM2.5 (tons/phase)	SOx (tons/phase)	CO2 (tons/phase)	CH4 (tons/phase)	N2O (tons/phase)	CO2e (MT/phase)								
Grubbing/Land Clearing		0.00	0.03	0.04	0.01	0.00	0.01	0.00	0.00	0.00	0.00	7.08	0.00	0.00	6.49								
Grading/Excavation		0.03	0.21	0.28	0.04	0.01	0.02	0.02	0.01	0.01	0.00	54.20	0.01	0.00	49.64								
Drainage/Utilities/Sub-Grade		0.04	0.35	0.31	0.05	0.02	0.04	0.02	0.02	0.01	0.00	58.88	0.01	0.00	53.77								
Paving		0.01	0.11	0.09	0.01	0.01	0.00	0.00	0.00	0.00	0.00	18.05	0.00	0.00	16.53								
Maximum (tons/phase)		0.04	0.35	0.31	0.05	0.02	0.04	0.02	0.02	0.01	0.00	58.88	0.01	0.00	53.77								
Total (tons/construction project)		0.08	0.69	0.73	0.11	0.04	0.07	0.05	0.04	0.01	0.00	138.21	0.03	0.00	126.43								
PM10 and PM2.5 estimates assume 50% control of fugitive dust from watering and associated dust control measures if a minimum number of water trucks are specified.																							
Total PM10 emissions shown in column F are the sum of exhaust and fugitive dust emissions shown in columns G and H. Total PM2.5 emissions shown in Column I are the sum of exhaust and fugitive dust emissions shown in columns J and K.																							
CO2e emissions are estimated by multiplying mass emissions for each GHG by its global warming potential (GWP), 1, 25 and 298 for CO2, CH4 and N2O, respectively. Total CO2e is then estimated by summing CO2e estimates over all GHGs.																							
The CO2e emissions are reported as metric tons per phase.																							

## Road Construction Emissions Model Data Entry Worksheet

Version 8.1.0

Note: Required data input sections have a yellow background.

Optional data input sections have a blue background. Only areas with a yellow or blue background can be modified. Program defaults have a white background.

The user is required to enter information in cells D10 through D24, E28 through G35, and D38 through D41 for all project types.

Please use "Clear Data Input & User Overrides" button first before changing the Project Type or begin a new project.

Clear Data Input & User  
Overrides



### Input Type

Project Name	Culver Drive and Alton Parkway Intersection Improvements	
Construction Start Year	2021	Enter a Year between 2014 and 2025 (inclusive)
Project Type	2	1) New Road Construction : Project to build a roadway from bare ground, which generally requires more sit 2) Road Widening : Project to add a new lane to an existing roadway 3) Bridge/Overpass Construction : Project to build an elevated roadway, which generally requires some dif 4) Other Linear Project Type: Non-roadway project such as a pipeline, transmission line, or levee constructi
Project Construction Time	4.00	months
Working Days per Month	22.00	days (assume 22 if unknown)
Predominant Soil/Site Type: Enter 1, 2, or 3 (for project within "Sacramento County", follow soil type selection instructions in cells E18 to E20 otherwise see instructions provided in cells J18 to J22)	2	1) Sand Gravel : Use for quaternary deposits (Delta/West County) 2) Weathered Rock-Earth : Use for Laguna formation (Jackson Highway area) or the lone formation (Scott I 3) Blasted Rock : Use for Salt Springs Slate or Copper Hill Volcanics (Folsom South of Highway 50, Rancho
Project Length	0.45	miles
Total Project Area	0.60	acres
Maximum Area Disturbed/Day	0.20	acres
Water Trucks Used?	1	1. Yes 2. No

Construction Periods	User Override of Construction Months	Program Calculated Months	User Override of Phase Starting Date	Program Default Phase Starting Date
Grubbing/Land Clearing	0.45	0.40	6/1/2021	1/1/2021
Grading/Excavation	1.10	1.80	6/15/2021	1/15/2021
Drainage/Utilities/Sub-Grade	1.60	1.20	7/20/2021	2/18/2021
Paving	0.70	0.60	9/8/2021	4/8/2021
<b>Totals (Months)</b>	4			